

Data Corruption Impact on Named Entity Recognition for Low Resourced Languages

Anonymous

Anonymous

anonymous

Abstract

African languages have recently been the subject of several studies in Natural Language Processing (NLP) and, this has caused a significant increase in their representation in the field. However, most studies tend to focus more on the models than the quality of the datasets when assessing the models' performance in tasks such as Named Entity Recognition (NER). While this works well in most cases, it does not account for the limitations of doing NLP with low-resource languages, that is, the quality and the quantity of the dataset at our disposal. This paper provides an analysis of the performance of various models based on the quality of the dataset. We evaluate different pre-trained models with respect to the entity density per sentence of some African NER datasets. We hope with this study to improve the way NLP studies are done in the context of low-resourced languages.

1 Introduction

Africa is one of the most culturally diverse continents in the world. With over 2000 languages spoken on the continent [Eberhard *et al.*, 2019], we could assume it is the epicentre of the most ground-breaking natural language processing (NLP) researches of the industry. However, this is not the case, as shown in previous studies [Nekoto *et al.*, 2020; Dossou and Emezue, 2021]. The main reason cited is the lack of discoverability of the resources required to conduct such NLP studies [Martinus and Abbott, 2019].

Moreover, considering the case of NER, which is an important subtask of information extraction (IE). Implementing systems that can perform these tasks in the African context could help reduce the communication barrier experienced in some remote parts of the continent, and boost the continent's economy. Therefore, there is a need to improve the representation of African languages in NLP.

Fortunately, some studies made impactful contributions to facilitate future research in NER [Adelani *et al.*, 2021a] and other NLP tasks [Guellil *et al.*, 2021; Adelani *et al.*, 2021b; Azunre *et al.*, 2021] for African languages. However, they fall short in assessing the performance of these models concerning some limitations faced with low-resource languages.

One of them is the difficulty of finding experienced annotators and the high cost of hiring them.

Therefore, our study aims at looking for ways to optimize the cost of hiring annotators in relation to the number of annotations we need to build a decently accurate NLP model. We achieve this by evaluating how the performance of pre-trained models in NER tasks evolves with the availability of annotations in the dataset. We considered NER due to its prevalence in many NLP systems, and we chose pre-trained models to evaluate how prior knowledge of one or more language morphologies could influence the performance of the models. We claim that a linear improvement in the labels' density of a NER dataset does not forcefully produce a linear improvement in the model's performance. As a result, the main contribution of our paper is the analysis of how the quality of low-resourced language data for NER tasks impacts the performance of pre-trained models.

Our work is structured as follows. Section 2 gives a brief overview of the work done in NER. Section 3 gives a thorough description of the approach we followed and, Section 4 provides the experiments we conducted to validate the claim made in this study. Section 5 provides the results of the experiments conducted and a discussion about the obtained results. Finally, we conclude our work in Section 7.

2 Background

NER has been an extensively studied NLP task throughout previous years [Wang *et al.*, 2019; Lample *et al.*, 2016; Strubell *et al.*, 2017; Wang *et al.*, 2021] and, while most studies were done with English corpora, a fair amount of them has also been done with other languages [Hafezi and Rezaeian, 2018; Nguyen and Nguyen, 2021; Al-Rfou *et al.*, 2014]. But despite the amount of work done, there are relatively few studies in NER about African languages. Nevertheless, due to the contributions of numerous researchers across the continent, NER studies can be conducted using publicly available datasets.

Among those publicly available datasets, we have the MasakhaNER corpus [Adelani *et al.*, 2021a], which includes annotations of sentences for ten spoken African languages and NaijaNER corpus [Oyewusi *et al.*, 2021], restricted to five Nigerian languages. In addition to those datasets, we have SADiLaR [Eiselen, 2016] for ten of the official South African languages and, though datasets play a crucial role in

every NLP system, we cannot neglect the part played by the models trained on these data.

From rule-based systems like FASTUS [Appelt *et al.*, 1995] to deep learning models [Li *et al.*, 2018], NER has evolved into a data-centric task. In between this evolution, many NER techniques were proposed. Among some of them, we have sequence labelling methods such as Conditional random fields (CRFs), which models the conditional probability over label sequences given a sequence of observations. Examples of CRFs for NER includes Bi-LSTM-CRF [Huang *et al.*, 2015], CNN-LSTM-CRF [Wu *et al.*, 2019] and BERT-CRF [Souza *et al.*, 2019]. Other NER systems use Hidden Markov Models (HMMs) to identify entities in a corpus [Ekbali and Bandyopadhyay, 2007]. The use of HMMs is motivated by their reliability to analyse sequential correlations between neighbouring samples, notably texts data.

However, the biggest breakthrough in NER and other NLP tasks came from the use of large pre-trained languages models such as BERT [Devlin *et al.*, 2018], RoBERTa [Liu *et al.*, 2019] and, GPT-3 [Brown *et al.*, 2020], and while these language models mainly differ by the number of parameters they possess, they are capable of achieving state-of-the-art results in various NLP tasks. The majority of these language models are trained on English corpora but, there exist some variants trained on other languages [Martin *et al.*, 2019; Scheible *et al.*, 2020; Cañete *et al.*, 2020] as well as others trained on more than one language. This is the case for mBERT [Libovický *et al.*, 2019] trained on 104 languages and XLM-RoBERTa [Lample and Conneau, 2019] trained on 100 languages.

3 Methodology

In this section, we introduce the different components that permit us to carry out this study. Firstly, we talk about the dataset used in this study. Secondly, we provide a detailed list of models used as well as the reason behind each choice. Lastly, we speak about the evaluation metric used in this study.

3.1 NER Dataset

For this study, we use a subset of the MasakhaNER dataset [Adelani *et al.*, 2021a]. This dataset consists of corpora from different sources and written in 10 spoken African languages, annotated with entities inspired from English CoNLL-2003 dataset [Tjong Kim Sang, 2002]. For each language, there is an annotated corpus divided into three sections: training, development, and testing, which amount to 70%, 10%, and 20% of the corpus, respectively. For this study, we chose to work on 3 languages, namely **Swahili**, **Nigerian-Pidgin** and **Kinyarwanda**. We selected the corpus of these languages based on the number of entities and the percentage of tokens that were named entities. By picking corpora with high entity density, we can vary this density throughout a wide range to see how our models are affected.

3.2 Models

To evaluate the performance of our datasets with different entity densities, we use four popular pre-trained models, namely, BERT, RoBERTa, two versions of multilingual

BERT (mBERT). All these models are available through the HuggingFace transformers library [Wolf *et al.*, 2019]. Half of these models are multilingual. We hypothesize that knowledge of different language morphologies can help in situations where the NER entities are scarce. So, in theory, multilingual models will work better than monolingual ones as the entity density in the training corpus reduces. We only use mBERT due to the limitations in computational resources which does permit us to train larger models such as XLM-RoBERTa.

BERT

was proposed as a pre-trained model which could get the bidirectional representation from unlabelled texts [Devlin *et al.*, 2018]. We fine-tune our model on our corpus for sequence labelling. We use the BERT-base model trained on English text with 12 layers of transformers block with a hidden size of 768, 12 attention heads and 110 parameters.

RoBERTa

is an optimized version of BERT that outperforms its predecessor [Liu *et al.*, 2019]. Through the modifications of some training parameters and an increase in the size of the training data. This version of BERT could achieve state-of-the-art results on popular benchmarks such as n GLUE, RACE and SQuAD. We use the RoBERTa-base model with the same architecture as BERT.

mBERT

is the fine-tuned version of BERT, trained on 104 languages [Libovický *et al.*, 2019] (Swahili included). We fine-tune two cased versions of this model with the same architecture as BERT. However, this model has 179M parameters. The first version is trained on 104 languages through masked-language modelling, and the second one is a fine-tuned version of the first on 10 high resourced languages for NER tasks. We hypothesize that the second version will outperform the first one due to the focus of its training objective towards NER.

3.3 Evaluation Metrics

We evaluate the performance of different models using the F1-score metrics. The formula is given by:

$$F1 = \frac{TP}{TP + \frac{1}{2}(FP + FN)}$$

where TP, FP, FN, TN represents the true positives, false positives, false negatives and true negatives of the model's prediction.

4 Experimental Setup

Throughout this section, we thoroughly explain how we plan to evaluate the performance of pre-trained models based on quality. Firstly, we describe the method used to vary the quality of the dataset and lastly, we will explain how we plan to evaluate the performance of different models holistically.




Figure 1: Distribution of entity labels per sentence for three language namely, Swahili (swa), Kriyananda (Kin) and Nigeria-Pidgin (pcm). The error bar represents the standard deviation




Figure 2: A plot of the frequency at which a sentence has a particular number of entity labels for three languages, Swahili (swa), Kriyananda (Kin) and Nigeria-Pidgin (pcm).

4.1 Varying the Quality of the Dataset

Our main claim in this study is to show that a linear improvement in the dataset’s quality does not forcefully produce a linear improvement in the performance of the model. Therefore, we need a method to vary the quality of the dataset linearly. For that, we must first explain what we mean by the quality of the dataset. In this study, the dataset’s quality is the number of entity labels per sentence in the NER corpus. So, varying this quality means modifying this attribute for every sentence in the datasets corpus. We do this by creating buckets where we threshold this attribute over a specific range. In other words, we build buckets of the same dataset in which each sentence in the corpus have at most n entity label with n being the threshold that characterizes the bucket.

We see from Figure 2 that the Nigerian corpus has the most diverse corpus in terms of the number of entities in a single sentence. Additionally, we see from Figure 1 that the number of sentences with entity labels in the range [1 - 10] is more frequent than sentences with this attribute in any other




Figure 3: A plot of the F1-score against the entity label cap for all sentences of the Nigerian Pidgin corpus (pcm).




Figure 4: A plot of the F1-score against the entity label cap for all sentences of the Kinyarwanda corpus (kin).

range. For this reason, bucketing training data with the number of entity labels varying along this range will suffice to get meaningful results.

4.2 Holistic Evaluation

This evaluation’s method consists of evaluating the performance of each model on the overall quality of our dataset. We perform this with the model and the uncapped version of the dataset used to train the model. This method does not differ from the usual way of evaluating models in research papers.

5 Results and Analysis

In this evaluation, we trained and evaluated our models with datasets with 10 entity cap values. For each cap value $j = \{1, 2, \dots, 10\}$, we created a corpus where we cut off (transform to O token) the labels of the sentences which had more than j entities and, we trained and evaluated our models with the processed corpus. From figures 5, 4 and 3, we see that the performance of our models does not differ much. It indicates that multilingual models do not bring any significant benefit

Models	Kinyarwanda	Nigerian Pidgin	Swahili
BERT-c1	37.95	44.97	38.72
BERT-c5	74.32	81.95	85.74
BERT-c10	77.46	86.33	86.25
mBERT-c1	36.19	46.81	40.8
mBERT-c5	81.0	80.61	86.56
mBERT-c10	82.64	86.69	88.12
RoBERTa-c1	38.9	44.19	42.95
RoBERTa-c5	82.33	83.09	86.18
RoBERTa-c10	81.75	86.23	85.41
mBERT10-c1	35.28	42.54	36.22
mBERT10-c5	79.84	79.53	83.17
mBERT10-c10	78.36	85.39	83.57

Table 1: Performance of each model for Entity Label Cap 1, 5, 10 for every language. (1) The name of model followed by **-c5** indicates that this model has been trained on training data with *Entity Label Cap* = 5. Example: BERT-c10 means that the BERT model was trained on training data with *Entity Label Cap* = 10. (2) mBERT10 is the fine-tuned version of mBERT on 10 high resourced languages, specifically of NER




Figure 5: A plot of the F1-score against the entity label cap for all sentences of the Swahili corpus (swa).

for this task. This may be because all low-resourced African languages, except Swahili, used in this study, were not part of the languages used to train these large multilingual models. Also, this can explain why the performance of models in the Swahili corpus at Figure 5 seems to be the best.

The original claim of this study was that a linear improvement in the labels’ density of a NER dataset does not forcefully produce a linear improvement in the model’s performance. We can confirm this by looking at the plot in figures 5, 4 and 3. We observe that while there is a steady increase in the performance of our model as we increase the entity cap, the curve starts to flatten down around *Entity Label Cap* = 6. This indicates that as we had more sentences to labels after this cap, there was not much performance improvement on the models (both monolingual and multilingual).

6 Impact Statement

Analyzing the performance of NER models in the way we did gives us some knowledge of how many resources we need to

construct NER corpora. In this way, we would build datasets with just enough labels to get good models’ performances and maximize the return per investment on the dataset creations.

Also, there are many benefits in carrying such studies. In the African context, NLP is still an undervalued field and scarcity of resources makes it hard to create an ecosystem in which this field can evolve. A direct consequence is the difficulty to find good annotators for African datasets’ creation. Our research cements the idea that the quality of a NER dataset mostly depends on the corpus itself and, more labels do not always equate to better performance. It can help us budget the cost of datasets creation efficiently. However, there are some drawbacks with this type of analysis: (i) It requires enormous training of our models with different instances of the same dataset. Our study, for example, trained 4 models for 3 languages using 10 different entity caps. It makes a total of 120 training experiments. In the long run, this will have negative effects on the environment. (ii) In addition, such studies, which require such a large amount of resources, cannot be carried out in the African context without consequent funding.

There is a possibility to do similar analyses with several African languages and other NLP tasks such as text classification. One example would be a study that trains models on different corpora with different levels of grammatical errors. The results obtained from that study could help us get insights into how corpus from unsupervised training corpus influences our models in terms of its performance and fairness.

7 Conclusion

In this study, we claimed that a linear improvement in the density of labels in the model does produce a linear improvement in the performance of pre-trained language models in the context of low-resourced NER tasks. This claim was verified by training different models on low-resource African language NER corpora and at different levels of density labels. After a certain level of entity cap, each model’s performance stagnates. This behaviour was consistent across all the language

corpora used to train our models.

Our study proves that we do not forcefully need to build a highly dense NER corpus to produce good models performance. We hope by this work to encourage dataset creators for NLP tasks to privilege the curation of their corpus over the density of the label present in these corpora. Finally, a future improvement could be to use more models to see if this behaviour replicates and extend this type of analysis for other NLP tasks.

References

- [Adelani *et al.*, 2021a] David Ifeoluwa Adelani, Jade Abbott, Graham Neubig, Daniel D’souza, Julia Kreutzer, Constantine Lignos, Chester Palen-Michel, Happy Buzaaba, Shruti Rijhwani, Sebastian Ruder, Stephen Mayhew, Israel Abebe Azime, Shamsuddeen H. Muhammad, Chris Chinenye Emezue, Joyce Nakatumba-Nabende, Perez Ogayo, Aremu Anuoluwapo, Catherine Gitau, Derguene Mbaye, Jesujoba Alabi, Seid Muhie Yimam, Tajudeen Rabi Gwadabe, Ignatius Ezeani, Rubungo Andre Niyongabo, Jonathan Mukiibi, Verrah Otiende, Iro Orife, Davis David, Samba Ngom, Tosin Adewumi, Paul Rayson, Mofetoluwa Adeyemi, Gerald Muriuki, Emmanuel Anebi, Chiamaka Chukwuneke, Nkiruka Odu, Eric Peter Wairagala, Samuel Oyerinde, Clemencia Siro, Tobius Saul Bateesa, Temilola Oloyede, Yvonne Wambui, Victor Akinode, Deborah Nabagereka, Maurice Katusime, Ayodele Awokoya, Mouhamadane MBOUP, Dibora Gebreyohannes, Henok Tilaye, Kelechi Nwaike, Degaga Wolde, Abdoulaye Faye, Blessing Sibanda, Orevaoghene Ahia, Bonaventure F. P. Dossou, Kelechi Ogueji, Thierno Ibrahima DIOP, Abdoulaye Diallo, Adewale Akinfaderin, Tendai Marengereke, and Salomey Osei. MasakhaNER: Named Entity Recognition for African Languages. *Transactions of the Association for Computational Linguistics*, 9:1116–1131, 10 2021.
- [Adelani *et al.*, 2021b] David Ifeoluwa Adelani, Dana Ruiter, Jesujoba O. Alabi, Damilola Adebajo, Adesina Ayeni, Mofe Adeyemi, Ayodele Awokoya, and Cristina España-Bonet. Menyo-20k: A multi-domain english-yorùbá corpus for machine translation and domain adaptation. *CoRR*, abs/2103.08647, 2021.
- [Al-Rfou *et al.*, 2014] Rami Al-Rfou, Vivek Kulkarni, Bryan Perozzi, and Steven Skiena. POLYGLOT-NER: massive multilingual named entity recognition. *CoRR*, abs/1410.3791, 2014.
- [Appelt *et al.*, 1995] Douglas E. Appelt, Jerry R. Hobbs, John Bear, David Israel, Megumi Kameyama, Andy Kehler, David Martin, Karen Myers, and Mabry Tyson. SRI International FASTUS SystemMUC-6 test results and analysis. In *Sixth Message Understanding Conference (MUC-6): Proceedings of a Conference Held in Columbia, Maryland, November 6-8, 1995*, 1995.
- [Azunre *et al.*, 2021] Paul Azunre, Salomey Osei, Salomey Addo, Lawrence Asamoah Adu-Gyamfi, Stephen Moore, Bernard Adabankah, Bernard Opoku, Clara Asare-Nyarko, Samuel Nyarko, Cynthia Amoaba, Esther Dan-soa Appiah, Felix Akwerh, Richard Nii Lante Lawson, Joel Budu, Emmanuel Debrah, Nana Boateng, Wisdom Ofori, Edwin Buabeng-Munkoh, Franklin Adjei, Isaac Kojo Essel Ampomah, Joseph Otoo, Rein-dorf Borkor, Standyllove Birago Mensah, Lucien Mensah, Mark Amoako Marcel, Anokye Acheampong Amponsah, and James Ben Hayfron-Acquah. Contextual text embeddings for twi. *CoRR*, abs/2103.15963, 2021.
- [Brown *et al.*, 2020] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. *CoRR*, abs/2005.14165, 2020.
- [Cañete *et al.*, 2020] José Cañete, Gabriel Chaperon, Rodrigo Fuentes, Jou-Hui Ho, Hojin Kang, and Jorge Pérez. Spanish pre-trained bert model and evaluation data. In *PMLAD at ICLR 2020*, 2020.
- [Devlin *et al.*, 2018] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. *CoRR*, abs/1810.04805, 2018.
- [Dossou and Emezue, 2021] Bonaventure F. P. Dossou and Chris C. Emezue. Crowdsourced phrase-based tokenization for low-resourced neural machine translation: The case of fon language. *ArXiv*, abs/2103.08052, 2021.
- [Eberhard *et al.*, 2019] David M Eberhard, Gary F Simons, and Charles D Fennig. *Languages of the world*. SIL International., 2019.
- [Eiselen, 2016] Roald Eiselen. Government domain named entity recognition for South African languages. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC’16)*, pages 3344–3348, Portorož, Slovenia, May 2016. European Language Resources Association (ELRA).
- [Ekbal and Bandyopadhyay, 2007] Asif Ekbal and Sivaji Bandyopadhyay. A hidden markov model based named entity recognition system: Bengali and hindi as case studies. In Ashish Ghosh, Rajat K. De, and Sankar K. Pal, editors, *Pattern Recognition and Machine Intelligence*, pages 545–552, Berlin, Heidelberg, 2007. Springer Berlin Heidelberg.
- [Guellil *et al.*, 2021] Imane Guellil, Ahsan Adeel, Façal Azouaou, Mohamed Boubred, Yousra Houichi, and Akram Abdelhaq Moumna. Sexism detection: The first corpus in algerian dialect with a code-switching in arabic/french and english. *CoRR*, abs/2104.01443, 2021.
- [Hafezi and Rezaeian, 2018] Leila Hafezi and Mehdi Rezaeian. Neural architecture for persian named entity recognition. In *2018 4th Iranian Conference on Signal Processing and Intelligent Systems (ICSPIS)*, pages 61–64, 2018.

- [Huang *et al.*, 2015] Zhiheng Huang, Wei Xu, and Kai Yu. Bidirectional LSTM-CRF models for sequence tagging. *CoRR*, abs/1508.01991, 2015.
- [Lample and Conneau, 2019] Guillaume Lample and Alexis Conneau. Cross-lingual language model pretraining. *CoRR*, abs/1901.07291, 2019.
- [Lample *et al.*, 2016] Guillaume Lample, Miguel Ballesteros, Sandeep Subramanian, Kazuya Kawakami, and Chris Dyer. Neural architectures for named entity recognition. *CoRR*, abs/1603.01360, 2016.
- [Li *et al.*, 2018] Jing Li, Aixin Sun, Jianglei Han, and Chenliang Li. A survey on deep learning for named entity recognition. *CoRR*, abs/1812.09449, 2018.
- [Libovický *et al.*, 2019] Jindrich Libovický, Rudolf Rosa, and Alexander Fraser. How language-neutral is multilingual bert? *CoRR*, abs/1911.03310, 2019.
- [Liu *et al.*, 2019] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized BERT pretraining approach. *CoRR*, abs/1907.11692, 2019.
- [Martin *et al.*, 2019] Louis Martin, Benjamin Müller, Pedro Javier Ortiz Suárez, Yoann Dupont, Laurent Romary, Éric Villemonte de la Clergerie, Djamé Seddah, and Benoît Sagot. Camembert: a tasty french language model. *CoRR*, abs/1911.03894, 2019.
- [Martinus and Abbott, 2019] Laura Martinus and Jade Z. Abbott. A focus on neural machine translation for african languages. *ArXiv*, abs/1906.05685, 2019.
- [Nekoto *et al.*, 2020] Wilhelmina Nekoto, Vukosi Marivate, Tshinondiwa Matsila, Timi Fasubaa, Taiwo Fagbohunge, Solomon Oluwale Akinola, Shamsuddeen Muhammad, Salomon Kabongo Kabenamualu, Salomey Osei, Freshia Sackey, Rubungo Andre Niyongabo, Ricky Macharm, Perez Ogayo, Orevaoghene Ahia, Musie Meressa Berhe, Mofetoluwa Adeyemi, Masabata Mokgesi-Seling, Lawrence Okegbemi, Laura Martinus, Kolawole Tajudeen, Kevin Degila, Kelechi Ogueji, Kathleen Siminyu, Julia Kreutzer, Jason Webster, Jamiil Toure Ali, Jade Abbott, Iroro Orife, Ignatius Ezeani, Idris Abdulkadir Dangana, Herman Kamper, Hady Elsahar, Goodness Duru, Ghollah Kioko, Murhabazi Espoir, Elan van Biljon, Daniel Whitenack, Christopher Onyefuluchi, Chris Chinenye Emezue, Bonaventure F. P. Dossou, Blessing Sibanda, Blessing Bassey, Ayodele Olabiyi, Arshath Ramkilowan, Alp Öktem, Adewale Akinfaderin, and Abdallah Bashir. Participatory research for low-resourced machine translation: A case study in African languages. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 2144–2160, Online, November 2020. Association for Computational Linguistics.
- [Nguyen and Nguyen, 2021] Linh The Nguyen and Dat Quoc Nguyen. Phonlp: A joint multi-task learning model for vietnamese part-of-speech tagging, named entity recognition and dependency parsing. *CoRR*, abs/2101.01476, 2021.
- [Oyewusi *et al.*, 2021] Wuraola Fisayo Oyewusi, Olubayo Adekanmbi, Ifeoma Okoh, Vitus Onuigwe, Mary Idera Salami, Opeyemi Osakuade, Sharon Ibejeh, and Usman Abdullahi Musa. Naijaner : Comprehensive named entity recognition for 5 nigerian languages. *CoRR*, abs/2105.00810, 2021.
- [Scheible *et al.*, 2020] Raphael Scheible, Fabian Thomczyk, Patric Tippmann, Victor Jaravine, and Martin Boeker. Gottbert: a pure german language model. *CoRR*, abs/2012.02110, 2020.
- [Souza *et al.*, 2019] Fábio Souza, Rodrigo Frassetto Nogueira, and Roberto de Alencar Lotufo. Portuguese named entity recognition using BERT-CRF. *CoRR*, abs/1909.10649, 2019.
- [Strubell *et al.*, 2017] Emma Strubell, Patrick Verga, David Belanger, and Andrew McCallum. Fast and accurate sequence labeling with iterated dilated convolutions. *CoRR*, abs/1702.02098, 2017.
- [Tjong Kim Sang, 2002] Erik F. Tjong Kim Sang. Introduction to the CoNLL-2002 shared task: Language-independent named entity recognition. In *COLING-02: The 6th Conference on Natural Language Learning 2002 (CoNLL-2002)*, 2002.
- [Wang *et al.*, 2019] Zihan Wang, Jingbo Shang, Liyuan Liu, Lihao Lu, Jiacheng Liu, and Jiawei Han. CrossWeigh: Training named entity tagger from imperfect annotations. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5154–5163, Hong Kong, China, November 2019. Association for Computational Linguistics.
- [Wang *et al.*, 2021] Xinyu Wang, Yong Jiang, Nguyen Bach, Tao Wang, Zhongqiang Huang, Fei Huang, and Kewei Tu. Improving named entity recognition by external context retrieving and cooperative learning. *CoRR*, abs/2105.03654, 2021.
- [Wolf *et al.*, 2019] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. Huggingface’s transformers: State-of-the-art natural language processing. *CoRR*, abs/1910.03771, 2019.
- [Wu *et al.*, 2019] Fangzhao Wu, Junxin Liu, Chuhan Wu, Yongfeng Huang, and Xing Xie. Neural chinese named entity recognition via CNN-LSTM-CRF and joint training with word segmentation. *CoRR*, abs/1905.01964, 2019.