

The Impact of Data Corruption on Named Entity Recognition for Low Resourced Languages

Abstract

Data is often a massively limiting factor in natural language processing for low-resourced languages. In particular, there is significantly less data than for higher-resourced languages. This data is also often of low-quality, rife with errors and invalid text. Many prior works focus on dealing with these problems, either by generating synthetic data, or filtering out low-quality parts thereof. We instead investigate these factors more deeply, by systematically measuring the effect of data quantity and quality on the performance of pre-trained language models. Our results show that having a missing annotation is preferred compared to having an incorrect one; and that models can perform remarkably well with only 10% of the training data. Finally, all of our results are very consistent across 11 languages and 4 different pre-trained models.

1 Introduction

Natural Language Processing (NLP) is an impactful field, and has received much interest recently, and has been applied in numerous settings [Vaswani *et al.*, 2017; Conneau *et al.*, 2020]. However, much of the focus is on high-resourced languages [Vaswani *et al.*, 2017; Conneau *et al.*, 2020; Radford *et al.*, 2018, 2019], such as English, German, Spanish, etc. While this has led to impressive results for these languages, lower-resourced languages have often not enjoyed as much attention, leading to a large gap in NLP system performance between high- and low-resourced languages. This gap has resulted in an increasingly large body of work focused exclusively on low-resourced languages, either developing models [Ogueji *et al.*, 2021; Alabi *et al.*, 2022] or introducing datasets [Oyewusi *et al.*, 2021; Adelani *et al.*, 2021, 2022a,b].

Despite this recent work and impressive progress, data is still one large limiting factor for low-resourced NLP [Adelani *et al.*, 2022a,b]. In particular, the two main problems are quality and quantity of data. First of all, the amount of data available for low-resourced languages is often a fraction of the high-resourced languages; and for many languages, no data exists at all. Secondly, the data that is available often has questionable quality, containing corruption, invalid tokens or just gibberish [Kreutzer *et al.*, 2022], which has detri-

mental downstream effects on the models trained using this data [Abdul-Rauf *et al.*, 2012; Alabi *et al.*, 2019].

The large amounts of poor-quality data has led to many works focusing on filtering data [Axelrod *et al.*, 2011; Xu *et al.*, 2019; Imankulova *et al.*, 2017; Abdulmumin *et al.*, 2021, 2022] to improve results by discarding all of the invalid or corrupt portions of a dataset. In many of these works, the perspective is that there is an existing, but noisy, dataset, and it must be filtered, keeping only the high-quality parts thereof. The data quality is often so poor that having a smaller high-quality dataset can be better than having a much larger, and lower-quality, dataset. The lack of data has also spurred research into synthetically generating more data, by using techniques such as backtranslation [Bojar and Tamchyna, 2011; Lambert *et al.*, 2011; Sennrich *et al.*, 2016] or using a translation model to generate labelled data for one language using by translating another language’s dataset.

We instead take a different perspective, and focus on analysing the effect of systematically reducing the quality of datasets, and examine the implications of this. In particular, we focus on a Named-Entity Recognition (NER) task due to its prevalence in many NLP systems and the existence of a few high-quality datasets in low-resourced languages. We further focus on fine-tuning existing pre-trained language models, as this is a common and high-performing approach, especially for low-resourced languages [Ogueji *et al.*, 2021; Adelani *et al.*, 2021; Alabi *et al.*, 2022]. We specifically focus on corrupting the training datasets in specific ways to examine the effects of data quality on the performance of models. We further alter the amount of data that the models train on to investigate the effect of the amount of training data on performance.

Our results reveal an interesting phenomenon, where the performance dropoff is not linear, i.e. training on 10% of the data does not result in 10% of the performance of training on the entire dataset, but rather close to 80%. We further find that having a wrong label in NER is more damaging than having a missing label – suggesting that when annotators are uncertain, leaving out an annotation is preferable compared to having a wrong one. Finally, we note that our results are consistent across 11 languages and 4 pre-trained models, suggesting that these observations are generally valid.

84	2 Background and Related Work	
85	2.1 Named Entity Recognition	
86	Named entity recognition (NER) is a token classification task,	
87	where the task is to classify each token in a text as an Organ-	
88	isation, Location, Person, Date, or “Other”. NER as a field	
89	has many impactful applications [Sang and Meulder, 2003;	
90	Lample and Chaplot, 2017].	
91	A typical NER dataset consists of multiple sentences, with	
92	each sentence containing both the words and their associated	
93	labels. The prevailing approach to train NER models is to use	
94	a pre-trained large language model (such as BERT [Devlin <i>et</i>	
95	<i>al.</i> , 2019], XLM-Roberta [Conneau <i>et al.</i> , 2020], etc.) and	
96	fine-tune it on a small amount of NER data [Conneau <i>et al.</i> ,	
97	2020; Adelani <i>et al.</i> , 2021].	
98	2.2 Data Collection and Annotation	
99	Since the lack of data has traditionally been a major limit-	
100	ing factor for low-resourced NLP research, multiple differ-	
101	ent approaches have developed to effectively collect data in	
102	resource-constrained settings. In particular, community in-	
103	volvement has played a large part in this [Nekoto <i>et al.</i> , 2020,	
104	2022], where native speakers annotate or create datasets to be	
105	used in research. This has led to the creation of many differ-	
106	ent datasets [Adelani <i>et al.</i> , 2021; Nekoto <i>et al.</i> , 2022], but it	
107	relies on community members instead of trained annotators,	
108	which may result in some aspects of the annotation being less	
109	accurate. Furthermore, while this approach can successfully	
110	develop datasets for low-resourced languages, due to logistic	
111	challenges and a limited amount of unlabelled text, these	
112	datasets are often significantly smaller than high-resourced	
113	datasets [Conneau <i>et al.</i> , 2020; Adelani <i>et al.</i> , 2021].	
114	2.3 Lack of Quality and Quantity in	
115	Low-resourced Languages	
116	While there has been significantly progress in recent years,	
117	datasets low-resource language are often quite small and lim-	
118	ited, or exhibit subpar quality. Both of these factors can lead	
119	to badly-performing models. For instance, Kreutzer <i>et al.</i>	
120	[2022] perform a large-scale audit of several web-scale and	
121	automatically extracted multilingual datasets, and find that	
122	the quality is often poor, with rubbish characters and sen-	
123	tences being commonplace. Other work has focused instead	
124	on the effect of quality on the performance of downstream	
125	models.	
126	This lack of quality can have great effects. Alabi <i>et</i>	
127	<i>al.</i> [2019] show that for certain low-resourced African lan-	
128	guages, using a significantly smaller, but curated dataset out-	
129	performs training a model on a large, but noisy dataset. Ab-	
130	dulmumin <i>et al.</i> [2022] find similar results, where training on	
131	filtered data of higher quality improved the performance of	
132	translation models for low-resourced languages.	
133	These two observations; that data is often of low-quality	
134	and that a smaller, higher-quality dataset is often preferred	
135	has led to much work being done on filtering existing	
136	datasets, to extract a smaller, but higher-quality subset of sen-	
137	tences. For instance, Abdulmumin <i>et al.</i> [2022] filter a large,	
138	automatically-aligned dataset, and find that this improved	
	the performance of translation models for low-resourced lan-	139
	guages.	140
	The second factor that can limit progress in NLP is a lack	141
	of datasets for many languages, or much smaller datasets	142
	for low-resourced languages compared to higher-resourced	143
	ones [Adelani <i>et al.</i> , 2022a].	144
	3 Methodology	145
	Our aim is to analyse and quantify the impact of data cor-	146
	ruption on the performance of pre-trained language models.	147
	It would allow us to better reason about the importance of	148
	quality and quantity of data, ideally informing the future data	149
	creation processes for low-resourced languages.	150
	While we can corrupt NER text corpora in various ways,	151
	we choose corruptions that simulate a mislabelling scenario	152
	during the annotation process, e.g. mislabelling a person in a	153
	sentence as an organisation. There are two main reasons for	154
	this choice. Firstly, many NER datasets are formed by taking	155
	an existing text source, which is usually of high quality, such	156
	as news data [Adelani <i>et al.</i> , 2021] and annotating each word;	157
	thus, errors are more likely to crop up during the annotation	158
	process. Secondly, it is challenging to corrupt the base sen-	159
	tences in a reasonable, quantifiable and incremental way, as	160
	sentences encompass meaning which is often hard to change	161
	atomically.	162
	Thus, we focus on corrupting only the labels, using dif-	163
	ferent strategies detailed in Section 3.1. For each corrup-	164
	tion strategy, we uniformly vary the amount of corruption	165
	and train our models using the new, corrupted dataset. This	166
	process allows us to evaluate how each corruption strategy	167
	affects the model as we vary the degree of corruption. We	168
	discussed the data for this study in Section 3.2.	169
	3.1 Different Corruption Strategies	170
	We describe the corruption strategies in the next sections, and	171
	Figure 1 shows some examples of the different strategies we	172
	consider. For corruption strategies involving the quality of la-	173
	bels, we consider the atomic element to be a single NER en-	174
	tity label, even if this consists of multiple words. Thus, when	175
	we change the label of a specific entity, we always change its	176
	span instead of just a part thereof. Also, we only change the	177
	train data while leaving the evaluation data unchanged. The	178
	reason for this is because we want an objective comparison	179
	of different corruption strategies. A visual illustration of our	180
	quality-related corruption strategies can be found in Figure 1.	181
	Sentence Pruning	182
	Dataset annotation is generally an expensive and logistically	183
	challenging process (ToDo cite this) when more than one	184
	participants are involved. As a result, low-resourced NLP	185
	datasets are often not particularly big. Due to this observa-	186
	tion, we first evaluate the effect of varying the amount of data	187
	available to the models. In this strategy, we randomly remove	188
	sentences from the original dataset to create sub-datasets with	189
	fewer sentences than the original dataset. This process allows	190
	us to measure the model performance as a function of data	191
	quantity. We choose to represent quantity as a function of the	192
	number of sentences because removing words can alter the	193




Figure 1: An illustration of the different corruption strategies we use. (Left) When capping labels, we effectively remove a certain number of labels, replacing them with “O”. (Right) When swapping labels, we instead randomly replace a label with an incorrect one. In these figures we illustrate the *local* version of the corruptions, with n being the parameter that determines the number of labels kept unchanged.

meaning impacting the model performance in ways we can’t control.

Entity Label Capping

A rich NER dataset would be a dataset that has a high annotation density, i.e. a high number of annotated entities per sentence. This strategy aims at inhibiting the model by thresholding the number of entity annotations allowed in the dataset. In the real world, this would be equivalent to a situation where an annotator failed to label a particular span of token as one of entities PER, LOC, ORG, DATE, instead giving it the default entity type O, which generally means *not relevant*.

We have two variations of this corruption, *local* and *global*. Local means that we have a per-sentence threshold for the number of annotations; for instance, if this threshold is 2, we keep only 2 annotations per sentence, deleting (i.e. setting to O) the others. Global, on the other hand, means that we keep only a certain percentage of labels across the entire dataset; for example, 50% would mean that we randomly remove half of all the labels. This, in contrast to the local setting, may leave some sentences unmodified, or completely remove all annotations from certain sentences.

Entity Label Swapping

Another scenario that could happen during the annotation procedure would be the mislabelling of a span of tokens with the wrong entity. For example, the organisation *John Deere* is mistakenly labelled as a person. This creates a situation where there are contradictory labels, with the same token potentially having different labels, some correct and some incorrect. The goal behind this strategy is to determine how robust large pre-trained language models are to such contradictions. In the same spirit as the previous corruption strategies, we corrupt the datasets at a local and global level by either setting a threshold per sentence or across the entire corpus.

3.2 Data

We use the MasakhaNER dataset [Adelani *et al.*, 2021], which is a high-quality dataset for 10 low-resourced, African

Table 1: The number of sentences for each NER dataset we consider.

Language	Number of Sentences
hau	1912
pcm	2124
ibo	2235
lug	1428
kin	2116
wol	1871
conll_2003_en	14042
luo	644
swa	2109
amh	1750
yor	2171

languages. We specifically focus on low-resourced languages, as these languages often suffer from the aforementioned quality and quantity problems. Furthermore, this dataset is of high-quality, which allows us to evaluate the full spectrum of quality, from gold-standard to completely corrupted. Additionally, we have 10 different languages to evaluate how much the specific language affects the results.

Finally, as a baseline, we also use the CONLL NER dataset, which is a staple NER dataset in English [Sang and Meulder, 2003].

Table 1 contains information about the relative sizes of each language’s dataset and Figure 2 shows how many entities of each type there are per language.




Figure 2: Number of Entities per Language

3.3 Metrics

In addition to considering the overall classification F1 score for each model, we consider the uncertainty of the models as the level of data corruption increases. This allows us quantify the effect of corruption on the certainty and confidence of the models. In particular, we use the *entropy* **TODO**.

4 Experiments

Having described our corruption strategies, we now perform our experiments and showcase our results. We consider the five corruption strategies described above, and use 4 different pre-trained language models, described in Section 4.1. Each run consists of fine-tuning a single pre-trained model on a single language’s dataset, either the original one or a corrupted version. We run all experiments over 3 seeds and average the results to obtain a more accurate performance estimation. The metric we use is the F1 score, as that is commonly used as the main metric when evaluating NER models [Sang and Meulder, 2003; Adelani *et al.*, 2021]. We specifically investigate the effect of progressively corrupting data on the performance of each model. This simulates the effect of having subpar data quality (for instance due to incorrect annotations), but allows us to study this in a controlled setting. We do not modify the test datasets at all.

Then, to normalise results across languages, we divide each F1 score by the value obtained when training with the full, uncorrupted dataset. This effectively measures what fraction of performance is lost and allows us to transform all of the metrics to fall between 0 and 1, resulting in the results being comparable across languages and models. We then average all of our results over the 11 languages and plot the mean and standard deviation. We first examine the effect of quantity in Section 4.3 and then move to understanding the implications of data quality in Section 4.4.

4.1 Different Pre-trained Language Models

We use four different pre-trained language models. We first consider two models developed specifically for low-resourced African languages, AfriBERTa and Afro-XLM-

R. AfriBERTa [Ogueji *et al.*, 2021] was pre-trained on less than 1GB of African language text. Afro-XLM-R [Alabi *et al.*, 2022] used *language adaptive fine-tuning*, where a pre-trained language model is fine-tuned on unlabelled data using the same objective as was used during pre-training. Afro-XLM-R performed this process on 20 languages, 17 of them from Africa, starting from XLM Roberta. XLM Roberta [Conneau *et al.*, 2020] is a high-performing model that was pre-trained on 100 languages. Finally, Multilingual BERT [Devlin *et al.*, 2019] used the standard BERT training process on 104 languages using data from Wikipedia.

We have two models pre-trained or adaptively fine-tuned on low-resourced, African languages, some of which are contained in our dataset. The other two models are traditional multilingual models, with the majority of the training datasets consisting of high-resourced languages. All of these models have been shown to perform well in the NER task [Adelani *et al.*, 2021; Ogueji *et al.*, 2021; Alabi *et al.*, 2022]. We choose the specific model versions to be roughly comparable in terms of number of parameters. More information about the models is included in Table 2.

4.2 Initial Results

In Table 3, we show the results when training on the entire training dataset, grouped by model. Overall, most models perform well on most languages, with Afro-XLM-R performing the best on average. mBERT, on the other hand, performs the worst overall, and even has 0 F1 score on Amharic, as it was not pre-trained on data containing this script [Adelani *et al.*, 2021].

4.3 Quantity

Here we investigate the effect of data quantity on the performance of the models. We specifically remove a certain percentage of the data and train the model on the remaining ones. Furthermore, since the specific fraction we keep/delete may have an effect, we run this experiment three times, each time with different random selections of data. We average over these three permutations, and find that the results are very similar across them.

In Figure 3, we examine the performance when randomly removing a certain percentage of sentences from the datasets. The results here emphasise that the relationship between quantity and performance is highly non-linear. For instance, when only having 60% of the sentences from the original dataset, the performance is nearly the same as using 100% of the data. Even more shockingly, when keeping only 10% of the data, AfriBERTa still retains 80% of the performance of training on the full data. Other models, such as XLMR, perform slightly worse, but still reaches roughly 70% performance at 10% of the data. When using even less data, such as 1% or 5%, we do see a sharp dropoff and much worse performance. This may be due to the phenomenon observed by Mindermann *et al.* [2022], where there are many datapoints that do not add in additional information, and do not need to be learnt.

Table 2: Information about the different pre-trained language models we use.

Name	Name	Source	Parameters	African Languages
AfriBERTa	afriberta-large	Ogueji <i>et al.</i> [2021]	126M	amh, hau, ibo, kin, pcm, swa, yor
Afro-XLM-R	afro-xlmr-base	Alabi <i>et al.</i> [2022]	270M?	amh, hau, ibo, kin, pcm, swa, yor
XLM Roberta	xlm-roberta-base	Conneau <i>et al.</i> [2020]	270M?	amh, hau, swa
Multilingual BERT	bert-base-multilingual-cased	Devlin <i>et al.</i> [2019]	110M	swa, yor

Table 3: The performance of each pre-trained model when fine-tuning on unaltered training data. The best performance per language is marked in bold.

Model Language	AfriBERTa	Afro-XLM-R	XLM-R	mBERT	Average
amh	0.72 (0.01)	0.76 (0.02)	0.72 (0.01)	0.00 (0.0)	0.55
en	0.89 (0.0)	0.93 (0.0)	0.93 (0.0)	0.93 (0.0)	0.92
hau	0.90 (0.0)	0.91 (0.0)	0.90 (0.0)	0.87 (0.01)	0.89
ibo	0.87 (0.0)	0.87 (0.01)	0.83 (0.0)	0.85 (0.0)	0.85
kin	0.74 (0.01)	0.78 (0.0)	0.72 (0.01)	0.71 (0.01)	0.74
lug	0.79 (0.0)	0.81 (0.0)	0.78 (0.0)	0.80 (0.01)	0.79
luo	0.68 (0.01)	0.69 (0.05)	0.69 (0.02)	0.72 (0.01)	0.70
pcm	0.86 (0.01)	0.89 (0.0)	0.86 (0.01)	0.88 (0.0)	0.87
swa	0.88 (0.01)	0.88 (0.0)	0.87 (0.01)	0.86 (0.01)	0.87
wol	0.61 (0.01)	0.66 (0.02)	0.64 (0.01)	0.63 (0.01)	0.64
yor	0.79 (0.01)	0.81 (0.01)	0.77 (0.01)	0.79 (0.01)	0.79
Average	0.79	0.82	0.79	0.73	0.78

4.4 Quality

We now consider the effect of quality on performance, specifically looking at the different corruption strategies mentioned in Section 3.

4.5 Global

In Figure 4, we delete a specific fraction of labels, replacing them with the wrong value “O”. Here, the performance dropoff is not quite linear, with keeping only 60% of the labels resulting in 80% performance. Even having only 40% of the labels provides 60% performance.

Figure 5 considers a similar scenario, but instead swaps a fraction of the labels with another incorrect entity label. Here we see a much more linear relationship, indicating that performance is more sensitive to the wrong label than a missing one.

4.6 Local

Now, considering the local perturbations, Figure 6 caps the number of labels per sentence, and replaces all excess labels with “O”. Here we see that having two labels per sentence is sufficient to recover 80% performance, and 4 entities is enough to obtain near full performance. In Figure 7, we see a more aggressive trend, where swapping one label per sentence with an incorrect one results in 60% performance, and swapping 2 results in an abysmal 30%. This again emphasises that incorrect labels are far more damaging to the model’s performance compared to merely removing labels.

4.7 Entropy

In this section we consider the effects of our data corruptions on the entropy of the models. When we progressively delete more sentences in Figure 8, the entropy steadily increases. In Figure 9, we see that when we delete labels randomly, the

entropy increases, reaches its peak around keeping 70% of the labels, and then decreases again. When swapping labels, in Figure 10, increasing the fraction of swapped labels decreases the entropy.

5 Discussion & Future Work

Our results shown above are interesting, and highlight quite a few important points. First of all, in most cases, all models exhibit roughly equal behaviour, in terms of the percentage dropoff in performance as the level of corruption increases. This ranges from the Africa-centric models (AfriBERTa and Afro-XLM-R) to the predominantly high-resourced models (XLMR and mBERT). This suggests that the behaviour we see here is quite general, as opposed to being particularly model-specific. The variation across languages is also remarkably low.

Secondly, we find that the quantity of data one trains on does not play a massive role in the final performance obtained; we could get around 80% performance with 10-20% of the sentences of the original dataset. This suggests that we do not need a lot of data to perform well, supporting prior findings [Adelani *et al.*, 2022a]. This means that even modest data-collection and annotation efforts should be able to result in datasets that are large enough to obtain decent performance. Our results are consistent across both the languages contained in the pre-trained models’ datasets and those that were not.

Thirdly, the type of corruption can have a large effect on the final performance. For instance, merely leaving out annotations (e.g. replacing them with “O”) can still result in high-performance; e.g. when keeping only 60% of the labels, we still obtain 80% performance. On the other hand, when we swap labels with incorrect ones, the relationship is much more linear. This suggests that having incorrect annotations is more harmful than having no annotations at all – which could help inform annotator training in data collection endeavours.

Finally, we find that the density of entities can be of great importance. For instance, deleting 60% of all sentences results in higher performance than deleting 60% of all entity labels and keeping all of the sentences. Thus, having fewer sentences could be feasible, provided each of the sentences is completely, and accurately, annotated.

There are numerous avenues for future work. One option would be to expand our work into other NLP tasks; for example, additional token classification tasks such as parts of speech tagging, or tasks such as machine translation. Additionally, developing more corruption strategies that cover other components of quality would be promising as well. Furthermore, combining multiple different corruption strategies and investigating how robust models are to these. Finally, us-




Figure 3: Showing the effect of training on a subset of data on the final performance of the models.




Figure 4: Showing the effect of deleting a certain fraction of labels across the entire dataset, replacing them with O.




Figure 5: Showing the effect of swapping a certain fraction of labels across the entire dataset, replacing the correct annotation with an incorrect entity.

Here we plot the performance (measured as a fraction of “optimal” performance – where the entire dataset is used) as we change the (a) fraction of the sentences we use for training or (b) the level of corruption in a dataset. These three figures contain the *global* corruptions, where we alter the entire dataset according to some corruption percentage. Standard Deviation across 11 languages is shaded.




Figure 6: Local Cap Labels




Figure 7: Local Swap Labels

Here we plot the local corruption strategies, where we either (a) cap the number of labels per sentence, replacing the excess ones with O; or (b) swap a certain number of labels per sentence with an incorrect entity. Standard Deviation across 11 languages is shaded.




Figure 8: Showing the effect of training on a subset of data on the final performance of the models.




Figure 9: Showing the effect of deleting a certain fraction of labels across the entire dataset, replacing them with O.




Figure 10: Showing the effect of swapping a certain fraction of labels across the entire dataset, replacing the correct annotation with an incorrect entity.

Here we show the effect of each data corruption strategy on the token entropy of the models.

ing our analysis, future work could develop better methods for dealing with corrupted datasets that would mitigate some of the effect of training on subpar data.

6 Conclusion

Our main aim in this paper is to systematically analyse the effect of data quality and quantity on the performance of pre-trained models on an NER task for low-resourced languages. We do this by designing multiple corruption strategies, and fine-tuning models on various degrees of corruption. Overall, our results emphasise that pre-trained models can perform quite well with remarkably little data, and that missing annotations are less harmful than misleading ones. Ultimately, we hope that this analysis can help inform future NER dataset creation endeavours, or help NLP practitioners when needing to decide on a dataset.

References

- Sadaf Abdul-Rauf, Mark Fishel, Patrik Lambert, Sandra Noubours, and Rico Sennrich. Extrinsic evaluation of sentence alignment systems. 2012.
- Idris Abdulmumin, Bashir Shehu Galadanci, Abubakar Isa, Habeebah Adamu Kakudi, and Ismaila Idris Sinan. A Hybrid Approach for Improved Low Resource Neural Machine Translation using Monolingual Data. *Engineering Letters*, 29(4):339–350, 2021.
- Idris Abdulmumin, Michael Beukman, Jesujoba O. Alabi, Chris Emezue, Evelyn Asiko, Tosin Adewumi, Shamsuddeen Hassan Muhammad, Mofetoluwa Adeyemi, Oreen Yousuf, Sahib Singh, and Tajuddeen Rabi Gwadabe. Separating grains from the chaff: Using data filtering to improve multilingual translation for low-resourced african languages. In *Proceedings of the Seventh Conference on Machine Translation: Shared Task Papers*, 2022.
- David Ifeoluwa Adelani, Jade Z. Abbott, Graham Neubig, Daniel D’souza, Julia Kreutzer, Constantine Lignos, Chester Palen-Michel, Happy Buzaaba, Shruti Rijh-

- wani, Sebastian Ruder, Stephen Mayhew, Israel Abebe Azime, Shamsuddeen Hassan Muhammad, Chris Chinenye Emezue, Joyce Nakatumba-Nabende, Perez Ogayo, Aremu Anuoluwapo, Catherine Gitau, Derguene Mbaye, Jesujoba Alabi, Seid Muhie Yimam, Tajuddeen Gwadabe, Ignatius Ezeani, Rubungo Andre Niyongabo, Jonathan Mukiibi, Verrah Otiende, Iro Orife, Davis David, Samba Ngom, Tosin P. Adewumi, Paul Rayson, Mofetoluwa Adeyemi, Gerald Muriuki, Emmanuel Anebi, Chiamaka Chukwuneke, Nkiruka Odu, Eric Peter Wairagala, Samuel Oyerinde, Clemencia Siro, Tobius Saul Bateesa, Temilola Oloyede, Yvonne Wambui, Victor Akinode, Deborah Nabagereka, Maurice Katusiime, Ayodele Awokoya, Mouhamadane Mboup, Dibora Gebreyohannes, Henok Tilaye, Kelechi Nwaike, Degaga Wolde, Abdoulaye Faye, Blessing Sibanda, Orevaoghene Ahia, Bonaventure F. P. Dossou, Kelechi Ogueji, Thierno Ibrahima Diop, Abdoulaye Diallo, Adewale Akinfaderin, Tendai Maren-gereke, and Salomey Osei. Masakhaner: Named entity recognition for african languages. *Trans. Assoc. Comput. Linguistics*, 9:1116–1131, 2021.

- David Ifeoluwa Adelani, Jesujoba O. Alabi, Angela Fan, Julia Kreutzer, Xiaoyu Shen, Machel Reid, Dana Ruitter, Dietrich Klakow, Peter Nabende, Ernie Chang, Tajuddeen Gwadabe, Freshia Sackey, Bonaventure F. P. Dossou, Chris Emezue, Colin Leong, Michael Beukman, Shamsuddeen Hassan Muhammad, Guyo Dub Jarso, Oreen Yousuf, Andre Niyongabo Rubungo, Gilles Hacheme, Eric Peter Wairagala, Muhammad Umair Nasir, Benjamin Ajibade, Tunde Ajayi, Yvonne Wambui Gitau, Jade Z. Abbott, Mohamed Ahmed, Millicent Ochieng, Aremu Anuoluwapo, Perez Ogayo, Jonathan Mukiibi, Fatoumata Ouoba Kabore, Godson Kalipe, Derguene Mbaye, Allahsera Auguste Tapo, Victoire Memdjokam Koagne, Edwin Munkoh-Buabeng, Valencia Wagner, Idris Abdulmumin, Ayodele Awokoya, Happy Buzaaba, Blessing Sibanda, Andiswa Bukula, and Sam Manthalu. A few thousand translations go a long way! leveraging pre-trained models for african

487	news translation. In <i>Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL 2022, Seattle, WA, United States, July 10-15, 2022</i> , pages 3053–3070. Association for Computational Linguistics, 2022.	547
488		548
489	David Ifeoluwa Adelani, Graham Neubig, Sebastian Ruder, Shruti Rijhwani, Michael Beukman, Chester Palen-Michel, Constantine Lignos, Jesujoba O. Alabi, Shamsuddeen Hassan Muhammad, Peter Nabende, Cheikh M. Bamba Dione, Andiswa Bukula, Rooweither Mabuya, Bonaventure F. P. Dossou, Blessing Sibanda, Happy Buzaaba, Jonathan Mukiibi, Godson Kalipe, Derguene Mbaye, Amelia Taylor, Fatoumata Ouoba Kabore, Chris Chinenye Emezue, Aremu Anuoluwapo, Perez Ogayo, Catherine Gitau, Edwin Munkoh-Buabeng, Victoire Memdjokam Koagne, Allahsera Auguste Tapo, Tebogo Macucwa, Vukosi Marivate, Elvis Mboning, Tajuddeen Gwadabe, Tosin P. Adewumi, Orevaoghene Ahia, Joyce Nakatumba-Nabende, Neo L. Mokono, Ignatius Ezeani, Chiamaka Chukwuneke, Mofetoluwa Adeyemi, Gilles Hacheme, Idris Abdulmumin, Odunayo Ogundepo, Oreen Yousuf, Tatiana Moteu Ngoli, and Dietrich Klakow. Masakhaner 2.0: Africa-centric transfer learning for named entity recognition. <i>CoRR</i> , abs/2210.12391, 2022.	549
490		550
491		551
492		552
493	Jesujoba O. Alabi, Kwabena Amponsah-Kaakyire, David Ifeoluwa Adelani, and Cristina España-Bonet. Massive vs. curated word embeddings for low-resourced languages. the case of yorùbá and twi. <i>CoRR</i> , abs/1912.02481, 2019.	553
494		554
495		555
496		556
497	Jesujoba O Alabi, David Ifeoluwa Adelani, Marius Mosbach, and Dietrich Klakow. Multilingual language model adaptive fine-tuning: A study on african languages. <i>CoRR</i> , abs/2204.06487, 2022.	557
498		558
499		559
500		560
501	Amittai Axelrod, Xiaodong He, and Jianfeng Gao. Domain adaptation via pseudo in-domain data selection. In <i>Proceedings of the 2011 Conference on Empirical Methods in Natural Language Processing, EMNLP 2011, 27-31 July 2011, John McIntyre Conference Centre, Edinburgh, UK, A meeting of SIGDAT, a Special Interest Group of the ACL</i> , pages 355–362. ACL, 2011.	561
502		562
503		563
504		564
505		565
506		566
507		567
508		568
509		569
510		570
511		571
512		572
513		573
514		574
515		575
516		576
517		577
518		578
519		579
520		580
521		581
522		582
523		583
524		584
525		585
526		586
527		587
528	Ondrej Bojar and Ales Tamchyna. Improving translation model by monolingual data. In Chris Callison-Burch, Philipp Koehn, Christof Monz, and Omar Zaidan, editors, <i>Proceedings of the Sixth Workshop on Statistical Machine Translation, WMT@EMNLP 2011, Edinburgh, Scotland, UK, July 30-31, 2011</i> , pages 284–293. Association for Computational Linguistics, 2011.	588
529		589
530		590
531		591
532		592
533		593
534	Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault, editors, <i>Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020</i> , pages 8440–8451. Association for Computational Linguistics, 2020.	594
535		595
536		596
537		597
538		598
539		599
540		600
541		
542		
543		
	Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In Jill Burstein, Christy Doran, and Thamar Solorio, editors, <i>Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)</i> , pages 4171–4186. Association for Computational Linguistics, 2019.	
	Aizhan Imankulova, Takayuki Sato, and Mamoru Komachi. Improving low-resource neural machine translation with filtered pseudo-parallel corpus. In <i>Proceedings of the 4th Workshop on Asian Translation (WAT2017)</i> , pages 70–78, Taipei, Taiwan, November 2017. Asian Federation of Natural Language Processing.	
	Julia Kreutzer, Isaac Caswell, Lisa Wang, Ahsan Wahab, Daan van Esch, Nasanbayar Ulzii-Orshikh, Allahsera Tapo, Nishant Subramani, Artem Sokolov, Claytone Sikasote, Monang Setyawan, Supheakmongkol Sarin, Sokhar Samb, Benoît Sagot, Clara Rivera, Annette Rios, Isabel Papadimitriou, Salomey Osei, Pedro Javier Ortiz Suárez, Irero Orife, Kelechi Ogueji, Andre Niyongabo Rubungo, Toan Q. Nguyen, Mathias Müller, André Müller, Shamsuddeen Hassan Muhammad, Nanda Muhammad, Ayanda Mnyakeni, Jamshidbek Mirzakhlov, Tapiwanashe Matangira, Colin Leong, Nze Lawson, Sneha Kudugunta, Yacine Jernite, Mathias Jenny, Orhan Firat, Bonaventure F. P. Dossou, Sakhile Dlamini, Nisansa de Silva, Sakine Çabuk Balli, Stella Biderman, Alessia Battisti, Ahmed Baruwa, Ankur Bapna, Pallavi Baljekar, Israel Abebe Azime, Ayodele Awokoya, Duygu Ataman, Orevaoghene Ahia, Oghenefego Ahia, Sweta Agrawal, and Mofetoluwa Adeyemi. Quality at a glance: An audit of web-crawled multilingual datasets. <i>Trans. Assoc. Comput. Linguistics</i> , 10:50–72, 2022.	
	Patrik Lambert, Holger Schwenk, Christophe Servan, and Sadaf Abdul-Rauf. Investigations on translation model adaptation using monolingual data. In Chris Callison-Burch, Philipp Koehn, Christof Monz, and Omar Zaidan, editors, <i>Proceedings of the Sixth Workshop on Statistical Machine Translation, WMT@EMNLP 2011, Edinburgh, Scotland, UK, July 30-31, 2011</i> , pages 284–293. Association for Computational Linguistics, 2011.	
	Guillaume Lample and Devendra Singh Chaplot. Playing FPS games with deep reinforcement learning. In Satinder Singh and Shaul Markovitch, editors, <i>Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence, February 4-9, 2017, San Francisco, California, USA</i> , pages 2140–2146. AAAI Press, 2017.	
	Sören Mindermann, Jan Markus Brauner, Muhammed Razak, Mrinank Sharma, Andreas Kirsch, Winnie Xu, Benedikt Höltingen, Aidan N. Gomez, Adrien Morisot, Sebastian Farquhar, and Yarin Gal. Prioritized training on points that are learnable, worth learning, and not yet learnt. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvári, Gang Niu, and Sivan Sabato, editors, <i>Internat-</i>	

601 *tional Conference on Machine Learning, ICML 2022, 17-* 657
602 *23 July 2022, Baltimore, Maryland, USA*, volume 162 of 658
603 *Proceedings of Machine Learning Research*, pages 15630–
604 15649. PMLR, 2022.

605 Wilhelmina Nekoto, Vukosi Marivate, Tshinondiwa Matsila,
606 Timi E. Fasubaa, Taiwo Fagbohunge, Solomon Olu-
607 wole Akinola, Shamsuddeen Hassan Muhammad,
608 Salomon Kabongo Kabenamualu, Salomey Osei, Freshia
609 Sackey, Rubungo Andre Niyongabo, Ricky Macharm,
610 Perez Ogayo, Orevaghene Ahia, Musie Meressa Berhe,
611 Mofetoluwa Adeyemi, Masabata Mokgesi-Selinga,
612 Lawrence Okegbemi, Laura Martinus, Kolawole Tajudeen,
613 Kevin Degila, Kelechi Ogueji, Kathleen Siminyu, Julia
614 Kreutzer, Jason Webster, Jamiil Toure Ali, Jade Z. Abbott,
615 Iroko Orife, Ignatius Ezeani, Idris Abdulkabir Dangana,
616 Herman Kamper, Hady Elsahar, Goodness Duru, Ghol-
617 lah Kioko, Espoir Murhabazi, Elan Van Biljon, Daniel
618 Whitenack, Christopher Onyefuluchi, Chris Chinenye
619 Emezue, Bonaventure F. P. Dossou, Blessing Sibanda,
620 Blessing Itoke Bassey, Ayodele Olabiyi, Arshath Ramk-
621 ilowan, Alp Öktem, Adewale Akinfaderin, and Abdallah
622 Bashir. Participatory research for low-resourced machine
623 translation: A case study in african languages. In Trevor
624 Cohn, Yulan He, and Yang Liu, editors, *Findings of the*
625 *Association for Computational Linguistics: EMNLP 2020,*
626 *Online Event, 16-20 November 2020*, volume EMNLP
627 2020 of *Findings of ACL*, pages 2144–2160. Association
628 for Computational Linguistics, 2020.

629 Wilhelmina Nekoto, Julia Kreutzer, Jenalea Rajab, Millicent
630 Ochieng, and Jade Abbott. Participatory translations of os-
631 hiwambo: Towards sustainable culture preservation with
632 language technology. In *3rd Workshop on African Natural*
633 *Language Processing*, 2022.

634 Kelechi Ogueji, Yuxin Zhu, and Jimmy Lin. Small data? no
635 problem! exploring the viability of pretrained multilingual
636 language models for low-resourced languages. In *Proceed-*
637 *ings of the 1st Workshop on Multilingual Representation*
638 *Learning*, pages 116–126, Punta Cana, Dominican Repub-
639 lic, November 2021. Association for Computational Lin-
640 guistics.

641 Wuraola Fisayo Oyewusi, Olubayo Adekanmbi, Ifeoma
642 Okoh, Vitus Onuigwe, Mary Idera Salami, Opeyemi Os-
643 akuade, Sharon Ibeji, and Usman Abdullahi Musa. Nai-
644 janer : Comprehensive named entity recognition for 5 nige-
645 rian languages. *CoRR*, abs/2105.00810, 2021.

646 Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya
647 Sutskever, et al. Improving language understanding by
648 generative pre-training. 2018.

649 Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario
650 Amodei, Ilya Sutskever, et al. Language models are unsu-
651 pervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

652 Erik F. Tjong Kim Sang and Fien De Meulder. Introduction to
653 the conll-2003 shared task: Language-independent named
654 entity recognition. In Walter Daelemans and Miles Os-
655 borne, editors, *Proceedings of the Seventh Conference on*
656 *Natural Language Learning, CoNLL 2003, Held in coop-* 657
eration with HLT-NAACL 2003, Edmonton, Canada, May 658
31 - June 1, 2003, pages 142–147. ACL, 2003.

Rico Sennrich, Barry Haddow, and Alexandra Birch. Improv- 659
ing neural machine translation models with monolingual 660
data. In *Proceedings of the 54th Annual Meeting of the* 661
Association for Computational Linguistics, ACL 2016, Au- 662
gust 7-12, 2016, Berlin, Germany, Volume 1: Long Papers. 663
The Association for Computer Linguistics, 2016. 664

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszko- 665
reit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia 666
Polosukhin. Attention is all you need. In Isabelle Guyon, 667
Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, 668
Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, 669
editors, *Advances in Neural Information Processing Sys-* 670
tems 30: Annual Conference on Neural Information Pro- 671
cessing Systems 2017, December 4-9, 2017, Long Beach, 672
CA, USA, pages 5998–6008, 2017. 673

Guanghao Xu, Youngjoong Ko, and Jungyun Seo. Improv- 674
ing neural machine translation by filtering synthetic paral- 675
lel data. *Entropy*, 21(12):1213, 2019. 676