MUTOKO RURAL DISTRICT COUNCIL

ICT administrator quick reference

Desk reference; editable source and PDF

One-Day Practical Training Programme | Mutoko, Zimbabwe

Development edition • 12 November 2026. Delivery and acceptance pending.

Start here

Confirm actual database/Redis drivers, workers, cron and backup evidence. No production changes are authorized by this package.

Training writes: isolated approved environment only. Missing access/evidence stays pending. Use the manual for full numbered instructions.

W14 | Review users, scopes, audit and MFA safely

Administration → Users / Roles; Reports & Monitoring → Audit events / Audit report

Rights: users.view; changes require separately approved users.*; audit.view/export

ICT identifies permissions/scopes and one audit event or records the evidence as pending.

Check: Unavailable scoped create/action: inspect the actual policy, permission and role-associated scope. Never edit production roles as a demonstration.

W15 | Monitor, troubleshoot and escalate

Reports & Monitoring → System health / M&E dashboard / Email operations

Rights: analytics.view, system-health.view, mail_operations.view or audit.view as needed

A support ticket identifies symptom, environment, URL/time, safe evidence, owner and action needed.

Check: Do not expose .env, passwords, cookies or real citizen data in screenshots/log exports. Record any current operational evidence that is missing.

W16 | Verify backups, recovery and release readiness

ICT runbooks → backup evidence / scratch recovery plan

Rights: Approved host access only; not provided by this package

ICT can explain DB/files/manifest/off-server/restore evidence and identify the responsible owner.

Check: Missing cron/backup/off-server evidence remains pending. A historical restoration record is not proof of current recoverability.

Read-only command reference — approved ICT environment only

Command / evidence	Meaning and limit
php artisan schedule:list --no-interaction	Intended schedule, not execution history.
php artisan queue:failed --no-interaction	Lists failures; redact payloads/recipient data.
php artisan production:check --no-interaction	Read-only but assumes Redis; not definitive database-host readiness.
Public GET /up	Liveness only; verify dependency/worker/backup evidence separately.

Change-controlled commands: backup:create, queue:restart, cache commands, migrate --force and any restore/deployment require approved operator/runbook/environment. queue:restart signals existing workers; it does not start one. NEVER migrate:fresh on production. Do not print .env or paste secret-bearing logs into support materials.

Escalation contacts — fill before delivery

Content owner: _____ | ICT: _____ | Hosting/software support: _____ | Privacy/security lead: _____

Report exact environment, URL/time, symptom, safe error text and record ID. No passwords, recovery codes, session cookies or private complaint data.

Known limits

Authenticated screenshots/role walkthroughs, production rights, host operations, complete audit coverage, approved translations/accessibility and legal compliance remain unverified. See the included approved discovery baseline for all limitations.