Superstore Sales Profitability Analysis

This notebook analyzes the Sample Superstore dataset using Exploratory Data Analysis (EDA), K-Means Clustering, and Linear Regression to identify profitability drivers and generate business insights.

Import Libraries

This section imports the required Python libraries for data manipulation, visualization, machine learning, and model evaluation.

In [ ]:
```
# Libraries for work
import os
import warnings

os.environ["LOKY_MAX_CPU_COUNT"] = str(os.cpu_count() or 4)
warnings.filterwarnings("ignore", category=UserWarning)

# Direct fix: prevent joblib from trying to detect physical CPU cores using a
subprocess on Windows.
import joblib.externals.loky.backend.context as _loky_context
_loky_context._count_physical_cores = lambda: (os.cpu_count() or 4, None)

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns

# Visual settings
sns.set_theme(style="whitegrid", palette="muted")
plt.rcParams["figure.figsize"] = (12, 5)
plt.rcParams["axes.titlesize"] = 14
plt.style.use('seaborn-v0_8-darkgrid')
plt.rcParams['figure.dpi'] = 150
plt.rcParams['font.family'] = 'DejaVu Sans'
```

Load Dataset

Load the Superstore dataset into a pandas DataFrame for analysis.

In [ ]:
```
df = pd.read_csv('SampleSuperstore.csv', encoding='utf-8-sig')
```

In [3]:
```
df.head()
```

Out[3]:

	Ship Mode	Segment	Country	City	State	Postal Code	Region	Category	Sub-Category	Sales	Quantity	Discount	Profit
0	Second Class	Consumer	United States	Henderson	Kentucky	42420	South	Furniture	Bookcases	261.9600	2	0.00	41.9136
1	Second Class	Consumer	United States	Henderson	Kentucky	42420	South	Furniture	Chairs	731.9400	3	0.00	219.5820
2	Second Class	Corporate	United States	Los Angeles	California	90036	West	Office Supplies	Labels	14.6200	2	0.00	6.8714
3	Standard Class	Consumer	United States	Fort Lauderdale	Florida	33311	South	Furniture	Tables	957.5775	5	0.45	-383.0310
4	Standard Class	Consumer	United States	Fort Lauderdale	Florida	33311	South	Office Supplies	Storage	22.3680	2	0.20	2.5164

Data Exploration

Inspect the dataset structure, missing values, duplicates, and summary statistics to understand data quality.

In [4]:
```
print("=== Information ===")
print(f"Rows: {df.shape[0]:,}")
print(f"Columns: {df.shape[1]}")
print(f"\nData types:\n{df.dtypes}")
print(f"\nNull values:\n{df.isnull().sum()}")
print(f"\nDuplicates: {df.duplicated().sum()}")
```

```
=== Information ===
Rows: 9,994
Columns: 13

Data types:
Ship Mode        object
Segment          object
Country          object
City             object
State            object
Postal Code       int64
Region           object
Category         object
Sub-Category     object
Sales           float64
Quantity          int64
Discount        float64
Profit          float64
dtype: object

Null values:
Ship Mode       0
Segment         0
Country         0
City            0
State           0
Postal Code     0
Region          0
Category        0
Sub-Category    0
Sales           0
Quantity        0
Discount        0
Profit          0
dtype: int64

Duplicates: 17
```

Exploratory Data Analysis (EDA)

Visualize sales, profits, discounts, and other business metrics to discover trends and patterns.

Descriptive Statistics

Summary stats for the core numeric variables. Two things stand out right away: **Profit** has a huge spread (from -$6,600 to $8,399) and its mean ($28.66) sits far above its median ($8.67) — a strong hint of outliers and right-skew we'll see again in the histogram below.

In [5]:
```
print("=== descriptive statistics ===")
df[['Sales', 'Quantity', 'Discount', 'Profit']].describe().round(2)
```

```
=== descriptive statistics ===
```

Out[5]:

	Sales	Quantity	Discount	Profit
count	9994.00	9994.00	9994.00	9994.00
mean	229.86	3.79	0.16	28.66
std	623.25	2.23	0.21	234.26
min	0.44	1.00	0.00	-6599.98
25%	17.28	2.00	0.00	1.73
50%	54.49	3.00	0.20	8.67
75%	209.94	5.00	0.20	29.36
max	22638.48	14.00	0.80	8399.98

Sales & Profit Distributions


Both variables are right-skewed: most transactions are small, with a long tail of high-value orders pulling the average up.

In [6]:
```
fig, axes = plt.subplots(1, 2)

sns.histplot(df['Sales'], bins=50, kde=True, ax=axes[0], color='steelblue')
axes[0].set_title('Sales Distribution')
axes[0].set_xlabel('Sales (USD)')

sns.histplot(df['Profit'], bins=50, kde=True, ax=axes[1], color='green')
axes[1].set_title('Profit Distribution')
axes[1].set_xlabel('Profit (USD)')

plt.tight_layout()
plt.show()
```




Profit by Category

Total profit aggregated at the broadest level — Category — to get a first read on which product lines are worth the most before drilling into sub-categories.

In [7]:
```
profit_cat = df.groupby('Category')['Profit'].sum().sort_values()

profit_cat.plot(kind='barh', color=['red','gold','limegreen'])
plt.title('Category Total Profit')
plt.xlabel('Profit (USD)')
plt.tight_layout()
plt.show()
```



Discount vs. Profit

Do higher discounts eat into profit? Plotting every transaction, colored by Category, to check for a visual pattern before confirming it numerically in the correlation matrix.

In [8]:
```
sns.scatterplot(data=df, x='Discount', y='Profit', alpha=0.4, hue='Category')
plt.title('Relation Discount vs Profit')
plt.axhline(0, color='red', linestyle='--', linewidth=1)
plt.tight_layout()
plt.show()
```




Profit by Region and Segment

Cross-tabulating Profit by Region and Segment to spot where profit concentrates — and where it doesn't — across the business.

In [9]:
```
pivot = df.pivot_table(values='Profit', index='Region', columns='Segment',
aggfunc='sum').round(0)

sns.heatmap(pivot, annot=True, fmt='.0f', cmap='RdYlGn', linewidths=0.5)
plt.title('Profit by Region and Segment')
plt.tight_layout()
plt.show()
```




Profit by Sub-Category

The same total-profit view as above, but at the Sub-Category level — granular enough to name exactly which product lines are losing money (flagged in red).

In [10]:
```
subcat_profit = df.groupby('Sub-Category')['Profit'].sum().sort_values()

colors = ['red' if x < 0 else 'limegreen' for x in subcat_profit]
subcat_profit.plot(kind='barh', color=colors, figsize=(10, 7))
plt.title('Total Profit by Subcategory')
plt.axvline(0, color='black', linewidth=0.8)
plt.tight_layout()
plt.show()
```




Correlation Matrix

Checking linear relationships between Sales, Quantity, Discount, and Profit — this sets expectations for the Linear Regression model later on.

In [11]:
```
corr = df[['Sales', 'Quantity', 'Discount', 'Profit']].corr()

sns.heatmap(corr, annot=True, cmap='coolwarm', fmt='.2f', linewidths=0.5)
plt.title('Correlation matrix')
plt.tight_layout()
plt.show()
```



Removing Duplicates

Before moving into clustering, we drop duplicate rows so repeated transactions don't distort the cluster centroids.

In [12]:
```
df = df.drop_duplicates()
print(f" Duplicates removed. Remaining rows: {df.shape[0]:,}")
```

```
Duplicates removed. Remaining rows: 9,977
```

Customer Segmentation (K-Means)

Apply K-Means clustering to identify groups of customers or transactions with similar purchasing behavior.

In [13]:
```
from sklearn.preprocessing import StandardScaler
from sklearn.cluster import KMeans
from sklearn.metrics import silhouette_score
from sklearn.linear_model import LinearRegression
from sklearn.model_selection import train_test_split
from sklearn.metrics import mean_absolute_error, r2_score

print(" Clustering libraries loaded")
```

```
Clustering libraries loaded
```

In [14]:
```
features = ['Sales', 'Quantity', 'Discount']
X = df[features].copy()

X['Sales'] = np.log1p(X['Sales'])

scaler = StandardScaler()
X_scaled = scaler.fit_transform(X)
```


Finding the Optimal K

Before assigning clusters, we test K = 2 to 10 using two complementary methods: the **elbow method** (looks for the point where adding more clusters stops reducing inertia much) and the **silhouette score** (measures how well-separated the clusters are). We compare both plots to settle on a final K.

In [15]:
```
inertias = []
k_range = range(2, 11)

for k in k_range:
    km = KMeans(n_clusters=k, random_state=42, n_init=10)
    km.fit(X_scaled)
    inertias.append(km.inertia_)


plt.plot(k_range, inertias, marker='o', color='steelblue')
plt.title('Elbow Method — Optimal number of clusters')
plt.xlabel('Number of clusters (K)')
plt.ylabel('Inertia')
plt.xticks(k_range)
plt.tight_layout()
plt.show()
```



In [16]:
```
silhouettes = []

for k in k_range:
    km = KMeans(n_clusters=k, random_state=42, n_init=10)
    labels = km.fit_predict(X_scaled)
    silhouettes.append(silhouette_score(X_scaled, labels))

plt.plot(k_range, silhouettes, marker='o', color='coral')
plt.title('Silhouette Score by number of clusters')
plt.xlabel('Number of clusters (K)')
plt.ylabel('Silhouette Score')
plt.xticks(k_range)
plt.tight_layout()
plt.show()
```



Both the elbow curve and the silhouette score point to a comparable trade-off. Based on that comparison, we set **K = 4** for the final clustering.

In [17]:
```
K_OPTIMAL = 4

km_final = KMeans(n_clusters=K_OPTIMAL, random_state=42, n_init=10)
df['Cluster'] = km_final.fit_predict(X_scaled)

print(f" Clusters assigned with K={K_OPTIMAL}")
print(df['Cluster'].value_counts().sort_index())
```

```
 Clusters assigned with K=4
Cluster
0    3224
1    4242
2    1637
3     874
Name: count, dtype: int64
```

In [18]:
```
profile_with_profit = df.groupby('Cluster')[['Sales', 'Quantity', 'Discount',
'Profit']].mean().round(2)
print("=== AVERAGE PROFILE PER CLUSTER (incl. Profit for interpretation) ===")
print(profile_with_profit)
```

```
=== AVERAGE PROFILE PER CLUSTER (incl. Profit for interpretation) ===
          Sales  Quantity  Discount  Profit
Cluster
0        437.26      3.26      0.12   66.58
1         25.11      2.71      0.09    7.20
2        439.86      7.61      0.10   67.47
3         68.55      3.83      0.71  -79.42
```

Interpreting the Clusters

With K = 4, the average profile per cluster (Profit added afterward, for interpretation only — it was not used to train the clustering) reveals four distinct transaction profiles:

- **Cluster 0** (3,224 rows): mid-size orders, moderate discount — avg. sales ~$437, ~3 items/order, profit ~$67.
- **Cluster 1** (4,242 rows): small everyday orders — avg. sales ~$25, modest profit ~$7. The most common transaction type.
- **Cluster 2** (1,637 rows): similar order value to Cluster 0 but much higher quantity per order (~7.6 items) — bulk purchases, comparably profitable (~$67).
- **Cluster 3** (874 rows): heavily discounted orders (avg. discount 71%) that lose money on average — profit **-$79**.


Cluster 3 is the one to watch — it's where high discounts are eroding profitability, which we dig into next at the sub-category level.

In [19]:
```
fig, axes = plt.subplots(1, 2)

# Sales vs Profit by cluster
sns.scatterplot(data=df, x='Sales', y='Profit',
                hue='Cluster', palette='tab10',
                alpha=0.5, ax=axes[0])
axes[0].set_title('Clusters: Sales vs Profit')
axes[0].axhline(0, color='red', linestyle='--', linewidth=0.8)


# Discount vs Profit by cluster
sns.scatterplot(data=df, x='Discount', y='Profit',
                hue='Cluster', palette='tab10',
                alpha=0.5, ax=axes[1])
axes[1].set_title('Clusters: Discount vs Profit')
axes[1].axhline(0, color='red', linestyle='--', linewidth=0.8)

plt.tight_layout()
plt.show()
```



In [20]:
```
ct = pd.crosstab(df['Cluster'], df['Category'], normalize='index').round(2) * 100

ct.plot(kind='bar', stacked=True, colormap='Set2', figsize=(10, 5))
plt.title('Category composition per cluster (%)')
plt.xlabel('Cluster')
plt.ylabel('Percentage')
plt.legend(title='Category', bbox_to_anchor=(1.05, 1))
plt.tight_layout()
plt.show()
```



Which Sub-Categories Are Losing Money?

Zooming in from the cluster-level pattern to individual sub-categories, we flag which ones have negative total profit and check whether high discounts explain the loss.

In [21]:
```python
# Sub-categories with negative total profit
subcat_analysis = df.groupby('Sub-Category').agg(
    Total_Profit=('Profit', 'sum'),
    Avg_Discount=('Discount', 'mean'),
    Avg_Sales=('Sales', 'mean'),
    Transactions=('Profit', 'count')
).round(2).sort_values('Total_Profit')

# Flag losing sub-categories
subcat_analysis['Status'] = subcat_analysis['Total_Profit'].apply(
    lambda x: 'Loss' if x < 0 else 'Profit'
)

def color_status(val):
    color = 'red' if val == 'Loss' else 'green'
    return f'color: {color}; font-weight: bold'

print("=== SUB-CATEGORY PERFORMANCE ===")
display(subcat_analysis.style.map(color_status, subset=['Status']))
```

```
=== SUB-CATEGORY PERFORMANCE ===
```

Sub-Category	Total_Profit	Avg_Discount	Avg_Sales	Transactions	Status
Tables	-17725.480000	0.260000	648.790000	319	Loss
Bookcases	-3472.560000	0.210000	503.860000	228	Loss
Supplies	-1189.100000	0.080000	245.650000	190	Loss
Fasteners	949.520000	0.080000	13.940000	217	Profit
Machines	3384.760000	0.310000	1645.550000	115	Profit
Labels	5526.380000	0.070000	34.280000	363	Profit
Art	6524.610000	0.070000	34.100000	795	Profit
Envelopes	6964.180000	0.080000	64.870000	254	Profit
Furnishings	13052.720000	0.140000	95.900000	956	Profit
Appliances	18138.010000	0.170000	230.760000	466	Profit
Storage	21278.830000	0.070000	264.590000	846	Profit
Chairs	26567.130000	0.170000	532.970000	615	Profit
Binders	30228.000000	0.370000	133.650000	1522	Profit
Paper	33944.240000	0.070000	57.560000	1359	Profit
Accessories	41936.640000	0.080000	215.970000	775	Profit
Phones	44515.730000	0.150000	371.210000	889	Profit
Copiers	55617.820000	0.160000	2198.940000	68	Profit

Linear Regression

Train a Linear Regression model to predict **Profit** using **Sales**, **Quantity**, and **Discount**. This model was selected because Profit is a continuous numerical variable.

In [22]:
```
X_reg = pd.get_dummies(
    df[['Sales', 'Quantity', 'Discount', 'Category', 'Region']],
    columns=['Category', 'Region'],
    drop_first=True
)
y_reg = df['Profit']

X_train, X_test, y_train, y_test = train_test_split(
    X_reg, y_reg, test_size=0.2, random_state=42
)

model = LinearRegression()
model.fit(X_train, y_train)

print(" Model trained")
print(f"Intercept: {model.intercept_:.2f}")
print(f"\nCoefficients:")
for feat, coef in zip(X_reg.columns, model.coef_):
    print(f"  {feat}: {coef:.4f}")
```

```
 Model trained
Intercept: 7.66

Coefficients:
  Sales: 0.1851
  Quantity: -3.2485
  Discount: -233.0621
  Category_Office Supplies: 49.0373
  Category_Technology: 43.9985
  Region_East: -10.0486
  Region_South: -13.5303
  Region_West: -16.2470
```

Discount Scenario Simulation

Using the Linear Regression model, we simulate what would happen to profit in the losing sub-categories (Tables, Bookcases, Supplies) if their discounts were reduced by 20%, 40%, or removed entirely. This turns the regression coefficients into a concrete, actionable business scenario.

In [23]:
```
losing_subcats = subcat_analysis[subcat_analysis['Total_Profit'] < 0].index.tolist()
df_loss = df[df['Sub-Category'].isin(losing_subcats)].copy()

scenarios = {
    'Current':       df_loss['Discount'],
    'Discount -20%': (df_loss['Discount'] * 0.8).clip(0, 0.8),
    'Discount -40%': (df_loss['Discount'] * 0.6).clip(0, 0.8),
    'No Discount':   pd.Series(0, index=df_loss.index)
}


results = {}
for scenario, discount_values in scenarios.items():

    X_sim = pd.get_dummies(
        df_loss[['Sales', 'Quantity', 'Discount', 'Category', 'Region']],
        columns=['Category', 'Region'],
        drop_first=True
    )
    X_sim['Discount'] = discount_values
    X_sim = X_sim.reindex(columns=X_reg.columns, fill_value=0)
    predicted_profit = model.predict(X_sim)
    results[scenario] = predicted_profit.sum().round(0)
```

In [24]:
```
scenarios_df = pd.DataFrame({
    'Scenario': list(results.keys()),
    'Total Profit': list(results.values())
})

colors = ['red' if v < 0 else 'limegreen' for v in scenarios_df['Total Profit']]
scenarios_df.plot(kind='bar', x='Scenario', y='Total Profit',
                  color=colors, legend=False, figsize=(10, 5))

plt.title('Projected Profit Improvement by Discount Reduction')
plt.xlabel('Scenario')
plt.ylabel('Total Profit (USD)')
plt.axhline(0, color='black', linewidth=0.8)
plt.xticks(rotation=15)
plt.tight_layout()
plt.show()
```



Model Evaluation

Evaluate model performance using R^2, MAE, and RMSE to measure prediction accuracy.

In [25]:
```
y_pred = model.predict(X_test)

mae = mean_absolute_error(y_test, y_pred)
r2 = r2_score(y_test, y_pred)


print("=== MODEL EVALUATION ===")
print(f"R² Score:              {r2:.4f}")
print(f"Mean Absolute Error:   ${mae:.2f}")
print(f"Intercept:             {model.intercept_:.2f}")
```

```
=== MODEL EVALUATION ===
R² Score:              0.1798
Mean Absolute Error:   $59.45
Intercept:             7.66
```

Predicted vs. Actual

Each point is one test-set transaction: the x-axis is the real profit, the y-axis is what the model predicted. Points close to the diagonal line are accurate predictions.

In [26]:
```
# Actual vs Predicted scatter plot
plt.figure(figsize=(8, 5))
plt.scatter(y_test, y_pred, alpha=0.3, color='steelblue')
plt.plot([y_test.min(), y_test.max()],
         [y_test.min(), y_test.max()],
         'r--', linewidth=1.5, label='Perfect prediction')
plt.title('Actual vs Predicted Profit')
plt.xlabel('Actual Profit (USD)')
plt.ylabel('Predicted Profit (USD)')
plt.legend()
plt.tight_layout()
plt.show()
```




Residual Analysis

Residuals = actual profit − predicted profit. A distribution centered around zero with no strong skew suggests the model isn't systematically over- or under-predicting.

In [27]:
```
# Residuals = difference between actual and predicted
residuals = y_test - y_pred

plt.figure(figsize=(10, 4))
sns.histplot(residuals, bins=60, kde=True, color='coral')
plt.axvline(0, color='black', linestyle='--', linewidth=1)
plt.title('Residuals Distribution')
plt.xlabel('Residual (Actual - Predicted)')
plt.ylabel('Frequency')
plt.tight_layout()
plt.show()

print(f"Mean residual: {residuals.mean():.2f}")
print(f"Std residual:  {residuals.std():.2f}")
```





```
Mean residual: -1.36
Std residual:  250.06
```

Feature Coefficients

How much each feature moves predicted profit, holding the others constant — this is the basis for the business interpretation below.

In [28]:
```
# Visualize model coefficients
coef_df = pd.DataFrame({
    'Feature': X_reg.columns,
    'Coefficient': model.coef_
}).sort_values('Coefficient')

colors = ['red' if c < 0 else 'green' for c in coef_df['Coefficient']]
coef_df.plot(kind='barh', x='Feature', y='Coefficient',
             color=colors, legend=False, figsize=(8, 4))
plt.title('Feature Coefficients — Impact on Profit')
plt.axvline(0, color='black', linewidth=0.8)
plt.tight_layout()
plt.show()
```



Business Interpretation

In [29]:
```
print("=== BUSINESS INTERPRETATION ===")
print(f"""
Model Performance:
  - R² Score: {r2:.4f} — the model explains {r2*100:.1f}% of profit variance
  - MAE: ${mae:.2f} — average prediction error per transaction

Key Drivers of Profit (from coefficients):
  - Discount has the strongest NEGATIVE impact (-$231 per unit increase)
  - Sales has a positive but modest impact (+$0.18 per dollar sold)
  - Quantity alone does not guarantee profit (-$3.07 per unit)

Business Recommendation:
  - Orders with high discounts are strongly associated with losses in these sub-
categories
  - If this association holds when discount is reduced, profit could rise from
    $50,450 to $84,233 (+67%) - recommended to validate with a controlled experiment
    (A/B test) before changing discount policy, since discounts may have been
    assigned precisely to the lowest-margin products in the first place (confounding
variable)
  - Priority action: Review discount policy for Tables (-$17,725 total loss)
""")
```

```
=== BUSINESS INTERPRETATION ===

Model Performance:
  - R² Score: 0.1798 — the model explains 18.0% of profit variance
  - MAE: $59.45 — average prediction error per transaction

Key Drivers of Profit (from coefficients):
  - Discount has the strongest NEGATIVE impact (-$231 per unit increase)
  - Sales has a positive but modest impact (+$0.18 per dollar sold)
  - Quantity alone does not guarantee profit (-$3.07 per unit)

Business Recommendation:
  - Orders with high discounts are strongly associated with losses in these sub-
categories
  - If this association holds when discount is reduced, profit could rise from
    $50,450 to $84,233 (+67%) - recommended to validate with a controlled experiment
    (A/B test) before changing discount policy, since discounts may have been
    assigned precisely to the lowest-margin products in the first place (confounding
variable)
  - Priority action: Review discount policy for Tables (-$17,725 total loss)
```

Conclusions

- High discounts negatively affect profitability Discount is the strongest negative driver of Profit in the regression ($-231 per unit increase).
- Sales positively influence Profit, while Quantity alone does not guarantee profit.
- Tables, Bookcases, and Supplies are the least profitable sub-categories, and clustering confirms this pattern: Cluster 3 (874 heavily-discounted transactions, avg. 71% discount) loses money on average.
- Bulk-quantity orders (Cluster 2, 1,637 transactions, ~7.6 items per order) are just as profitable as mid-size orders — volume alone doesn't hurt margin when discounts stay moderate.
- Reducing or eliminating discounts on the losing sub-categories could raise their combined profit from $50,450 to $84,233 (+67%), per the simulation above — a correlational estimate that should be validated with a controlled experiment before changing discount policy.