

Implementing Predictive Analytics with Spark in Azure HDInsight

Lab 1 – Exploring and Preprocessing Data

Overview

In this lab, you will provision an HDInsight Spark cluster. You will then use the Spark cluster to explore data interactively.

What You'll Need

To complete the labs, you will need the following:

- A web browser
- A Microsoft account
- A Microsoft Azure subscription
- A Windows, Linux, or Mac OS X computer
- The lab files for this course

Note: To set up the required environment for the lab, follow the instructions in the **Setup** document for this course. Specifically, you must have signed up for an Azure subscription and installed the Azure CLI tool.

Provisioning an HDInsight Spark Cluster

The first task you must perform is to provision an HDInsight Spark cluster.

Note: The Microsoft Azure portal is continually improved in response to customer feedback. The steps in this exercise reflect the user interface of the Microsoft Azure portal at the time of writing, but may not match the latest design of the portal exactly.

Provision an HDInsight Cluster

1. In a web browser, navigate to <http://portal.azure.com>, and if prompted, sign in using the Microsoft account that is associated with your Azure subscription.
2. In the Microsoft Azure portal, in the Hub Menu, click **New**. Then in the **Data + Analytics** menu, click **HDInsight**.
3. In the **New HDInsight Cluster** blade, enter the following settings, and then click **Create**:
 - **Cluster Name:** *Enter a unique name (and make a note of it!)*
 - **Subscription:** *Select your Azure subscription*

- **Select Cluster Type:**
 - **Cluster Type:** Spark
 - **Cluster Operating System:** Linux
 - **Cluster Tier:** Standard
 - **Credentials:**
 1. **Cluster Login Username:** *Enter a user name of your choice (and make a note of it!)*
 2. **Cluster Login Password:** *Enter and confirm a strong password (and make a note of it!)*
 - **SSH Username:** *Enter another user name of your choice (and make a note of it!)*
 - **SSH Authentication Type:** Password
 - **SSH Password:** *Enter and confirm a strong password (and make a note of it!)*
 - **Data Source:**
 - **Create a new storage account:** *Enter a unique name consisting of lower-case letters and numbers only (and make a note of it!)*
 - **Choose Default Container:** *Enter the cluster name you specified previously*
 - **Location:** *Select any available region*
 - **Node Pricing Tiers:**
 - **Number of Worker nodes:** 1
 - **Worker Nodes Pricing Tier:** *Use the default selection*
 - **Head Node Pricing Tier:** *Use the default selection*
 - **Optional Configuration:** *None*
 - **Resource Group:** *Create a new resource group with a unique name*
 - **Pin to dashboard:** *Not selected*
4. In the Azure portal, view **Notifications** to verify that deployment has started. Then wait for the cluster to be deployed (this can take a long time – often 30 minutes or more. Feel free to catch up on your social media networks while you wait!)

Note: As soon as an HDInsight cluster is running, the credit in your Azure subscription will start to be charged. The free-trial subscription includes a credit limit of approximately \$200 (or local equivalent) that you can spend over a period of 30 days, which is enough to complete the labs in this course as long as clusters are deleted when not in use. If you decide not to complete this lab, follow the instructions in the *Clean Up* procedure at the end of the lab to delete your cluster in order to avoid using your Azure credit unnecessarily.

View the HDInsight Cluster in the Azure Portal

1. In the Azure portal, browse to the Spark cluster you just created.
2. In the blade for your cluster, under **Quick Links**, click **Cluster Dashboards**.
3. In the **Cluster Dashboards** blade, note the dashboards that are available. These include a Jupyter Notebook that you will use later in this course.

Uploading Source Data

The azure command-line interface is a cross-platform tool that you can use to work with Azure services, including HDInsight. In this exercise, you will use the Azure CLI to upload a data file to the Azure blob store for processing with Spark.

View Azure Service Information

1. Open a new command line window.
2. Enter the following command to switch the Azure CLI to resource manager mode.

```
azure config mode arm
```

Note: If a command not found error is displayed, ensure that you have followed the instructions in the setup guide to install the Azure CLI.

3. Enter the following command to log into your Azure subscription:

```
azure login
```

4. Follow the instructions that are displayed to browse to the Azure device login site and enter the authentication code provided. Then sign into your Azure subscription using your Microsoft account.
5. Enter the following command to view your Azure resources:

```
azure resource list
```

6. Verify that your HDInsight cluster and the related storage account are both listed. Note that the information provided includes the resource group name as well as the individual resource names.
7. Note the resource group and storage account name, you will need them in the next procedure.
8. Enter a `dir` (Windows) or `ls` (Mac OS X or Linux) command to view the contents of the **HDPredictLabs\Lab01** folder where you extracted the lab files for this course (for example, `dir c:\HDPredictLabs\Lab01` or `ls HDPredictLabs/Lab01`), and verify that this folder contains a file named **iris-multiclass.csv**. This file contains observations of different flowers, their attributes and types.
9. Enter the following command on a single line to determine the connection string for your Azure storage account, specifying the storage account and resource group names you noted earlier:

```
azure storage account connectionstring show account -g resource_group
```

10. Note the connection string, copying it to the clipboard if your command line tool supports it.
11. If you are working on a Windows client computer, enter the following command to set a system variable for the connection string:

```
SET AZURE_STORAGE_CONNECTION_STRING=your_connection_string
```

If you are using a Linux or Mac OS X client computer, enter the following command to set a system variable for the connection string (enter the connection string in quotation marks):

```
export AZURE_STORAGE_CONNECTION_STRING="your_connection_string"
```

12. Enter the following command on a single line to upload the `autos.csv` file to a blob named `autos.csv` in the container used by your HDInsight cluster. Replace **iris_path** with the local path to `iris-multiclass.csv` (for example `c:\HDPredictLabs\Lab01\iris-multiclass.csv` or `HDPredictLabs/Lab01/iris-multiclass.csv`) and replace **container** with the name of the storage container used by your cluster (which should be the same as the cluster name):

```
azure storage blob upload iris_path container iris-multiclass.csv
```

13. Wait for the file to be uploaded.

Exploring Data




HDInsight provides Jupyter Notebook support for Spark. Jupyter supports both Python and Scala. In this exercise you will use Scala to explore data in the iris dataset.

Create a Folder and Notebook

1. In your web browser, in the Azure Portal, view the blade for your cluster. Then, under **Quick Links**, click **Cluster Dashboards**; and in the **Cluster Dashboards** blade, click **Jupyter Notebook**.
2. If you are prompted, enter the HTTP user name and password you specified for your cluster when provisioning it (not the SSH user name).
3. In the Jupyter web page that opens in a new tab, on the **Files** tab, note that there are folders for **PySpark** and **Scala**.
4. In the **New** drop-down menu, click **Folder**. This create a folder named **Untitled Folder**.
5. Select the checkbox for the **Untitled Folder** folder, and then above the list of folders, click **Rename**. Then rename the directory to **Labs**.
6. Open the **Labs** folder, and verify that it contains no notebooks.
7. In Jupyter, in the **Labs** folder, in the **New** drop-down list, click **Spark**. This create a new Spark notebook named **Untitled**.
8. At the top of the new notebook, click **Untitled**, and rename notebook to **Iris Data Exploration**.

Explore Data in an RDD

RDDs are the basic building block of programming in Spark. In this task, you will explore the Iris data by loading it into an RDD.

1. In the empty cell at the top of the notebook, enter the following code to load the iris-multiclass.csv file you uploaded earlier into an RDD, and count the number of lines it contains:
2. With cursor still in the cell, on the toolbar click the **run cell, select below** button. As the code runs the  symbol next to **Spark** at the top right of the page changes to a  symbol, and then returns to  when the code has finished running.
3. When the code has finished running (it can take a short time to execute initially while the Spark context, SQL context, and Hive context are created), view the output, which should display the number of lines of text in the file.
4. In the new cell that has appeared, enter the following to view the first Iris flower in the dataset:

```
input.first()
```

5. Click the **run cell, select below** button to run the contents of this cell. You should be able to see a comma-separated list of doubles and a string value containing the features we'll be using and the label of the Iris flower
6. In the cell that appears below, enter the following code which will split the Iris rows by comma and create a map-reduce function to enable each of the different classes of Iris to be counted:

```
val splitter = input.map(line => line.split(','))  
val num = splitter.map(line => (line(4), 1)).reduceByKey((a, b) => a + b)
```

7. Click the **run cell, select below** button to run the contents of this cell.
8. In the cell that appears below, enter the following code to list the first three items of the new RDD:

```
num.take(3)
```

9. Click the **run cell, select below** button to run the contents of this cell.
10. Review the output, which shows three different species of iris and the count of each species in the source data:

Explore Data in a DataFrame

While RDDs are a good data structure for working with datasets, they can be tricky to work with. In this task, you'll load the iris data from the RDD into a dataframe and use it to explore the data.

1. In the empty cell at the bottom of the notebook, enter the following to split the dataset again by comma and take all of the feature values and use a case class called Iris to represent them. Then create a Spark DataFrame from the output:

```
import sqlContext.implicits._
case class Iris(SepalLength : Double, SepalWidth : Double, PetalLength
: Double, PetalWidth : Double, Species : String)
val splitter = input.map(line => line.split(',')).map{ line =>
  Iris(line(0).toDouble, line(1).toDouble, line(2).toDouble,
line(3).toDouble, line(4))
}
val df = splitter.toDF()
```

2. Click the **run cell, select below** button to run the contents of this cell. Note that the dataframe that is created contains **SepalLength**, **SepalWidth**, **PetalLength**, **PetalWidth**, and **Species** columns.
3. In the new empty cell, enter the following code to do the same map-reduce operation as you did with the RDD but this time using the DataFrame's `groupBy` method:

```
df.groupBy("Species").count().show()
```

4. Click the **run cell, select below** button to run the contents of the cell, and verify that the species counts are the same as those extracted from the RDD.
5. In the new cell below, enter the following code to create a table from the dataframe and query it using Spark SQL:

```
df.registerTempTable("iris")
sqlContext.sql("SELECT Species, COUNT(Species) FROM iris GROUP BY
Species").show()
```

6. Click the **run cell, select below** button to run the contents of the cell and verify that the species counts are returned.
7. On the **File** menu, click **Close and Halt**.

Quantizing and Normalizing Data

A common task when preparing to create machine learning models is to preprocess data by quantizing (or *binning*) numerical data into categorical ranges and normalizing data so that numerical values lie within similar scales.

Create a New Notebook

You can use Scala code in a Jupyter notebook to preprocess data.

1. In Jupyter, in the **Labs** folder, in the **New** drop-down list, click **Spark**. This creates a new Spark notebook named **Untitled**.

2. At the top of the new notebook, click **Untitled**, and rename notebook to **Quantizing and Normalizing**.

Quantize Data

In his task, you will create a dataframe from an array of sample data values, and then quantize them into categorical value ranges.

1. In the new notebook, in the empty cell, enter the following code to create a set of “buckets” so that we can put data from an array in respective bins:

```
import org.apache.spark.ml.feature.Bucketizer
import org.apache.spark.sql.DataFrame
val splits = Array(Double.NegativeInfinity, 8.0, 12.0, 15.0,
Double.PositiveInfinity)
val temp = Array((1, 10.2), (2, 17.1), (3, 9.6), (4, 5.0), (5, 3.4))
val rainfall = sc.parallelize(temp)
```

2. Click the **run cell, select below** button and wait for the code to finish executing (it can take a short time to execute initially while the Spark context, SQL context, and Hive context are created). Then view the output, which should confirm the creation of an RDD named **rainfall**.
3. In the new empty cell, enter the following code to load the rainfall RDD into a dataframe:

```
val df = sqlContext.createDataFrame(rainfall).toDF("id", "rainfall")
```

4. Click the **run cell, select below** button to run the contents of the cell.
5. In the new cell, enter the following code to create a **Bucketizer** class using the **splits** array that you created earlier:

```
val bucketizer = new Bucketizer()
bucketizer.setInputCol("rainfall")
bucketizer.setOutputCol("discrainfall")
bucketizer.setSplits(splits)
```

6. Click the **run cell, select below** button to run the contents of the cell.
7. In the new cell below enter the following code to transform the dataframe rainfall values into bucketed values and then show the results in a table:

```
val bucketedData = bucketizer.transform(df)
bucketedData.show()
```

8. Click the **run cell, select below** button, and view the discretized rainfall values that indicate the bins into which the original rainfall values have been assigned.

Normalize Data

In his task, you will create a set of vectors that contain widely disparate values, and then normalize those values.

1. In the empty cell at the bottom of the notebook, enter the following code to create a set of vectors and load them into an RDD:

```
import org.apache.spark.ml.feature.Bucketizer
import org.apache.spark.sql.DataFrame
val splits = Array(Double.NegativeInfinity, 8.0, 12.0, 15.0,
Double.PositiveInfinity)
val temp = Array((1, 10.2), (2, 17.1), (3, 9.6), (4, 5.0), (5, 3.4))
```

```
val rainfall = sc.parallelize(temp)

import org.apache.spark.mllib.feature.Normalizer
import org.apache.spark.mllib.util.MLUtils
import org.apache.spark.mllib.linalg.Vectors

val data = Seq(Vectors.dense(1, 34D, 587D), Vectors.dense(5, 76D,
1005D), Vectors.dense(3, 22D, 867D), Vectors.dense(5, 19D, 475D),
Vectors.dense(2, 22D, 666D))
val input = sc.parallelize(data)
```

2. Click the **run cell, select below** button to run the contents of the cell.
3. Enter the following code to display the first five items in the RDD, each of which is an array containing three values:

```
input.take(5)
```

4. Click the **run cell, select below** button to run the contents of the cell, and note that the values in each array are significantly different in scale from one another.
5. Enter the following code to create a normalizer and transform the RDD:

```
val normalizer = new Normalizer()
val normalized = normalizer.transform(input)
```

6. Click the **run cell, select below** button to run the contents of the cell.
7. Enter the following to display the first five items in the RDD and see the normalized arrays.:

```
normalized.take(5)
```

8. Click the **run cell, select below** button to run the contents of the cell. It should be evident that the scale has changed and all of the values are now between zero and one.
9. On the **File** menu, click **Close and Halt**.

Using PCA to Reduce Features

When a feature vector contains multiple features, it can be useful to reduce the number of features using a technique called *principal component analysis*, or *PCA*.

Create a New Notebook

You can use Scala code in a Jupyter notebook to preprocess data.

1. In Jupyter, in the **Labs** folder, in the **New** drop-down list, click **Spark**. This creates a new Spark notebook named **Untitled**.
2. At the top of the new notebook, click **Untitled**, and rename notebook to **Feature Reduction**.

Use PCA to Reduce Features

In this task, you will return to the iris dataset and use PCA to reduce the number of features in the feature vectors.

1. In the new notebook, in the empty cell, enter the following code to load the iris-multiclass.csv file into an RDD, and then create an RDD containing arrays that contain four features:

```
import org.apache.spark.ml.feature.PCA
import org.apache.spark.mllib.linalg.Vectors
import sqlContext.implicits._
```

```
val input = sc.textFile("wasb:///iris-multiclass.csv")
val vec = input.map(line => line.split(",")).map(mapped =>
Vectors.dense(Array(mapped(0).toDouble, mapped(1).toDouble,
mapped(2).toDouble, mapped(3).toDouble)))
```

2. Click the **run cell, select below** button and wait for the code to finish executing (it can take a short time to execute initially while the Spark context, SQL context, and Hive context are created). Then view the output, which should confirm the creation of an RDD named **vec**.
3. Enter the following code to display the first five items in the RDD:

```
vec.take(5)
```

4. Click the **run cell, select below** button to run the contents of the cell, and note that each array in the RDD contains four values.
5. In the cell that appears enter the following code to load the RDD into in dataframe:

```
import sqlContext.implicits._
val data = vec.collect()
val df =
sqlContext.createDataFrame(data.map(Tuple1.apply)).toDF("features")
```

6. Click the **run cell, select below** button to run the contents of the cell.
7. In the cell below enter the following code to set the input column to **features** and the output column after the PCA is done to **outfeatures**, setting $k = 2$ to reduce the 4 dimensions from the Iris featureset to 2:

```
val pca = new
PCA().setInputCol("features").setOutputCol("outfeatures").setK(2)
val pcsModel = pca.fit(df)
```

8. Click the **run cell, select below** button to run the contents of the cell.
9. Enter the following code to use the model you've just created to transform the features and view them – you should be able to see two features per row instead of four:

```
val pcaDF = pcsModel.transform(df)
val result = pcaDF.select("outfeatures")
result.take(5)
```

10. Click the **run cell, select below** button to run the contents of the cell.
11. In the next cell you'll enter the following code to see how to do the same transformation using a **RowMatrix**:

```
import org.apache.spark.mllib.linalg.distributed.RowMatrix
val matrix = new RowMatrix(vec)
val comps = matrix.computePrincipalComponents(2)
```

12. Click the **run cell, select below** button to run the contents of the cell, and verify that a matrix containing vectors consisting of two features is displayed.
13. On the **File** menu, click **Close and Halt**.

Clean Up

If you intend to continue to the next lab immediately, you can leave your cluster running and use it to complete the next lab. Otherwise, you should delete your cluster and the associated storage account. This ensures that you avoid being charged for cluster resources when you are not using them. If you are

using a trial Azure subscription that includes a limited free credit value, deleting the cluster maximizes your credit and helps to prevent using it all before the free trial period has ended.

Delete the Resource Group for your HDInsight Cluster

1. If it is not already open in a tab in your web browser, browse to the new Azure portal at <https://portal.azure.com>.
2. In the Azure portal, view your **Resource groups** and select the resource group you created for your cluster. This resource group contains your cluster and the associated storage account.
3. In the blade for your resource group, click **Delete**. When prompted to confirm the deletion, enter the resource group name and click **Delete**.
4. Wait for a notification that your resource group has been deleted.