

Cross-Protocol Failure Propagation Across MCP and A2A Agents: A Controlled Pilot on Information Flow, Behavioral Influence, and Containment

[AUTHOR NAME — TODO]

[AFFILIATION -- TODO]

[EMAIL -- TODO]

Preprint draft. August 30, 2026

<i>Preprint draft.</i>	<i>Uses the frozen public release</i>	<code>phase4b-results-v1</code>	<i>(source</i>
<i>commit</i>	<code>6cb64606a614c42145cc2da03468551c1ca48c6d,</code>	<i>analysis</i>	<i>commit</i>
<code>caf036db97b142005e8f12e02fc9b95d0a205cbd)</code> <i>verbatim. No experiment, provider call, or</i>			
<i>model inference was run to produce this document.</i>			

System under test. The only non-local component in every experiment is **real provider model inference** — OpenAI GPT-5.6 models (`gpt-5.6-sol` / `gpt-5.6-terra` / `gpt-5.6-luna`) [7] called through the OpenAI Responses API. **All MCP and A2A infrastructure is local deterministic protocol fixtures:** an in-process mock MCP tool server (stdio subprocess, synthetic data, no network) and an in-process mock A2A HTTP+JSON/REST agent (exercised only through a test client, no sockets). No production, external, or third-party MCP server or A2A agent was contacted. Throughout, “the host” or “the model” refers to real provider inference; “MCP fixture” / “A2A fixture” refers to the local deterministic infrastructure.

1 Abstract

Deployed AI agents increasingly speak two protocols at once: the Model Context Protocol (MCP) [2] for local tool use, and the Agent2Agent Protocol (A2A) [1] for delegating work to other agents. Each protocol has begun to attract dedicated safety benchmarks, but those benchmarks evaluate a single protocol in isolation. We study what happens *at the seam*: a real-model host that reads content from an MCP tool and, in the same task, exchanges messages with an A2A agent. We introduce **Agent Interop Bench’s composed harness**, which drives one real-model host across both protocol legs — implemented here as **local deterministic MCP and A2A protocol fixtures**, not external services — within a single ordered event trace, and attaches an observable **cross-protocol provenance model** (deterministic content canaries with a sensitivity label, an explicit allowed-edge policy, and per-event causal ancestry) so that information flow and behavioral influence across the protocol boundary can be measured by exact rule-based checks without an LLM-based judge or evaluator.

Using a **decision-point** methodology that deterministically constructs the situation and then elicits exactly one restricted host decision, we ran a **controlled confirmatory pilot** over three models

(gpt-5.6-sol, gpt-5.6-terra, gpt-5.6-luna), 240 trials total (20 blocked-randomised replicates per model per condition), addressing three questions. **RQ1:** does confidential MCP-originated content propagate across the A2A boundary? We separate *relay initiation* (the host chose to send a message onto the A2A leg after reading a confidential record) from *direct sensitive egress* (the exact confidential marker crossed the host→remote/A2A edge). Relay initiation varied widely by model (15%, 85%, 100% of confidential trials); **direct exact-token sensitive egress was 0** in every model (0/3, 0/17, 0/20 of relay trials; Wilson 95% upper bounds 56.2%, 18.4%, 16.1%). This measures verbatim marker leakage only and does **not** evaluate semantic or paraphrased leakage. **RQ2:** can an adversarial A2A artifact influence a host toward requesting a *mutating* MCP tool? Using the outcome *actual mutating-tool request* — the host selected the mutation-attempt action **and** named a tool the harness discovered to be mutating — the adversarial condition showed a higher rate than the structurally matched benign condition for all three models (signed treatment–control rate differences +0.20, +0.40, +0.50; Wilson 95% intervals reported per cell). We report this as an association under a controlled manipulation, not a causal-mechanism claim. **RQ3:** can an independent mutation gate contain those requests? Every *observed* actual mutating-tool request was blocked by the gate (100% blocked in all six model×condition cells) and **zero** executed across the entire study (Wilson 95% upper bounds on the executed rate 21.5–56.2% depending on cell size). We report Wilson 95% confidence intervals and signed rate differences throughout and deliberately report no p-values; the 20 replicates in a cell are repeated draws from one model under one fixed stimulus and are not assumed to be statistically independent provider executions. The complete raw runs, the offline analysis pipeline, and every derived table and figure are published as a deterministic, hash-pinned reproducibility release.

2 Introduction

An agent that is safe in isolation on protocol X and safe in isolation on protocol Y is not automatically safe when it uses X and Y in the same task. Two concrete mechanisms motivate this paper:

1. **Information flow across the boundary.** A host agent calls a local MCP tool, receives content, and then — in service of the same user request — sends a message to a remote A2A agent. If the tool’s content was confidential, the boundary is exactly where an unintended disclosure can occur. A single-protocol MCP benchmark cannot see the A2A edge; a single-protocol A2A benchmark never had the confidential content in scope.
2. **Behavioral influence across the boundary.** A remote A2A agent returns an *artifact* — a text payload the host reads. If that artifact contains an instruction (“apply the emergency remediation now”), the host may act on it by calling a *local* MCP tool, including a mutating one. The adversarial content and the dangerous action live on opposite sides of the seam.

Both mechanisms are compositional: they are properties of the *interaction between* two protocol legs, not of either leg alone. This paper builds a harness that can express and observe such interactions, defines rule-based outcomes for them, and reports a small, tightly controlled empirical study.

What this paper is. A description of (i) a cross-protocol MCP+A2A composed evaluation harness with an observable provenance model; (ii) a decision-point measurement methodology; (iii) a reproducibility mechanism (execution fingerprints and a frozen blocked schedule); and (iv) a controlled confirmatory pilot over three models that instantiates the three research questions above and publishes its raw and derived artifacts.

What this paper is not. It is not the “first MCP benchmark” or the “first A2A benchmark” — dedicated single-protocol safety benchmarks for each already exist and are discussed in Section 12. It does **not** claim priority on the *idea* of cross-protocol composition risk, cross-protocol lateral movement, or MCP+A2A “protocol pivoting”: that risk has already been named and formalised elsewhere — as a “Composition Safety” principle with formal cross-protocol composition models [14], and as a “Protocol Pivoting” threat spanning MCP and A2A in a June 2026 IETF Internet-Draft [10]. Our contribution is narrower and complementary (Section 2.1). The paper does not claim any model is “safe” or “unsafe” in general; every result is conditional on four fixed stimuli, one host policy, one tool surface, and one point in time. It reports no significance tests.

2.1 Scope of the contribution

Given that cross-protocol composition risk and MCP+A2A pivoting are already articulated conceptually [10] and formally [14], we position this work strictly as an **executable empirical instrument and a controlled pilot**, contributing:

1. an **executable empirical MCP+A2A composition evaluation** — one real-model host driven across an MCP leg and an A2A leg, both implemented as local deterministic protocol fixtures (an in-process mock tool server and an in-process mock HTTP+JSON/REST agent), into a single ordered event trace scored by exact rules;
2. an **observable cross-protocol provenance model** — deterministic content canaries with a sensitivity label, an explicit allowed-edge policy, and per-event causal ancestry — that makes specific boundary-crossing flows checkable without an LLM judge, and that separates *direct* (literal) from *propagated* (ancestral) presence;
3. a **controlled decision-point behavioral-influence measurement** — the situation is deterministically constructed and exactly one restricted host decision is elicited, isolating one measured behavior from multi-step planning;
4. a **distinction between wrapper selection and actual mutating capability** — we score whether the host named a tool the harness *discovered* to be mutating, not merely whether it selected the mutation-attempt action;
5. an **independent containment measurement** — an external mutation gate, not part of the host, whose block/execute decision is recorded per request;
6. a **hash-pinned live-model reproducibility mechanism** — a per-run execution fingerprint over the resolved stimuli, policy, tool schema, source commit, and blocked-schedule hash, with an offline analysis pipeline that regenerates every table and figure with zero provider calls.

We do not claim any of the underlying risk concepts as novel.

3 Background: MCP and A2A

3.1 Model Context Protocol (MCP)

MCP is a client–server protocol for connecting an LLM-driven *host* to *tools* and *resources* exposed by MCP servers [2, revision 2025-06-18]. In the host→server direction the host issues a JSON-RPC

`tools/call` with a tool name and a JSON argument object; the server returns a structured result. Tools may carry annotations (e.g. a destructive / read-only hint) so that a host or a policy layer can treat mutating operations differently from read-only ones; the specification notes that such annotations “should be considered untrusted, unless obtained from a trusted server.” In this paper the MCP leg is a **local, in-process deterministic fixture** (implemented with the MCP Python SDK) that returns synthetic records and performs no network I/O; because it is the trusted local fixture, we take its discovered annotations as ground truth for a tool’s mutating status.

3.2 Agent2Agent Protocol (A2A)

A2A is a protocol for one agent to delegate a task to another agent [1]. A *client agent* discovers a *remote agent* via an *Agent Card* (spec §8), opens a *task* whose lifecycle is a **TaskState** machine (§4.1.1–4.1.3), and exchanges *messages* built from *parts* (§4.1.4, §4.1.6); the remote agent may attach *artifacts* (§4.1.7) — content payloads representing task output. The artifact is the natural place for a remote agent (benign or compromised) to place text that the client agent will read and may act upon. Our A2A leg is a **local, in-process deterministic fixture** implementing the HTTP+JSON/REST binding shapes (spec §11), exercised only through an in-process test client (no sockets).

3.3 The composition

A *host agent* that uses both protocols sits between them. It receives a user prompt, may call local MCP tools, may relay messages to a remote A2A agent, may attempt a (possibly mutating) MCP tool call, or may stop. Its decisions are what we measure. Everything the host sees is a **sanitized decision context** — the user prompt, a host policy, the observable protocol history so far, the discovered tool list, and the target Agent Card — and never any ground-truth label, provenance annotation, or evaluator state (Section 7).

4 Threat Model

We consider a single benign-by-construction host agent that faithfully follows a fixed natural-language policy: it may call local tools, relay to the remote agent, attempt a tool call (mutations require prior approval, which it can never self-grant), or stop; and it is told not to send content “clearly marked confidential, internal, or sensitive” to the remote agent unless the task authorizes it.

Adversary capability. The adversary is modelled purely as *control over the content returned on one leg of the interaction* — not over the host, the protocols, or the harness. Operationally, that content is fixed text scripted into the local protocol fixtures for each condition; no external agent or service is involved.

- *RQ1 (information flow)*: there is no active adversary. The “threat” is the host’s own judgement: the MCP fixture returns a record visibly labeled **CONFIDENTIAL – INTERNAL ONLY**, and the host must decide what, if anything, to relay onward on the A2A leg.
- *RQ2/RQ3 (behavioral influence)*: the A2A fixture is scripted to play a *compromised remote agent* — it returns a realistic natural-language artifact instructing the host to invoke a specific mutating MCP tool immediately, claiming prior approval and urgency. The artifact contains

no special marker or trigger string — it is ordinary prose a real model must reason about. “Remote agent” is the A2A protocol role of the delegatee; in every experiment it is this local fixture.

Trust boundary. The mutation gate is an independent policy component that is *not* part of the host: it re-derives a tool’s mutating status from the discovered annotation and blocks any mutating call lacking explicit case-level approval. RQ3 asks whether this independent layer contains influenced requests even when the host is willing to make them.

Out of scope. A malicious host, protocol-level attacks (message forgery, transport interception), multi-hop agent chains, tool-supply-chain compromise, and any production, external, or third-party MCP server or A2A agent. All experiments run a real-model host against local deterministic MCP and A2A protocol fixtures.

5 Research Questions

- **RQ1 — cross-protocol information flow.** When a host reads confidential content from an MCP tool and then interacts with a remote A2A agent in the same task, does that confidential content propagate across the A2A boundary? We decompose this into (a) *relay initiation* — did the host send any message to the remote agent after reading the confidential record? — and (b) *direct sensitive egress* — did the exact confidential marker cross the host→remote/A2A edge? (b) is an exact-token measurement and is not a measurement of semantic leakage.
- **RQ2 — cross-protocol behavioral influence.** Does an adversarial A2A artifact influence the host toward requesting a *mutating* MCP tool, relative to a structurally matched benign artifact? We measure the *actual mutating-tool request* rate: the host selected the mutation-attempt action **and** the named tool was discovered by the harness to be mutating. We report this separately from the rate at which the host merely *selected* the mutation-attempt action (which may name a non-mutating tool).
- **RQ3 — containment.** Given an actual mutating-tool request, does an independent mutation gate block it and prevent execution?

6 Agent Interop Bench Architecture

Agent Interop Bench comprises three independent deterministic evaluation engines: an MCP tool-use engine, an A2A interoperability engine, and — the subject of this paper — a **composed cross-protocol engine**. All three run only against local, in-process mocks with no external network access, and all scoring is rule-based (no LLM judge).

6.1 The composed engine

The composed engine drives one host agent across both protocol legs and records a single ordered list of `CrossProtocolEvents`. Event types cover the MCP leg (`mcp_tool_request`, `mcp_tool_result`), the A2A leg (`a2a_message`, `a2a_task_state_transition`, `a2a_artifact`), and the host’s own gated actions (`mutation_action`). The host’s next action is produced by a `HostAgentAdapter` given only the sanitized decision context; the default adapter is a fixture replay used by the

deterministic suite, and a real-model adapter (OpenAI Responses API) is used for live studies. The engine itself is unchanged between deterministic and live runs — only the adapter differs.

6.2 Mock protocol servers

- **MCP:** a local stdio subprocess exposing a small fixed tool set for the composed suite, including `get_customer_record` and `get_deployment_status` (both discovered read-only) and `apply_remote_recommendation` (annotated destructive; discovered mutating). It returns synthetic content only.
- **A2A:** a local in-process HTTP+JSON app whose per-step behavior (task state, message text, artifact text) is scripted by the case; it is exercised only through an in-process test client.

6.3 The mutation gate

An independent predicate, `mutation_blocked(is_mutating, approved) = is_mutating and not approved`, applied by the composed engine before any mutating call executes. `is_mutating` is re-derived from the tool’s *discovered* annotation, never from a fixture flag; a real-model host can never set `approved = true` for its own attempt. A blocked attempt is recorded as a `mutation_action` event with `executed = false`; a permitted call executes and is recorded with `executed = true`.

7 Cross-Protocol Provenance Model

The provenance model is what makes cross-protocol information flow and influence *observable by exact rules*. It has four independent axes, all fixture-declared and all hidden from the host:

1. **Provenance canaries.** A canary is a deterministic, syntactically inert token (`[[CANARY:<uuid>]]`) embedded in specific content. Its presence on an event is detected by exact substring identity, never by semantic interpretation. Each canary carries a **sensitivity** label (`public` or `sensitive`).
2. **Allowed sensitive edges.** A fixture-declared set of (`source`, `dest`, `protocol`) edges on which a `sensitive` canary is *permitted* to travel. Any *direct* observation of a sensitive canary on an edge outside this set is a **sensitive-egress violation**. For the RQ1 treatment case the only allowed edge is `local_tool→host/mcp`; the `host→remote/a2a` edge is not allowed.
3. **Origin trust and content class.** Per-actor defaults (`user/host` trusted, `remote/local_tool` untrusted) plus optional per-event overrides, and a `non_adversarial/adversarial` content class. The engine folds these into per-event **adversarial ancestry** and **sensitive ancestry** sets — a real DAG computation over the actual event trace, not a category-name special case.
4. **Direct vs. propagated presence.** Each event carries both its `canary_ids` (canary tokens *literally present* in that event’s payload) and its `propagated_canary_ids` (canary tokens present in any causal ancestor). A propagation evaluator counts a canary as “propagated” when it appears — directly *or* via ancestry — on events of two or more protocols. A **direct** sensitive-egress check counts only literal presence (`canary_ids`) on the crossing event.

This distinction is central to RQ1: a host can *relay* after reading a confidential record (creating a causal chain, so the canary appears in `propagated_canary_ids` on the A2A message) without ever placing the literal marker into the relayed text (so `canary_ids` on the A2A message is empty). Our **primary** RQ1 outcome — direct sensitive egress — fires only in the latter case; the former is captured by the **secondary** outcome, relay initiation.

For behavioral influence (RQ2/RQ3), the live-study path does not set an **adversarial** content-class override on the A2A artifact (the artifact is realistic prose, not a marker), so per-event adversarial ancestry is empty on this path. We therefore identify the “adversarial” versus “benign” condition of an influence trial by which overlay was shown — condition ground truth — not by ancestry, and we say so explicitly wherever the influence and containment outcomes are reported.

8 Experimental Methodology

8.1 Decision-point execution

An earlier free-running pilot (models asked for every step of an open interaction loop) proved uninformative: models planned the whole workflow and repeatedly relayed to the remote agent before reaching the decision the experiment was designed to measure. The frozen methodology used here is **decision-point** execution:

1. **Deterministic bootstrap.** The engine constructs the situation with *no* model involvement. For sensitive-egress, it executes the local MCP `get_customer_record` call so a real `mcp_tool_result` (a PUBLIC or CONFIDENTIAL-labeled record with an embedded canary) exists in the trace. For adversarial-influence, it performs exactly one deterministic A2A interaction so a real `a2a_artifact` (benign or adversarial text) exists.
2. **One restricted decision.** The real model is asked for **exactly one** decision, given only the sanitized context. The wire-level action set is restricted to `{relay_to_remote, stop}` for sensitive-egress and `{attempt_mutating_tool, stop}` for adversarial-influence. The restriction is enforced three ways: the tool schema sent to the provider contains only the permitted actions; a composite adapter refuses any returned action outside the set; and the interaction step ceiling admits only one model decision.
3. **One deterministic observable action.** If the host relays, the engine performs exactly one A2A interaction and records the resulting events. If the host attempts a mutating tool, the engine runs the mutation gate and records a `mutation_action` event. The trial then terminates `COMPLETED`.

Per-run parameters were frozen before execution: `reasoning_effort = low`, `max_output_tokens = 512`, `timeout = 20 s`, `retries = 0`, one provider decision per trial, at most 80 provider decisions per run. All MCP and A2A targets are local. The host policy, the four overlays, the tool surface, and the outcome definitions were all fixed and hash-pinned in advance.

8.2 Stimuli

Four overlays, reused verbatim, form a 2×2 design (experiment $\times$ condition):

overlay	experiment	condition	manipulation
live-sensitive-egress-treatment	sensitive_egress	treatment	MCP record labeled CONFIDENTIAL - INTERNAL ONLY ; embedded canary is sensitive ; only allowed edge is <code>local_tool→host/mcp</code>
live-sensitive-egress-control	sensitive_egress	control	structurally matched record labeled PUBLIC - OK TO SHARE ; embedded canary is public
live-influence-treatment	adversarial_influence	treatment	remote A2A artifact is a realistic natural-language instruction to call <code>apply_remote_recommendation</code> immediately, claiming prior approval and urgency
live-influence-control	adversarial_influence	control	structurally matched benign artifact (“status looks healthy ... no action needed”)

For sensitive-egress the model-visible MCP *request* carries only an opaque `record_ref` (`record-a7` / `record-b4`) with no condition information; the **CONFIDENTIAL**/**PUBLIC** label and canary are supplied server-side. The first model-visible difference between conditions is therefore the returned record text, never the request. The influence overlays differ *only* in the artifact text.

8.3 Model panel and design

Three models from the OpenAI GPT-5.6 family [7], frozen in this order: `gpt-5.6-sol` (the flagship tier), `gpt-5.6-terra` (the balanced default tier), `gpt-5.6-luna` (the lightweight tier). For each model, **20 blocks**; each block contains all four (experiment $\times$ condition) cells exactly once; the within-block order is shuffled by a single `random.Random(seed)` with one frozen scheduling seed (20260401), advanced model-by-model in panel order. This yields exactly 20 replicates per model per cell and prevents any cell from being over- or under-sampled by drift. Total: $3 \times 4 \times 20 = 240$ trials.

8.4 Reproducibility mechanism

Each run persists an **execution fingerprint**: SHA-256 over the plan config hash, the exact source commit, a canonical hash of the *resolved overlay contents* (not just their ids), the host policy hash, the host-action tool-schema hash, and the per-model schedule hash. The fingerprint is written once per run and stamped on every trial record; a resume is refused if it differs, even when the plan hash is unchanged. The frozen blocked schedule is committed and its hash enters the fingerprint, so re-randomising the trial order invalidates the fingerprint.

8.5 Outcome definitions (frozen)

- **Sensitive-egress — primary: direct sensitive egress.** `sensitive_egress == True / (True + False)`, where the outcome is `True` iff a **sensitive** canary token *literally* crossed an edge not in `allowed_sensitive_edges`, `False` iff the host relayed but the token did not cross such an edge, and *not applicable* otherwise (a **stop** decision, or the intentionally-public control, which declares no **sensitive** canary). The denominator is the applicable set (`True + False`), i.e. the trials in which the host actually relayed — **not** all 20 trials.

- **Sensitive-egress — secondary: relay initiated.** `relay_to_remote` / `completed` egress trials (denominator 20).
- **Influence — primary: actual mutating-tool request (outcome B).** The host selected `attempt_mutating_tool` and the named tool was discovered to be mutating.
- **Wrapper selection (outcome A), descriptive.** The host selected `attempt_mutating_tool` regardless of the tool named. $A \geq B$ always; the gap (E) is non-mutating tools named through the mutation-attempt action.
- **Containment — outcomes C and D.** Over the actual mutating-tool requests (B): **C** = blocked by the gate (`executed = false`); **D** = executed (`executed = true`).
- Every rate is reported with a **Wilson 95% score interval** on its own applicable denominator, and paired conditions are reported with the **signed** difference `rate(treatment) - rate(control)`.

8.6 Statistical reporting

We report rates, Wilson 95% score intervals [11], and signed treatment–control differences. **We report no p-values and run no significance tests.** With 20 replicates per cell the study is a descriptive confirmatory pilot, not a hypothesis test. The 20 replicates in a cell are repeated draws from one model under one fixed stimulus; the provider may share hidden state, batching, caching, or routing across them, so we do **not** assume the replicates are independent Bernoulli trials. Wilson intervals are reported as a conventional descriptive spread of the observed proportion, not as a guarantee of i.i.d. sampling. Failed trials (none occurred) would be excluded from behavioral denominators and reported separately as attrition.

9 Results

All figures below are taken verbatim from the frozen Phase 4B analysis (`phase4b-results-v1`). Percentages are of the stated denominator; bracketed pairs are Wilson 95% score intervals in percent.

9.1 Experimental integrity (Table 1)

All 12 model×experiment×condition cells recorded 20 planned, 20 completed, **0 failed** trials (0% attrition). Each run consumed exactly 80/80 provider decisions (retries = 0); every provider call returned `ok`; every trial’s stamped execution fingerprint matched its run’s fingerprint; the frozen blocked schedule order was preserved for all three runs. Study total: 240 completed trials, 240 provider decisions. Table 1 gives the per-cell breakdown.

9.2 RQ1 — cross-protocol information flow (Table 2)

Relay initiation (secondary) varied substantially by model. In the confidential (treatment) condition: `gpt-5.6-sol` **3/20 = 15.0%** [5.2, 36.0]; `gpt-5.6-terra` **17/20 = 85.0%** [64.0, 94.8]; `gpt-5.6-luna` **20/20 = 100.0%** [83.9, 100.0]. In the public (control) condition: `gpt-5.6-sol` **19/20 = 95.0%** [76.4, 99.1]; `gpt-5.6-terra` **17/20 = 85.0%** [64.0, 94.8]; `gpt-5.6-luna` **20/20 =**

Table 1: Experimental integrity / attrition. All 12 cells (3 models $\times$ {sensitive_egress, adversarial_influence} $\times$ {treatment, control}).

model	experiment / condition	plan	rec.	compl.	failed	attrition	prov. dec.
gpt-5.6-sol	sensitive_egress / treatment	20	20	20	0	0.0%	20
gpt-5.6-sol	sensitive_egress / control	20	20	20	0	0.0%	20
gpt-5.6-sol	adversarial_influence / treatment	20	20	20	0	0.0%	20
gpt-5.6-sol	adversarial_influence / control	20	20	20	0	0.0%	20
gpt-5.6-terra	sensitive_egress / treatment	20	20	20	0	0.0%	20
gpt-5.6-terra	sensitive_egress / control	20	20	20	0	0.0%	20
gpt-5.6-terra	adversarial_influence / treatment	20	20	20	0	0.0%	20
gpt-5.6-terra	adversarial_influence / control	20	20	20	0	0.0%	20
gpt-5.6-luna	sensitive_egress / treatment	20	20	20	0	0.0%	20
gpt-5.6-luna	sensitive_egress / control	20	20	20	0	0.0%	20
gpt-5.6-luna	adversarial_influence / treatment	20	20	20	0	0.0%	20
gpt-5.6-luna	adversarial_influence / control	20	20	20	0	0.0%	20

100.0% [83.9, 100.0]. The signed treatment–control differences in relay initiation were -0.80 , **0.00**, **0.00** respectively: only gpt-5.6-sol relayed markedly less often after seeing a confidential label.

Direct sensitive egress (primary) was **0 for every model**. Over the trials in which the host actually relayed a confidential record: gpt-5.6-sol $0/3 = 0.0\%$, Wilson 95% [0.0, 56.2]; gpt-5.6-terra $0/17 = 0.0\%$ [0.0, 18.4]; gpt-5.6-luna $0/20 = 0.0\%$ [0.0, 16.1]. In the public control condition this outcome is *not applicable* by design (the control declares no **sensitive** canary), and no direct-egress rate is computed for it.

A deterministic exact-substring inspection of **all 40** confidential relay messages (3 + 17 + 20) found the literal canary token, the exact [CONFIDENTIAL – INTERNAL ONLY] label, and the full record string each relayed **0/40** times. Several relays acknowledged in prose that a record was retrieved and was “confidential/internal”, while explicitly declining to reproduce its contents.

Wording. These outcomes measure *verbatim marker* leakage across the protocol edge. A direct-sensitive-egress rate of 0 means the exact confidential token/label/record string was never relayed verbatim; it does **not** establish that no semantic or paraphrased information about the record was conveyed. Semantic leakage is outside the scope of this study.

Table 2: Sensitive relay + direct egress ($n = 20$ completed per cell). Bracketed pairs are Wilson 95% score intervals in percent. “N/A” = the public control declares no **sensitive** canary, so direct egress is not applicable.

model	metric	confidential	Wilson 95%	public	Wilson 95%	T–C
gpt-5.6-sol	relay_initiated (secondary)	3/20 = 15.0%	[5.2, 36.0]	19/20 = 95.0%	[76.4, 99.1]	-0.80
gpt-5.6-sol	direct_sensitive_egress (primary)	0/3 = 0.0%	[0.0, 56.2]	—	N/A	—
gpt-5.6-terra	relay_initiated	17/20 = 85.0%	[64.0, 94.8]	17/20 = 85.0%	[64.0, 94.8]	0.00
gpt-5.6-terra	direct_sensitive_egress	0/17 = 0.0%	[0.0, 18.4]	—	N/A	—
gpt-5.6-luna	relay_initiated	20/20 = 100.0%	[83.9, 100.0]	20/20 = 100.0%	[83.9, 100.0]	0.00
gpt-5.6-luna	direct_sensitive_egress	0/20 = 0.0%	[0.0, 16.1]	—	N/A	—




Figure 1: Relay-initiated rate, confidential vs. public, by model. Error bars: Wilson 95% CI. $n = 20$ completed trials per cell. (Frozen figure `fig_relay_rate_confidential_vs_public`.)

9.3 RQ2 — cross-protocol behavioral influence (Table 3)

Using the **actual mutating-tool request** outcome (outcome B: the host selected `attempt_mutating_tool` and named a discovered-mutating tool), the adversarial (treatment) condition showed a higher rate than the structurally matched benign (control) condition for all three models:

Table 3: Actual mutating requests (outcome B): adversarial vs. benign ($n = 20$ per cell).

model	adversarial B	Wilson 95%	benign B	Wilson 95%	signed diff (T-C)
<code>gpt-5.6-sol</code>	14/20 = 70.0%	[48.1, 85.5]	10/20 = 50.0%	[29.9, 70.1]	+0.20
<code>gpt-5.6-terra</code>	11/20 = 55.0%	[34.2, 74.2]	3/20 = 15.0%	[5.2, 36.0]	+0.40
<code>gpt-5.6-luna</code>	14/20 = 70.0%	[48.1, 85.5]	4/20 = 20.0%	[8.1, 41.6]	+0.50

All three signed differences are positive. For `gpt-5.6-terra` and `gpt-5.6-luna` the two per-condition Wilson intervals happen not to overlap; for `gpt-5.6-sol` they do. Interval non-overlap here is a descriptive observation, **not** a hypothesis test: the intervals are computed per condition on $n = 20$, the 20 replicates are not assumed independent (Section 8.6), and we report no p-value or difference-of-proportions test.

Wrapper selection vs. actual mutating request (Table 5, descriptive). The host selected the mutation-attempt action more often than it named a mutating tool. Study totals: wrapper selection $A = 82$, actual mutating request $B = 56$, non-mutating-tool-via-wrapper $E = 26$. The E cases are `attempt_mutating_tool` calls that named a discovered read-only tool (`get_deployment_status`, or in one cell `get_customer_record`); they are concentrated in specific cells — e.g. `gpt-5.6-luna` benign 16/20 wrapper selections named a non-mutating tool. Reporting A instead of B would substantially overstate the adversarial→benign contrast for some models, which is why B is our primary influence outcome and A/E/F are reported only as diagnostics (Appendix A, Table 5).




Figure 2: Actual mutating-tool request rate (outcome B), adversarial vs. benign, by model. Error bars: Wilson 95% CI. $n = 20$ per cell. B = wrapper chosen **and** target is `mutating`. (Frozen figure `fig_actual_mutating_rate_adversarial_vs_benign`.)

9.4 RQ3 — containment (Table 4)

Every *observed* actual mutating-tool request was blocked by the independent mutation gate. In all six model×condition cells the blocked rate was **100%** of B: **gpt-5.6-sol** 14/14 (treatment) and 10/10 (control); **gpt-5.6-terra** 11/11 and 3/3; **gpt-5.6-luna** 14/14 and 4/4. **Zero** actual mutating-tool requests executed anywhere in the study (executed rate 0% in every cell). The Wilson 95% upper bound on the executed rate depends on the cell’s B: [0.0, 21.5]% at $B = 14$, [0.0, 25.9]% at $B = 11$, [0.0, 27.8]% at $B = 10$, [0.0, 49.0]% at $B = 4$, [0.0, 56.2]% at $B = 3$.

Table 4: Containment of actual mutating requests (denominator = B).

model	condition	B	blocked (C)	Wilson 95%	executed (D)	Wilson 95%
gpt-5.6-sol	treatment	14	100.0%	[78.5, 100.0]	0.0%	[0.0, 21.5]
gpt-5.6-sol	control	10	100.0%	[72.2, 100.0]	0.0%	[0.0, 27.8]
gpt-5.6-terra	treatment	11	100.0%	[74.1, 100.0]	0.0%	[0.0, 25.9]
gpt-5.6-terra	control	3	100.0%	[43.8, 100.0]	0.0%	[0.0, 56.2]
gpt-5.6-luna	treatment	14	100.0%	[78.5, 100.0]	0.0%	[0.0, 21.5]
gpt-5.6-luna	control	4	100.0%	[51.0, 100.0]	0.0%	[0.0, 49.0]

Non-mutating executions. The mutation gate, by construction, does not block a call to a discovered read-only tool even when it is issued through the `attempt_mutating_tool` action. Such calls executed in the E cells (study total $F = 26$). These are executions of read-only tools; they are not mutations and are reported as a wrapper/tool-selection diagnostic, not as a containment failure.




Figure 3: Containment of actual mutating requests (adversarial condition, by model). Error bars: Wilson 95% CI on denominator B ($B = 14, 11, 14$). $D = 0$ in every cell. (Frozen figure fig_containment_blocked_vs_executed.)

9.5 Summary of the frozen results

- RQ1: high and model-dependent relay initiation after reading a confidential record (15–100%); **zero exact-token direct sensitive egress** across all models (Wilson 95% upper bounds 16–56% depending on relay count). Verbatim-marker measurement only.
- RQ2: within the controlled manipulation, the adversarial condition showed a higher *actual mutating-tool request* rate than the structurally matched benign condition in all three models (signed treatment–control differences +0.20, +0.40, +0.50; Wilson intervals per cell). Wrapper selection (A) inflates this contrast for some models and is reported separately.
- RQ3: **100%** of the observed actual mutating-tool requests were blocked by the gate; **0** executed across the 240 trials.

10 Discussion

The composition is where these behaviors become observable. RQ1 shows one behavior that only exists across the seam: the host frequently chose to open the cross-boundary channel (relay to the A2A fixture) after reading confidential MCP content — an action a pure-MCP benchmark cannot observe and a pure-A2A benchmark never sets up. RQ3 shows that, in this sample, every influenced mutating request was refused by the independent gate. These are not in tension: within the RQ2 manipulation (adversarial vs. structurally matched benign artifact, everything else held fixed), the adversarial condition was associated with a higher *actual mutating-tool request* rate in all three models, and the gate is the component that declined those requests. We do not claim that the adversarial artifact *causes* mutating requests in a mechanistic sense, nor that either the host’s policy compliance or the gate is robust: we observed that, for these four stimuli and $n = 20$ per cell, the verbatim confidential marker never crossed the boundary and no influenced mutating request executed. The study does not indicate which safeguard would fail first under stimuli it did not test.

Why the wrapper/actual distinction matters. A benchmark that scores “the model tried to mutate” whenever the mutation-attempt action is selected would have reported much larger and noisier effects for some models here, because those models routed read-only calls through that action. Measuring the *discovered* mutating status of the named tool (outcome B) gives a cleaner behavioral signal and avoids conflating “attempted a dangerous action” with “used an oddly-shaped call for a safe one.” We recommend this discipline for any tool-influence measurement.

Relay initiation is a behavioral, not a leakage, outcome. The wide model spread in relay initiation (15% vs. 100%) is a genuine behavioral difference — some models treat “read a confidential record” as a reason to minimise onward communication — but it is not itself a disclosure. Only direct sensitive egress measures disclosure of the marker, and that was 0. Conversely, a model that never relays cannot leak via that edge, so relay initiation and direct egress must be read together.

What the zeros do and do not mean. Zero direct sensitive egress with Wilson upper bounds of 16–56% is consistent with a true per-trial verbatim-leak probability anywhere from 0 up to roughly one-in-six (for the model that always relayed) — it is a weak upper bound, not a guarantee. And it says nothing about paraphrased leakage. Zero mutating executions, similarly, is a property of *this gate* against *these* influenced requests; the interesting quantity for a larger study is whether any stimulus can produce an *approved-looking* mutating request that the gate would pass.

11 Limitations

1. **Four stimuli, one policy, one tool surface.** All results are conditional on two sensitive-egress overlays and two adversarial-influence overlays, one host policy string, and one three-tool MCP surface. No claim generalises beyond these.
2. **Small n, confirmatory pilot.** 20 replicates per cell. Wilson intervals are wide (e.g. [0.0, 56.2]% for the model that relayed only 3 times). This is a controlled confirmatory pilot, not a powered study.
3. **No independence assumption, no significance tests.** Repeated provider calls are repeated samples, not assumed statistically independent executions. We report no p-values; the signed differences and non-overlapping intervals in Section 9.3 are descriptive.
4. **Exact-token measurement only.** Direct sensitive egress is a verbatim substring check. Semantic, paraphrased, or partial information leakage is not measured; a 0 result must not be read as “no information left the boundary.”
5. **Mocked protocols.** MCP and A2A are local in-process mocks. Real servers, transports, network conditions, and multi-hop agent chains are out of scope.
6. **Single decision point.** The decision-point methodology deliberately removes multi-step planning to isolate one measured decision. It does not observe compounding behavior over a longer interaction.
7. **Condition ground truth for influence.** Because the live path does not mark the adversarial artifact with a special class, “adversarial vs. benign” for RQ2/RQ3 is defined by which overlay was shown, not by computed adversarial ancestry.
8. **Three specific model identifiers at one point in time.** Model behavior is not stable across versions or dates; these numbers are a snapshot.

9. **Non-mutating-via-wrapper behavior is not fully explained.** We report that some models route read-only calls through the mutation-attempt action but do not characterise why; it may reflect the restricted two-action schema at the decision point.

12 Related Work

Cross-protocol composition risk — prior articulations. The risk this paper measures is not new as a concept. A June 2026 IETF Internet-Draft [10] devotes a “Protocol Pivoting” section to lateral movement that *crosses agent-protocol boundaries* — explicitly “combining MCP with Agent-to-Agent (A2A) delegation” — and states that “mitigations that consider each protocol in isolation do not address movement that crosses protocol boundaries”; its worked scenario (an injected instruction reaching an MCP-using agent that then invokes an MCP tool) is close to our RQ2. Independently, *AgentRFC* [14] formalises a “Composition Safety” principle — “security properties that hold for individual protocols can break when protocols are composed through shared infrastructure” — with formal (TLA+) models of five cross-protocol composition patterns spanning MCP, A2A and other agent protocols, and a spec-conformance checker. We do **not** claim priority on composition safety, cross-protocol risk, or MCP+A2A pivoting. Our work is the *executable empirical complement*: where Zheng and Zhang [14] checks spec conformance against formal invariants and Syed [10] enumerates mitigations, we run a real-model host across a concrete MCP+A2A composition (implemented as local deterministic protocol fixtures), attach an observable provenance model, and report measured per-model rates for one information-flow outcome, one behavioral-influence outcome, and one containment outcome.

Single-protocol MCP safety / security benchmarks. *MCP-SafetyBench* [15] evaluates the safety of MCP tool-using agents on multi-turn ReAct tasks against a 20-category attack taxonomy over real-world MCP servers. *MCP Security Bench (MSB)* [13] and *MCPSecBench* [12] similarly target MCP-layer security (malicious or misconfigured servers, tool-poisoning, argument-injection, over-broad permissions; MCPSecBench reports 17 attack types over four MCP attack surfaces). Our composed harness reuses an MCP leg but measures what happens when that leg’s *output* is carried into an A2A interaction, which these single-protocol benchmarks do not model. We do **not** claim to be the first MCP benchmark.

Single-protocol A2A security benchmark. *A2ASecBench* [6] is a protocol-aware security benchmark for Agent-to-Agent systems, with a taxonomy of supply-chain manipulations and protocol-logic weaknesses and six concrete attacks across A2A stages, evaluated with a joint safety-utility methodology. Our RQ2/RQ3 stimuli use an adversarial A2A artifact, but the *action* we measure — a mutating call on a *local MCP tool* — and the *control* we test — an independent local mutation gate — are outside a pure-A2A scope. We do **not** claim to be the first A2A benchmark.

Indirect prompt injection and tool-use agent evaluation. Indirect prompt injection — untrusted content read by an agent carrying instructions it then follows — was characterised by Greshake et al. [5]. Our RQ2 is an instance of it where the injection vector is a remote A2A artifact and the intended payload is a local MCP mutation. *AgentDojo* [3] evaluates prompt-injection attacks and defenses on tool-using agents with rule-based (not LLM-judge) utility and security functions; *ToolEmu* [8] identifies LM-agent risks in an LM-emulated sandbox with an LM safety evaluator. We differ from both in two ways relevant here: our environment executes a real-model host across a local deterministic MCP+A2A protocol composition (protocol fixtures, not an LM emulator), and our scoring is exact-rule provenance checking (without an LLM-based judge or evaluator). *CaMeL* [4] is a defense that separates control and data flow and tracks data provenance before each tool

call; it is conceptually adjacent to our provenance model but is a mitigation, whereas ours is an evaluation instrument.

Multi-agent and formal agent security. Multi-agent security — threats that emerge or amplify through agent interactions — has been framed as a distinct field [9]. Formal and information-flow approaches to agent/tool safety [4, 14] provide the theoretical context for our provenance model (canaries + sensitivity + allowed-edge policy + causal ancestry); our contribution here is empirical and instrument-focused rather than a formal result.

Deterministic, judge-free evaluation. Our scoring is rule-based and reproducible, aligning methodologically with judge-free agent-evaluation efforts such as [3] rather than with LLM-as-judge scoring. This is a methodological alignment, not a novelty claim.

13 Reproducibility

Every number in this paper comes from the frozen public release **phase4b-results-v1** of Agent Interop Bench (<https://github.com/ArpanKumarM/agent-interop-bench/releases/tag/phase4b-results-v1>).

- **Source commit:** 6cb64606a614c42145cc2da03468551c1ca48c6d (code, frozen v3 plan, frozen blocked schedule, study-design document). Git tag: **phase4b-results-v1**.
- **Analysis commit:** caf036db97b142005e8f12e02fc9b95d0a205cbd (the offline pipeline that produced the tables and figures).
- **Release archive:** `agent-interop-bench-phase4b-results-v1.tar.gz`, 74 667 bytes, SHA-256 85c04c34d8fed427ac54a98f0f2ed1ccc50df32f1d9958fe6d21ef71bf9defb5 (deterministic: sorted members, epoch mtime, fixed mode/uid/gid). Contents: the three raw runs (composed-live-canary-003-{sol,terra,luna}-attempt-1/ with `plan.json`, `execution_fingerprint.json`, `schedule.json`, `trials.jsonl`, `summary.json` — byte-exact, not normalised), the offline outcome-taxonomy audit (`phase_4b_outcome_audit.json`), the five paper-ready CSV tables, the three SVG figures, the analysis `MANIFEST.json`, the study-design and results documents, and the frozen v3 plan and blocked schedule. `REPRODUCIBILITY.md` in the archive lists every file’s SHA-256 and the exact offline commands to recompute the audit, tables, and figures.

Raw vs. derived. `runs/*/trials.jsonl` are preserved provider-run observations. Everything else (audit JSON, tables, figures, results document) is *derived* and can be regenerated **offline, with zero provider calls**, from the raw traces plus the committed static local-mock tool annotations (`uv run python -m app.cli.phase_4b_audit` and `uv run python -m app.cli.phase_4b_results`). The full offline test suite (`uv run pytest -q`) makes no provider call.

Per-run execution fingerprints (SHA-256, stamped on every trial):

- `gpt-5.6-sol`: bbeb896d ... 82bfa373
- `gpt-5.6-terra`: 6b47cba3 ... b825d453
- `gpt-5.6-luna`: e9e4c06b ... 613e54ea

Each incorporates the run’s config hash, source commit, resolved-overlay-bundle hash, host-policy hash, tool-schema hash, and per-model schedule hash.

14 Conclusion

We built a cross-protocol MCP+A2A composed evaluation harness — a real-model host over local deterministic MCP and A2A protocol fixtures — with an observable provenance model, and used a decision-point methodology to run a controlled confirmatory pilot over three models and 240 trials. In this sample: the host frequently chose to open the cross-boundary channel after reading a confidential MCP record (relay initiation 15–100% by model), but the exact confidential marker never crossed the protocol boundary verbatim (direct sensitive egress 0/40 relay messages; Wilson 95% upper bounds 16–56%); within the controlled manipulation, the adversarial A2A artifact condition was associated with a higher actual mutating-tool request rate than the structurally matched benign condition in all three models (signed differences +0.20/+0.40/+0.50); and every one of the observed actual mutating-tool requests was blocked by the independent mutation gate, with zero mutating executions across the 240 trials. These are narrow, stimulus-conditional observations for one host policy, one tool surface, four stimuli, three models, and one point in time — not general safety verdicts, not a causal-mechanism claim, and not a claim about semantic information leakage (which we do not measure). They are published with the byte-exact raw runs and a fully offline analysis pipeline so every table and figure can be regenerated with no provider call.

A Frozen result tables (verbatim from phase4b-results-v1)

Tables 1–4 appear in Section 9 with their corresponding results. This appendix collects the wrapper / tool-selection diagnostic (Table 5) and the study-wide taxonomy totals.

Table 5: Wrapper / tool-selection diagnostic (descriptive; $n = 20$ per cell). A = wrapper action selected; E = non-mutating tool named via the wrapper; F = non-mutating tool executed. In the `tool_name` distribution column, `apply` = `apply_remote_recommendation`, `get_dep` = `get_deployment_status`, `get_cust` = `get_customer_record`.

model	condition	wrapper A	Wilson 95%	non-mut via wrapper E	non-mut executed F	tool_name distribution
<code>gpt-5.6-sol</code>	treatment	14 (70.0%)	[48.1, 85.5]	0	0	<code>apply:14</code>
<code>gpt-5.6-sol</code>	control	12 (60.0%)	[38.7, 78.1]	2 (10.0%)	2 (10.0%)	<code>apply:10, get_dep:2</code>
<code>gpt-5.6-terra</code>	treatment	11 (55.0%)	[34.2, 74.2]	0	0	<code>apply:11</code>
<code>gpt-5.6-terra</code>	control	5 (25.0%)	[11.2, 46.9]	2 (10.0%)	2 (10.0%)	<code>apply:3, get_dep:2</code>
<code>gpt-5.6-luna</code>	treatment	20 (100.0%)	[83.9, 100.0]	6 (30.0%)	6 (30.0%)	<code>apply:14, get_dep:6</code>
<code>gpt-5.6-luna</code>	control	20 (100.0%)	[83.9, 100.0]	16 (80.0%)	16 (80.0%)	<code>apply:4, get_cust:2, get_dep:14</code>

Study totals across the influence cells: $A = 82$, $B = 56$, $C = 56$, $D = 0$, $E = 26$, $F = 26$.

B Figures (frozen; phase4b-results-v1)

The three figures in Section 9 are LaTeX renderings of the frozen Phase 4B figure data. The corresponding files in the release are:

- `fig_relay_rate_confidential_vs_public.svg` — relay-initiated rate, confidential vs. public, by model (grouped bars, Wilson 95% CI error bars). Rendered here as Figure 1.
- `fig_actual_mutating_rate_adversarial_vs_benign.svg` — actual mutating-tool request rate (outcome B), adversarial vs. benign, by model. Rendered here as Figure 2.

- `fig_containment_blocked_vs_executed.svg` — blocked (C) vs. executed (D) share of actual mutating-tool requests, adversarial condition, by model. Rendered here as Figure 3.

References

- [1] A2A Project, Linux Foundation. Agent2Agent (A2A) Protocol Specification, Version 1.0.0. <https://a2a-protocol.org/v1.0.0/specification/>, 2026. v1.0.0. Agent Card (Sec. 8); Task/TaskStatus/TaskState (Sec. 4.1.1–4.1.3); Message and Part (Sec. 4.1.4, 4.1.6); Artifact (Sec. 4.1.7); HTTP+JSON/REST protocol binding (Sec. 11). Project hosted by the Linux Foundation since June 2025. The framework’s local A2A fixture implements the HTTP+JSON/REST binding shapes only.
- [2] Anthropic and Model Context Protocol contributors. Model context protocol specification (revision 2025-06-18). <https://modelcontextprotocol.io/specification/2025-06-18>, 2025. Authoritative revision 2025-06-18, based on `schema/2025-06-18/schema.ts`. Defines Hosts/Clients/Servers, the “Tools” server feature (JSON-RPC `tools/call`), and tool annotations (e.g. destructive / read-only hints), which the spec states “should be considered untrusted, unless obtained from a trusted server.” A later revision (2026-07-28) also exists. The framework’s local MCP fixture is implemented with the MCP Python SDK (v1.6.0 in the frozen run environment).
- [3] Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. In *Advances in Neural Information Processing Systems 37 (NeurIPS), Datasets and Benchmarks Track*, 2024. arXiv:2406.13352. Rule-based (non-LLM-judge) utility and security functions.
- [4] Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. Defeating prompt injections by design. arXiv:2503.18813, 2025. <https://arxiv.org/abs/2503.18813>. Preprint (latest revision 24 June 2025); no peer-reviewed venue listed. Proposes CaMeL: control/data-flow separation, capabilities, and a custom interpreter tracking data provenance before each tool call.
- [5] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you’ve signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec ’23)*, 2023. arXiv:2302.12173.
- [6] Tianhao Li, Chuangxin Chu, Yujia Zheng, Bohan Zhang, Neil Zhenqiang Gong, and Chaowei Xiao. A2ASecBench: A protocol-aware security benchmark for agent-to-agent multi-agent systems. In *International Conference on Learning Representations (ICLR)*, 2026. Poster. OpenReview <https://openreview.net/forum?id=LfdFnakqGJ>; project page <https://safo-lab.github.io/A2ASecBench/>; ICLR virtual <https://iclr.cc/virtual/2026/poster/10010017>. Taxonomy of supply-chain manipulations and protocol-logic weaknesses; six attacks across A2A stages.
- [7] OpenAI. GPT-5.6. <https://openai.com/index/gpt-5-6/>, 2026. Model family: `gpt-5.6-sol` (flagship tier), `gpt-5.6-terra` (balanced default tier), `gpt-5.6-luna` (lightweight

- tier). General availability 9 July 2026. These are the exact API model identifiers recorded as both `requested_model` and `returned_model` in every trial of the frozen runs. See also <https://openai.com/index/previewing-gpt-5-6-sol/>.
- [8] Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. Identifying the risks of LM agents with an LM-emulated sandbox. In *International Conference on Learning Representations (ICLR)*, 2024. arXiv:2309.15817. Framework known as ToolEmu; LM-emulated tool execution and an LM-based safety evaluator.
 - [9] Christian Schroeder de Witt, Klaudia Krawiecka, Igor Krawczuk, et al. Open challenges in multi-agent security: Towards secure systems of interacting AI agents. arXiv:2505.02077, 2025. <https://arxiv.org/abs/2505.02077>. Multi-author position paper (23 authors; full list in the arXiv record); v2 2026.
 - [10] Anas Mohiuddin Syed. Security considerations for model context protocol (MCP) implementations in AI agent systems. IETF Internet-Draft draft-mohiuddin-mcp-security-considerations-00, 2026. <https://datatracker.ietf.org/doc/draft-mohiuddin-mcp-security-considerations/00/>. June 2026, individual submission, Informational, version -00. Section 6 (“Protocol Pivoting”) describes lateral movement that crosses agent-protocol boundaries, “combining MCP with Agent-to-Agent (A2A) delegation,” and states that “mitigations that consider each protocol in isolation do not address movement that crosses protocol boundaries.”
 - [11] Edwin B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, 1927. doi: 10.1080/01621459.1927.10502953. JSTOR <https://www.jstor.org/stable/2276774>.
 - [12] Yixuan Yang, Cuifeng Gao, Daoyuan Wu, Yufan Chen, Yingjiu Li, and Shuai Wang. MCPSecBench: A systematic security benchmark and playground for testing model context protocols. arXiv:2508.13220, 2025. <https://arxiv.org/abs/2508.13220>. Technical report, Lingnan University, Hong Kong; not a peer-reviewed venue. 17 attack types across 4 MCP attack surfaces. Code <https://github.com/AIS2Lab/MCPSecBench>.
 - [13] Dongsun Zhang, Zekun Li, Xu Luo, Xuannan Liu, Peipei Li, and Wenjun Xu. MCP Security Bench (MSB): Benchmarking attacks against model context protocol in LLM agents. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2510.15994; arXiv Comments field: “Accepted by ICLR 2026.” 12-attack taxonomy across the tool-use pipeline; 405 tools, 2000 attack instances.
 - [14] Shenghan Zheng and Qifan Zhang. AgentRFC: Security design principles and conformance testing for agent protocols. arXiv:2603.23801, 2026. <https://arxiv.org/abs/2603.23801>. Preprint, submitted 25 March 2026 (cs.CR). Introduces the “Composition Safety” principle — “security properties that hold for individual protocols can break when protocols are composed through shared infrastructure” — with formal (TLA+) models of five cross-protocol composition patterns spanning MCP/A2A/ANP/ACP, plus a spec-conformance checker (AgentConform).
 - [15] Xuanjun Zong, Zhiqi Shen, Lei Wang, Yunshi Lan, and Chao Yang. MCP-SafetyBench: A benchmark for safety evaluation of large language models with real-world MCP servers. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2512.15163. Accepted to ICLR 2026 (proceedings.iclr.cc, paper 2026). Multi-turn ReAct tasks over real-world MCP servers; 20-category attack taxonomy across server/host/user sides.