


4 Agenda	-> Calculator Basic
	- Lists and anays in fy man
	-> Intro to Online Judges

- console In fy than to break a loof in between break? - segward

Wec	an haue	rested	looks.	so who	m cue coril	a break,
			1			
£ 1	brenks	tho	nianiat	lo coh	always_	
• 1		, ~		. 7		

Les for taking multiple input in same line, you need to use lists or use you can take the whole unkert in Stoing & use Split femction


F13 default -> s paus  $\epsilon$ 12 . tuell split he string based 24



) -> if we don't pass anything it | treates it as "1" (space ch O menure chaleur cue pars con una stoig

```
> checks the condut -> True
        pri<del>nt(m</del>enu)
        operator = input()
        print("Please enter two valid inputs to perform ", operator, " operations"
        a = int(input())
        b = int(input())
        if operator == '+':
            print("Output is ", a+b)
        elif operator == '-':
21
22
23
24
25
26
28
29
30
            print("Output is ", a-b)
        elif operator == '*':
            print("Output is ", a*b)
        elif operator == '/':
            print("Output is ", a/b)
        elif operator == '**':
            print("Output is ", a**b)
        elif operator == '%':
            print("Output is ", a%b)
31
32
33
34
35
36
       else:
            print("Invalid operation!!!")
        print("Do you want to continue ?? If yes then write -> Y/y/Yes/yes")
        again = input()
          not lagain == 'Y' or again == 'Yes' or again == 'y' or again == 'yes'):
           (break)) break always breaks the nearest loop in case of nested
```

112,37 [41,67 Ls (Lials) in by than to aways in by then dists are alturate array means homogenous collection By default the word of clements But lists genes you all the feature of arrays & 1225 are helirogenous [], "sanket", 2.3....] Sefer [[], [], 2,3)



10, 20, 4.9 [10,20,30]

