

EDS Lab Assignment 2

Practical 4

Name:-Arpit Pramod Patil

PRN-202501040075

Division:-CS1

Batch:-C14

Practice Lab Assignment

4.1.1 Pandas – Series Creation Manipulation

Problem statement :

Write a Python program that takes a list of numbers from the user, creates a Pandas series from it, and then calculates the mean of even and odd numbers separately using the groupby and mean() operations.

Hint: You can group the Series based on whether each number is even or odd.

Input Format:

- The user should enter a list of numbers separated by space when prompted.

Output Format:

- The program should display the mean of even and odd numbers separately.
- Each mean value should be displayed with a label indicating whether it corresponds to even or odd numbers.

CODE :

```
import pandas as pd

# Take inputs from the user to create a list of numbers
numbers = list(map(int, input().split()))

# Create a Pandas series from the list of numbers
df=pd.Series(numbers)

# Grouping by even and odd numbers and calculating the mean
grouped = df.groupby(df % 2 == 0).mean()

# Display the mean of even and odd numbers with labels
grouped.index = ['Even' if is_even else 'Odd' for is_even in grouped.index]

print("Mean of even and odd numbers:")

print(grouped)
```

OUTPUT :

Average time
0.011 s
10.67 ms

Maximum time
0.026 s
26.00 ms

3 out of 3 shown test case(s) passed
3 out of 3 hidden test case(s) passed

Test case 1 26 ms Debug

Expected output
1 2 3 4 5 6 7 8 9 10
Mean of even and odd numbers:
Odd: 5.0
Even: 6.0
dtype: float64

Actual output
1 2 3 4 5 6 7 8 9 10
Mean of even and odd numbers:
Odd: 5.0
Even: 6.0
dtype: float64

Test case 2 8 ms Debug

Expected output
4 4 4 6 6 2 2 2 10 12 14 16
Mean of even and odd numbers:
Even: 6.833333
dtype: float64

Actual output
4 4 4 6 6 2 2 2 10 12 14 16
Mean of even and odd numbers:
Even: 6.833333
dtype: float64

Test case 3 8 ms Debug

Expected output
1 5 7 9 11 13 15 17 111 21 25
Mean of even and odd numbers:
Odd: 21.363636
dtype: float64

Actual output
1 5 7 9 11 13 15 17 111 21 25
Mean of even and odd numbers:
Odd: 21.363636
dtype: float64

4.1.2 Dictionary Data frame

Problem statement :

A dictionary of lists has been provided to you in the editor. Create a DataFrame from the dictionary of lists and perform the listed operations, then display the DataFrame before and after each manipulation.

Create the DataFrame:

- Convert the dictionary to a Pandas DataFrame.

Add a new row:

- Take inputs from the user for the new row data (name, age).
- Add the new row to the DataFrame.
- Display the DataFrame after adding the new row.

Modify a row:

- Modify a specific row by changing the age. Take the row index and new age value from the user.
- Display the DataFrame after modifying the row.

Delete a row:

- Take the row index to be deleted from the user.
- Remove the specified row.
- Display the DataFrame after deleting the row.

Add a new column:

- Add a column **Gender** with values taken from the user.
- Display the DataFrame after adding the new column.

Modify a column:

- Convert names to uppercase.
- Display the DataFrame after modifying the column.

Delete a column:

- Remove the **Age** column.
- Display the DataFrame after deleting the column.

CODE :

```
import pandas as pd
```

```

# Provided dictionary of lists
data = {
    'Name': ['Alice', 'Bob', 'Charlie'],
    'Age': [25, 30, 35],
}

# Convert the dictionary to a DataFrame
df = pd.DataFrame(data)

# Display the original DataFrame
print("Original DataFrame:")
print(df)

# Adding a new row
new_name=input("New name: ")
new_age=int(input("New age: "))
df.loc[len(df)]=[new_name,new_age]

# Display the DataFrame after adding a new row
print("After adding a row:\n",df)

# Modifying a row
row_modify=int(input("Index of row to modify: "))
new_age_value=int(input("New age: "))
df.at[row_modify,"Age"]=new_age_value

# Display the DataFrame after modifying a row
print("After modifying a row:")
print(df)

# Deleting a row
delete_index=int(input("Index of row to delete: "))
df=df.drop(index=delete_index).reset_index(drop=True)

# Display the DataFrame after deleting a row
print("After deleting a row:")

```

```
print(df)

# Adding a new column

genders_add=input("Enter genders separated by space: ").split()

df["Gender"]=genders_add

# Display the DataFrame after adding a new column

print("After adding a new column:")

print(df)

# Modifying a column

df['Name']=df['Name'].str.upper()

# Display the DataFrame after modifying a column

print("After modifying a column:")

print(df)

# Deleting a column

df=df.drop('Age',axis=1)

# Display the DataFrame after deleting a column

print("After deleting a column:")

print(df)
```

OUTPUT :

Average time

0.103 s

103.50 ms



Maximum time

0.120 s

120.00 ms



✓ 1 out of 1 shown test case(s) passed

✓ 1 out of 1 hidden test case(s) passed

✓ Test case 1 120 ms

Debug



Expected output

Original DataFrame:

.....Name..Age

0....Alice...25

1.....Bob...30

2..Charlie...35

New name: Susan

New age: 29

After adding a row:

.....Name..Age

0....Alice...25

1.....Bob...30

2..Charlie...35

3....Susan...29

Index of row to modify: 0

New age: 27

After modifying a row:

.....Name..Age

0....Alice...27

1.....Bob...30

2..Charlie...35

3....Susan...29

Actual output

Original DataFrame:

.....Name..Age

0....Alice...25

1.....Bob...30

2..Charlie...35

New name: Susan

New age: 29

After adding a row:

.....Name..Age

0....Alice...25

1.....Bob...30

2..Charlie...35

3....Susan...29

Index of row to modify: 0

New age: 27

After modifying a row:

.....Name..Age

0....Alice...27

1.....Bob...30

2..Charlie...35

3....Susan...29

Index of row to delete: 3

After deleting a row:

```
.....Name..Age
```

```
0....Alice...27
```

```
1.....Bob...30
```

```
2..Charlie...35
```

Enter genders separated by space:

```
· F M M
```

After adding a new column:

```
.....Name..Age..Gender
```

```
0....Alice...27.....F
```

```
1.....Bob...30.....M
```

```
2..Charlie...35.....M
```

After modifying a column:

```
.....Name..Age..Gender
```

```
0....ALICE...27.....F
```

```
1.....BOB...30.....M
```

```
2..CHARLIE...35.....M
```

After deleting a column:

```
.....Name..Gender
```

```
0....ALICE.....F
```

```
1.....BOB.....M
```

```
2..CHARLIE.....M
```

Index of row to delete: 3

After deleting a row:

```
.....Name..Age
```

```
0....Alice...27
```

```
1.....Bob...30
```

```
2..Charlie...35
```

Enter genders separated by space:

```
· F M M
```

After adding a new column:

```
.....Name..Age..Gender
```

```
0....Alice...27.....F
```

```
1.....Bob...30.....M
```

```
2..Charlie...35.....M
```

After modifying a column:

```
.....Name..Age..Gender
```

```
0....ALICE...27.....F
```

```
1.....BOB...30.....M
```

```
2..CHARLIE...35.....M
```

After deleting a column:

```
.....Name..Gender
```

```
0....ALICE.....F
```

```
1.....BOB.....M
```

```
2..CHARLIE.....M
```

4.1.3 Student information :

Problem statement :

Write a program to read a text file containing student information (name, age, and grade) using Pandas. Perform the following tasks:

- Display the first five rows of the data frame.
- Calculate the average age of the students (limit the average age up to 2 decimal places).

- Filter out the students who have a grade above a certain threshold (consider the threshold grade is 'B').

CODE :

```
import pandas as pd

# Read the text file into a DataFrame

file = input()

data = pd.read_csv(file, sep="\s+", header=None, names=["Name", "Age", "Grade"])

print("First five rows:")

print(data.head())

average_age = round(data["Age"].mean(),2)

print(f"Average age: {average_age}")

# write your code here..

filtered_students = data[data["Grade"] <="B"]

print("Students with a grade up to B")

print(filtered_students)
```

OUTPUT :

Lab Assignment :

4.2.1 Month with highest total sales

Average time
0.069 s
68.60 ms

Maximum time
0.101 s
101.00 ms

✓ 1 out of 1 shown test case(s) passed
✓ 1 out of 1 hidden test case(s) passed

✓ Test case 1 101 ms Debug

Expected output
Actual output

studentdata.txt
studentdata.txt

First five rows:
First five rows:

...Name...Age...Grade
...Name...Age...Grade

0..John...25.....A
0..John...25.....A

1..Alin...22.....B
1..Alin...22.....B

2..Emma...24.....A
2..Emma...24.....A

3..Mike...23.....C
3..Mike...23.....C

4..Sony...21.....B
4..Sony...21.....B

Average age: 23.29
Average age: 23.29

Students with a grade up to B
Students with a grade up to B

...Name...Age...Grade
...Name...Age...Grade

0..John...25.....A
0..John...25.....A

1..Alin...22.....B
1..Alin...22.....B

2..Emma...24.....A
2..Emma...24.....A

4..Sony...21.....B
4..Sony...21.....B

5..Amia...26.....A
5..Amia...26.....A

Problem statement :

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by Month and calculate the total sales for each month.
- Find the month with the highest total sales and display it.
- Also, display the total sales for the best month.

CODE :

```
import pandas as pd

# Prompt the user for the file name
file_name = input()

# Load the data

df = pd.read_csv(file_name)

df["Date"] = pd.to_datetime(df["Date"])

df["Month"] = df["Date"].dt.to_period("M")

df["Total Sales"] = df["Quantity"] * df["Price"]

monthly_sales = df.groupby("Month")["Total Sales"].sum()

best_month = monthly_sales.idxmax()

highest_sales = monthly_sales.max()

print(f"Best month: {best_month}")

print(f"Total sales: ${highest_sales:.2f}")
```

OUTPUT :

Average time

0.059 s

59.00 ms

Maximum time

0.116 s

116.00 ms

✓ 1 out of 1 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 116 ms Debug

Expected output

Actual output

sales_data.csv

sales_data.csv

Best month: 2025-01

Best month: 2025-01

Total sales: \$1210.00

Total sales: \$1210.00

4.2.2 Best Selling Product

Problem statement :

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Find the product that sold the most in terms of quantity sold.
- Display the product that sold the most and the total quantity sold for that product.

CODE :

```
import pandas as pd

# Prompt the user for the file name
file_name = input()

# Load the data
df = pd.read_csv(file_name)

product_sales = df.groupby("Product")["Quantity"].sum()

# Find the product with the highest total quantity sold
best_product = product_sales.idxmax()
```

```
highest_quantity = product_sales.max()

# Display the result

print(f"Best selling product: {best_product}")

print(f"Total quantity sold: {highest_quantity}")
```

OUTPUT :

4.2.3 City that sold the product most :

Problem statement :

Average time
0.033 s
32.67 ms

Maximum time
0.065 s
65.00 ms

✓ 1 out of 1 shown test case(s) passed
✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 65 ms Debug

Expected output	Actual output
sales_data.csv	sales_data.csv
Best selling product: Product A	Best selling product: Product A
Total quantity sold: 23	Total quantity sold: 23

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by City and calculate the total quantity of products sold for each city.
- Find the city that sold the most products (based on the total quantity sold).

CODE :

```
import pandas as pd

# Prompt the user for the file name

file_name = input()

# Load the data

df = pd.read_csv(file_name)
```

```
# write the code..

city_sales = df.groupby("City")["Quantity"].sum()

best_city = city_sales.idxmax()

# Display the result

print(f"City sold the most products: {best_city}")
```

OUTPUT :

4.2.4 Most frequently Sold product Pairs

Problem statement :

Average time 0.047 s 46.67 ms	Maximum time 0.097 s 97.00 ms	✓ 1 out of 1 shown test case(s) passed ✓ 2 out of 2 hidden test case(s) passed
--	--	---

✓ Test case 1 97 ms Debug	
Expected output sales_data.csv City·sold·the·most·products:·Los·Angeles	Actual output sales_data.csv City·sold·the·most·products:·Los·Angeles

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the following columns: Date, Product, Quantity, Price, and City.

- For each date, find all pairs of products that were sold together (i.e., two products sold on the same date).
- Output the product pair/s that was sold most frequently.

CODE :

```
import pandas as pd

from itertools import combinations

from collections import Counter

# Prompt user to input the file name
file_name = input()

# Read data from the specified CSV file
df = pd.read_csv(file_name)

# write the code
grouped = df.groupby("Date")["Product"].apply(list)

# Output the most frequent product pairs
pairs_counter = Counter()

for products in grouped:
    pairs = combinations(sorted(products), 2)
    pairs_counter.update(pairs)

max_frequency = max(pairs_counter.values())

most_common_pairs = [(pair,freq) for pair , freq in pairs_counter.items() if freq ==
max_frequency]

for (product1, product2),frequency in most_common_pairs:
    print(f"{product1} and {product2}: {frequency} times")
```

Output :

4.2.5 Titanic dataset Analysis and Data cleaning

Problem statement :

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset. For

Average time
0.030 s
30.00 ms



Maximum time
0.058 s
58.00 ms



✓ 1 out of 1 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 58 ms   

Expected output	Actual output
sales_data.csv	sales_data.csv
Product A and Product B: 2 times	Product A and Product B: 2 times
Product A and Product C: 2 times	Product A and Product C: 2 times

each question, perform necessary data cleaning, transformations, and calculations as required.

1. Display the first 5 rows of the dataset.
2. Display the last 5 rows of the dataset.
3. Get the shape of the dataset (number of rows and columns).
4. Get a summary of the dataset (using `.info()`).
5. Get basic statistics (mean, standard deviation, etc.) of the dataset using `.describe()`.
6. Check for missing values and display the count of missing values for each column.
7. Fill missing values in the 'Age' column with the median age.
8. Fill missing values in the 'Embarked' column with the most frequent value (`mode()`).
9. Drop the 'Cabin' column due to many missing values.

Create a new column, 'FamilySize' by adding the 'SibSp' and 'Parch' columns.

CODE :

```
import pandas as pd
```

```
import numpy as np
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# 1. Display the first 5 rows of the dataset
```

```
print(data.head())
```

```
# 2. Display the last 5 rows of the dataset
```

```
print(data.tail())
```

```
# 3. Get the shape of the dataset
```

```
print(data.shape)
```

```
# 4. Get a summary of the dataset (info)
```

```
print(data.info())
```

```
# 5. Get basic statistics of the dataset
```

```
print(data.describe())
```

```
# 6. Check for missing values
```

```
print(data.isnull().sum())
```

```
# 7. Fill missing values in the 'Age' column with the median age
```

```
median_age = data['Age'].median()
```

```
data['Age'].fillna(median_age, inplace=True)
```

```
# 8. Fill missing values in the 'Embarked' column with the mode
```

```
mode_Embarked = data['Embarked'].mode()[0]
```

```
data['Embarked'].fillna(mode_Embarked, inplace = True)
```


9. Drop the 'Cabin' column due to many missing values

```
data.drop('Cabin', axis=1, inplace =True)
```

10. Create a new column 'FamilySize' by adding 'SibSp' and 'Parch'

```
data['FamilySize']=data['SibSp'] + data['Parch']
```

OUTPUT :

Average time
0.277 s
277.00 ms



Maximum time
0.277 s
277.00 ms



1 out of 1 shown test case(s) passed

Test case 1 277 ms

Debug

Expected output

Actual output

PassengerId Survived Pclass Fare Cabin Embarked

0 1 0 7.2500 NaN S

1 2 1 71.2833 C85 C

2 3 1 7.9250 NaN S

3 4 1 53.1000 C123 S

4 5 0 8.0500 NaN S

[5 rows x 12 columns]

PassengerId Survived Pclass Fare Cabin Embarked

886 887 0 13.00 NaN S

887 888 1 30.00 B42 S

888 889 0 23.45 NaN S

889 890 1 30.00 C148 C

890 891 0 7.75 NaN Q

[5 rows x 12 columns]

(891, -12)

<class 'pandas.core.frame.DataFrame'>

RangeIndex: 891 entries, 0 to 890

Data columns (total 12 columns):

PassengerId Survived Pclass Fare Cabin Embarked

0 1 0 7.2500 NaN S

1 2 1 71.2833 C85 C

2 3 1 7.9250 NaN S

3 4 1 53.1000 C123 S

4 5 0 8.0500 NaN S

[5 rows x 12 columns]

PassengerId Survived Pclass Fare Cabin Embarked

886 887 0 13.00 NaN S

887 888 1 30.00 B42 S

888 889 0 23.45 NaN S

889 890 1 30.00 C148 C

890 891 0 7.75 NaN Q

[5 rows x 12 columns]

(891, -12)

<class 'pandas.core.frame.DataFrame'>

RangeIndex: 891 entries, 0 to 890

Data columns (total 12 columns):

dtypes: float64(2), int64(5), object(5)	dtypes: float64(2), int64(5), object(5)
memory usage: 66.2+ KB	memory usage: 66.2+ KB
None	None
.....PassengerId....Survived.....Pclass.....SibSp.....Parch.....Fare	PassengerId....Survived.....Pclass.....SibSp.....Parch.....Fare
count.....891.000000....891.000000....891.000000.....891.000000....891.000000....891.000000	count.....891.000000....891.000000....891.000000.....891.000000....891.000000....891.000000
mean.....446.000000....0.383838....2.308642.....0.523008....0.381594....32.204208	mean.....446.000000....0.383838....2.308642.....0.523008....0.381594....32.204208
std.....257.353842....0.486592....0.836071.....1.102743....0.806057....49.693429	std.....257.353842....0.486592....0.836071.....1.102743....0.806057....49.693429
min.....1.000000....0.000000....1.000000.....0.000000....0.000000....0.000000	min.....1.000000....0.000000....1.000000.....0.000000....0.000000....0.000000
25%.....223.500000....0.000000....2.000000.....0.000000....0.000000....7.910400	25%.....223.500000....0.000000....2.000000.....0.000000....0.000000....7.910400
50%.....446.000000....0.000000....3.000000.....0.000000....0.000000....14.454200	50%.....446.000000....0.000000....3.000000.....0.000000....0.000000....14.454200
75%.....668.500000....1.000000....3.000000.....1.000000....0.000000....31.000000	75%.....668.500000....1.000000....3.000000.....1.000000....0.000000....31.000000
max.....891.000000....1.000000....3.000000.....8.000000....6.000000....512.329200	max.....891.000000....1.000000....3.000000.....8.000000....6.000000....512.329200
[8 rows x 7 columns]	[8 rows x 7 columns]
PassengerId.....0	PassengerId.....0
Survived.....0	Survived.....0
dtype: int64	dtype: int64

[8 rows x 7 columns]	[8 rows x 7 columns]
PassengerId.....0	PassengerId.....0
Survived.....0	Survived.....0
Pclass.....0	Pclass.....0
Name.....0	Name.....0
Sex.....0	Sex.....0
Age.....177	Age.....177
SibSp.....0	SibSp.....0
Parch.....0	Parch.....0
Ticket.....0	Ticket.....0
Fare.....0	Fare.....0
Cabin.....687	Cabin.....687
Embarked.....2	Embarked.....2
dtype: int64	dtype: int64

4.2.6 Titanic dataset Analysis and Data cleaning -2

Problem statement :

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Create a new column 'IsAlone' which is 1 if the passenger is alone (FamilySize = 0), otherwise 0.
2. Convert the 'Sex' column to numeric values (male: 0, female: 1).
3. One-hot encode the 'Embarked' column, dropping the first category.
4. Get the mean age of passengers.
5. Get the median fare of passengers.
6. Get the number of passengers by class.

7. Get the number of passengers by gender.
8. Get the number of passengers by survival status.
9. Calculate the survival rate of passengers.
10. Calculate the survival rate by gender.

CODE :

```
import pandas as pd
import numpy as np

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')
data['FamilySize'] = data['SibSp'] + data['Parch']

# 1. Create a new column 'IsAlone' (1 if alone, 0 otherwise)
data['Alone'] = np.where(data['FamilySize']== 0, 1, 0)

# 2. Convert 'Sex' to numeric (male: 0, female: 1)
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})

# 3. One-hot encode the 'Embarked' column
data = pd.get_dummies(data, columns=['Embarked'], drop_first= True )

# 4. Get the mean age of passengers
mean_age= data['Age'].mean()
print(mean_age)

# 5. Get the median fare of passengers
median_fare = data['Fare'].median()
print(median_fare)
```

6. Get the number of passengers by class

```
passenger_by_class = data['Pclass'].value_counts()
```

```
print(passenger_by_class)
```

7. Get the number of passengers by gender

```
passenger_by_gender = data['Sex'].value_counts().sort_index()
```

```
print(passenger_by_gender)
```

8. Get the number of passengers by survival status

```
passenger_by_survival = data['Survived'].value_counts().sort_index()
```

```
print(passenger_by_survival)
```

9. Calculate the survival rate

```
survival_rate = data['Survived'].mean()
```

```
print(survival_rate)
```

10. Calculate the survival rate by gender

```
survival_rate_gender = data.groupby('Sex')['Survived'].mean()
```

```
print(survival_rate_gender)
```

OUTPUT :

Average time
0.122 s
122.00 ms

Maximum time
0.122 s
122.00 ms

1 out of 1 shown test case(s) passed

Test case 1 122 ms
Debug
⋮
📄
^

Expected output	Actual output
29.69911764705882	29.69911764705882
14.4542	14.4542
3...491	3...491
1...216	1...216
2...184	2...184
Name: Pclass, dtype: int64	Name: Pclass, dtype: int64
0...577	0...577
1...314	1...314
Name: Sex, dtype: int64	Name: Sex, dtype: int64
0...549	0...549
1...342	1...342
Name: Survived, dtype: int64	Name: Survived, dtype: int64
0.3838383838383838	0.3838383838383838
Sex	Sex
0...0.188908	0...0.188908
1...0.742038	1...0.742038
Name: Survived, dtype: float64	Name: Survived, dtype: float64

4.2.7 Titanic dataset Analysis and Data cleaning -3

Problem statement :

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Calculate the survival rate by class.
2. Calculate the survival rate by embarkation location (Embarked_S).
3. Calculate the survival rate by family size (FamilySize).
4. Calculate the survival rate by being alone (IsAlone).
5. Get the average fare by passenger class (Pclass).
6. Get the average age by passenger class (Pclass).
7. Get the average age by survival status (Survived).

8. Get the average fare by survival status (Survived).
9. Get the number of survivors by class (Pclass).
10. Get the number of non-survivors by class (Pclass).

CODE :

```
import pandas as pd

import numpy as np

# Load the Titanic dataset

data = pd.read_csv('Titanic-Dataset.csv')

data['FamilySize'] = data['SibSp'] + data['Parch']

data['IsAlone'] = np.where(data['FamilySize'] > 0, 0, 1)

data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# 1. Calculate the survival rate by class

print(data.groupby('Pclass')['Survived'].mean())

# 2. Calculate the survival rate by embarked location

print(data.groupby('Embarked_S')['Survived'].mean())

# 3. Calculate the survival rate by family size

print(data.groupby('FamilySize')['Survived'].mean())

# 4. Calculate the survival rate by being alone

print(data.groupby('IsAlone')['Survived'].mean())


# 5. Get the average fare by class

print(data.groupby('Pclass')['Fare'].mean())

# 6. Get the average age by class

print(data.groupby('Pclass')['Age'].mean())
```

7. Get the average age by survival status

```
print(data.groupby('Survived')['Age'].mean())
```

8. Get the average fare by survival status

```
print(data.groupby('Survived')['Fare'].mean())
```

9. Get the number of survivors by class

```
print(data[data['Survived']==1]['Pclass'].value_counts())
```

10. Get the number of non-survivors by class

```
print(data[data['Survived']==0]['Pclass'].value_counts())
```

OUTPUT :

Average time
0.164 s
164.00 ms

Maximum time
0.164 s
164.00 ms

1 out of 1 shown test case(s) passed

Test case 1 164 ms Debug

Expected output

Actual output

Pclass	Pclass
1...0.629630	1...0.629630
2...0.472826	2...0.472826
3...0.242363	3...0.242363
Name: Survived, dtype: float64	Name: Survived, dtype: float64
Embarked_S	Embarked_S
0...0.506073	0...0.506073
1...0.336957	1...0.336957
Name: Survived, dtype: float64	Name: Survived, dtype: float64
FamilySize	FamilySize
0...0.303538	0...0.303538
1...0.552795	1...0.552795
2...0.578431	2...0.578431
3...0.724138	3...0.724138
4...0.200000	4...0.200000
5...0.136364	5...0.136364
6...0.333333	6...0.333333
7...0.000000	7...0.000000
10...0.000000	10...0.000000
Name: Survived, dtype: float64	Name: Survived, dtype: float64
Tc Alone	Tc Alone

Terminal Test cases

0...0.505650	0...0.505650
1...0.303538	1...0.303538
Name: Survived, dtype: float64	Name: Survived, dtype: float64
Pclass	Pclass
1...84.154687	1...84.154687
2...20.662183	2...20.662183
3...13.675550	3...13.675550
Name: Fare, dtype: float64	Name: Fare, dtype: float64
Pclass	Pclass
1...38.233441	1...38.233441
2...29.877630	2...29.877630
3...25.140620	3...25.140620
Name: Age, dtype: float64	Name: Age, dtype: float64
Survived	Survived
0...30.626179	0...30.626179
1...28.343690	1...28.343690
Name: Age, dtype: float64	Name: Age, dtype: float64
Survived	Survived
0...22.117887	0...22.117887
1...48.395408	1...48.395408
Name: Fare, dtype: float64	Name: Fare, dtype: float64
1...136	1...136
3...119	3...119
2...87	2...87
Name: Pclass, dtype: int64	Name: Pclass, dtype: int64
3...372	3...372
2...97	2...97
1...80	1...80
Name: Pclass, dtype: int64	Name: Pclass, dtype: int64

4.2.8 Titanic dataset Analysis and Data cleaning -4

Problem statement :

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Get the number of survivors by gender (Sex).
2. Get the number of non-survivors by gender (Sex).
3. Get the number of survivors by embarkation location (Embarked_S).
4. Get the number of non-survivors by embarkation location (Embarked_S).
5. Calculate the percentage of children (Age < 18) who survived.
6. Calculate the percentage of adults (Age >= 18) who survived.
7. Get the median age of survivors.
8. Get the median age of non-survivors.
9. Get the median fare of survivors.
10. Get the median fare of non-survivors.

CODE :

```
import pandas as pd

import numpy as np

# Load the Titanic dataset

data = pd.read_csv('Titanic-Dataset.csv')

data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)


# 1. Get the number of survivors by gender

survivors_by_sex = data[data['Survived'] == 1]['Sex'].value_counts()
```

```
print(survivors_by_sex)
```

2. Get the number of non-survivors by gender

```
nonsurvivors_by_sex = data[data['Survived'] == 0]['Sex'].value_counts()
```

```
print(nonsurvivors_by_sex)
```

3. Get the number of survivors by embarkation location (Embarked_S)

```
survivors_embarked_s = data[data['Survived'] == 1]['Embarked_S'].value_counts()
```

```
print(survivors_embarked_s)
```

4. Get the number of non-survivors by embarkation location (Embarked_S)

```
nonsurvivors_embarked_s = data[data['Survived'] == 0]['Embarked_S'].value_counts()
```

```
print(nonsurvivors_embarked_s)
```

5. Percentage of children (Age < 18) who survived

```
children = data[data['Age'] < 18]
```

```
children_survived_pct = children['Survived'].mean()
```

```
print(children_survived_pct)
```

6. Percentage of adults (Age >= 18) who survived

```
adults = data[data['Age'] >= 18]
```

```
adults_survived_pct = adults['Survived'].mean()
```

```
print(adults_survived_pct)
```

7. Median age of survivors

```
median_age_survivors = data[data['Survived'] == 1]['Age'].median()
```

```
print(median_age_survivors)
```

8. Median age of non-survivors

```
median_age_nonsurvivors = data[data['Survived'] == 0]['Age'].median()
```

```
print(median_age_nonsurvivors)
```

9. Median fare of survivors

```
median_fare_survivors = data[data['Survived'] == 1]['Fare'].median()
```

```
print(median_fare_survivors)
```

10. Median fare of non-survivors

```
median_fare_nonsurvivors = data[data['Survived'] == 0]['Fare'].median()
```

```
print(median_fare_nonsurvivors)
```

OUTPUT :

Average time
0.129 s
129.00 ms

Maximum time
0.129 s
129.00 ms

✓ 1 out of 1 shown test case(s) passed

✓ Test case 1 129 ms Debug

Expected output

Actual output

female...233	female...233
male...109	male...109
Name: Sex, dtype: int64	Name: Sex, dtype: int64
male...468	male...468
female...81	female...81
Name: Sex, dtype: int64	Name: Sex, dtype: int64
1...217	1...217
0...125	0...125
Name: Embarked_S, dtype: int64	Name: Embarked_S, dtype: int64
1...427	1...427
0...122	0...122
Name: Embarked_S, dtype: int64	Name: Embarked_S, dtype: int64
0.5398230088495575	0.5398230088495575
0.3810316139767055	0.3810316139767055
28.0	28.0
28.0	28.0
26.0	26.0
10.5	10.5