


PadhAI: Batch Normalization and Dropout

One Fourth Labs


Batch Normalization

We have standardized inputs but what about hidden representations?

1. When we normalize/standardize the inputs, most of the inputs lie around the mean value, in the standard deviation range for all inputs X_{mn} where (m: no. of training samples, n: no. of features)



2. Now, let's try applying normalizations to any particular hidden representations. Consider one particular Hidden representation H




3. Now, standardization is done on the H matrix so that all of the columns are in the same range.
4. In a sense, the H matrix acts as an input to the next layer.
5. Thus, to learn the weights effectively, Standardization is done on all the columns to bring them to a comparable range.

PadhAI: Batch Normalization and Dropout

One Fourth Labs

6. Just as we standardize the inputs, we standardize the activations at all layers



7. Now, why is it called batch normalization?

8. Let's take a look at the formulae for Batch normalizing H

a. $h_{ij}^{(norm)} = \frac{h_{ij} - \mu_j}{\sigma_j}$ for each feature of each training sample.

b. Where mean: $\mu_j = \frac{1}{k} \sum_{i=1}^k h_{ij}$

c. And Variance/Standard deviation: $\sigma_j = \sqrt{\frac{1}{m} \sum_{i=1}^k (h_{ij} - \mu_j)^2}$

9. Now, for the input normalization, we consider the entire training size (m) when computing mean and std. However, here we only consider a smaller subset of samples (k). **Mean (μ) and Std (σ) are calculated using a batch of k samples, hence it is called batch normalization.** K = 32 is commonly used.