



The GoogLeNet Architecture

What does the full network look like?


- Let's take a look at the entire GoogLeNet architecture



- Up till the second max-pooling layer, the architecture is similar to what we've seen in earlier configurations. Post that, we begin moving into the Inception modules.
- Inception Module 1:**



4. Inception Module 2:



5. Then there is a **Max-pooling layer which reduces the Dimensions by Half (480x14x14)**. This Max-pooling layer is used because the Max-pooling layers in the Inception modules do not reduce the dimensions.
6. **Inception Module 3,4 & 5:**
 - a. **Input at Inception Module 3** is: 480x14x14
 - b. **Output at Inception Module 5** is: 512x14x14
7. **Inception Module 6:**
 - a. **Input:** 512x14x14
 - b. **Output:** 528x14x14
8. **Inception Module 7:**
 - a. **Input:** 528x14x14
 - b. **Output:** 832x14x14
9. Then there is a **Max-pooling layer which reduces the Dimensions by Half (832x7x7)**.
10. **Inception Module 8:**
 - a. **Input:** 832x7x7
 - b. **Output:** 832x7x7
11. **Inception Module 9:**
 - a. **Input:** 832x7x7
 - b. **Output:** 1024x7x7
12. **Average Pool layer is used to reduce the output from Inception Module 9**, thereby reducing the number of parameters between the non-FC and FC layer interface.
13. Each Inception Module counts as 2 layers, therefore we have more than 20 layers in GoogLeNet.