Index

Note: Page numbers followed by "*f*" and "*t*" refer to figures and tables, respectively.

A

Access and Mobility Management Function (AMF), 47
Acknowledged Mode (AM), 220–221
Acknowledgment (ACK), 180–181, 202–203
Acknowledgment SN (ACK_SN), 220
Acknowledgment/negative acknowledgment (ACK/NACK), 126
Active users, 249
  selection, 251
Adjacent Channel Leakage Ratio (ACLR), 78, 335
Advanced Vector Extensions (AVX), 176
Agile development, 329
All-in-one base station, 15, 15*f*
Allocation and Retention Priority (ARP), 53
Analog gain control, 84
Analog-to-Digital Conversion (ADC), 159–162
Analog-to-digital converter, 77
"Anchored NR-U", 13–14
Announce messages, 281
Antenna diversity at UE, 353
Antenna Element (AE), 168
Application architecture, 210–212
Application Function (AF), 47
Application Programming Interface (API), 16
Application-specific integrated circuit (ASIC), 5, 140
Arg(max) vectorization, 258–260
  example of input array, 258*f*
  vectorized comparison to find highest value, 259*f*
Arm, 176–177, 183, 185
Artificial Intelligence (AI), 2
ASN.1, 96–97
Asynchronous network, 275–276
Asynchronous Transfer Mode (ATM), 245
Authentication and Key Agreement (AKA), 47
Authentication Server Function (AUSF), 47
Automatic gain control, 84
Automatic Neighbor Relations (ANR), 205
Automatic Repeat Request (ARQ), 61, 245–246

B

Backhaul IO, 148–149
Backhaul testing, 345
Bandwidth (BW), 22–23, 112
Bandwidth adaptation (BA), 67–69
Bandwidth parts/partitioning (BWP), 5–6, 67–69, 320–321
Bare metal/RTOS, 183
Base Station (BS), 43
  output power, 335
  scheduler algorithms, 242–248
    combined quality of service and opportunistic schedulers, 247
    multiuser multiple input multiple output, 247–248
    opportunistic scheduler, 243–245
    quality of Service scheduler, 245–246
  wireless scheduler algorithm
    active user selection, 251
    architectural framework for, 249–254
    frequency allocation, 252–253
    primary user selection, 251–252
    secondary and remainder user selection, 253–254
    static and regular scheduling, 250, 250*f*
    user database reduction, 249*f*
Base Transceiver Station (BTS), 43
Baseband to radio frequency conversion, 158–159
  intermediate frequency, 160*f*
  zero-intermediate frequency, 160*f*
Baseboard Management Controller (BMC), 184
BBDEV, 194–196
Beam switch process steps, 171
Beamforming and time, 228–229

Behavior Aggregate, 99
Best Effort (BE), 99
Best Master Clock Algorithm, 281
Bit Error Rate (BER), 124
BitIsClear, 324
BitIsSet, 324
Black box testing, 340–343
  cell performance, 342–343
  latency, 342
  stability, 342
  throughput, 341
    PDCP throughput test setup, 341*f*
Board bring-up software, 141
Board Support Package software (BSP software), 141, 185–186, 329
Boot process and application load, 183–185
  microcontroller and microprocessor characteristics, 184*t*
  private key signing and public key verification, 185*f*
Boundary clocks, 280–281
Bridging functions, 93
Broadband Fixed Wireless Access (BFWA), 13
Broadband Wireless Access (BWA), 242
Broadcast Channel (BCH), 71
Broadcast Control Channel (BCCH), 71
Buffer and memory management, 191–193
Buffer descriptors (BD), 195

C

C-plane latency, 342
C-RAN, 7–8
C-V2X, 355–357
Calibration, 336–337
Capacity enhancement, 18
Car makers, 358
Cell identity (Cell ID), 88
Cell performance, 342–343
Cell site integrated (CU/DU) solutions, 146–154
  optimized hardware, 150–154
  scale-out by multiple iNICs, 146*f*
  server-based solutions, 148–150
Cell site router/gateway, 95
Cell site solution, 139
Cellular network synchronization requirements, 290–291
  frequency accuracy and stability, 290
  time accuracy, 291
Central Processing Unit (CPU), 109, 184, 215, 309, 331, 359
  cores, 140
  loading, 319
Central unit (CU), 3, 30–33, 43, 48–59, 103, 254, 329. *See also* Radio Unit (RU)
  based small cell solution, 139
  blades perform CU processing, 143
  control plane user plane split and central unit/distributed unit interface, 50–51
  dual and multiconnectivity, 56–59
  Internet Protocol and Internet Protocol Security, 51–52
  Packet Data Convergence Protocol, 55
  Quality of Service and related concepts, 52–55
Centralized processing, 21–28
Centralized/distributed unit use-case dimensioning for throughput, 103–108
  elephant flows, 107–108
  traffic requirements based performance analysis, 104–106
  user data rate dimensioning, 106–107
Certificate Transparency, 207
Certified Professional Installer (CPI), 12
Channel coding, 74
Channel equalization, 315
Channel estimation, 314
Channel mapping, 70–73
Channel state information (CSI), 242
Channelization, 78
China Academy of Information and Communications Technology (CAICT), 149
China Mobile Research Institute (CMRI), 7
“Clean up” function, 277
Clipping, 79
Clock, 276
  cycles, 310
802.1CM, 91–94
  bridging functions, 93
  Fronthaul profiles, 93–94
  traffic classes, 92–93

Cobalt, 187
Code analysis tools, 330
Code blocks (CBs), 74, 123–124
  level CRC, 124–125
Coexistence methods, 12
Combined quality of service and opportunistic schedulers, 247
Commercial grade, 186
Commercial-off-the-shelf (COTS), 141
Common Control Channel (CCCH), 71
Common Public Radio Interface (CPRI), 15–16
Common Vulnerabilities and Exposures (CVE), 210
CoMP. *See* Cooperative Multipoint (CoMP)
Complementary Cumulative Distribution Function, 232
Complex MAC (CMAC), 314
Complexity analysis
  eCPRI, 311–312
  physical layer complexity analysis, 313–318
Congestion window, 100
Connected users, 249
Containerization (Docker), 188
Control and Management (C&M), 92
Control Element (CE), 223
Control PDU Type (CPT), 220
Control plane (CP), 43, 45*f*, 46*f*, 143
  user plane split and central unit/distributed unit interface, 50–51
Cooperative Intelligent Transport Systems (C-ITS), 354
Cooperative Multipoint (CoMP), 28–34, 84, 94, 353
  processing, 25–28
Coordinated Universal Time (UTC), 267–268
COUNT values, 218
Crest factor (CF), 77
Crest factor reduction (CFR), 77, 79–80, 230–232, 231*f*
  feed-forward digital predistorter, 232*f*
CU Control Plane (CU-CP), 32
CU User Plane (CU-UP), 32
Cycle budget, 310
Cycle counting, 310
Cyclic prefix (CP), 69, 238–239
Cyclic redundancy check (CRC), 63
Cyclomatic Complexity, 330

D

Data breach, 207
Data center, 139
  architecture, 142–146, 143*f*
    cell site integrated (CU/DU) solutions, 146–154
    iNIC solutions, 145*f*
    key CU interfaces, 144*f*
Data converter, 133–136
Data locality, 354
Data network (DN), 44–46
Data plane (DP), 48
Data Plane Development Kit (DPDK), 190–191, 311
Data Radio Bearers (DRBs), 47, 217
Data/Control (D/C), 217
Dedicated Control Channel (DCCH), 71
Dedicated Transport Channel (DTCH), 71
Demodulation Reference Signal (DMRS), 311
Development cycle, 141–142
  development timelines for typical product, 142*f*
Development testing, 329–332
  functional, 330–331
  performance, 331–332
  static analysis, 329–330
Device under test (DUT), 331–332
Dhrystone, 177
DiffServ (DS), 97–101
DiffServ code point (DSCP), 52–53
Digital beamforming, 77–78
Digital down conversion, 78
Digital Front End (DFE), 128, 158, 163, 172, 224, 230–234
  CFR, 231–232
  DPD, 232–234
  receive side gain control, 234
  signal aggregation and digital up conversion, 230–231
Digital predistortion (DPD), 77, 80–83, 131–132, 162, 230, 232–234
Digital signal processing (DSP), 7, 66–67, 310
Digital Signal Processor, 183

Digital Unit (DU), 156
Digital Upconversion (DUC), 78, 230–231
Digital-to-Analog Conversion (DAC), 159–162
Digital-to-analog converter, 77
Digital ↔ analog conversion and analog components, 83
Digitally controlled oscillator (DCO), 301
Dimensioning, 103
Direct RF, 159
Discontinuous Reception (DRX), 67, 249
Discontinuous Transmission (DTX), 67
Discontinuous transmission and reception, 66–67
Distributed antenna systems (DAS), 19
Distributed processing, 21–28
Distributed unit (DU), 3, 30–33, 43, 59–76, 103, 254, 314, 329
  based small cell solution, 139
  blades implement Layer 2, 146
  F1 termination, 59
  interface, 86
  internal IO, 115–117
  Physical Layer, 70–76
  Radio Link Control and Medium Access Control, 59–70
  testing, 330
Double data rate (DDR), 319
Downlink (DL), 330
  chain tests, 330
  directions, 350
Downlink Control Information (DCI), 63–64, 203
Downlink Shared Channel (DL-SCH) transport channel, 202–203
Dual connectivity (DC), 49, 56–59

E

E-LSP, 101
Earliest deadline due (EDD), 246
Earliest deadline first algorithm (EDF algorithm), 245
Edge compute networking, 353–354
Effective Isotropic Radiated Power (EIRP), 11, 168, 335
Effective Number of Bits (ENOB), 161
Electromagnetic Compatibility (EMC), 96
Elephant Flows, 107–108
Eligible users, 249
Embedded Linux, 183
End-to-end congestion notification (ECN), 99
End-to-end performance tests, 341
Enhanced Common Public Radio Interface (eCPRI), 76, 112–115, 309
  complexity analysis, 311–312
  fronthaul transport options, 223*f*
  fronthaul transport protocol encapsulation options, 224*f*
  processing flow
    receive from Ethernet, 227*f*
    transmit to Ethernet, 227*f*
  protocol, 86, 223–228
  termination, 157–158
  U-plane message format, 225*f*
Enhanced Mobile Broadband (eMBB), 352
Enterprise 5G networking, 34–40
  applications, 36
  key performance indicators, 36
  network installation and maintenance, 34–36
  RF aspects, 37–40
  total cost of ownership, 36–37
  use-case example, 37
  users of network, 36
Environment optimization development, 321–322
Environmental and power requirements, 96
Equalization Matrix, 314
Ethernet, 275–276
Evolved NB (eNB), 43
Evolved Packet Core (EPC), 44
Extended Logical Channel ID (eLCID), 223

F

F1 termination, 59
Fast Fourier transform (FFT), 76–78, 237–238
Feature testing, 333–334
Federal Communications Commission (FCC), 346–347
File enumeration, 207
5G Core Network (5GC Network), 143
5G New Radio (5G NR), 143
5G non-Standalone (5G NSA), 332
5G QoS Identifier (5QI), 53
5G Reduced Capabilities (5G RedCap), 360–362

combinations of abovementioned features, 362
equipment bandwidth reduction, 361
half-duplex frequency division duplexing operation, 361–362
reduced number of Rx/Tx antennas, 361
relaxed maximum modulation order, 362
relaxed maximum number of multiple-input, multiple-output layers, 362
relaxed user equipment processing time, 362
5G Standalone (5G SA), 332
5G
bandwidth examples, 112–113
base station architectures, 17–20
C-RAN, 20
DAS, 19
ISC, 17–18
massive multiple-input, multiple-output, 19–20
pico/micro cell, 18
centric data center, 142
modem, 173
networks, 215
protocol, 349–350
Spectrum, 8–14
allocations, 9*f*
CBRS spectrum options, 10*f*
Japan Government/Enterprise 5G bands, 13*f*
licensed operator spectrum, 9–10
licensed private spectrum, 10–13
unlicensed spectrum, 13–14
system, 43
5G/NR, URLLC in, 350–353
Fixed Wireless Access deployment, 234
Floating-Point (FP), 176
Flow Identifier, 226
FLR. *See* Frame Loss Ratio (FLR)
Form factor, 96
Forward Error Correction (FEC), 149
4G
bandwidth examples, 113–114
C-V2X (PC5), 356–357, 357*f*
FPGAs, 140, 145–146
Fractional frequency reuse, 26
Frame, 73
Frame Loss Ratio (FLR), 92
Frequency, 265–267, 266*f*, 274
accuracy, 290
allocation, 252–253
domain conversion, 228–229
frequency-domain scheduling, 252
frequency-only systems, 298–299
filtering effect of PLL, 299*f*
PLL, 298*f*
synchronization, 148
Frequency Division Duplexing (FDD), 352
Front-End Module (FEM), 165
Front-testing, 345
Fronthaul
bandwidth, 112–115
IO, 148–149
latency, 114–115
networks, 345
profiles, 93–94
switch, 142
throughput, 25
Fronthaul gateway (FHGW), 94
Full-timing support (FTS), 280, 289, 294–296
Functional application platform interface (FAPI), 201–206
functional application platform interface internal API, 201*f*
hardware traffic bifurcation, 201*f*
Functional splits, 20–28
distributed *vs*. centralized processing, 21–28
Functional testing, 330–331

G

G-PDU, 216
Gain Control algorithms, 234
GCC, 321
General Authorized Access (GAA), 11
General-purpose processor (GPP), 237
Generalized Memory Polynomial, 233
Global Navigation by Satellite Systems (GNSS), 269–273
constellation, 271*f*
receiver interfaces, 273*f*
Global synchronization, 101
Global System for Mobile communication (GSM), 55

gNB, 143
GPRS Tunneling Protocol (GTP), 3, 50–51
  GTP-U, 215
  GTPv1, 215
    GTPv1-U, 217
  GTPv2, 215
    GTPv2-C, 215
  protocol, 215–217
    GTP-U PDU format, 216*f*
    PDU session information format, 216*f*
GPRS Tunneling Protocol—Control (GTP-C), 53
GPRS Tunneling Protocol—User (GTP-U), 53
Grandmaster, 282
Graphical User Interface (GUI), 186

H

Half-duplex frequency division duplexing operation, 361–362
Hardware acceleration model, 193–194
  accelerator physical implementation, 193*f*
  inline accelerator, 194*f*
  parallelizing accelerator calls, 193*f*
Hardware architecture choices, 139
  data center architecture, 142–146
  development cycle, 141–142
  ISC, 172–174
  multicore central processing unit selection criteria, 174–179
  PCIe performance, 179–181
  RU, 154–171
  scalability, 139–141
Hardware offload, 179
Hardware system dimensioning
  centralized/distributed unit use-case dimensioning for throughput, 103–108
  distributed unit internal IO, 115–117
  eCPRI, fronthaul bandwidth and latency, 112–115
  HARQ process count dimensioning, 126–127
  memory dimensioning, 117–126
  radio unit, 127–136
  use-case dimensioning for latency, 108–110
  users/transmission time interval, 110–111
“Heisenbugs”, 344–345
High reliability, 352–353
High-priority fronthaul (HPF), 93
HPF. *See* High-priority fronthaul (HPF)
Hybrid Automatic Repeat Request (HARQ), 61, 63–65, 123–124, 250, 321, 353
  memory and bandwidth dimensioning, 123–126
  process count dimensioning, 126–127

I

I/O
  dimensioning, 178
  termination, 331
IEEE 1588 standard, 280
In-band selectivity and blocking, 336
In-channel selectivity, 336
Industrial automation, 353–354
Information elements (IEs), 69
Initial access, 87–91
Inline Acceleration Model, 194
Instantaneous BandWidth (IBW), 79, 128
Instruction Set Architecture (ISA), 148
Instructions Per Clock/Cycle (IPC), 319, 322
Integrated Architectures, 153
Integrated Small Cell (ISC), 17–18, 33–34, 43, 139, 154, 156, 172–174
  networking processor/host, 173
  physical layer/5G modem, 173
  radio frequency subsystem, 174
Intellectual Property Rights (IPR), 184
Inter Cell Interference Coordination (ICIC), 205
Inter process communication, 194–196, 194*f*, 195*f*
Inter Processor Communication (IPC), 194–195
Intermediate Frequency interface (IF interface), 159
International Electrotechnical Commission (IEC), 214
  security requirements, 212–214
    security algorithms for 4G/LTE, 212*t*
    security algorithms for 5G/NR, 213*t*
Internet Protocol (IP), 43, 51–52
Internet Protocol Security (IPSec), 51–52, 145, 320
Interoperability and Test (IoT), 1, 329
  development testing, 329–332
  front-, mid-, and backhaul testing, 345

operator acceptance testing, 345–346
performance testing, 340–345
regulatory approval testing, 346–347
system test setup, 332–340
Interoperability testing, 338–340
plug fest, 338–340
use-case scenarios, 338
User Equipment test pool, 338
Inverse discrete Fourier transform (IDFT), 237–238
Inverse fast Fourier transform (IFFT), 237–238

J

JESD, 77, 162–163

K

Key performance indicators (KPI), 36, 333, 350–351
15-KHz SCS, 351
Knots Complexity, 330

L

L-LSP, 101
"L1 bypass" testing, 341
Latency, 112–115, 350, 354
testing, 342
License-Assisted Access (LAA), 13–14
Licensed operator spectrum, 9–10
Licensed private spectrum, 10–13
in United States, 10–12
Life-of-a-packet double data rate utilization analysis, 320
Life-of-a-packet memory bandwidth analysis, 117–123
Limited Buffer Rate Matching (LBRM), 124
Linux
distribution, 186
kernel, 184
and processor performance tuning, 196–197
Log Likelihood Ratios (LLRs), 116, 315
generation process, 317
Logical Channel ID (LCID), 223
Logical channels, 70–71
Long term support (LTS), 185–186
Long-Term Evolution (LTE), 1, 9, 43, 351
C-V2X, 356–357
macro cell, 223–224
Look-aside Acceleration Model, 193
Lookup Tables (LUTs), 81, 233
Low physical layer, 158, 228–229
beamforming and time/frequency domain conversion, 228–229
PRACH extraction and filtering, 229
Low-priority fronthaul (LPF), 93
Lower Layer Split/CU plane (LLS-CU), 31
Lower Level Split (LLS), 31

M

Management plane (MP), 3
Massive multiple-input, multiple-output, 19–20
Master Information Block (MIB), 71
Max Coupling Loss (maxCL), 351
Maximum Transfer Unit (MTU), 216
Medium Access Control (MAC), 48, 59–70, 240, 312, 330
layers, 354
MAC-I field, 217
protocol, 222–223, 222*f*
Medium-priority fronthaul (MPF), 93
Memory
dimensioning, 117–126
HARQ memory and bandwidth dimensioning, 123–126
life-of-a-packet memory bandwidth analysis, 117–123
memory sizing, 117
scrubbers, 196
sizing, 117
Memory Management Unit (MMU), 322
Messaging Channel, 277
"Micro kernel", 188
Mid-testing, 345
Mini-slot structure, 352, 352*f*
Mitigation techniques, software performance, 320–321
mmWave radio frequency module, 168–171, 169*f*
beam switch process steps, 171
mmWave link budget example, 168–170
Mobile World Congress (MWC), 8
Modern Network Interface Cards, 200

Modified Largest Weighted Delay First (M-LWDF), 251
Modulation Coding Scheme (MCS), 74, 221–222, 242
Modulation schemes, 241–242, 242*f*
Moore's law, 5, 186–187
MTU Discovery (MTUD), 216
Multiconnectivity, 56–59
Multicore central processing unit selection criteria, 174–179
  Arm, 176–177
  hardware offload, 179
  memory and I/O dimensioning, 178
  performance benchmarking, 177–178
  SIMD, 174–176
  x86, 176
Multiple blades, 145
Multiple input multiple output (MIMO), 7, 70, 76, 237, 246–247, 253–254, 359
Multiple smaller (MPS), 180
Multiple-input layers, 362
Multiple-output layers, 362
Multiprotocol Label Switching support for DiffServ, 101
Multiuser diversity, 243
Multiuser multiple input multiple output, 247–248

N

Negative Acknowledgement (Nack), 63, 180–181, 202–203, 220
NETCONF protocol, 33
Network asymmetry, 287
Network Exposure function (NEF), 47
Network Interface Card (NIC), 16, 114, 148
Network Listening Mode, 205
Network monitor mode API, 204–206
Network PDV, 287–288
Network Processor Units (NPUs), 145–146
Network reconnaissance, 208–209
Network Slice Selection Function (NSSF), 47
Network Time Protocol (NTP), 278–279
Network-based synchronization, 274–275
  network time distribution, 275*f*
Network-level synchronization, 292–296
  FTS or PTS, SyncE or no SyncE, 294–296
    mixed PTP profiles, 296*f*
    O-DU sync functions, 294*t*
    SyncE and precision time protocol, 294*t*
  O-RAN LLS architectures, 293*f*
Networked Femto Application Programming Interface (nFAPI), 32–33, 203–204
  timing window management, 204*f*
Networking processor/host, 148–149, 173
Networking stacks, 197–200
  features, 197
  performance, 199–200, 200*f*
  security, 197–199
New Radio (NR), 43, 351
Next-generation radio access network (NG-RAN), 43–48, 45*f*
  wired networking analogy, 48
NF Repository function (NRF), 47
NMEA-0183 standard, 273
NodeB (NB), 43
Noise Figure (NF), 129, 167
Non Access Stratum (NAS), 47
Non-Real-Time (non-RT), 2
Non-Stand Alone deployments (NSA deployments), 57
NR C-V2X (PC5), 357
NR-Unlicensed (NR-U), 13–14
Numerically Controlled Oscillator (NCO), 159, 301
Numerology, 73–74

O

Occupied BandWidth (OBW), 128, 335
OCXO, 304
One-way protocol, 278–279
Open Base Station Architecture Initiative (OBSAI), 15–16
Open Networking Foundation (ONF), 48
Open Radio Access Network (O-RAN), 1, 141, 265, 311, 329, 349
  5G base station architectures, 17–20
  5G RedCap, 360–362
  alliance, 1–6
  C-RAN, 7–8
  cellular network synchronization requirements, 290–291

centralized RAN architecture, 21*f*
CoMP, 28–34
effects of timestamping location and resolution, 303–305
enterprise 5G networking, 34–40
functional splits, 20–28
members, 4, 5*f*
network-level synchronization, 292–296
Open vRAN, 7–8
OpenRAN, 7–8
spectrum, 8–14
supported functional splits, 30–34
synchronization, 273–290, 292
  equipment requirements, 296–298
  solution implementation, 298–302
system components, requirements, and interfaces, 43
  802. 1CM, 91–94
  ASN. 1, 96–97
  cell site router/gateway, 95
  central unit, 48–59
  DiffServ, 97–101
  distributed unit, 59–76
  distributed unit/radio unit interface, Enhanced Common Public Radio Interface protocol overview, 86
  FHGW, 94
  form factor, environmental and power requirements, 96
  initial access, 87–91
  Multiprotocol Label Switching support for DiffServ, 101
  next-generation radio access network, 43–48, 45*f*
  radio unit, 76–86
telecommunications infrastructure project, 7–8
traditional base station architectures, 14–17
understanding frequency, time, syntonization, and synchronization, 265–269
  frequency, 265–267
  global navigation by satellite systems, 270–273
  syntonized *vs*. synchronized, 269, 270*f*
  time, 267–273
  time and phase, 267
  unraveling standards spaghetti, 305–306
  URLLC, 349–354
  vehicle-to-infrastructure roadside unit architecture and implementation, 354–360
  working groups, 2*f*
  xRAN, 7–8
Open Telecom IT Infrastructure (OTII), 149
Open vRAN, 7–8
OpenFlow, 48
OpenRAN, 7–8
Operating band unwanted emissions (OBUE), 335
Operating System (OS), 117, 140, 183–197
  bare metal/RTOS *vs*. embedded Linux, 183
  BBDEV and inter process communication, 194–196
  boot process and application load, 183–185
  buffer and memory management, 191–193
  hardware acceleration model, 193–194
  Linux and processor performance tuning, 196–197
  long term support, 185–186
  realtime and timing, 186–191
  roll your own *vs*. commercial grade, 186
Operation and Maintenance (OAM), 156, 172
Operator acceptance testing, 345–346
Opportunistic scheduler, 243–245
Oprofile, 319
Optimization techniques
  architectural framework for base station wireless scheduler algorithm, 249–254
  base station scheduler algorithms, 242–248
  OFDM(A), 237–242
    subcarrier allocation, 240–241
  software optimization techniques, 257–260
  system-level optimization, 254–257
Optimized hardware, 150–154
  deeply integrated/embedded approach, 154*f*
  disaggregated approach, 155*f*
  software defined approach, 156*f*
Orbiting satellites, 270
Orthogonal frequency division multiple access (OFDM(A)), 237–242
  subcarrier allocation, 240–241
Orthogonal frequency division multiplexing (OFDM), 66, 237, 330

Orthogonal frequency division multiplexing (OFDM) (*Continued*)
numerologies, 351–352, 351*t*
Oscillator selection and holdover, 303–305
Out-of-band blocking, 336
Output power, 167
dynamics, 335
Oversubscription, 104
ratio, 106–107

P

802.11p standard, 356
Packet Data Convergence Protocol (PDCP), 48, 55, 330
performance, 341
protocol, 217–220
PDCP PDU example, 217*f*
robust header compression, 219–220
stack memory domains, 218*f*
Packet Delay Variation (PDV), 285
Packet processing, 331–332
Packet processing cycle budget analysis, 310–312
eCPRI complexity analysis, 311–312
Packet time transport, 278–279
one-way protocol, 278*f*
two-way protocol, 279*f*
Paging Channel (PCH), 71
Paging Control Channel (PCCH), 71
Partial-timing support (PTS), 280, 294–296
PC5 interface, 356–357
PCIe performance, 179–181
example calculation, 181
transaction layer packetization, 180–181
Peak cancellation, 80
Peak to Average Power Ratio (PAPR), 78, 230
reduction and performance improvement techniques, 78–83
Peak windowing, 80
Per Hop Behavior (PHB), 98
Performance, 199–200, 331–332
benchmarking, 177–178
exploration, 344
metrics, 309
proof points, 316–318
testing, 340–345
black box testing, 340–343
white box testing, 343–345
Phase, 267
Phase-locked loop (PLL), 133–136, 298
PHY API, 202–203
Physical Broadcast Channel (PBCH), 73, 88, 202
Physical Cell ID (PCI), 190–191
Physical channels, 70–73
ID, 226
mapping and modulation, 75–76
Physical Downlink Control Channel (PDCCH), 71–72
Physical Downlink Shared Channel (PDSCH), 73
Physical Layer, 70–76, 173, 354
channel coding, 74
channel mapping, 70–73
complexity analysis, 313–318
L1 processing in DU, 313*f*
numerology, 73–74
performance proof points, 316–318
QAM demodulation, 317*f*
physical channel mapping and modulation, 75–76
processing, 228–229
Radio Network Temporary Identifier, 73
stack development, 318
TBs, 223
theoretical analysis, 314–316
Physical Layer Acceleration, 149
Physical Network Function (PNF), 203
Physical Random Access Channel (PRACH), 73, 85–86, 315
extraction and filtering, 229, 229*f*
Physical resource block (PRB), 69
Physical Uplink Control Channel (PUCCH), 73
Physical Uplink Shared Channel (PUSCH), 73
Physical-layer transport, 275–278
“Pico kernel”, 187
Pico/micro cell, 18
Platform Control Hub (PCH), 184
Plug fest, 338–340, 339*f*
Policy Control Function (PCF), 47
Polling (P), 220
Polynomial algorithm, 233
Polynomial models, 233

Power
control, 66
receive side, 66
transmit side, 66
efficiency, 167
Power Amplifier (PA), 78, 131, 155, 230
Precision Time Protocol (PTP), 269, 278–290
example network PDV, 286*f*
head of line blocking, 286*f*
master selection process, 282*f*
network topology, 280*f*
one-way protocol, 278*f*
PTP + SyncE solution, 302, 304*f*
synchronization
message flow, 282*f*
process, 284*f*
syntonization process, 283*f*
effect of timestamping point, 287*f*
two-way protocol, 279*f*
Predictive HARQ, 65
PREEMPT_RT, 187
Primary Reference Clock, 273
Primary Synchronization Signal (PSS), 88
Primary user selection, 251–252
frequency-domain scheduling challenge, 253*f*
PF time-domain scheduling, 252*f*
Priority Access Licensed (PAL), 10–11
"Processing cycle budget analysis", 310
Processor binding, 196
Profiling, 206–208
Program Counter (PC), 184
Proportional fair (PF), 250
Protocol, 277, 333

Q

QoS Class Identifier (QCI), 55
QoS Flow Identifier (QFI), 52–53, 215
Quadrature amplitude modulation (QAM), 74, 159, 241, 315, 335
Quadrature Phase Shift Keying (QPSK), 241, 335
Quality of Service (QoS), 44, 242
flows in 5GC and NG-RAN, 52*f*
and related concepts, 52–55
scheduler, 245–246

R

Radio access network (RAN), 1
performance, 354
Radio Access Network Application Part (RANAP), 53
Radio Equipment (RE), 66
Radio frequency (RF), 154, 354
compliance testing, 335–338
calibration, 336–337
receiver, 336, 337*f*
tools needed, 337–338
transmitter, 335, 337*f*
subsystem, 162–165, 174
analog, 163–165
JESD, 162–163
Radio Link Control (RLC), 48, 59–70, 249, 330
layers, 220–221, 354
protocol, 220–222
RLC header example, 221*f*
Radio Network Temporary Identifier (RNTI), 67, 73
Radio Resource Control (RRC), 48, 330
Radio resource management (RRM), 2
Radio Unit (RU), 3, 30–33, 43, 76–86, 103, 127–136, 154–171, 215, 254, 316, 329. *See also* Central unit (CU)
analog gain control, 84
baseband to radio frequency conversion, 158–159
data converter and PLL, 133–136
digital beamforming and fast Fourier transform, 77–78
digital predistortion, 131–132
digital up conversion, channelization, and digital down conversion, 78
digital-to-analog conversion and analog-to-digital conversion, 159–162
digital ↔ analog conversion and analog components, 83
eCPRI termination, 157–158
generalized block diagram, 76–77
IBW, 128
key components in integrated radio unit, 157*f*
latency and delay, 130–131
low physical layer and digital front end, 158

Radio Unit (RU) (*Continued*)
disaggregated approach, 159*f*
software defined approach, 158*f*
mmWave radio frequency module, 168–171
OBW, 128
peak-to-average power ratio reduction and performance improvement techniques, 78–83
PRACH, 85–86
radio frequency subsystem, 162–165
receiver chain analysis, 128–129
sub 6 GHz front end module, 165–167
time and frequency synchronization, 84
Ramdisk, 184
RAN Intelligent Controller (RIC), 2
Random Access Channel (RACH), 23, 71
Random Early Discard (RED), 98, 100
Random-access procedure, 89–91
Random-access response (RAR), 90
Read Only Memory (ROM), 184
Real Time (RT), 127
support, 186
and timing, 186–191
operating system latency for interrupt handling, 188*f*
time synchronization features in Linux, 189*f*
timeout array, 190*f*
Receiver, 336
chain analysis, 128–129
dynamic range, 167
intermodulation, 336
sensitivity, 167
spurious emissions, 336
Reference sensitivity level, 336
Reflective Quality of Service, 55
Regular scheduling, 250
Regulatory approval testing, 346–347
Relaxed maximum modulation order, 362
Relaxed User Equipment processing time, 362
Reliability, 350
Remote Radio Head (RRH), 315
Resource blocks (RBs), 335
Resource element (RE), 335
Retroactive software optimization, 331–332
RISC-V, 183
Roadside unit (RSU), 358–360, 359*f*
system architecture, 359–360
Robust Header Compression (RoHC), 49, 219–220, 219*f*
ROHC v1, 219
Roll your own (RYO), 186
Round Trip Time (RTT), 100
Round-Robin algorithm (RR algorithm), 245
Rx DC offset, 336
Rx/Tx antennas, reduced number of, 361
Rx/Tx IQ mismatch, 336

S

"Safe For Network" testing, 338
Scalability aspect, 139–141
Scalable Vector Extension (SVE), 176
Scale-out scenarios, 140
SCHED–FIFO (Scheduler policy), 196
SCHED–OTHER (Scheduler policy), 196
SCHED–RR (Scheduler policy), 196
Scheduled users, 249
Scheduling, static and regular, 250
Secondary eNB (SeNB), 58–59
Secondary Synchronization Signal (SSS), 88
Security aspects, 206–214
application architecture, 210–212
network reconnaissance, 208–209
profiling, 206–208
security updates, 209–210
Segmentation Indicator bits (SI bits), 220
Segmentation Offset (SO), 220
Self-Organizing Networks (SON), 204
Semi-persistent scheduling (SPS), 67, 352
Sentences, 273
Sequence Number (SN), 217, 220–221, 334
Serial Rapid IO (sRIO), 16
Server, 143
Server-based solutions, 148–150
alternative server PCIe/offload scenario, 151*f*
DU acceleration blade, 147*f*
scale-out to multiple blades, 147*f*
server-based cell site DU solution, 148*f*
typical server PCIe/offload scenario, 150*f*
Service Data Adaptation Protocol (SDAP), 48
Service Data Unit (SDU), 218, 333, 350

Shared Channel (ULSCH), 71
Sigmoid method, 80
Signal aggregation, 230–231, 231*f*
Signal processing chain, 331
Signal-to interference and noise ratio (SINR), 352–353
Signal-to-interference ratio (SIR), 241–242
Signal-to-noise ratio (SNR), 28, 78, 243
Signaling Radio Bearers (SRBs), 49, 217
Silicon devices, 140
Single Frequency Network (SFN), 202
Single Instruction Multiple Data (SIMD), 174–176, 257–258, 312
Single-Rate Tri Color Marking (srTCM), 99–100
Slot-slot structure, 352
Slow start, 100
Small cells, 354
"Smart Network Interface Card" (SmartNIC), 148–149
Software Defined Approach, 158
Software defined solution, 154
Software optimization techniques, 257–260
  arg(max) vectorization, 258–260
Software optimization techniques, 322–327
Software performance, 309
  central processing unit loading summary, 319
  development environment optimization, 321–322
  life-of-a-packet double data rate utilization analysis, 320
  mitigation techniques, 320–321
  packet processing cycle budget analysis, 310–312
  physical layer complexity analysis, 313–318
  software optimization techniques, 322–327
  system-on-chip performance counters, 319
Software-defined networking (SDN), 1, 48, 350
  deployment options including, 353–354, 353*f*
Software-defined radio (SDR), 5
Sounding Reference Signal (SRS), 315
SPECint, 178
Spectral aspects, 355
  V2X spectrum allocation, 356*f*
Spectrum, 8–14
Spectrum allocation system (SAS), 11–12, 11*f*
Stability
  cellular network synchronization requirements, 290
  testing, 342
Stack processing, 331–332
Standardization efforts, 224
Static code analysis, 329–330
Static scheduling, 250
STREAM, 178
Sub 6 GHz front end module, 165–167
  control, 166–167
  receive, 166
  transmit, 166
Subcarrier spacing (SCS), 351
"SubPDUS", 223
Supplementary Uplink operation (SUL operation), 69–70
Symbol duration/subcarrier spacing (SCS), 65
Sync equipment requirements, O-RAN, 296–298
Sync solution implementation, 298–302
  designing PTP + SyncE solution, 302
  frequency-only systems, 298–299
  time-synchronization systems, 299–302
Synchronization, 88–89, 269
  O-RAN, 265–269, 273–290, 274*f*, 292
    network-based synchronization, 274–275
    packet time transport and precision time protocol, 278–279
    physical-layer transport and synchronous Ethernet, 275–278
    PTP, 279–289
    putting PTP and SyncE, 289–290
  process, 285
Synchronization Signal Block (SSB), 88
Synchronization Status Messages (SSMs), 277
Synchronous Ethernet (SyncE), 275–278, 289–290, 294–296
  asynchronous Ethernet clocking, 276*f*
  Ethernet rate mismatch, 276*f*
  SyncE ESMC messaging, 277*f*
  SyncE propagation, 277*f*
Syntonization, O-RAN, 265–269
System dimensioning, 103
System information (SI), 49
System integration, 343

System mapping, 103
System software
  3GPP and IEC security requirements, 212–214
  functional application platform interface, 201–206
    network monitor mode API, 204–206
    nFAPI, 203–204
    PHY API, 202–203
  networking stacks, 197–200
  operating system, 183–197
  security aspects, 206–214
    application architecture, 210–212
    network reconnaissance, 208–209
    profiling, 206–208
    security updates, 209–210
System tests, 329
  consumer application hardening, 340
  feature testing, 333–334
    example of feature compliance matrix, 334*f*
  interoperability testing, 338–340
  RF compliance testing, 335–338
  SA/NSA, 332*f*
  setup, 332–340
System Validation Test (SVT), 329
System-level optimization, 254–257
  high-level view of an O-RAN CU/DU/RU system implementation, 255*f*
  system-level scheduling challenge, 255*f*
System-on-Chip (SoC), 117–119, 309
  performance counters, 319

T

TCXO, 304
Telecommunications Infrastructure Project (TIP), 7–8
3G networks, 215
3G/4G/5G macro cell, 15–17
3GPP, 212–214, 320
  5G standards, 357
  I/Q transport, 223–224
  Layer-2 protocol stack and interfaces, 49*f*, 60*f*
  protocol, 187–188
    split and terminology, 44*f*
  standards, 32, 333, 350–353
    high reliability, 352–353
    interference management, 353
    orthogonal frequency division multiplexing numerologies, 351–352
    slot/mini-slot structure, 352
    uplink grant-free transmission, 352
  systems, 189
Throughput, 320–321
  testing, 341
Time, 267–273
  accuracy, 291
  and frequency synchronization, 84
  holdover, 305
  O-RAN, 265–269
  relationship of TAI to UTC, 268*f*
  synchronization, 148
  time-domain scheduling, 250
  time–frequency offset estimation, 314
Time-Division Duplex (TDD), 63, 311
Time-Sensitive Networking (TSN), 33, 349
Time-synchronization systems, 299–302
  PTP + SyncE solution flow, 302*f*
  servo performance comparison, 301*f*
  timestamping points, 300*f*
Timestamping location and resolution, effects of, 303–305
  oscillator selection and holdover, 303–305
Timing, 143
Tool Command Language (TCL) scripting, 330
Top of Rack (TOR), 142
Traditional base station architectures, 14–17
  3G/4G/5G macro cell, 15–17
  all-in-one base station, 15
Traffic classes, 92–93
Traffic generators, 333
Traffic requirements based performance analysis, 104–106
Transaction layer packetization, 180–181
  PCIe per-lane performance, 179*t*
Transmission Time Interval (TTI), 65, 110
Transmit ON/OFF power, 335
Transmit operation, 126
Transmit Power Control (TPC), 66
Transmit/reception point (TRP), 28, 255
Transmitted signal quality, 335
Transmitter, 335

intermodulation, 335
spurious emissions, 335
Transparent Mode (TM), 220–221
Transport Blocks (TBs), 59, 123–124, 223
level CRC, 124–125
Transport channels, 70–71
Tunnel Endpoint Identifier (TEID), 53, 215
"Turbo" frequency, 140
Two-way protocol, 279
2G networks, 215
Tx droop correction, 337
Tx gain/phase error, 337
Tx LO leakage correction, 336
Type of Service (ToS), 98

U

U-plane latency, 342
Ubuntu, 186
Ultra-reliable low-latency communication (URLLC), 5–6, 349–354
3GPP standards, 350–353
in 5G/NR, 350–353
deployment options including edge compute and software-defined networking, 353–354
use cases and requirements, 350*t*
UMTS Terrestrial Radio Access Network (UTRAN), 53
Unacknowledged Mode (UM), 220–221
Unified Data Management (UDM), 47
Unit testing, 330, 333
Unlicensed spectrum, 13–14
Unmanned arial vehicle (UAV), 338
UP function (UPF), 44–47
Uplink (UL), 330
chain tests, 330
directions, 350
grant-free transmission, 352
Urban canyons, 271
Use-case
dimensioning for latency, 108–110
scenarios, 338
User count, 103
User data rate dimensioning, 106–107
User Equipment (UE), 11–12, 202, 251, 332–333, 352
test pool, 338
User Equipment bandwidth reduction, 361
User Plane (UP), 31, 43, 45*f*, 46*f*, 143
application components
DFE, 230–234
eCPRI protocol, 223–228
GTP protocol, 215–217
low physical layer, 228–229
MAC protocol, 222–223
PDCP protocol, 217–220
RLC protocol, 220–222
User selection
active, 251
primary, 251–252
Users/transmission time interval, 110–111
UTC. *See* Coordinated Universal Time (UTC)
Utility function, 251

V

Vector-Length Agnostic programming model (VLA programming model), 176
Vehicle-to-anything standards and deployment timeline, 355–358
4G C-V2X (PC5), 356–357
802.11p, 356
deployment timeline, 358
NR C-V2X (PC5), 357
standards summary, 357–358
different wireless protocol stacks, 357–358
V2X protocol stacks, 358*f*
Vehicle-to-infrastructure (V2I), 355, 355*f*
roadside unit architecture and implementation, 354–360
RSU, 358–360
spectral aspects, 355
vehicle-to-anything standards and deployment timeline, 355–358
Vehicle-to-Network (V2N), 355, 355*f*
Vehicle-to-Pedestrian (V2P), 355, 355*f*
Vehicle-to-Vehicle (V2V), 355, 355*f*
Vendor lock-in, 6
"Vendor-independent API" concept, 33
Virtual local area networks (VLAN), 209
Virtual Network Function (VNF), 203
Virtual private network (VPN), 208

Virtualization (KVM), 188
VoIP, 219

W
Weighted RED (WRED), 100
White box
  hardware system, 141
  systems, 35
  testing, 343–345
    DU L2 stack unit test benchmarking platform, 345*f*
    system lifecycle performance tracking, 343*f*
Wideband Code Division Multiple Access (WCDMA), 86

X
x86, 176, 183
xRAN, 7–8
  Forum, 8

Z
Zadoff–Chu sequence, 85–86
Zero-Intermediate Frequency (Zero IF), 159