

Question #1: What is little endian?

```
0100 BB6500      MOV     AX,0005
```

From above example we see, **The hexadecimal value stored (0500) is reversed**. This means that AX actually holds 0005, even though it's stored as 05 00 in memory.

Question #2: Explain B8 and BB concept.

Both are name/opcode of the operation “MOV”. They are used for following purposes:

```
0100 BB6500      MOV     AX,0005
```

B8 moves 16 bit value into AX register

```
0103 BB0A00      MOV     BX,000A
```

BB moves 16-bit value into BX register

Question #3: M1 0100?

CS	0000	SP	FFFE	SS	19F5	FS	19F5	+6	E000	0	0	1	0	0	0	0
CMD >										0	1	2	3	4	5	6
0100	BB6500									DS:0100	BB	65	00	BB	0A	00
0103	BB0A00									DS:0103	BB	0A	00	01	00	00
0106	01D8									DS:0106	CD	21	00	04	31	02
0109	BB6F00									DS:0109	89	56	E4	89	46	E6
010B	01D8									DS:010B	F6	00	00	8B	46	F6
010D	01D8									DS:010D	D1	E0	C5	5E	D0	01
010F	BB6F00									DS:010F	07	00	57	02	05	D2
0110	BB6F00									DS:0110	85	C0	74	1C	C7	46
0110	CD21									DS:0110	00	BE	5E	FC	83	7D

M1 0100 points the memory address 0100 in the system’s memory segment as marked above.

Question #4: Program terminate and interrupt?

```
0100 01D8      MOV     AX,BX
010D BB0A00      MOV     AX,000A
```

Program is **terminated** when **4C00** is moved to AX register as shown above.

After this **interrupt (INT 21)** is executed as shown below:

```
010D BB0A00      MOV     AX,4C00
0110 CD21      INT     21
```