



State Machine design

Using one model:-


- Designing a simple collision Avoidance system to use state machine for implementation
- Starting from waiting state and switching to driving state if distance is higher than threshold which is 50 in our case



- Flow of implementation



- Simulation result




- Implementation with C

```
Driving State : Distance = 49 Speed = 30
Waiting State : Distance = 52 Speed = 0
Driving State : Distance = 45 Speed = 30
Waiting State : Distance = 49 Speed = 0
Waiting State : Distance = 54 Speed = 0
Driving State : Distance = 53 Speed = 30
Driving State : Distance = 53 Speed = 30
Driving State : Distance = 45 Speed = 30
Waiting State : Distance = 53 Speed = 0
Driving State : Distance = 47 Speed = 30
Waiting State : Distance = 47 Speed = 0
Waiting State : Distance = 48 Speed = 0
Waiting State : Distance = 48 Speed = 0
Waiting State : Distance = 45 Speed = 0
Waiting State : Distance = 48 Speed = 0
Waiting State : Distance = 45 Speed = 0
Waiting State : Distance = 50 Speed = 0
Waiting State : Distance = 46 Speed = 0
Waiting State : Distance = 46 Speed = 0
Waiting State : Distance = 52 Speed = 0
Driving State : Distance = 50 Speed = 30
Waiting State : Distance = 53 Speed = 0
Driving State : Distance = 52 Speed = 30
Driving State : Distance = 53 Speed = 30
Driving State : Distance = 52 Speed = 30
Driving State : Distance = 47 Speed = 30
Waiting State : Distance = 48 Speed = 0
```


Codes Can be found in the Repo

Using multiple models


- Here we implement using 3 models, one for CA program, one for US sensor and one for DC motor




- US diagram




- DC diagram



- CA diagram



- Simulation



- C implementation

```
CA_Waiting State: distance =47 Speed =0
CA -----speed = 0-----> DC

DC_busy State: speed =0
US_Waiting State: distance =46
US -----distance = 46-----> CA

CA_Waiting State: distance =46 Speed =0
CA -----speed = 0-----> DC

DC_busy State: speed =0
US_Waiting State: distance =53
US -----distance = 53-----> CA

CA_driving State: distance =53 Speed =0
CA -----speed = 30-----> DC

DC_busy State: speed =30
US_Waiting State: distance =47
US -----distance = 47-----> CA

CA_Waiting State: distance =47 Speed =30
CA -----speed = 0-----> DC

DC_busy State: speed =0
US_Waiting State: distance =51
US -----distance = 51-----> CA

CA_driving State: distance =51 Speed =0
CA -----speed = 30-----> DC

DC_busy State: speed =30
US_Waiting State: distance =53
US -----distance = 53-----> CA
```

Codes Can be found in the Repo