

Ehcache Cache Plugin - Reference Documentation

Authors: Burt Beckwith

Version: 1.0.0.M2

Table of Contents

- 1** Introduction To The Cache Plugin
 - 1.1** Change log
- 2** Usage
 - 2.1** Cache DSL

1 Introduction To The Cache Plugin

The Grails Cache Ehcache plugin extends the [Cache](#) plugin and uses [Ehcache](#) as the storage provider for cached content. It replaces the core plugin's `grailsCacheManager` bean with one that uses an Ehcache backend.

1.1 Change log

Version 1.0.0.M2 - May 12, 2012

2 Usage

Although this plugin uses a different backing store than the core plugin, its usage is the same. You annotate service methods, controller action methods, and taglib closures with the three caching annotations, and configure caches in `Config.groovy` and/or `*CacheConfig.groovy` artifacts in `grails-app/conf`. See the [core plugin docs](#) for general usage information.

Ehcache supports many configuration options and most are available in the cache DSL, including support for distributed caching. See the DSL section for details.

2.1 Cache DSL

The full Ehcache DSL will not be documented because except for some exceptions and extensions, the DSL is nearly identical to the XML format for the `ehcache.xml` file, although of course the syntax is somewhat different. The `ehcache.xml` syntax is described in [this well commented example](#) and you can view the XML Schema [here](#). The DSL uses types where appropriate, for example numeric and boolean values; this isn't possible in XML since all attributes must be strings.

Caches

Like in the core plugin, you configure a cache with the `cache` call, and set configuration options in a closure, for example

```
cache {
  name 'mycache'
  eternal false
  overflowToDisk true
  maxElementsInMemory 10000
  maxElementsOnDisk 10000000
}
```

The name attribute is mandatory, and all of the other attributes correspond to the `ehcache.xml` XML attributes for the `<cache>` tag.

Default cache and cache defaults

Ehcache supports auto-creation of caches and this is enabled in this implementation, so if you call the `getCache(String name)` method on the `CacheManager` (via the `grailsCacheManager` bean) and the cache didn't already exist it would be created and returned. Since it didn't already exist there is no configuration for it, so it uses the settings for the "default cache", for example:

```
defaultCache {
  maxElementsInMemory 10000
  eternal false
  timeToIdleSeconds 120
  timeToLiveSeconds 120
  overflowToDisk true
  maxElementsOnDisk 10000000
  diskPersistent false
  diskExpiryThreadIntervalSeconds 120
  memoryStoreEvictionPolicy 'LRU'
}
```

It is important to specify the `defaultCache` configuration since Ehcache will throw an exception if you attempt to auto-create a cache and there is no default configuration. You may want this behavior though, since if you are confident that you have specified all known caches then auto-creating a new cache is probably due to a typo or programming error.

Don't confuse `defaultCache` with `defaults`, which helps keep your configuration DRY and isn't a feature of Ehcache. This feature lets you specify default values that all caches must have, for example

```
defaults {
  maxElementsInMemory 1000
  eternal false
  overflowToDisk false
  maxElementsOnDisk 0
}
```

These values are set on each cache configuration while the DSL is being parsed, and you can override any value in a cache definition, for example where most caches use the default value but a few have custom values.

Note that the special `hibernateQuery` and `hibernateTimestamps` caches (see below) and caches auto-created by Ehcache using the values in `defaultCache` do not use values in the `defaults` configuration. The Hibernate caches don't because they are special-purpose caches and unlikely to share general default settings, and the auto-created caches don't because Ehcache doesn't know about this feature.

The "provider" block

All cache DSLs support a `provider` block, it isn't applicable for all DSLs. This is a way to specify provider-specific values, for example

```
provider {
  updateCheck false
  monitoring 'on'
  dynamicConfig false
  defaultTransactionTimeoutInSeconds 30
  maxBytesLocalHeap 10
  maxBytesLocalOffHeap 20
  maxBytesLocalDisk 30
}
```

In the case of Ehcache, these settings end up in the top-level `<ehcache>` tag, e.g.

```
<ehcache defaultTransactionTimeoutInSeconds="30" dynamicConfig="false"
  maxBytesLocalDisk="30" maxBytesLocalHeap="10"
  maxBytesLocalOffHeap="20" monitoring="on" updateCheck="false">
```

Hibernate second-level cache

It is possible to use Ehcache as the Hibernate second-level cache provider and as the provider for the caches managed by this plugin, or use different providers for each. It's more convenient to use Ehcache for both however and the DSL has support for configuring both at the same time.

Hibernate uses two caches, one for its query cache (with name "org.hibernate.cache.StandardQueryCache") and one for tracking the timestamps of the most recent table updates (with name "org.hibernate.cache.UpdateTimestampsCache"). The DSL supports two methods that create reasonable configurations for these caches (but you're free to configure your own). Including a call to the `hibernateQuery()` method will generate this XML:

```
<cache name="org.hibernate.cache.StandardQueryCache"
      maxElementsInMemory="50"
      timeToLiveSeconds="120"
      eternal="false"
      overflowToDisk="true"
      maxElementsOnDisk="0"
/>
```

and a call to the `hibernateTimestamps()` method will generate this XML:

```
<cache name="org.hibernate.cache.UpdateTimestampsCache"
      maxElementsInMemory="5000"
      eternal="true"
      overflowToDisk="false"
      maxElementsOnDisk="0"
/>
```

Hibernate domain class second-level caches

Typically you configure a cache with the `cache` call, but "domain" is an alias for "cache" and can be used when configuring caches for domain classes to make it clear what the cache is used for. Hibernate expects that the cache name is the full class name including the package; you can specify the full class and package as the "name" attribute:

```
domain {
  name 'com.yourcompany.yourapp.Person'
  eternal false
  overflowToDisk true
  maxElementsInMemory 10000
  maxElementsOnDisk 10000000
}
```

but you also use the class name to get a compile-time verification that the class is correct:

```
import com.yourcompany.yourapp.Person

...

domain {
  name Person
  eternal false
  overflowToDisk true
  maxElementsInMemory 10000
  maxElementsOnDisk 10000000
}
```

When you have configured caching for a mapped collection (for example the books collection in an Author class) Hibernate expects the cache name to be the containing class full name plus the collection field name. Use the domainCollection call with an inner domain attribute to tell the DSL what the name of the owning class is, e.g.

```
domain {
  name 'com.foo.Author'
  eternal false
  overflowToDisk true
  maxElementsInMemory 10000
  maxElementsOnDisk 10000000
}
domainCollection {
  name 'books'
  domain 'com.foo.Author'
  eternal true
  overflowToDisk true
  maxElementsInMemory 100
  maxElementsOnDisk 10000
}
```

Or you can use the more compact inner closure syntax and omit the domain attribute:

```
domain {
  name 'com.foo.Author'
  eternal false
  overflowToDisk true
  maxElementsInMemory 10000
  maxElementsOnDisk 10000000

  collection {
    name 'books'
    eternal true
    overflowToDisk true
    maxElementsInMemory 100
    maxElementsOnDisk 10000
  }
}
```

diskStore

If any cache supports overflowing to disk, you need to configure where to store this data with the diskStore call. You can specify an absolute path (but this is likely to be a brittle and non-portable approach):

```
diskStore {
    path '/tmp/ehcache'
}
```

You can also call `temp true` to use the value of the `java.io.tmpdir` system property:

```
diskStore {
    temp true
}
```

or `home true` to use the value of the `user.home` system property:

```
diskStore {
    home true
}
```

or `current true` to use the value of the `user.dir` system property:

```
diskStore {
    current true
}
```

Overriding values

You can specify cache configuration in multiple places; the application's `Config.groovy`, the application's `*CacheConfig.groovy` artifact files in `grails-app/conf`, and in plugins' `*CacheConfig.groovy` artifact files in their `grails-app/conf` directories. Configurations that are loaded later will replace previously set values and add new ones; this can be configured with the `order` attribute.

So for example a plugin might have this configuration:

```
order = 500
config = {
    cache {
        name 'the_cache'
        eternal false
        overflowToDisk true
        maxElementsInMemory 2
        maxElementsOnDisk 3
    }
}
```

and the application's `Config.groovy` might have this:


```
grails.cache.config = {
  cache {
    name 'the_cache'
    maxElementsInMemory 10000
    maxElementsOnDisk 100000000
  }

  cache {
    name 'another_cache'
    ...
  }

  defaults {
    timeToLiveSeconds 1234
  }
}
```

Since the plugin's order is lower than that of the `Config.groovy` (since order is unspecified it defaults to 1000) the resulting configuration will be as if this single configuration existed:

```
grails.cache.config = {
  cache {
    name 'the_cache'
    eternal false
    overflowToDisk true
    maxElementsInMemory 10000
    maxElementsOnDisk 100000000
  }

  cache {
    name 'another_cache'
    ...
  }

  defaults {
    timeToLiveSeconds 1234
  }
}
```

Environments

A cache (or domain) element can specify one or more environment names to define when the cache is valid; when the DSL is evaluated the XML will only contain caches that are valid for the active environment. You can specify a single string:

```
domain {
  name 'com.foo.Other'
  env 'staging'
}
```

or a list of strings

```
domain {
  name 'com.foo.Book'
  env(['staging', 'production'])
}
```

and if no environments are specified the cache will be included in all environments.

Distributed caches

The DSL includes support for distributed caches, which are implemented with the `cacheManagerPeerProviderFactory`, `cacheManagerPeerListenerFactory`, `cacheManagerEventListenerFactory`, `bootstrapCacheLoaderFactory`, `cacheExceptionHandlerFactory`, `cacheEventListenerFactory`, `cacheLoaderFactory`, and `cacheExtensionFactory` calls. These support the same attributes as the corresponding XML elements except that the `class` XML attribute is `className` in the DSL.

In addition, there are several shortcuts for common values. These include symbols to use for time to live (TTL) numeric values for the `timeToLive` property in a `cacheManagerPeerProviderFactory` element:

DSL name	value
"host"	0
"subnet"	1
"site"	32
"region"	64
"continent"	128
"unrestricted"	255

symbols to use for `cacheManagerPeerProviderFactory` element `className` attribute:

DSL name	class name
"rmi"	"net.sf.ehcache.distribution.RMICacheManagerPeerProviderFactory"
"jgroups"	"net.sf.ehcache.distribution.jgroups.JGroupsCacheManagerPeerProviderFactory"
"jms"	"net.sf.ehcache.distribution.jms.JMSCacheManagerPeerProviderFactory"

symbols to use for `cacheEventListenerFactory` element `className` attribute:

DSL name	class name
"rmi"	"net.sf.ehcache.distribution.RMICacheReplicatorFactory"
"jgroups"	"net.sf.ehcache.distribution.jgroups.JGroupsCacheReplicatorFactory"
"jms"	"net.sf.ehcache.distribution.jms.JMSCacheReplicatorFactory"

and symbols to use for `bootstrapCacheLoaderFactory` element `className` attribute:

DSL name	class name
"rmi"	"net.sf.ehcache.distribution.RMIBootstrapCacheLoaderFactory"
"jgroups"	"net.sf.ehcache.distribution.jgroups.JGroupsBootstrapCacheLoaderFactory"

Note also that environment support (which is valid in any `cache` (or `domain`) element and any distributed element) is especially important for distributed configuration. Most users will run non-distributed in development and possibly test environments, and only enable it in production or production-like environments. By adding one or more environment values to these elements you can have a single DSL that works in any environment. For example, this Groovy code

```

defaults {
    maxElementsInMemory 1000
    eternal false
    overflowToDisk false
    maxElementsOnDisk 0
    cacheEventListenerFactoryName 'cacheEventListenerFactory'
}

domain {
    name 'com.foo.Book'
}

cacheManagerPeerProviderFactory {
    env 'production'
    factoryType 'rmi'
    multicastGroupAddress '${ehcacheMulticastGroupAddress}'
    multicastGroupPort '${ehcacheMulticastGroupPort}'
    timeToLive 'subnet'
}

cacheManagerPeerListenerFactory {
    env 'production'
}

cacheEventListenerFactory {
    env 'production'
    name 'cacheEventListenerFactory'
    factoryType 'rmi'
    replicateAsynchronously false
}

```

will generate this XML in production:

```

<ehcache ...>
<diskStore path="java.io.tmpdir" />
<defaultCache
    maxElementsInMemory="10000"
    eternal="false"
    timeToIdleSeconds="120"
    timeToLiveSeconds="120"
    overflowToDisk="true"
    maxElementsOnDisk="10000000"
    diskPersistent="false"
    diskExpiryThreadIntervalSeconds="120"
    memoryStoreEvictionPolicy="LRU"
/>
<cacheManagerPeerProviderFactory
    class='net.sf.ehcache.distribution.RMICacheManagerPeerProviderFactory'
    properties="multicastGroupAddress=${ehcacheMulticastGroupAddress},
                multicastGroupPort=${ehcacheMulticastGroupPort},
                timeToLive=1,peerDiscovery=automatic"
    propertySeparator=', '
/>
<cacheManagerPeerListenerFactory
    class='net.sf.ehcache.distribution.RMICacheManagerPeerListenerFactory'
/>
<cache name="com.foo.Book"
    maxElementsInMemory="1000"
    eternal="false"
    overflowToDisk="false"
    maxElementsOnDisk="0">
<cacheEventListenerFactory
    class='net.sf.ehcache.distribution.RMICacheReplicatorFactory'
    properties="replicateAsynchronously=false"
    propertySeparator=', '
/>
</cache>
</ehcache>

```

(note that `${ehcacheMulticastGroupAddress}` and `${ehcacheMulticastGroupPort}` are an Ehcache feature that lets you use system property names as variables to be resolved at runtime)

and this XML in development:

```
<ehcache ...>
<diskStore path="java.io.tmpdir" />
<defaultCache
    maxElementsInMemory="10000"
    eternal="false"
    timeToIdleSeconds="120"
    timeToLiveSeconds="120"
    overflowToDisk="true"
    maxElementsOnDisk="10000000"
    diskPersistent="false"
    diskExpiryThreadIntervalSeconds="120"
    memoryStoreEvictionPolicy="LRU"
/>
<cache name="com.foo.Book"
    maxElementsInMemory="1000"
    eternal="false"
    overflowToDisk="false"
    maxElementsOnDisk="0"
/>
</ehcache>
```