1.	B
2.	C
3.	A
4.	C
5.	B
6.	A
7.	A
8.	A
9.	A
10	B
11	B
12.	C
13	B
14	C.
15	B
16.	C

17. A

18 B

19. A

20. D

Answer

21. Supervised learning in the machine learning algorithm it's the algorithm that use and learn from the label data set.

22. Data pre-processing is use for cleaning data set. Imagine you have a data set that have alot of N/A value so for make your more clean we use preprocessing. ~~pre~~ during the preprocessing it'll check the missing value. After it'll decise to to replace or delete and it find the outlier and cut it out if unnessary.

~~23.~~

24. • the first SVM classifier
  - as show in the picture the linear boundaries is near to the node so that it not best optimal what we want is we need the linear boundaries as far as it can from the node.
• the seconde SVM classifiers:
  - it tha same as the first the linear boundaries is very close to the node.
• the last SVM classifier: it is the best optimal since the linear boundaries ~~that~~ stay in the middle and far from node.

22. for model M1 it accuracy for the training data since given 99% of accuracy. but it seem low with testing data set which is only 30%. so model M1 should Improve on the testing data set to maine sure it is fully accuracy before implement.

31. K in K-means algorithm which mean the ~~nu~~ number of block.

29. in K-NN we need ~~f~~ to find the distance, voting, and choosing. for finding the distance we have 4 function and 1 of them which is ~~e~~ call "Hamming Distance" is use in case of categorical variable. and After that it required for normalization for scaling data in range base on k that we provide when building. After ~~tha~~ that we have ~~a~~ an activity for voting if ~~whic~~ which class wining, the new data will ~~bt~~ ~~belog~~ belong to that class.

27. Outlier in the Data is the unnessary value that we need to delete. for an example you predict the age of people and most of data have two ~~nu~~ number but some data have three number so the data that have ~~3~~ three number is the outlier that we need to ~~deleted~~ for reduce ~~to~~ our dataset. for find the outlier we have function.

30.

23. Regression analysis is analy base on the independent Varaible to ~~a~~ analy the dependent Varaible. Independt Varaible can have one or more but dependent ~~d~~ Variable have only one.

26. Distinguish between the term: structured and semi-structure is that structred data is more easy to understand than semi-structured data.