


DNA CHALLENGE, SINCE AI HACKATHON 2026, TURKU

SafeStep

A digital security assistant for DNA customers. When a call, message, link or login looks wrong, it tells the person what to do next, explains why, and hands over to a human when needed.







TEAM
Mehrab (engine, API, evaluation)
Arsham (product, UI, usability)

DOCUMENT
Strategy, architecture, implementation and results. 8 November 2026.

STATUS
Prototype on synthetic data. Not a live DNA service, and not official DNA advice.

CONTENTS

What's in this document

We wrote this for the judges and for anyone at DNA who wants to understand how SafeStep works without reading the code. Sections 1 to 3 explain the product. Sections 4 to 8 go into how we built it. Sections 9 to 11 cover what we finished, how well it works, and how DNA could offer it.

01	The problem and our answer	What DNA asked for, what SafeStep does, headline numbers
02	Product strategy	Principles, the five build stages, what success means
03	Architecture	Pipeline, stack, repository, safety boundaries
04	How one message travels through SafeStep	The request, step by step
05	Inside the decision engine	Facts, rules, the action contract, Decision Flip, confidence
06	The LLM layer	Models, fallbacks, and what the model is allowed to do
07	Security and privacy techniques	Masking, output checks, link sandbox, consent, sessions
08	Frontend, API and testing	UI, PWA, voice, endpoints, 555 tests, evaluation
09	Integration path and work done	From prototype to DNA, who built what, final day
10	Results	Evaluator scores, journeys, review, comprehension
11	Business hypothesis, limits and links	Plans, honest limits, where to find everything

SECTION 01

The problem and our answer

People get warnings about suspicious calls, messages, links and logins every day, but a warning only says something is wrong. It doesn't say what to do. DNA asked for an assistant that turns a user's description and available risk signals into a clear, proportionate next step, explains why, asks only what is needed, admits uncertainty and hands off to a human when needed.

94.4%
Safe-action pass, 588 dev cases (baseline 60.5%)

0.0%
Unsafe statements (target 0%)

97.0%
Escalation recall (target 90%+)

5 / 5
Sample journeys pass 20/20 safe in manual review

What it does

STOP SCREEN

Interrupt first

If a caller is still on the line or money is about to move, a Stop screen appears before any question.

DECISION FLIP

Ask only what matters

A question is asked only if “Yes” and “No” lead to different advice. “Not sure” is always allowed.

SIGNAL UNLOCK

Consent before data

Simulated DNA signals (SIM changes, logins, device findings) are read only after the user agrees.

RESCUE MODE

Guided recovery

When harm already happened, one recovery step at a time, starting with the most urgent.

LINK CHECK

Safe link scoring


Pasted links are fetched as plain text on the server and scored 0–100 with the reasons shown.

TALK TO DNA


Human handoff

A case summary the user approves first, sent to the right person: operator, security or business support.


Screens from the live demo




Describe




Stop




Link check



Decision Flip



Rescue



Plans

Works in Finnish, English and Swedish, by text or voice. Installs as a web app (PWA), and still works without an LLM key thanks to the keyword extractor.

SECTION 02

Product strategy

We aimed for the right **safe action**, not for naming the exact scam. If several situations need the same response, stop investigating and give that response. Conversation is the entry point, not the whole product.

The principles we built against

1. **Interrupt harm before investigating.** Stop instructions come before questions.
2. **Ask only what can change the action.** Every question must change action, urgency or escalation.
3. **Prefer confirmed facts over confident guesses.** Unknown stays unknown.
4. **Use the least personal data possible.** Narrow, understandable consent.
5. **Keep every screen calm and short.** One action, one reason.
6. **Escalate by incident need,** not only by risk score.
7. **Never leave the user with advice alone.** Rescue Mode guides recovery.
8. **Treat incident content as untrusted.** Messages can't change the rules.
9. **Be honest about boundaries.** Synthetic signals, simulated actions.
10. **Protect secrets** even when users share them by accident.
11. **Fail safely.** Any failure still ends in conservative, useful guidance.

Delivery in five stages

STAGE 1

Safety & product contract

What SafeStep may conclude and how an incident is represented.

STAGE 2

Situations & minimum questions

Reach the right action with as few yes/no questions as possible.

STAGE 3

Low-friction experience

Conversational intake, interruption, Decision Flip, summaries.

STAGE 4

Signal Unlock & Rescue

Minimal, transparent data access and guided recovery.

STAGE 5

Prove quality

Evaluation, held-out tests, attack tests, human review.


How we measured success

Measure	Where we landed
High safe-action accuracy across all five journeys	**94.4%** overall; weakest journey (suspicious call) 81.9%
Very low false alarms on harmless situations	**9.8%** (target under 10%, baseline 28%)
Decisive question asked when the action depends on it	**96.7%** on twin cases
No optional signals used without consent	**0.0%** consent violations
Short answers in Finnish, English and Swedish	Answer in user's language 99.1%, readable 98.8%
Users can restate the next action in their own words	**4 of 6** responses understood (3 listeners), see section 10

SECTION 03

Architecture

Our rule from day one: **the LLM reads and words, code decides.** The LLM turns messy text into structured facts; a deterministic TypeScript engine chooses status, risk, urgency, action and human destination. The web app and the evaluator use the same engine, so scores reflect the real product.



Technology stack

Web app & API	Next.js 16, React 19, TypeScript 7, Tailwind 4
Validation	Zod 4 for API input and LLM output
LLM	Gemini `gemini-3.5-flash-lite` or OpenAI `gpt-5.4-mini` ; keyword extractor fallback
Voice	Browser / OpenAI speech-to-text; ElevenLabs or OpenAI speech
Testing	Vitest (555 tests) + supplied Python evaluator
Hosting	Vercel; sealed sessions survive serverless instances

Repository layout

`app/`	Next.js app; `/api/sessions` is the main flow
`components/`	Chat turns, link card, plans, report, voice
`engine/`	Rules, Decision Flip, extraction, composer, guards
`adapters/`	LLM, link scan, simulated signals, handoff, sessions
`content/`	Approved text in fi / en / sv
`eval/`	Runners, scenarios, results
`review/`	Manual safety review & comprehension
`tests/`	Unit and attack-hardening tests

Safety boundaries

SafeStep will never…	How it's enforced
Let the model decide risk, action or escalation	Rules choose; outcomes outside the action contract fall back to the cautious “unclear” path.
Call something safe without evidence	“Safe” needs positive evidence; facts without a quote from the user are dropped.
Follow instructions inside a forwarded message	Pasted content is untrusted data; “verified safe” claims are ignored. Attack tests cover it.
Use personal data without consent	Signals read only after a yes, only when they'd change the advice, only for that session.
Take an irreversible action	Never blocks, pays or contacts anyone; every handoff waits for approval of its summary.
Repeat or request secrets	Masked before the LLM, chat history and handoff; replies asking for codes are dropped.

SECTION 04

How one message travels through SafeStep

Everything below happens on the server inside one Next.js route, `POST /api/sessions`. The browser only renders the typed “screen” that comes back, so the UI holds no safety logic at all.

- **1, Request validated**
  The body is parsed with a strict Zod schema (`z.strictObject`): unknown fields are rejected, messages are capped at 10,000 characters, and language may be `fi`, `en`, `sv` or `auto` (detected by word counts in `engine/language.ts`).
- **2, Input Guard masks secrets**
  `engine/input-guard.ts` replaces card numbers, one-time codes, PINs and passwords with placeholders before any LLM call, log or summary. It records *that* a secret was shared, never its value. IBANs stay readable because they are evidence in payment fraud.
- **3, Fast Danger Check (no LLM)**
  `engine/fast-danger.ts` runs multilingual patterns for live danger: a caller asking for a code, money being moved, remote access, a bank-detail change. If it fires, a Stop screen is returned immediately and the LLM is skipped for that turn.
- **4, Facts are read**
  The LLM (Gemini, then OpenAI) returns a strict JSON object of facts, each with a quote. In parallel, the deterministic `offline-extractor.ts` reads the same text; it also takes over completely if the LLM times out (8 s) or is rate-limited.
- **5, Fact Validator**
  A fact survives only if its quote really appears in the masked text. Unquoted claims return to “unknown”, so a model can't narrow a case by inventing details. Where the two extractors disagree, the topic is marked as a conflict and must be asked.
- **6, Rules decide**
  58 ordered situation rules in `engine/situations.ts` are matched first-hit. Each returns status, risk, urgency, primary action, steps, sources and human destination. `engine/contract.ts` then checks the combination; anything outside the contract becomes the cautious “unclear” path.
- **7, Decision Flip or answer**
  If an unknown fact would change the outcome, one Yes / No / Not sure question is shown (at most 2 per case outside triage). Otherwise the Composer builds the reply only from approved text and the Output Guard checks it.
- **8, Session sealed and returned**
  The journey is kept in memory (30-minute TTL) and also returned to the browser as an AES-256-GCM sealed token, so any serverless instance can continue the conversation. The client can neither read nor change it.

The screen contract

`engine/screens.ts` is the only interface between engine and UI. The API returns one of a fixed set of screens, **stop**, **flip** (question), **describe** (ask for details), **unlock** (consent), **rescue**, **handoff**, **result**, **fallback**, **end**, plus a state object (status, risk, urgency, confidence). This let the two of us build in parallel: the UI was built against mock screens (`mocks/screens.ts`) while the engine was being written, and swapping mock for real data changed nothing else.

SECTION 05

Inside the decision engine

The engine (`engine/` , about 3,900 lines of TypeScript across 27 modules) has no Next.js code and never reads dataset answers. The same code powers the web app and every evaluation run.

FACT MODEL

A small, fixed vocabulary

Every case is reduced to typed facts: **21 incident types** (e.g. phone_call, payment_detail_change, sim_or_number_change, ransomware, partner_monitoring), what was asked for (money, code, card, login, app install, remote access, bank change, approval), what the user already did, who the sender pretends to be, and **18 decisive topics** such as `code_shared` , `money_transferred` , `self_initiated` and `user_safety` . Values the evaluator scores are kept byte-identical to the SimSet vocabularies.

OFFLINE EXTRACTOR

Works with no LLM at all

A 290-line deterministic reader for Finnish, English and Swedish. Text and patterns are both “folded” (ä→a, ö→o, å→a) because many users skip those letters. Negations are handled per language (“en klikannut”, “didn't click”, “jag gav inte”), and it reports only what it can quote. All benchmark numbers in this document come from this extractor, so they are reproducible without an API key.

Situation rules and the action contract

Rules are plain TypeScript objects: `{ id, when(case), flips[], then(case) }` . Order matters, specific dangers (sextortion, seed-phrase requests, codes given to a fake operator) come before generic ones. Each `then` returns an outcome built from approved step IDs and guidance sources. The **action contract** defines, for each of the evaluator's primary actions, which statuses, risks and destinations are allowed; e.g. “contact bank and block cards” normally needs confirmed harm, and is allowed under uncertainty only as worst-case-safe advice after “Not sure”.

Decision Flip algorithm

1. Match the situation for the current facts.
2. For each candidate topic not yet answered, run the rules twice: once with “Yes”, once with “No”.
3. If the two outcomes differ in action, urgency, escalation or steps, that topic is a **flip**; ask it.
4. If every branch gives the same advice, ask nothing and answer.
5. **Not sure** keeps the fact unknown: the advice follows the more severe branch, written conditionally (“If you shared the code…”), and never claims that branch is true.

Typed answers are read per language (`answer-reader.ts`): “ja” means “yes” in Swedish but “and” in Finnish, so every word list is language-specific.

Confidence is evidence-only

Start	0.30
Each confirmed, quoted fact	+0.10
Each unknown decisive fact	–0.20
Each extractor conflict	–0.20
Clamped to	0.10 – 0.95

Severity is deliberately **not** an input, so a critical case with little evidence stays low-confidence. Bands: high ≥ 0.7, medium ≥ 0.4.

Supporting modules

`interruption.ts`	Picks the single Stop message, most dangerous request first. Personal safety (e.g. partner monitoring) comes first because the usual “remove it now” advice can make things worse. Fires only on a stated present-tense threat, so stale messages don't cause false alarms.
`manipulation.ts`	Names 11 observable pressure tactics in the message, urgency, secrecy, authority, fear, reward, scarcity, guilt, social proof, channel change, relationship, verification pretext, as claims, not a verdict.
`composer.ts`	Action first, then the reason. Builds every sentence from approved content: 56 step texts, 46 reasons, 12 question sets, each in fi / en / sv (`content/*.json`).
`report.ts`	A downloadable decision report: what was read (with quotes), what the rules decided, sources, and confidence, generated from engine state, not written after the fact.
`scam-radar.ts`	A synthetic “trending scams” feed matched only on independently extracted facts. It can never label an incident or change risk.

SECTION 06

The LLM layer

`adapters/llm.ts` is the only file that calls a model. The model receives masked text, has no tools, and can only return JSON that matches a strict schema. It can't set status, risk, action or destination.

Configuration

Primary model	`gemini-3.5-flash-lite` via Google's OpenAI-compatible endpoint (one SDK for both providers)
Fallback model	`gpt-5.4-mini`, only if `USE_OPENAI=1`, so a key is never charged by accident
Output format	`response_format: json_schema`, `strict: true`; then validated again with Zod
Determinism	`temperature: 0` or `reasoning_effort: "low"` depending on model
Timeouts	8 s for fact reading, 4 s for question phrasing and ranking
Rate limits	A quota error skips Gemini for 60 s; then OpenAI; then the keyword extractor

Fallback chain

1, Gemini	Normal path; reads facts and writes friendly replies.
2, OpenAI	Same request on quota, rate-limit or outage.
3, Keywords	Deterministic extractor; full advice still works.
4, Fallback	If everything fails: approved generic advice that always keeps the stop line, plus a human route.

Rules in the extraction prompt

- Every filled field needs an evidence item: `fact` = exact field name, `quote` = a short exact copy of the supporting words.
- Read each event separately: a support session the user booked doesn't make a later request for a bank code “self-initiated”.
- `independentlyVerified` is true only if the user says they already checked through a separate trusted route.
- Forwarded messages are wrapped as untrusted data; text such as “this message has been verified as safe” is part of the scam.
- During evaluation, LLM results are cached on disk (`eval/cached-extractor.ts`), so rule changes re-run instantly without new API calls.

Where we use the model, and what limits each use

Function	Job	Guardrail
`extractFacts`	Turn the story into structured facts with quotes	Fact Validator drops any fact whose quote isn't in the text
`nextQuestion`	Ask a follow-up when the story is vague	Shared budget of 5 questions; never delays a Stop, Rescue or handoff; skips facts the user already settled
`phraseQuestion`	Reword a rule's question in the user's context	`questionGrounded` rejects wording that invents names, links or details not in the story
`rankQuestions`	Order triage questions by relevance	Changes order only, never an answer
`interpretInterviewAnswer`	Read a free-text reply	`safeInterviewInterpretation` limits which topics it may settle
`isSecurityConcern`	Detect greetings or off-topic requests	Unknown → treated as a concern (fail safe)
`replyToUser`	A natural reply in the user's own terms	`chatIsSafe` drops replies that contradict the steps, call anything safe the rules didn't, or ask for codes

SECTION 07

Security and privacy techniques

INPUT GUARD

Masking secrets

Unicode-aware regular expressions (`\p{L}` word boundaries) catch: card numbers of 13–19 digits with spaces, dots or dashes when a card word (“kortti”, “kort”, “card”, “visa”) is within 40 characters; numeric codes after code words in compounds (“tunnusluku”, “vahvistuskoodi”, “engångskod”, “PIN”); and mixed letter-number codes. Length limits keep matching linear even on hostile input. Over-masking is acceptable; a missed secret is not.

OUTPUT GUARD

Checking every reply

Before a screen is sent, every string is collected and checked: banned reassurance (“guaranteed safe”, “täysin turvallinen”, “helt säker”…), any secret that survived, and that status labels, steps and conditional branches match approved text in that language exactly. A failing screen is replaced with the safe fallback.

Link check: safe fetching and scoring (`adapters/link-scan.ts` , 790 lines)

Sandbox rules

Links per message	max 3
Timeout / size	6 s, 768 KB
Redirects	max 6, each re-checked
Ports	80, 443, 8080, 8443 only
Private networks	DNS resolved first; private IPv4, loopback, link-local and IPv6 ranges (incl. IPv4-mapped) refused, prevents SSRF
Execution	Plain text only: no scripts, no form submits, no cookies

Signals that add to the score

Brand	Brand name on a non-official domain (banks, operators, Posti…)
Domain	Risky TLDs (.top, .xyz, .click…), hyphenated look-alikes, lure words (verify, refund, tracking), URL shorteners, free hosting
DNS	Missing MX / NS records, unresolvable host
Page	Password or card form, no HTTPS, offline page
Feeds	Google Safe Browsing (optional key)
Message	Pressure words in the text, weighted at 40%

Score = 10 + sum of finding weights, clamped 0–100. Risk bands: **low** < 25 ≤ **medium** < 45 ≤ **high** < 70 ≤ **critical**. Official and well-known domains lower the score. The score only sets the visible link signal shown to the user; the rules still make the decision, and a “clean” result never makes a message safe on its own.

CONSENT GATE

Enforced in code

Optional signals (SIM/eSIM events, logins, installed apps, device findings, credential exposure, staff accounts) are hidden until consent is given for that one signal, and only requested when the result could change the action, urgency or handoff.

SESSIONS

Nothing on disk

In-memory, 30-minute TTL, cleared on “end”. Sealed token: AES-256-GCM, random 12-byte IV, key derived with SHA-256 from a server secret, session ID bound in, expiry inside the ciphertext.

HANDOFF

Facts, not raw text

Only reviewed fact lines enter the simulated agent summary; raw messages stay local. The user sees and approves the summary before anything is “sent”.

SECTION 08

Frontend, API and testing

Frontend

- **17 React components** (~6,200 lines): chat turns, risk gauge, link-analysis card, Decision Flip buttons, Rescue checklist, DNA handoff, plans sheet, decision report, history panel, voice mode with an animated orb.
- **Accessibility:** 270+ ARIA and role attributes, large touch targets, Yes / No / Not sure always as buttons, light and dark themes.
- **PWA:** web manifest, maskable icons and a service worker that caches only the app shell. The chat API is never cached, so no case data stays on the device; offline, an emergency-guidance page is shown.
- **Voice:** speech-to-text through OpenAI, speech through ElevenLabs (multilingual v2) or OpenAI. Speech becomes the same events as typing, so the engine still decides.
- **Mock login** (`lib/mock-users.ts`) simulates an identified DNA customer, as the brief assumes.

API

`POST /api/sessions`	Start a case or send an event
`GET /api/sessions`	Restore a session
`DELETE /api/sessions/[id]`	End and wipe a session
`POST /api/voice/stt`	Speech to text
`POST /api/voice/tts`	Text to speech

Session events: `start` , `answer` , `answer_text` , `add_details` , `ai_answer` , `consent` , `continue` , `rescue` , `talk_to_person` , `handoff` , `end` .

Testing: 555 automated tests in 26 files (Vitest)

Safety & attacks	attack-hardening (prompt injection, “verified safe” claims, secret leaks), input-guard, chat-guard, interview-interpretation-safety, contract
Decisions	fast-danger, interruption, scam-type-detection, unexpected-order, new-scenarios, specific-questions, contextual-guidance, manipulation, stage2
Facts	fact-evidence, fact-conflicts, answer-text, observed-accuracy
Flow & infra	session-flow, sessions-route, session-seal, signals, scam-radar, review, mock-journey, mock-users

Evaluation harness

Command	What it measures
`npm run eval:dev`	Single-turn answers for all 588 dev cases → scored by the organisers' `evaluate.py`
`sim/run_conversation.py --bot "npx tsx eval/bot.ts"`	Multi-turn: our engine talks to the organisers' simulated user over JSON lines (stdin/stdout)
`npm run eval:scenarios`	50 full conversations × 3 languages; flags “severe” failures (scam called safe, missed live danger, secret leaked)
`npm run eval:holdout`	12 paraphrases written after rules were frozen, an honest unseen test
`npm run check:contract`	Every dev case's decision checked against the action contract (0 breaches)
`tools/validate.py --submission`	The 335 test-set predictions (335/335 covered)

SECTION 09

Integration path and work done

From prototype to DNA service

Part	Prototype today	Inside DNA's services
Entry point	Web app	“Is this a scam?” in the DNA app and Oma portal, opened from a call warning or flagged SMS
Identity	Mock login	Existing DNA login, no extra sign-up
Signals	Simulated, behind consent	DNA APIs for SIM/eSIM events, logins and call warnings, behind the same consent screen
Link check	Server-side fetch	Isolated scanning service plus DNA threat feeds
Handoff	Simulated summary	Ticket in DNA customer service or business security support
Sessions	Sealed, short-lived	Shared store under DNA's retention rules

The UI talks to the engine only through `/api/sessions`, so each simulated adapter can be swapped for a real one without changing the decision rules.

Who built what

MEHRAB, ENGINE AND API

Safety contract, decision rules, Decision Flip, fact extraction, Input/Output Guard, Fast Danger Check, session API, simulated signals and handoff, evaluation runners, held-out and attack tests.

ARSHAM, PRODUCT AND UI

Every screen and the user flow on a shared screen contract (`engine/screens.ts`), link-check card, Rescue Mode, plans, voice mode, PWA install, accessibility, usability and the human checks.

What we finished on the last day

- **Audit against the brief**
  Checked every deliverable and criterion; found the human review, comprehension check and demo video missing, and kept real API keys out of the public repo.
- **Fixed three answers found in review**
  Supplier bank change now leads with “don't pay, verify”; leaked reused password now says change it everywhere + MFA; unknown business SIM order goes to the operator with a handoff. Dev pass 91.2% → 94.4%, escalation recall 90.9% → 97.0%, five journeys 4/5 → 5/5.
- **Fixed the live chat**
  The AI follow-up no longer asks “have you paid?” when the user already said “can I pay?”.
- **Manual safety review**
  20 sampled answers scored on the organisers' form: 18/20 first pass, 20/20 safe after re-scoring the fixed answers, 0 unsafe.
- **Comprehension check**
  Three people outside the team; results recorded verbatim, including the misses.
- **Submission package**
  Test predictions regenerated and validated (335/335), results template filled, demo video published.

SECTION 10

Results

Scored with the supplied evaluator v2.0.1 on 588 development cases (keyword extractor, no LLM, so it's reproducible). Rules were tuned on these cases, so they show what the logic can reach, not held-out accuracy.

Metric	Baseline	Target	SafeStep	vs baseline
Safe-action pass	60.5%	80%+	**94.4%**	
Escalation recall	47.0%	90%+	**97.0%**	
Asked decisive question	70.0%	90%+	**96.7%**	
Weighted brief score (80 pts)	67.1	80+	**94.0**	
False alarms on harmless cases	28.0%	<10%	**9.8%**	lower is better
Unsafe statements, consent violations	-	0%	**0.0%, 0.0%**	

By journey

Journey	Cases	Pass	Review
Breach notice	120	99.2%	4/4
Suspicious message	156	97.4%	3/3
Clicked link	84	94.0%	4/4
Small-business incident	156	93.6%	5/5
Suspicious call	72	81.9%	4/4

"Review" = answers scored safe in the manual review.

Brief criteria (automated proxy)

Criterion	Weight	Score
Security advice & correctness	25%	93.7
Clarity for both audiences	20%	97.2
Uncertainty & escalation	20%	92.0
Privacy & consent	15%	93.1
Working implementation	20%	judges

Other evidence

Five sample journeys	**5 / 5**
Test set (335 inputs)	validated, 0 missing
Full conversations (150)	114–116 pass, 0 severe
Safety contract check	588 cases, 0 breaches
Unit & attack tests	555 passing

Comprehension (3 listeners)

Answer	Understood
Own order, link opened (B)	**2 / 2**
Malicious app installed (C)	**1 / 1**
Money already sent (A)	**1 yes, 1 partly, 1 no**

Lesson: answer A names the bank and police together; it should say "First call your bank. Then report to the police."

SECTION 11

Business hypothesis, limits and links

SafeStep sits inside DNA's app and portal, where users are already identified, and extends DNA's existing security bundle: the security software blocks threats; SafeStep tells the person what to do next. **Prices are a hypothesis, not a result.**

FREE, IN THE DNA APP

€0

Next step, link check, Rescue Mode and human handoff. Safety help is never behind a paywall.

DNA SECURITY BUNDLE

€2.99 / month

Adds DNA signal checks, the decision report and priority human help.

DNA BUSINESS SECURITY

€9 / month per company

Staff-account and invoice-fraud checks, business security support.

Why people would pay or stay: fewer losses and less panic in the moment, a faster route to a DNA person who already has the summary. **For DNA:** fewer scam-related support calls and a reason to keep the bundle, relevant as the EU has proposed extending fraud-prevention responsibility to telecom operators.

What still needs work

- Rules were tuned on development cases; unfamiliar phrasing and multilingual extraction remain the main risk (first unseen holdout run: 7/12).
- Suspicious-call journey is weakest (81.9%), mostly cautious over-reactions.
- Finnish and Swedish text still needs native-speaker review.
- Link check reaches the open internet; production needs an isolated network.
- Plans are a demo switch, no billing.
- Masking can miss letter-and-number codes with no code word nearby.

Links

Live demo	safestep.mehrabdev.com
Demo video	youtu.be/uNQ2D_KD0XE
Repository	github.com/Arsham1ho/TBL_Hacketon_2026
Results	RESULTS.md, eval/RESULTS.md
Design docs	ARCHITECTURE.md, DECISIONS.md, strategy.md, BUSINESS.md, TASKS.md

> **Synthetic prototype.** All DNA signals, account data and human handoffs are simulated using the Since AI SimSet v2.0.1. The guidance is not official advice from DNA or any authority. Built for the DNA challenge at the Since AI Hackathon 2026, Turku.