

Download the followings in your prompt if you are using local environment

```
pip install datasets
```

```
!pip install huggingface_hub datasets
```

Go to <https://huggingface.co/>, register an acc, click on ur profile and find setting, go to "access tokens" tab, create your own token, then paste the token link in the login session

```
from huggingface_hub import hf_hub_download
from huggingface_hub import login
```

```
login()
```

```
import json
```

```
↳ VBox(children=(HTML(value='<center>
<img\src=https://huggingface.co/front/assets/huggingface_logo_noborder.svg
```

```
!git clone https://huggingface.co/datasets/kdave/Indian_Financial_News
```

If the git clone block doesnt work, use this one

```
from datasets import load_dataset
```

```
dataset = load_dataset("kdave/Indian_Financial_News")
```

```
↳ Downloading readme: 0.00B [00:00, ?B/s]
```

Run this one if imported from dataset instead of git clone

```
➡ Index(['URL', 'Content', 'Summary', 'Sentiment'], dtype='object')
```

Content \

Summary Sentiment

Page 2 of 19

```
from datasets import Dataset
```

```
ds = Dataset.from_pandas(df)
print(ds[0])
```

```
➦ {'URL': 'https://www.moneycontrol.com/news/business/economy/covid-19-pandemic-
```

```


```

```
print("Number of records:", len(ds))
print("Columns:", ds.column_names)
```

```
➦ Number of records: 26961
Columns: ['URL', 'Content', 'Summary', 'Sentiment']
```

```
summary_lengths = [len(x.split()) for x in ds['Summary'] if isinstance(x, str)]
content_lengths = [len(x.split()) for x in ds['Content'] if isinstance(x, str)]
```

```
import numpy as np
```

```
print("\nSummary Stats:")
print("  Avg length:", np.mean(summary_lengths))
print("  Min length:", np.min(summary_lengths))
print("  Max length:", np.max(summary_lengths))
```

```
print("\nContent Stats:")
print("  Avg length:", np.mean(content_lengths))
print("  Min length:", np.min(content_lengths))
print("  Max length:", np.max(content_lengths))
```

```
➦ Summary Stats:
  Avg length: 61.362115648529354
  Min length: 1
  Max length: 108
```

```
Content Stats:
  Avg length: 609.7049070880161
  Min length: 9
  Max length: 8328
```

```
def is_content_valid(example):
    return isinstance(example["Content"], str) and len(example["Content"].split())

def is_summary_valid(example):
    return isinstance(example["Summary"], str) and len(example["Summary"].split())

a_filtered_ds = ds.filter(is_content_valid)

b_filtered_ds = a_filtered_ds.filter(is_summary_valid)
print("Filtered dataset size:", len(b_filtered_ds))
```

```
Filter: 0% | 0/26961 [00:00<?, ? examples/s]
Filter: 0% | 0/26254 [00:00<?, ? examples/s]
Filtered dataset size: 26233
```

```
summary_lengths = [len(x.split()) for x in b_filtered_ds['Summary'] if isinstance(x, str)]
content_lengths = [len(x.split()) for x in b_filtered_ds['Content'] if isinstance(x, str)]
```

```
import numpy as np
```

```
print("\nSummary Stats (Filtered for extreme short entry):")
print("  Avg length:", np.mean(summary_lengths))
print("  Min length:", np.min(summary_lengths))
print("  Max length:", np.max(summary_lengths))
```

```
print("\nContent Stats: (Filtered for extreme short entry)")
print("  Avg length:", np.mean(content_lengths))
print("  Min length:", np.min(content_lengths))
print("  Max length:", np.max(content_lengths))
```

```
Summary Stats (Filtered for extreme short entry):
  Avg length: 61.58052834216445
  Min length: 13
  Max length: 98

Content Stats: (Filtered for extreme short entry)
  Avg length: 624.5348225517478
  Min length: 100
  Max length: 8328
```

```
print(b_filtered_ds[1])
```

```
➦ {'URL': 'https://www.businesstoday.in/top-story/state-run-banks-need-urgent-ci  
□
```

now summary and content has been filtered by length b_filtered_ds

```
# use this if not already downloaded  
!pip install nltk
```

```
import re  
import nltk
```

```
nltk.download('punkt') # only once
```

```
➦ [nltk_data] Downloading package punkt to  
[nltk_data] C:\Users\qq258\AppData\Roaming\nltk_data...  
[nltk_data] Package punkt is already up-to-date!  
True
```

```
def clean_text(text):
    # Lowercase
    text = text.lower()

    # Remove URLs
    text = re.sub(r'https?:\/\/\S+|www\.\S+', '', text)

    # Remove extra whitespace and newlines
    text = re.sub(r'\s+', ' ', text).strip()

    # Replace unicode smart quotes and dashes with ASCII
    replacements = {
        '': '',
        '': '',
        '': '',
        '': '',
        '': '',
        '': '',
        '': '',
        '\u2013': '-', # en dash
        '\u2014': '-', # em dash
    }
    for k, v in replacements.items():
        text = text.replace(k, v)

    # Remove any remaining non-printable characters
    text = ''.join(c for c in text if c.isprintable())

    return text

def filter_entry(entry):
    # For example, skip if content or summary too short
    if len(entry['Content'].split()) < 30:
        return False
    if len(entry['Summary'].split()) < 5:
        return False
    return True
```

```
def clean_example(example):
    example['Content'] = clean_text(example['Content'])
    example['Summary'] = clean_text(example['Summary'])
    return example
```

```
# Assuming b_filtered_ds is your Dataset object:
b_filtered_ds = b_filtered_ds.map(clean_example)
```

↔ Map: 0% | 0/26233 [00:00<?, ? examples/s]

```
print(b_filtered_ds[1])
```

↔ {'URL': '<https://www.businesstoday.in/top-story/state-run-banks-need-urgent-c>'}

```
b_filtered_ds.to_csv("cleaned_dataset.csv")
```

↔ Creating CSV from Arrow format: 0% | 0/27 [00:00<?, ?ba/s]
113619219

```
# saving files
df = b_filtered_ds.to_pandas()
#df.to_json("cleaned_dataset.jsonl", orient="records", lines=True, index=False)
df.to_json("cleaned_dataset.jsonl", orient="records", lines=True)
```

DATASET PRE-PROCESSED, NOW BASELINE WIHT TEXTRANK

```
import nltk
nltk.download('punkt')
nltk.download('punkt_tab')

def split_sentences(text):
    return nltk.sent_tokenize(text)
```

```
↗ [nltk_data] Downloading package punkt to
[nltk_data]    C:\Users\qq258\AppData\Roaming\nltk_data...
[nltk_data]    Package punkt is already up-to-date!
[nltk_data] Downloading package punkt_tab to
[nltk_data]    C:\Users\qq258\AppData\Roaming\nltk_data...
[nltk_data]    Package punkt_tab is already up-to-date!
```

```
# download networkx if module error
!pip install networkx
```

```
↗ Defaulting to user installation because normal site-packages is not writeable
Requirement already satisfied: networkx in c:\all files\anaconda3\lib\site-pa
```



```
import networkx as nx
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.metrics.pairwise import cosine_similarity
import numpy as np

def textrank(sentences, top_n=5):
    # vectorize sentences with TF-IDF
    vectorizer = TfidfVectorizer()
    tfidf_matrix = vectorizer.fit_transform(sentences)

    # compute similarity matrix
    sim_matrix = cosine_similarity(tfidf_matrix)

    # build graph and apply PageRank
    nx_graph = nx.from_numpy_array(sim_matrix)
    scores = nx.pagerank(nx_graph)

    # rank sentences and pick top N
    ranked_sentences = sorted(((scores[i], s) for i, s in enumerate(sentences)),
                              selected = [s for _, s in ranked_sentences[:top_n]])

    return ' '.join(selected)
```

```
from google.colab import drive
drive.mount('/content/drive')
```

```
-----
ModuleNotFoundError                                Traceback (most recent call last)
Cell In[23], line 1
----> 1 from google.colab import drive
      2 drive.mount('/content/drive')

ModuleNotFoundError: No module named 'google'
```

```
# suppose dataset is a list of dicts or a pandas DataFrame
entry = b_filtered_ds[1] # or dataset.iloc[1] if pandas

text = entry['Content'] # get the content field

# assuming you have your baseline pipeline functions from before:
```

```
sentences = split_sentences(text)
summary = textrank(sentences, top_n=5)
```

```
print("Original Content:\n", text)
print("Summary:\n", summary)
```

```
⇒ Original Content:
state-run lenders require an urgent rs 1.2 trillion in the capital in the ne
Summary:
as per the norms, the banks ought to have their tier-i capital at 9.5 per cer
```



```
def baseline_summary_pipeline(text):
    sentences = split_sentences(text)
    summary = textrank(sentences, top_n=5)
    return summary
```

```
pip install rouge-score
```

```

from rouge_score import rouge_scorer

scorer = rouge_scorer.RougeScorer(['rouge1', 'rouge2', 'rougeL'], use_stemmer=True)

rouge1_scores = []
rouge2_scores = []
rougeL_scores = []

for entry in b_filtered_ds.select(range(20)):
    generated = baseline_summary_pipeline(entry['Content']) # your generated summary
    reference = entry['Summary'] # human reference summary

    score = scorer.score(reference, generated)

    rouge1_scores.append(score['rouge1'].fmeasure)
    rouge2_scores.append(score['rouge2'].fmeasure)
    rougeL_scores.append(score['rougeL'].fmeasure)

print("Average ROUGE-1 F1:", sum(rouge1_scores)/len(rouge1_scores))
print("Average ROUGE-2 F1:", sum(rouge2_scores)/len(rouge2_scores))
print("Average ROUGE-L F1:", sum(rougeL_scores)/len(rougeL_scores))

```

```

➞ Average ROUGE-1 F1: 0.3117687753680703
   Average ROUGE-2 F1: 0.18014261244658297
   Average ROUGE-L F1: 0.22399678411130425

```

```
len(b_filtered_ds)
```

```
➞ 26233
```

✓ Keyword Extraction

✓ Tokenize and filter keywords

we will use nltk to tokenize the text, then remove stopwords and punctuation.

```

import nltk
nltk.data.path.append(r"C:\Users\qq258\AppData\Roaming\nltk_data")
from nltk.corpus import stopwords
from nltk import pos_tag, word_tokenize

nltk.download('punkt')
nltk.download('averaged_perceptron_tagger')
nltk.download('stopwords')

def extract_pos_filtered_tokens(text):
    stop_words = set(stopwords.words('english'))
    words = word_tokenize(text.lower())
    words = [w for w in words if w.isalpha() and w not in stop_words]

    tagged = pos_tag(words)
    # Keep only nouns and adjectives
    keep_tags = {'NN', 'NNS', 'NNP', 'NNPS', 'JJ', 'JJR', 'JJS'}
    filtered = [word for word, tag in tagged if tag in keep_tags]

    return filtered

```

```

[↩] [nltk_data] Downloading package punkt to
[nltk_data]      C:\Users\qq258\AppData\Roaming\nltk_data...
[nltk_data]      Package punkt is already up-to-date!
[nltk_data] Downloading package averaged_perceptron_tagger to
[nltk_data]      C:\Users\qq258\AppData\Roaming\nltk_data...
[nltk_data]      Package averaged_perceptron_tagger is already up-to-
[nltk_data]      date!
[nltk_data] Downloading package stopwords to
[nltk_data]      C:\Users\qq258\AppData\Roaming\nltk_data...
[nltk_data]      Package stopwords is already up-to-date!

```

✓ Build co-occurrence graph

Create edges between words that co-occur within a fixed window size (e.g., 2–4), then use `networkx` to build and rank nodes.

```
import networkx as nx
from itertools import combinations

def build_cooccurrence_graph(words, window_size=4):
    graph = nx.Graph()
    for i in range(len(words)):
        for j in range(i+1, min(i+window_size, len(words))):
            if words[i] != words[j]:
                graph.add_edge(words[i], words[j])
    return graph
```

✓ Apply pagerank to rank keywords

```
def extract_keywords(text, top_n=10):
    tokens = extract_pos_filtered_tokens(text)
    graph = build_cooccurrence_graph(tokens)
    scores = nx.pagerank(graph)
    ranked = sorted(scores.items(), key=lambda x: x[1], reverse=True)
    return [word for word, _ in ranked[:top_n]]
```

```
text = b_filtered_ds[1]['Content']
keywords = extract_keywords(text, top_n=10)
print("Extracted Keywords:", keywords)
```

➡ Extracted Keywords: ['capital', 'banks', 'rs', 'government', 'report', 'fiscal']

✓ Accumulate all keywords across the dataset and find the top 100 most frequent keywords

```
from collections import Counter

all_keywords = []

# Iterate over each summary in your DataFrame
for summary in df["Summary"]:
    keywords = extract_keywords(summary, top_n=10) # your existing function
    all_keywords.extend(keywords) # collect all keywords

# Count frequency of each keyword
keyword_freq = Counter(all_keywords)

# Get top 100 most common keywords across all summaries
top_100_keywords = [word for word, _ in keyword_freq.most_common(100)]

print(top_100_keywords)
```

➡ ['government', 'rs', 'india', 'market', 'cent', 'company', 'crore', 'economy',



✓ Image Lookup Table

```

import requests
import os

def download_image_from_pexels(keyword, save_dir="./images"):
    os.makedirs(save_dir, exist_ok=True)

    headers = {
        "Authorization": "API_KEY"
    }

    response = requests.get(
        "https://api.pexels.com/v1/search",
        headers=headers,
        params={"query": f"insurance {keyword}", "per_page": 1}
    )

    if response.status_code == 200:
        data = response.json()
        photo_url = data["photos"][0]["src"]["original"] # use 'medium' or 'small'
        image_data = requests.get(photo_url).content
        file_path = os.path.join(save_dir, f"{keyword}.jpg")

        with open(file_path, "wb") as f:
            f.write(image_data)

        print(f"Downloaded image for '{keyword}' to {file_path}")
    else:
        print(f"Failed to fetch image for {keyword} - HTTP {response.status_code}")

keywords = ['bank', 'government', 'capital', 'market'] # example
keywords1 = ['government', 'rs', 'india', 'market', 'cent', 'company', 'crore', 'growth', 'new', 'markets', 'percent', 'vaccine', 'pandemic', 'global', 'points', 'last', 'investors', 'companies', 'economic', 'coronavirus', 'world', 'oil', 'sector', 'herd', 'index', 'trade', 'years', 'people', 'prices', 'lakh', 'sensex', 'indian', 'rate', 'nifty', 'stocks', 'business', 'financial', 'high', 'natural', 'lockdown', 'tax', 'infection', 'nifty', 'banks', 'investment', 'months', 'quarter', 'week', 'industry', 'march', 'higher', 'due', 'dollar', 'china', 'day', 'spot', 'tax', 'stock', 'capital', 'fund', 'demand', 'minister', 'state', 'report', 'top', 'month', 'gold', 'price', 'equity', 'operations', 'likely', 'fiscal', 'funds', 'key', 'total', 'domestic', 'major', 'countries', 'report', 'first', 'interest', 'strong', 'shares', 'sales', 'rupee',

```

```
'states', 'women', 'end', 'gdp', 'many', 'trading', 'recovery', 'pos  
for word in keywords1:  
    download_image_from_pexels(word)
```

```
Downloaded image for 'people' to ./images/people.jpg  
Downloaded image for 'prices' to ./images/prices.jpg  
Downloaded image for 'lakh' to ./images/lakh.jpg  
Downloaded image for 'sensex' to ./images/sensex.jpg  
Downloaded image for 'indian' to ./images/indian.jpg  
Downloaded image for 'rate' to ./images/rate.jpg  
Downloaded image for 'number' to ./images/number.jpg  
Downloaded image for 'stocks' to ./images/stocks.jpg  
Downloaded image for 'business' to ./images/business.jpg  
Downloaded image for 'financial' to ./images/financial.jpg  
Downloaded image for 'high' to ./images/high.jpg  
Downloaded image for 'natural' to ./images/natural.jpg  
Downloaded image for 'lockdown' to ./images/lockdown.jpg  
Downloaded image for 'time' to ./images/time.jpg  
Downloaded image for 'infection' to ./images/infection.jpg  
Downloaded image for 'nifty' to ./images/nifty.jpg  
Downloaded image for 'banks' to ./images/banks.jpg  
Downloaded image for 'investment' to ./images/investment.jpg  
Downloaded image for 'months' to ./images/months.jpg  
Downloaded image for 'quarter' to ./images/quarter.jpg  
Downloaded image for 'week' to ./images/week.jpg  
Downloaded image for 'industry' to ./images/industry.jpg  
Downloaded image for 'march' to ./images/march.jpg  
Downloaded image for 'higher' to ./images/higher.jpg  
Downloaded image for 'due' to ./images/due.jpg  
Downloaded image for 'dollar' to ./images/dollar.jpg  
Downloaded image for 'china' to ./images/china.jpg  
Downloaded image for 'day' to ./images/day.jpg  
Downloaded image for 'spokesman' to ./images/spokesman.jpg  
Downloaded image for 'tax' to ./images/tax.jpg  
Downloaded image for 'stock' to ./images/stock.jpg  
Downloaded image for 'capital' to ./images/capital.jpg  
Downloaded image for 'fund' to ./images/fund.jpg  
Downloaded image for 'demand' to ./images/demand.jpg  
Downloaded image for 'minister' to ./images/minister.jpg  
Downloaded image for 'state' to ./images/state.jpg  
Downloaded image for 'rbi' to ./images/rbi.jpg  
Downloaded image for 'top' to ./images/top.jpg  
Downloaded image for 'month' to ./images/month.jpg  
Downloaded image for 'gold' to ./images/gold.jpg  
Downloaded image for 'price' to ./images/price.jpg  
Downloaded image for 'equity' to ./images/equity.jpg  
Downloaded image for 'operations' to ./images/operations.jpg  
Downloaded image for 'likely' to ./images/likely.jpg  
Downloaded image for 'cases' to ./images/cases.jpg  
Downloaded image for 'fiscal' to ./images/fiscal.jpg
```



```

Downloaded image for 'funds' to ./images\funds.jpg
Downloaded image for 'key' to ./images\key.jpg
Downloaded image for 'total' to ./images\total.jpg
Downloaded image for 'domestic' to ./images\domestic.jpg
Downloaded image for 'major' to ./images\major.jpg
Downloaded image for 'countries' to ./images\countries.jpg
Downloaded image for 'policy' to ./images\policy.jpg
Downloaded image for 'report' to ./images\report.jpg
Downloaded image for 'first' to ./images\first.jpg
Downloaded image for 'interest' to ./images\interest.jpg
Downloaded image for 'strong' to ./images\strong.jpg
Downloaded image for 'shares' to ./images\shares.jpg
Downloaded image for 'sales' to ./images\sales.jpg
Downloaded image for 'success' to ./images\success.jpg

```

The images folder is too big to be uploaded, so we saved them in a google drive folder. Here is a link:

<https://drive.google.com/drive/folders/1pk4AJnD0eAlziyIF7IWwn2snwX2D0dEj?usp=sharing>

Now we are able to download images based on the keywords. below is a plot function that will plot out the downloaded images that correspond to the keywords.

```
import os
import matplotlib.pyplot as plt
import matplotlib.image as mpimg

# Display images corresponding to the given list of keywords.
def show_keyword_images(keywords, image_dir="./images"):

    image_files = [f"{word}.jpg" for word in keywords if os.path.exists(os.path.join(image_dir, word))]

    if not image_files:
        print("No matching images found.")
        return

    cols = 5
    rows = (len(image_files) + cols - 1) // cols # Round up

    plt.figure(figsize=(15, 3 * rows))

    for i, img_file in enumerate(image_files):
        img_path = os.path.join(image_dir, img_file)
        img = mpimg.imread(img_path)

        plt.subplot(rows, cols, i + 1)
        plt.imshow(img)
        plt.axis("off")
        plt.title(img_file.split(".")[0])

    plt.tight_layout()
    plt.show()
```

```
show_keyword_images(keywords)
```

