

SQL Cheat Sheet: Views, Stored Procedures and Transactions

Views

Topic	Syntax	Description	Example
Create View	CREATE VIEW view_name AS SELECT column1, column2, ... FROM table_name WHERE condition;	A CREATE VIEW is an alternative way of representing data that exists in one or more tables.	CREATE VIEW EMP_SALARY AS SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, SALARY FROM EMPLOYEES;
Update a View	CREATE OR REPLACE VIEW view_name AS SELECT column1, column2, ... FROM table_name WHERE condition;	The CREATE OR REPLACE VIEW command updates a view.	CREATE OR REPLACE VIEW EMP_SALARY AS SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, JOB_TITLE, MIN_SALARY, MAX_SALARY FROM EMPLOYEES, JOBS WHERE EMPLOYEES.JOB_ID = JOBS.JOB_ID;
Drop a View	DROP VIEW view_name;	Use the DROP VIEW statement to remove a view from the database.	DROP VIEW EMP_SALARY;

Stored Procedures in IBM Db2 using SQL

Stored Procedures	<pre>--#SET TERMINATOR @ CREATE PROCEDURE PROCEDURE_NAME LANGUAGE BEGIN END @</pre>	<p>A stored procedure is a prepared SQL code that you can save, so the code can be reused over and over again.</p> <p>The default terminator for a stored procedure is semicolon(;). To set a different terminator we use SET TERMINATOR clause followed by the terminator such as '@'.</p>	<pre>--#SET TERMINATOR @ CREATE PROCEDURE RETRIEVE_ALL LANGUAGE SQL READS SQL DATA DYNAMIC RESULT SETS 1 BEGIN DECLARE C1 CURSOR WITH RETURN FOR SELECT * FROM PETSAL; OPEN C1; END @</pre>
-------------------	--	---	---


Stored Procedures in MySQL using phpMyAdmin

Stored Procedures	<pre>DELIMITER // CREATE PROCEDURE PROCEDURE_NAME BEGIN END // DELIMITER ;</pre>	<p>A stored procedure is a prepared SQL code that you can save, so the code can be reused over and over again.</p> <p>The default terminator for a stored procedure is semicolon(;). To set a different terminator we use DELIMITER clause followed by the terminator such as \$\$ or //.</p>	<pre>DELIMITER // CREATE PROCEDURE RETRIEVE_ALL() BEGIN SELECT * FROM PETSAL; END // DELIMITER ;</pre>
-------------------	--	---	---

Transactions with Db2

Commit command	COMMIT;	<p>A COMMIT command is used to persist the changes in the database.</p> <p>The default terminator for a COMMIT command is semicolon (;).</p>	<pre>CREATE TABLE employee(ID INT, Name VARCHAR(20), City VARCHAR(20), Salary INT, Age INT); INSERT INTO employee(ID, Name, City, Salary, Age) VALUES(1, 'Priyanka pal', 'Nasik', 36000, 21), (2, 'Riya chowdar 82000, 29); SELECT *FROM employee; COMMIT;</pre>
Rollback command	ROLLBACK;	<p>A ROLLBACK command is used to rollback the transactions which are not saved in the database.</p> <p>The default terminator</p>	<p>As auto-commit is enabled by default, all transactions will be committed. We need to disable this option to see rollback works.</p> <p>For db2, we have to disable auto-commit manually. Click the gear icon located on the right side of the SQL Assi window. Next, select the "On Success" drop-down and choose "commit after the last statement in the script" Remember save your changes!</p>

for a ROLLBACK command is semicolon (;).



```
INSERT INTO employee VALUES (3, 'Swetha Tiwari', 'Kanpur', 38000, 38);
SELECT *FROM employee;
ROLLBACK;
SELECT *FROM employee;
```

Transactions with MySQL

Commit command	COMMIT;	<p>A COMMIT command is used to persist the changes in the database.</p> <p>The default terminator for a COMMIT command is semicolon (;).</p>	<pre>CREATE TABLE employee(ID INT, Name VARCHAR(20), City VARCHAR(20), Salary INT, Age INT); START TRANSACTION; INSERT INTO employee(ID, Name, City, Salary, Age) VALUES(1, 'Priyanka pal', 'Nasik', 36000, 21), (2, 'Riya chowdary', 'Bangalor', 82000, 29); SELECT *FROM employee; COMMIT;</pre>
Rollback command	ROLLBACK;	<p>A ROLLBACK command is used to rollback the transactions which are not saved in the database.</p> <p>The default terminator for a ROLLBACK command is semicolon (;).</p>	<p>As auto-commit is enabled by default, all transactions will be committed. We need to disable this option to see how rollback works. For MySQL use the command "SET autocommit = 0;"</p> <pre>INSERT INTO employee VALUES (3, 'Swetha Tiwari', 'Kanpur', 38000, 38); SELECT *FROM employee; ROLLBACK; SELECT *FROM employee;</pre>

Db2 Transactions using Stored Procedure

Commit command	<pre>--SET TERMINATOR @ CREATE PROCEDURE PROCEDURE_NAME BEGIN COMMIT; END @</pre>	<p>A COMMIT command is used to persist the changes in the database.</p> <p>The default terminator for a COMMIT command is semicolon (;).</p>	<pre>--SET TERMINATOR @ CREATE PROCEDURE TRANSACTION_ROSE LANGUAGE SQL MODIFIES SQL DATA BEGIN DECLARE SQLCODE INTEGER DEFAULT 0; DECLARE retcode INTEGER DEFAULT 0; DECLARE CONTINUE HANDLER FOR SQLEXCEPTION SET retcode = SQLCODE; UPDATE BankAccounts SET Balance = Balance-200 WHERE AccountName = 'Rose'; UPDATE BankAccounts SET Balance = Balance-300 WHERE AccountName = 'Rose'; IF retcode < 0 THEN ROLLBACK WORK; ELSE COMMIT WORK;</pre>
----------------	---	--	---

			END IF; END @
Rollback command	--#SET TERMINATOR @ CREATE PROCEDURE PROCEDURE_NAME BEGIN ROLLBACK; COMMIT; END @	A ROLLBACK command is used to rollback the transactions which are not saved in the database. The default terminator for a ROLLBACK command is semicolon (;).	--#SET TERMINATOR @ CREATE PROCEDURE TRANSACTION_ROSE LANGUAGE SQL MODIFIES SQL DATA BEGIN DECLARE SQLCODE INTEGER DEFAULT 0; DECLARE retcode INTEGER DEFAULT 0; DECLARE CONTINUE HANDLER FOR SQLEXCEPTION SET retcode = SQLCODE; UPDATE BankAccounts SET Balance = Balance-200 WHERE AccountName = 'Rose'; UPDATE BankAccounts SET Balance = Balance-300 WHERE AccountName = 'Rose'; IF retcode < 0 THEN ROLLBACK WORK; ELSE COMMIT WORK; END IF; END @

MySQL Transactions using Stored Procedure

Commit command	DELIMITER // CREATE PROCEDURE PROCEDURE_NAME BEGIN COMMIT; END // DELIMITER ;	A COMMIT command is used to persist the changes in the database. The default terminator for a COMMIT command is semicolon (;).	DELIMITER // CREATE PROCEDURE TRANSACTION_ROSE() BEGIN DECLARE EXIT HANDLER FOR SQLEXCEPTION BEGIN ROLLBACK; RESIGNAL; END; START TRANSACTION; UPDATE BankAccounts SET Balance = Balance-200 WHERE AccountName = 'Rose'; UPDATE BankAccounts SET Balance = Balance-300 WHERE AccountName = 'Rose'; COMMIT; END // DELIMITER ;
Rollback command	DELIMITER // CREATE PROCEDURE PROCEDURE_NAME BEGIN ROLLBACK; COMMIT; END // DELIMITER ;	A ROLLBACK command is used to rollback the transactions which are not saved in the database. The default terminator for a ROLLBACK command is semicolon (;).	DELIMITER // CREATE PROCEDURE TRANSACTION_ROSE() BEGIN DECLARE EXIT HANDLER FOR SQLEXCEPTION BEGIN ROLLBACK; RESIGNAL; END; START TRANSACTION; UPDATE BankAccounts SET Balance = Balance-200 WHERE AccountName = 'Rose'; UPDATE BankAccounts SET Balance = Balance-300 WHERE AccountName = 'Rose'; COMMIT; END // DELIMITER ;

Author(s)

[D.M Naidu](#)

