

SELF-DRIVING CARS BEHAVIOR ESTIMATION



Photogrammetry & Robotics Lab


Behavior Estimation for Self-Driving Cars

Benedikt Mersch

Part of the Course: Techniques for Self-Driving Cars by
C. Stachniss, J. Behley, N. Chebrolu, B. Mersch, I. Bogoslavskyi, L. Peters

Motivation


Why
Plan Jointly?



TESLA LIVE

Motivation

Why
Plan Jointly?



TESLA LIVE

Motivation


Why
Plan Jointly?



TESLA LIVE

Motivation

Why
Plan Jointly?




Planning in General

High abstraction



Low abstraction


Global Planning



Behavior Planning



Local Planning



Low frequency



High frequency


Planning in General

High abstraction




Low abstraction


Global Planning



Behavior Planning



Local Planning



Low frequency



High frequency



Behavior Planning vs. Estimation

- Plan maneuvers to follow global plan
- Transitions between maneuvers depend on traffic participants
- Behavior estimation can support decision making




What Information Can We Use?

- Infer behavior of other traffic participants from
 - past states (e.g. position, velocity, acceleration)
 - map information
 - sensor data (e.g. camera, LiDAR, radar)




Graphical Model




- n -agent partially observable stochastic game
- Physical state $x_i^{(t)}$, observations $z_i^{(t)}$, internal state $b_i^{(t)}$ and control action $u_i^{(t)}$

Graphical Model




- n -agent partially observable stochastic game
- Physical state $x_i^{(t)}$, observations $z_i^{(t)}$, internal state $b_i^{(t)}$ and control action $u_i^{(t)}$

Graphical Model




- n -agent partially observable stochastic game
- Physical state $x_i^{(t)}$, observations $z_i^{(t)}$, internal state $b_i^{(t)}$ and control action $u_i^{(t)}$

Graphical Model




- n -agent partially observable stochastic game
- Physical state $x_i^{(t)}$, observations $z_i^{(t)}$, internal state $b_i^{(t)}$ and control action $u_i^{(t)}$

Graphical Model




- n -agent partially observable stochastic game
- Physical state $x_i^{(t)}$, observations $z_i^{(t)}$, internal state $b_i^{(t)}$ and control action $u_i^{(t)}$

Graphical Model




- State estimation: $x_{1:n}^{(t)}$
- Intention and trait estimation: $b_{1:n}^{(t)}$
- Motion prediction: $x_{1:n}^{(t+1:t_f)}$

Graphical Model




- State estimation: $x_{1:n}^{(t)}$
- Intention and trait estimation: $b_{1:n}^{(t)}$
- Motion prediction: $x_{1:n}^{(t+1:t_f)}$

Graphical Model



- State estimation: $x_{1:n}^{(t)}$
- Intention and trait estimation: $b_{1:n}^{(t)}$
- Motion prediction: $x_{1:n}^{(t+1:t_f)}$

Graphical Model




- State estimation: $x_{1:n}^{(t)}$
- Intention and trait estimation: $b_{1:n}^{(t)}$
- Motion prediction: $x_{1:n}^{(t+1:t_f)}$

**This
lecture**

Intention Estimation

Intention Estimation

Is the white car turning right or driving straight?



Intention Estimation

- Infer what other drivers **want to do** in the future
- Often probability distribution over high-level behavior modes (e.g. lane changing, turning, overtaking)
- Motion prediction can be conditioned on estimated intention

Intention Estimation Paradigms

- **Recursive** estimation

$$p \left(b_{1:n}^{(t)} \right) = f \left(p \left(b_{1:n}^{(t-1)} \right), z_{\text{ego}}^{(t)} \right)$$

- **Single-shot** estimation


$$p \left(b_{1:n}^{(t)} \right) = f \left(z_{\text{ego}}^{(t_p:t)} \right)$$

- Bayesian model
- Deep learning methods (black box)
- Game-theory

Trait Estimation


Trait Estimation

- In contrast to intention, a trait defines **how** the goal should be accomplished
- Traits depend on e.g. driver skill, preferences, aggressiveness




Trait Estimation

- In contrast to intention, a trait defines **how** the goal should be accomplished
- Traits depend on e.g. driver skill, preferences, aggressiveness




Trait Estimation

- In contrast to intention, a trait defines **how** the goal should be accomplished
- Traits depend on e.g. driver skill, preferences, aggressiveness



Trait Estimation

- In contrast to intention, a trait defines **how** the goal should be accomplished
- Traits depend on e.g. driver skill, preferences, aggressiveness



Trait Estimation

- Example traits:
 - Policy parameters of a driver model like minimum desired gap, maximum feasible acceleration
 - Parametric cost function that players try to optimize
- **Offline**: Estimate parameters in advance based on observations
- **Online**: Update parameters for previously unobserved drivers


Trait Estimation Paradigms

- Bayesian model
- Optimization e.g. inverse reinforcement learning
- Heuristics (use for example recommended parameters)

Motion Prediction

Motion Prediction

Now we are interested in the **full trajectory**, not the high-level action



Motion Prediction

- Predict future states $x_{1:n}^{(t+1:t_f)}$ of n traffic participants
- State transition model

$$x_i^{(t+1)} \sim F_i \left(x_i^{(t)}, u_i^{(t)} \right)$$

can be physics-/geometry-based or learned from data

- Future interactions among traffic participants

Motion Hypotheses

- Single trajectories
- Multi-modal trajectories
- 3D/2D Bounding boxes
- Gaussian (mixture) distributions
- Occupancy grid maps
- Forward/backward reachable sets
- Raw sensor data

Motion Prediction Paradigms

▪ Closed-loop forward simulation

- + Interaction aware
- Requires control policy

Algorithm 1 Motion Prediction via Forward Simulation

```
for  $\tau \in t, \dots, t_f - 1$ 
  for  $i \in 1, \dots, n$ 
     $\mathbf{z}_i^{(\tau)} \leftarrow \mathbf{G}_i(\mathbf{x}_{1:n}^{(\tau)})$            ▷ receive observation
     $\mathbf{b}_i^{(\tau)} \leftarrow \mathbf{H}_i(\mathbf{b}_i^{(\tau-1)}, \mathbf{z}_i^{(\tau)})$    ▷ update internal state
     $\mathbf{u}_i^{(\tau)} \leftarrow \pi_i(\mathbf{b}_i^{(\tau)})$              ▷ select action
     $\mathbf{x}_i^{(\tau+1)} \leftarrow \mathbf{F}_i(\mathbf{x}_i^{(\tau)}, \mathbf{u}_i^{(\tau)})$    ▷ step forward
```


Motion Prediction Paradigms

▪ Closed-loop forward simulation

- + Interaction aware
- Requires control policy

Algorithm 1 Motion Prediction via Forward Simulation

```
for  $\tau \in t, \dots, t_f - 1$ 
  for  $i \in 1, \dots, n$ 
     $\mathbf{z}_i^{(\tau)} \leftarrow G_i(\mathbf{x}_{1:n}^{(\tau)})$ 
     $\mathbf{b}_i^{(\tau)} \leftarrow H_i(\mathbf{b}_i^{(\tau-1)}, \mathbf{z}_i^{(\tau)})$ 
     $\mathbf{u}_i^{(\tau)} \leftarrow \pi_i(\mathbf{b}_i^{(\tau)})$ 
     $\mathbf{x}_i^{(\tau+1)} \leftarrow F_i(\mathbf{x}_i^{(\tau)}, \mathbf{u}_i^{(\tau)})$ 
```



- ▷ receive observation
- ▷ update internal state
- ▷ select action
- ▷ step forward


Motion Prediction Paradigms

▪ Closed-loop forward simulation

- + Interaction aware
- Requires control policy

Algorithm 1 Motion Prediction via Forward Simulation

```
for  $\tau \in t, \dots, t_f - 1$ 
  for  $i \in 1, \dots, n$ 
     $\mathbf{z}_i^{(\tau)} \leftarrow \mathbf{G}_i(\mathbf{x}_{1:n}^{(\tau)})$ 
     $\mathbf{b}_i^{(\tau)} \leftarrow \mathbf{H}_i(\mathbf{b}_i^{(\tau-1)}, \mathbf{z}_i^{(\tau)})$ 
     $\mathbf{u}_i^{(\tau)} \leftarrow \pi_i(\mathbf{b}_i^{(\tau)})$ 
     $\mathbf{x}_i^{(\tau+1)} \leftarrow \mathbf{F}_i(\mathbf{x}_i^{(\tau)}, \mathbf{u}_i^{(\tau)})$ 
```



▷ receive observation
▷ update internal state
▷ select action
▷ step forward


Motion Prediction Paradigms

- **Closed-loop forward simulation**
 - + Interaction aware
 - Requires control policy
- **Independent prediction**
 - + Fast and parallelizable
 - No interactions
- **Game-theoretic approaches**
 - + Accounting for future interactions
 - Not easy to solve with many agents

Motion Prediction Methods

Constant Velocity Model


- Idea: Assume that agents move with constant velocity within prediction horizon



Single trajectory

Constant Velocity Model

- Idea: Assume that agents move with constant velocity within prediction horizon




Multiple trajectories

Constant Velocity Model


- Idea: Assume that agents move with constant velocity within prediction horizon

Easy &
good
baseline




Constant Velocity Model

- Idea: Assume that agents move with constant velocity within prediction horizon




But fails for
non-linear
motion




Constant Velocity Model

- Idea: Assume that agents move with constant velocity within prediction horizon



But fails for
non-linear
motion




Alternative:
Constant acceleration, yaw rate

Social Forces

- Idea: Agents A, B act in a force field
- Get trajectory from differential equation

$$\ddot{x}(t) = \frac{F(t)}{m}$$

- Force depends on **goal**, humans and obstacles




Social Forces


- Idea: Agents A, B act in a force field
- Get trajectory from differential equation

$$\ddot{x}(t) = \frac{F(t)}{m}$$

- Force depends on **goal**, humans and obstacles



Social Forces - Simulation



Social Forces


- Need to define and parameterize forces that explain behavior
- Less realistic predictions
- Does not apply for cars that follow road structures

Social Forces

- Need to define and parameterize forces that explain behavior
- Less realistic predictions
- Does not apply for cars that follow road structures

Can we model human driving behavior?

Intelligent Driver Model



Intelligent Driver Model

- Car following model with parameters θ
- Output: Acceleration of ego vehicle

$$\dot{v}_\alpha = f(v_\alpha, v_{\alpha-1}, s_\alpha, \theta)$$



Intelligent Driver Model

$$\dot{v}_\alpha = a \left(1 - \left(\frac{v_\alpha}{v_0} \right)^\delta - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

$$\text{with } s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

$$\dot{v}_\alpha = a \left(1 - \left(\frac{v_\alpha}{v_0} \right)^\delta - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

$$\text{with } s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

$$\dot{v}_\alpha = a \left(1 - \left(\frac{v_\alpha}{v_0} \right)^\delta - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

with $s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

$$\dot{v}_\alpha = a \left(1 - \left(\frac{v_\alpha}{v_0} \right)^\delta - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

$$\text{with } s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

$$\dot{v}_\alpha = a \left(1 - \left(\frac{v_\alpha}{v_0} \right)^\delta - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

with $s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

$$\dot{v}_\alpha = a \left(1 - \left(\frac{v_\alpha}{v_0} \right)^\delta - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

with $s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

$$\dot{v}_\alpha = a \left(1 - \left(\frac{v_\alpha}{v_0} \right)^\delta - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

$$\text{with } s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

Free road behavior

$$\dot{v}_\alpha = a \left(\boxed{1 - \left(\frac{v_\alpha}{v_0} \right)^\delta} - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

$$\text{with } s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

Interaction term

$$\dot{v}_\alpha = a \left(1 - \left(\frac{v_\alpha}{v_0} \right)^\delta - \left(\frac{s^*(v_\alpha, \Delta v_\alpha)}{s_\alpha} \right)^2 \right)$$

$$\text{with } s^*(v, \Delta v_\alpha) = s_0 + v_\alpha T + \frac{v_\alpha \Delta v_\alpha}{2\sqrt{ab}}$$

- Maximum vehicle acceleration a
- Desired velocity v_0
- Minimum spacing s_0 in congested traffic
- Desired time headway T
- Comfortable braking deceleration b
- Exponent δ

Intelligent Driver Model

- **Advantages:**
 - Simple but effective model
 - Parameters are intuitive
- **Disadvantages:**
 - Less realistic in some scenarios
 - Does not work well for pedestrians

Intelligent Driver Model


- **Advantages:**
 - Simple but effective model
 - Parameters are intuitive
- **Disadvantages:**
 - Less realistic in some scenarios
 - Does not work well for pedestrians

How can we model more realistic motion?

Deep Learning-based Prediction

- Learn to predict a future trajectory from large real-world datasets
- **Advantages:**
 - Implicit trait modeling
 - High model representation capacity
- **Disadvantages:**
 - Parameters are not interpretable
 - No explicit modeling of interactions
 - Less robust for unseen scenarios

Training Scheme



Deep Learning Paradigms


- Sequence-to-sequence prediction with
 - Recurrent Neural Networks (RNN)
 - Convolutional Neural Networks (CNN)
 - Combination of RNN and CNN
 - Graph Neural Networks
 - Transformers
 - Generative Adversarial Networks
- Deterministic vs stochastic models

Deep Learning Paradigms


- Sequence-to-sequence prediction with
 - Recurrent Neural Networks (RNN)
 - Convolutional Neural Networks (CNN)
 - Combination of RNN and CNN
 - Graph Neural Networks
 - Transformers
 - Generative Adversarial Networks
- Deterministic vs stochastic models

**This
lecture**

Recurrent Neural Networks




Recurrent Neural Networks



What happens in A ?

$$h_t = \sigma (W [h_{t-1}, x_t] + b)$$

Recurrent Neural Networks




What happens in A?

$$h_t = \sigma (W [h_{t-1}, x_t] + b)$$

Diagram illustrating the components of the equation:

- σ : Activation function (indicated by a red arrow)
- W : Learnable weights (indicated by a red arrow)
- b : Learnable bias (indicated by a red arrow)


Recurrent Neural Networks



Advantages: Weight sharing, variable sequence length

Disadvantages: Slow prediction, vanishing/exploding gradients

Recurrent Neural Networks




Advantages: Weight sharing, variable sequence length



Disadvantages: Slow prediction, vanishing/exploding gradients

Long Short-Term Memory

From RNN





To LSTM





[Hochreiter and Schmidhuber]
[Courtesy of Christopher Olah]


Long Short-Term Memory



Long Short-Term Memory




LSTM Forget Gate




$$f_t = \sigma (W_f \cdot [h_{t-1}, x_t] + b_f)$$

LSTM Input Gate




$$i_t = \sigma(W_i \cdot [h_{t-1}, x_t] + b_i)$$
$$\tilde{C}_t = \tanh(W_C \cdot [h_{t-1}, x_t] + b_C)$$

LSTM Cell Update



$$C_t = f_t * C_{t-1} + i_t * \tilde{C}_t$$


LSTM Output Gate



$$o_t = \sigma (W_o [h_{t-1}, x_t] + b_o)$$

$$h_t = o_t * \tanh (C_t)$$

LSTM Output Gate




$$o_t = \sigma(W_o [h_{t-1}, x_t] + b_o)$$

$$h_t = o_t * \tanh(C_t)$$

How Can We Use LSTMs for Sequence Prediction?


Sequence Prediction

- Encode past states of agent i
- Decode future states in autoregressive manner




Example: SocialLSTM

- What about the influence of neighbors?
- How to consider interactions?




Example: SocialLSTM

- Assumption: Hidden state contains motion information
- Hidden states of neighbors are shared




Example: SocialLSTM

- Assumption: Hidden state contains motion information
- Hidden states of neighbors are shared
- Pool hidden states into fixed-sized tensor




SocialLSTM Comparison




Temporal Convolutions

- Apply convolutions across time dimensions
- Easier to train, but needs sufficient receptive field




Temporal Convolutions

- Apply convolutions across time dimensions
- Easier to train, but needs sufficient receptive field



Example: Fast and Furious


- Voxelize LiDAR into bird's eye view
- 3D CNN for end-to-end detection, tracking and motion prediction



What If Our Perception System Fails?


End-to-end Learning

- Most prediction approaches require already tracked past trajectories
- Misperception is not considered
- Idea: End-to-end learning




End-to-end Learning

- Most prediction approaches require already tracked past trajectories
- Misperception is not considered
- Idea: End-to-end learning




End-to-end Learning

- Most prediction approaches require already tracked past trajectories
- Misperception is not considered
- Idea: End-to-end learning




End-to-end Learning

- Most prediction approaches require already tracked past trajectories
- Misperception is not considered
- Idea: End-to-end learning




Self-supervised Prediction

- Labeling trajectories or bounding boxes is expensive
- Idea: Predict raw sensor data into the future



[Lange et al.]



[Hu et al.] 93

How Do We Evaluate Our Prediction?


Loss & Evaluation Metrics

- Final Displacement Error
- Average Displacement Error




Loss & Evaluation Metrics

- Final Displacement Error
- Average Displacement Error



Loss & Evaluation Metrics


- Final Displacement Error
- Average Displacement Error



$$\text{FDE} = \left\| \hat{x}_i^{(t_f)} - x_i^{(t_f)} \right\|_2$$

Loss & Evaluation Metrics


- Final Displacement Error
- Average Displacement Error



$$\text{ADE} = \frac{1}{P} \sum_{t=1}^P \left\| \hat{x}_i^{(t)} - x_i^{(t)} \right\|_2$$

Loss & Evaluation Metrics

- Final Displacement Error
- Average Displacement Error



- Unimodal vs multimodal

Datasets and Benchmarks

- KITTI
- SemanticKITTI
- Lyft Level 5
- Waymo Challenge
- nuScenes
- Argoverse
- highD, inD, round
- Pedestrian prediction: ETH, UCY
- ...

Summary

- Estimate intention, traits of future trajectory for planning own behavior
- Different solution strategies depending on e.g. model complexity or level of interaction
- Can learn behavior estimation from large real-world datasets with deep learning

Thank you for your attention

References

- B. Paden et al. "A Survey of Motion Planning and Control Techniques for Self-Driving Urban Vehicles." IEEE Transactions on Intelligent Vehicles, 2016.
- K. Brown et al. "Modeling and Prediction of Human Driver Behavior: A Survey". arXiv preprint, abs/2006.08832, 2020.
- F. Poggenhans et al. "Lanelet2: A high-definition map framework for the future of automated driving." 2018 21st International Conference on Intelligent Transportation Systems (ITSC) (2018): 1672-1679.
- H. Li, R. Dai. "The merging control method of on-ramp vehicles based on cooperative vehicle infrastructure system for highway entering ramp." IOP Conference Series: Materials Science and Engineering, 2019.
- D. Helbing, P. Molnar. "Social force model for pedestrian dynamics", 1995.
- M. Treiber et al. "Congested Traffic States in Empirical Observations and Microscopic Simulations." Physical Review E. 62. 1805-1824, 2000.
- C. Olah "Understanding LSTM Networks". Retrieved from <http://colah.github.io/posts/2015-08-Understanding-LSTMs/>, 2015.
- S. Hochreiter, J. Schmidhuber. "Long Short-term Memory". Neural computation. 9. 1735-80. 10.1162/neco.1997.9.8.1735., 1997.
- A. Alahi et al. "Social LSTM: Human Trajectory Prediction in Crowded Spaces." In Proc. of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR), 2016.
- S. Bai et al. "An Empirical Evaluation of Generic Convolutional and Recurrent Networks for Sequence Modeling.", arXiv preprint, abs/1803.01271, 2018.
- W. Luo et al. "Fast and Furious: Real Time End-to-End 3D Detection, Tracking and Motion Forecasting with a Single Convolutional Net." In Proc. of the IEEE Conf. on Computer Vision and 318 Pattern Recognition (CVPR), 2018.
- P. Hu et al. „Safe Local Motion Planning with Self-Supervised Freespace Forecasting.“, Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2021.
- B. Lange et al. „Attention Augmented ConvLSTM for Environment Prediction .“, In Proc. of the IEEE/RSJ Intl. Conf. on Intelligent Robots and Systems (IROS), 2021.