




Assurement Report - system

Part of Quality Assurance Denmark

Executing part:

Own company Adress CVR and contact info.- company setup.



Static control plan: Project name – project setup.

For those executed within the construction part:

Document ID: B2.X number

Special text

Applicable EU standards 2024

- Eurocode 0: Design basis for structures
- Eurocode 1: Load on load-bearing structures
- Eurocode 2: Concrete structures
- Eurocode 3: Steel structures
- Eurocode 4: Composite Structures
- Eurocode 5: Timber structures
- Eurocode 6: Masonry structures
- Eurocode 7: Geotechnical Engineering
- Eurocode 8: Structures in seismic areas
- Eurocode 9: Aluminium structures.
- EN 1520: Lightweight concrete with porous aggregates
- EN 12602: Aerated concrete

STATIC CONTROL PLAN

For load-bearing structures, cf. DS1140 applies to:

Construction Part: Special text

The control plan is built according to the current EU standard:

Eurocode: Eurocode

CONSTRUCTION CASE:

Project INFO		Main Contractor/Customer	
ID/Case no.	Project setup.	Name	Project setup
Name	Project setup	Address	Project setup
Address	Project setup	Post no./City.	Project setup
post no./City	Project setup	CVR no.	Project setup
Contact person	Project setup	Email.	Project setup
Startup	Project setup	Contact person	Project setup

DOCUMENT TYPE:	VERSION	CONSTRUCTION CLASS
STATIC CONTROL PLAN	1 OR OTHER,	KKX

Signing:


Same data as static report.

Signed	Prepared/approved by:	Company
[Select Date]	Admin – company organization	Own company– company organization

Signed	Own Control (OC)	Company
[Select Date]	Project manager– company organization	Own company– company organization

Signed	Independent controller (IC)	Company
[Select Date]	company organization	

Document completion status



The figure to the right from SBI 271 Item 4.3 indicates which phase you are in in your document submissions, and must also help to ensure that both the contractor and the consultant work proactively to communicate back and forth in connection with any corrections.

The document is signed when this has been approved by the structural engineer, until then the document is a dynamic document.

Expected approval time 14 days, after which the content of the document is considered approved.

Status:	Approval
18-11-2025	Under Approval
18-11-2025	

Content

Static control plan	1
Construction Part: Special text	1
Eurocode: Eurocode	1
Signing:	1
1. General	4
1.1 Description of the control work	4
1.2 Control types	5
1.3 Level of control	5
1.4 Organisation of the control work	6
1.5 Controllers	6
1.6 Use of assistance	6
1.7 Follow-up on deviations	6
2. General controls	7
2.1 General	7
2.2 Control section	7
2.3 Explanation of the selection of controls	7
2.4 Checkpoints	7
3. Special controls	8
3.1 General	8
3.2 Special checkpoints	8
4. Documentation	8
4.1 General description of documentation	8
4.2 Documentation of general controls	8
4.3 Documentation of special controls	8
4.4 Documentation of deviations and follow-up	8
4.5 Checking Control Documentation	9
5. Listings	9
5.1 Scope of control	9
6. Control points selected	10
7. Static controls (schematic)	11
7.1 Review of the execution basis from the design B1	12
7.2 Verification of the basis for execution of the work B2	13
7.3 Verification of Documentation of Materials and Products B3	14
7.4 RECEIPT CONTROL DELIVERIES B4	15
7.5 PERFORMANCE CONTROL; B5	16
7.6 FINAL INSPECTION B6	17

1.1 Description of the control work

This static control plan covers the control for the execution of the construction section mentioned on the front page and associated works. The inspection is carried out in accordance with the building designer's:

LISTING	DOCUMENT	CONSTRUCTION PART:	ACCOMPLISHMENT
B2. X number	STATIC CONTROL PLAN	Special text	

The focus is on seeing between the construction designer's material and the execution of the construction section on the site. Particular consideration is given to the materials used and their dimensions in reception control, placement on level versus location on site and compliance with tolerances.

The following forms the basis for the checks carried out:

- Building Regulations 2018 - **BR18**
- **SBI 271** "Documentation and Control of Load-Bearing Structures"
- **DS/EN 1990 DK NA:2021**, Annex **B5**
- **DS 1140:2019** "Execution of load-bearing structures – General control"
- **DS/INF 1140:2022** "Guide to **DS 1140**"

In addition, the inspection is carried out on the basis of the contractor's documented quality assurance system, which is regularly reviewed to ensure that it works as intended.

The review is carried out internally in the company and includes, among other things:

- The quality assurance system has been updated and approved by the company's management
- Procedures are complied with as described in the quality assurance system
- A review of the execution basis from the design phase has been carried out
- The materials used are in accordance with the design basis
- The basis for the execution of the work has been controlled/approved and reflects the requirements of the
- The basis for execution from the design
- Employees have the necessary qualifications and competencies
- Self-monitoring and independent control are described in control plans and carried out as prescribed
- Controls are documented in control reports as described
- Deviations are processed according to the procedure for deviations
- Documentation of construction as executed is available

The independent control is carried out by the executor, with the exception of a few of the special control points where the independent control is carried out by the designing organisation. This is because the control requires a certain insight into the static conditions that form the basis for the construction.

1.2 Control types

The structure is classified as construction class KKX

Self-monitoring and independent control of the work carried out are carried out.

There is no requirement for third-party control.

Self-monitoring

The self-inspection of the execution is carried out by the person who carried out the construction when the construction or parts thereof are completed. Where structural parts are subsequently hidden, the self-inspection is carried out during the execution of the relevant structural part.

The own-check includes at least an assessment of whether:

- The entire construction and all of its parts are actually done.
- The construction based on a craftsmanship assessment is carried out correctly and is in accordance with good building practice.
- The construction has been carried out in accordance with the execution basis and agreements with the design and/or construction management on details or other matters that are not stated in the execution basis.
- Tolerances in the execution are complied with in relation to relevant standards, good practice within the type of work in question (see e.g. tolerancer.dk) and any project-specific tolerances that may appear in the execution basis.
- Documentation of the execution of the construction has been carried out, collected and systematised in accordance with SBi 271 section 2.6, Construction as executed.

After completion of the self-inspection, the person carrying out the inspection documents this in the current inspection report. *Self-monitoring is always carried out.*

Standards:

This section is taken from the Eurocode table here we need an extra field with a static text talking about which standards covering the chosen EUROCODE.

Independent controls

The independent inspection shall be carried out by persons who have not directly participated in the actual performance of the inspection section in question. All independent checks within a control section are carried out by the same person. The independent inspector is not carried out by the head of the work team, The independent inspector must have the necessary competencies that allow him to have knowledge within the chosen construction section that is stated on the front page.

When the performance of an inspection section or parts thereof has been carried out and the performer has been ready for independent control (i.e. after self-monitoring has been carried out), the independent inspection is carried out.

The independent control is carried out according to the project-specific static control plan for execution.

1.3 Level of control

The level of control for the general control is governed by the selected execution classes, cf. DS/EN 1990 DK NA, Annex B5.

The execution class is EXCX and Self-control is performed as a maximum control. The independent control is carried out as a random and maximum control.

Performance classes indicate the importance of the design for the safety of a load-bearing structure:

- EXC1: The design has limited impact on the safety of a load-bearing structure
- EXC2: The execution is important for the safety of a load-bearing structure
- EXC3: The execution is of great importance for the safety of a load-bearing structure.

1.4 Organisation of the control work

Each inspection section must be assigned one, and only one inspector who is ensured that he has not contributed to the execution of the construction section in question. The executing party or its representative has drawn up the control plan and will act as the lead inspector in connection with the selection of inspectors for the individual control sections, as well as compiling and checking the inspection report. As far as possible, the aim is that the lead inspector also carries out the actual inspection on site in order to simplify the inspection work.

1.5 Controllers

- The independent inspection is carried out by an operator who has not acted as the executor on the site.
- Controls are carried out by the same organisation as the executing organisation.
- It is ensured that the inspector has the right and necessary skills to carry out the inspection.
- Inspectors must always have the necessary qualifications acquired through training and the necessary competences acquired through experience both in relation to the subject of the inspection and in planning, carrying out and documenting the inspection.

Therefore, the inspector must at least

- be familiar with best practices for the execution of the relevant structural parts and construction sections.
- Have the ability to create an overview and wonder
- Have knowledge of your own limitations and make use of professional experts for parts of the control task
- Have competencies at least equivalent to those of the person who has performed the work
- Have professional qualifications and competencies for carrying out the construction work
- Be able to understand standards, control plans and good craftsmanship
- Be able to familiarize themselves with the documents that form the basis for the execution

In order to document the examiner's qualifications and competences, his/her competences are described in detail in the inspection report, e.g. in the examiner's CV.

Applier	Name	Education	Experience	Initials
Own Controller	From Company organisation			OC Fixed
Independent controller	From Company organisation			IC Fixed

1.6 Use of assistance

Create new fields (education & Experience) on the Admin, Project manager, worker, independent controller, sub-contractor setup.

If the inspector chooses to use assistance in carrying out the inspection, the assistant inspector must have at least the competencies described in section 1.2 above. In addition, it is important to be aware that the final responsibility for the inspection at all times rests with the inspector and is therefore not transferred to the assistant inspector. The inspector must therefore follow up on inspections carried out by assistant inspectors and ensure that the inspection has been carried out sensibly by checking the documentation for the inspection and sign this as the inspector.

1.7 Follow-up on deviations

If deviations are found in the controls, the following procedure shall be followed:

- The work on the structural part is stopped and may not be continued until the deviation has been corrected.
- The inspector prepares a non-conformance report, which may include illustrations of the non-conformity and proposed solutions.
- The inspector assesses, together with the executors, whether the defect is of a nature that makes it necessary to reassess the working basis for the execution and the associated controls.
- The inspector assesses, together with the executors, the implications of the deviation for the further execution and suitability in relation to the intended purpose of the design.
- The verifier assesses, together with the performing measures, the necessary measures to make the component acceptable.
- The inspector assesses, together with the contractors, the necessity of rejecting and replacing the non-repairable building part.
- After rectifying the deviation, this is checked again and the result is documented.
- If it is not possible to correct the deviation, the building designer must approve the deviation.

If there are serious or more repeated errors in a control point, the control can be extended to a maximum control of the current control point and/or the building designer can be involved in the assessment of the deviation.

2. GENERAL CONTROLS

2.1 General

The general control is carried out in accordance with the Constitution. **DS 1140**. In addition, the general control is carried out in accordance with the rules of **DS/EN 1992-DS/EN 1999** including the associated national annexes and in accordance with the rules of the related execution standards including the corresponding national application documents.

The general control is carried out on the basis of the division in **DS 1140, Annex B**.

Control subject
B.1 Execution basis from design
B.2 Basis for execution of the work
B.3 The material and products
B.4 Reception control
B.5 Execution
B.5.1 Transport and storage on site
B.5.2 Previously completed construction
B.5.3 Assembly of prefabricated structural parts
B.5.4 Execution of non-certified structural parts
B.6 Final inspection

The independent verification that the own-check has been carried out is always carried out as a maximum control.

Explanation of B.5.2 to B.5.4:

When constructing structures that are of critical importance to the functioning and integrity of the structure, Control points are fully checked (maximum) for:

- Presence of structural parts
- Presence of joint parts
- Remuneration depths for assembly of prefabricated structural parts
- The subsoil for geotechnical constructions with regard to whether the soil is as assumed in the execution basis from the design stage.

2.2 Control section

The delimited design section is subdivided into control sections according to e.g. construction types, scope or time of execution, however, common to the fact that control sections must always be well defined, delimited in relation to other control sections and delimited by a continuous production period of a maximum of 4 weeks.

The execution of the construction section is divided according to the tender control plan for the following control sections:

LISTING	DOCUMENT	CONSTRUCTION PART:	ACCOMPLISHMENT
B2. X number	STATIC CONTROL PLAN	Special text	

2.3 Explanation of the selection of controls

As this construction section is placed in construction class **KKX**, the selected control points must be explained. This is done in connection with the inspection report.

2.4 Checkpoints

LISTING	DOCUMENT	CONSTRUCTION PART:	ACCOMPLISHMENT
B2. X number	STATIC CONTROL PLAN	Special text	

Control points are stated in the control plan prepared by the executing contractor.

3. SPECIAL CONTROLS

3.1 General

There are no special controls assigned by the building designers, cf. This construction section.
Should there be special controls, they will be stated in section 3.2

3.2 Special checkpoints

Cf. section 3.1, no special controls are required.

If there are special checks, it will be stated below in the form, otherwise there will be none.

Data from Special Control points - IF Any

ID	SPECIAL CONTROL	DESCRIPTION
----	-----------------	-------------

4. DOCUMENTATION

4.1 General description of documentation

The documentation of the control consists of this control plan and associated appendices for the present construction section.
In addition, this also consists of an inspection report and associated appendices.

Document:

LISTING	DOCUMENT	CONSTRUCTION PART:	ACCOMPLISHMENT
B3. X number	STATIC INSPECTION REPORT	Special text	
A5. X number	A5 AS DONE	Special text	

The above is updated every time a change occurs in the execution.

Documentation contains the actual control result, but also contains a follow-up on the control, including an account of the points where there have been comments from the control in relation to how the comment has been followed up.

4.2 Documentation of general controls

The general control is documented in accordance with the requirements specified in the control plans.

Documentation of general controls consists of a completed control report, with all points clarified, approved and signed by the examiner. Deviations must be documented to be remedied by a deviation report, and the item in the control report cannot be approved until the deviation report has been completed.

The documentation for the general control is kept with the contractor. Documentation is stored for at least 5 years after the occupancy permit.

4.3 Documentation of special controls

In its documentation, the building designer has not required any special controls.

4.4 Documentation of deviations and follow-up

If, in the course of the general or special control, deviations are detected, this shall be noted in the
The control scheme for that control point in the static report.

A deviation report will be created for this report, which will be attached to the inspection report as a annex. The non-conformity report shall agree on how the non-conformity will be remedied, possibly with the involvement of the construction designer. If a remedy is agreed that deviates from the basis for execution, the building project designer is involved and must be informed.

4.5 Checking Control Documentation

The control documentation is collected and reviewed by the inspector and it is ensured that all documents are present, as well as all controls are completed, dated and signed.

5. LISTINGS

LISTING	DOCUMENT	CONSTRUCTION PART:	ACCOMPLISHMENT
B2. <i>X number</i>	STATIC CONTROL PLAN	<i>Special text</i>	
B3. <i>X number.</i>	STATIC INSPECTION REPORT	<i>Special text</i>	
A5. <i>X number</i>	A5 AS DONE	<i>Special text</i>	

The naming of the documents above is determined by the building designer.

The above documents will be part of the overall static documentation for the section of this construction when the work is completed.

See also the table further down in the control plan under section 7.1

5.1 Scope of control

The scope of controls is stated in the tables under section 7.1 and is determined on the basis of which (classes) the Structural Engineer has stated in the project material.

6. CONTROL POINTS SELECTED

OVERVIEW:

DRAWINGS INDICATING SELECTED INSPECTION POINTS:

DRAWING NAME: **File name**

Marked main drawing.

Above are points indicated where the executor intends to carry out inspections.

(If no comment is received on this within 8 days, this is considered approved)

7. STATIC CONTROLS (SCHEMATIC)

LISTING	DOCUMENT	CONSTRUCTION PART:	ACCOMPLISHMENT
B2. X number	STATIC CONTROL PLAN	Special text	

In the form below, control has been carried out of the project material that has been handed out when awarding awards, and forms the basis for the intended and executed work, which is a dynamic process until delivery.

Standards and norms:

- DS/EN 13670: Execution of concrete structures [DI Denmark](#)
- DS/EN 206: Concrete – Specification, Properties, Manufacture and Conformity [DS1140 Load-Bearing Structures](#)

Checklist

7.1 REVIEW OF THE EXECUTION BASIS FROM THE DESIGN									B1
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.1.1				Special text		100%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.1.2				Special text		100%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.1.3				Special text		100%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.1.4				Special text		100%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.1.5				Special text		100%			IC

Fixed text
100%

Fixed text
IC = Independent controller

7.2 VERIFICATION OF THE BASIS FOR EXECUTION OF THE WORK

B2

POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.2.1				Special text		XX%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.2.2				Special text		XX%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.2.3				Special text		XX%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.2.4				Special text		XX%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.2.5				Special text		XX%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.2.6				Special text		XX%			IC

Scope 10% if KK1 or kk2
scope 20% if KK3 or KK4

Fixed text
IC = Independet controler

7.3 VERIFICATION OF DOCUMENTATION OF MATERIALS AND PRODUCTS

B3

POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.3.1			Special text			XX%			IC
US	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.3.2			Special text			XX%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.3.3			Special text			XX%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.3.4			Special text			XX%			IC
POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.3.5			Special text			XX%			IC

Scope 10% if KK1 or kk2
scope 20% if KK3 or KK4

Fixed text
IC = Independent controller

7.4 RECEIPT CONTROL DELIVERIES

B4

POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
-----	--------------	---------	-------------------	-------	----------------	-------	---------------------	------	---------

7.4.1

Special text

XX%

IC

Planned
Sample
Checks

POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
-----	--------------	---------	-------------------	-------	----------------	-------	---------------------	------	---------

7.4.2

Special text

XX%

IC

Planned
Sample
Checks

POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
-----	--------------	---------	-------------------	-------	----------------	-------	---------------------	------	---------

7.4.3

Special text

XX%

IC

Planned
Sample
Checks

Fixed text
IC = Independent controller

Scope 10% if KK1 or kk2
scope 20% if KK3 or KK4
+ Fixed text
Planned Sample Checks

7.5 PERFORMANCE CONTROL;

B5

POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.5.1			Special text			XX% Planned Sample Checks			IC
7.5.2			Special text			XX% Planned Sample Checks			IC
7.5.3			Special text			XX% Planned Sample Checks			IC
7.5.4			Special text			XX% Planned Sample Checks			IC
7.5.5			Special text			XX% Planned Sample Checks			IC
7.5.6			Special text			XX% Planned Sample Checks			IC

Scope 10% if KK1 or kk2
scope 20% if KK3 or KK4
+ Fixed text
Planned Sample Checks

Fixed text
IC = Independent controller

7.6 FINAL INSPECTION

B6

POS	CHECKING THE	SUBJECT	CONSTRUCTION PART	BASIS	CONTROL METHOD	SCOPE	ACCEPTANCE CRITERIA	TIME	CONTROL
7.6.1			Special text			100% Max			IC/OC
7.6.2			Special text			100% Max			IC/OC
7.6.3			Special text			100% Max			IC/OC

Fixed text
100%
MAX

Fixed text
IC = Independent controller
OC = Own Controller