No cell holds a recall lower bound of 90 % on this sample (300 confirmed suspicious): lower the floor knowingly, or measure a longer window of history.

Sample on public data, not a client's file. The alerts were constructed by Crusetra from the synthetic IBM AMLworld transactions (Erik Altman and IBM, CDLA-Sharing 1.0, changed from the original): AMLworld labels transactions, and no monitoring system raised these alerts. Read "your" below as "this file's". 1200 alerts (300 confirmed suspicious, 900 benign) in a file with SHA-256 `58ee67e865d4e4309a9f51ed72ca0ede…`, rebuilt into cases from 17826 transaction rows over 1200 accounts (SHA-256 `5bca84e6ed11085aee1387d0c4ff4d54…`). Measured 2026-10-11 16:24 UTC with tool commit `8e87d5a`. Every figure below is read from the sealed record 13d0ad682c461ac7 (a content hash).

n/a
no cell is recommended

60.1 %
the strongest recall lower bound any cell reaches on this sample

1200
alerts in this history: 300 confirmed suspicious, 900 benign

01 **The recommended cell**

No cell holds a recall lower bound of 90 % on this sample (300 confirmed suspicious). The strongest bound any cell reaches is 60.1 %: lower the floor knowingly, or measure a longer window of history, since the bound tightens with n.

02 **Every scenario across the thresholds: recall, then false alerts, each with its 95 % interval; the recommended one is shaded**

SCENARIO	0.50	0.60	0.70	0.80	0.90	1.00
amount	65.7 % [60–71] 49.7 % [46–53]	61.3 % [56–67] 46.7 % [43–50]	54.7 % [49–60] 43.6 % [40–47]	52.0 % [46–58] 40.9 % [38–44]	48.3 % [43–54] 35.9 % [33–39]	18.0 % [14–23] 12.7 % [11–15]
velocity	48.0 % [42–54] 46.1 % [43–49]	39.3 % [34–45] 38.3 % [35–42]	29.3 % [24–35] 26.8 % [24–30]	20.0 % [16–25] 19.3 % [17–22]	11.3 % [8–15] 11.6 % [10–14]	0.0 % [0–1] 0.0 % [0–0]
structuring	0.3 % [0–2] 0.6 % [0–1]	0.3 % [0–2] 0.2 % [0–1]	0.3 % [0–2] 0.2 % [0–1]	0.3 % [0–2] 0.2 % [0–1]	0.3 % [0–2] 0.2 % [0–1]	0.0 % [0–1] 0.0 % [0–0]
round	16.3 % [13–21] 15.1 % [13–18]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]
zscore	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]
passthrough	28.3 % [24–34] 23.3 % [21–26]	27.3 % [23–33] 21.8 % [19–25]	26.3 % [22–32] 20.9 % [18–24]	25.7 % [21–31] 19.9 % [17–23]	25.3 % [21–31] 19.2 % [17–22]	24.3 % [20–29] 18.3 % [16–21]
peer	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]	0.0 % [0–1] 0.0 % [0–0]

03 **What the saving rests on**

There is no saving to price: no cell is recommended.

04 **What this sample cannot tell**

This history holds only the alerts your current program raised and your analysts dispositioned: a pattern nobody ever alerted on is invisible to it, and recall here means recall among the cases your analysts confirmed. 1200 of the 1200 cases had no transaction before their window; the scenarios that compare a case with its own past or with its peers score 0 there.

05 **How it was measured**

Each alert is rebuilt into a case from your transactions, then every scenario is replayed at every threshold. Recall is the share of the cases your analysts confirmed that the scenario would have raised; the false-alert rate is the share of the cases they closed without action that it would have raised. Each rate carries a 95 % interval (Wilson) and its n. Recall is quoted from 5 confirmed cases and a false-alert rate from 20 benign cases. The recommended cell is the one with the fewest false alerts among those whose recall lower bound holds the floor the client declares.

06 **What this report does not do**

It does not see a value: the sealed record holds counts and rates per scenario and threshold, the first and last decision dates, the declared volume, the scales it was measured under, a disposition and a history flag per alert, and the SHA-256 of the two files. It holds no account, no transaction date, no country, no amount written out and no score per alert. The steps of the thresholds place each alert's largest amount between two values of the declared scale, and its transaction count the same way. The alert ids and the two file names come back in the record; this page prints none of them. It does not test robustness on cases nobody fabricated: that is measured apart, on the public record, which is entirely fabricated and says so. It measures these 1200 alerts; another program or another period needs its own sample.