

Recursive Bridge Calibration: Calibrators, Residuals, and Bridge Selection in Relation-First Inference

Author: Artur Motruk

Affiliation: Independent researcher

ORCID: 0009-0003-6928-1701

Programme: Relation-First Organization Programme

Document role: Core bridge methodology / programme analytic method

Public release status: Repository manuscript

Abstract

This paper defines Recursive Bridge Calibration, a relation-first method for selecting and revising bridge candidates under declared source, target, boundary, readout, calibrator, obstruction, and trace-update data.

The method is designed for claims of the form

$$X \Rightarrow Y,$$

where the source structure, target distinctions, and mediating bridge are not yet adequately separated. Recursive Bridge Calibration expands such claims into source-bridge-target form, identifies the target distinctions at stake, consults the theorem/no-go register, generates candidate bridge paths, calibrates those candidates against explicit success and failure conditions, and records the resulting trace state.

The procedure is recursive because success, partial success, and failure all update the later branch field. A failed bridge attempt is therefore not discarded; it becomes a traceable obstruction that constrains the next attempt.

The paper's main worked orientation is the Lorentzian bridge chain, but the method is not a Lorentzian-specific construction. Its public role is methodological: it formalizes how the programme chooses, tests, repairs, and sequences bridges without treating analogy, formal resemblance, or partial success as verified transfer.

0. Scope

This is a methodology paper for the programme.

It does not claim to derive physics, spacetime, General Relativity, the Standard Model, empirical predictions, or a completed theory of nature.

It claims that the programme has a reusable method for disciplined expansion:

Recursive Bridge Calibration.

This method is not an external planning heuristic. It is generated by the programme's own primitives:

relation — boundary — observer/readout.

It is also the programme-scale version of Recursive Chart Learning: branch attempts are evaluated, admitted or rejected, recorded as a trace state, and used to recalibrate the next branch field.

0.1 Strong reading: analytic method of the programme

The strong reading of this paper is:

Recursive Bridge Calibration is the analytic method of the Theory of Organization.

This should not be read as a completed “theory of everything” claim. It is a claim about method.

The programme’s proposal is that unification is not achieved by declaring that two theories are identical. It is achieved by recursively constructing, testing, repairing, and composing calibrated relations between source structures and target distinctions.

In this sense, Recursive Bridge Calibration is the relation-first recursive loop:

relation $\rightarrow$ boundary $\rightarrow$ observer/readout $\rightarrow$ calibrator $\rightarrow$ trace record $\rightarrow$ next relation.

The branching atlas later in this note records the programme’s current register of claims of the form:

our X may be a calibrated bridge to Z in discipline Y .

But the method is stronger than a list of analogies. Each proposed bridge must pass through the same discipline:

1. declare the source;
2. declare the target distinction;
3. declare the relation;
4. declare the boundary/tolerance;
5. declare the observer/readout/calibrator;
6. consult the theorem/no-go register;
7. attempt construction;
8. record success, partial success, or failure;
9. recurse.

Thus this paper states the programme’s working account of unification:

unification is an atlas of calibrated relations generated by recursive bridge learning.

0.2 Terminology note: path, trace, and closure bound

The programme-wide terminology used here is:

path / trace / closure-bound record

rather than ledger.

The reason is conceptual. A bridge attempt is not merely recorded; it becomes part of the programme’s path structure. Its success, partial success, or failure changes the trace and updates the closure bounds for later moves.

Where earlier terminology appears elsewhere in the programme, it should be read through this broader formulation:

ledger $\rightsquigarrow$ trace record / closure-bound state.

1. Adjacent methodological literatures

Recursive Bridge Calibration is programme-native, but it is not isolated from existing philosophy-of-science methodology.

It is adjacent to several established traditions.

1.1 Analogical reasoning

The procedure is close to disciplined analogical reasoning: a source structure is proposed as a bridge template for a target structure, and the analogy is admitted only after the relation, target distinction, and preservation condition are declared.

The difference is that Recursive Bridge Calibration does not treat analogy as sufficient. Analogy generates a candidate bridge; calibration decides whether it is admissible.

1.2 Research programmes and progressive repair

The method also resembles the Lakatosian distinction between progressive and degenerative research programmes. A bridge repair is progressive when it reduces obstruction, recovers a declared target distinction, or turns a vague failure into a precise next obligation. It becomes degenerative when it only protects an overbroad claim by adding undeclared rescue conditions.

The calibrator boundedness theorem is the programme-native version of this discipline: too little declaration is z_- ; totalizing rescue is z_+ ; admissible work lies between.

1.3 Robustness and negative results

The method treats failure as information. A failed bridge localizes what is missing: relation, boundary, readout, chart compatibility, tolerance, physical interpretation, or empirical semantics.

This is aligned with robustness and negative-results methodology: failures are not discarded but used to constrain the next trace.

1.4 Operational reconstruction

The procedure is also close to operational reconstruction. It asks what roles must be declared for a target distinction to be recovered: event algebra, measurement/readout, admissibility rule, update rule, covariance, or calibration.

The programme's distinctive contribution is to put these roles into a general relation-first bridge procedure.

1.5 Scientific realism, structural realism, and pragmatism

Recursive Bridge Calibration is best read as a structural-realist method with pragmatist safeguards.

It is structural-realist because it treats recovery of declared relations and preserved distinctions as the unit of unification. This is close in spirit to the ontic structural-realist orientation defended by Ladyman and Ross.

It is pragmatist in the limited sense that it does not claim the procedure guarantees truth. The procedure can terminate in success, stable partial success, or explicit blockage. Physical truth and empirical realization require further calibration and testing. This caution is compatible with van Fraassen-style empiricist restraint about what formal success licenses.

Thus the method does not replace realism with usefulness. It makes realism inspectable by forcing the relation, boundary, readout, and calibrator into declared form.

2. Motivation

The programme repeatedly faces claims of the form:

$$X \Rightarrow Y.$$

Examples:

positive information geometry $\Rightarrow$ Lorentzian structure,

causal order + number $\Rightarrow$ geometry,

scale readout $\Rightarrow$ dynamics,

formal action-like evaluator $\Rightarrow$ physical field equation.

Relation-first discipline says that each compressed arrow must be expanded:

$$X - \mathfrak{B}_{X \rightarrow Y} - Y.$$

But once the bridge form is explicit, a new question appears:

which bridge should be attempted first?

Recursive Bridge Calibration answers that question by using the programme's theorem and no-go registers to determine which bridge is upstream, which bridge is blocked, which bridge is premature, and which bridge unlocks the most downstream structure with the least overclaim.

3. Primitive schema

The method is built from the programme's primitive triadic structure:

boundary – relation / mediation – observer / readout.

Every bridge candidate must declare all three faces.

3.1 Relation face

The relation face answers:

what connects source to target?

Examples:

- order embedding;
- count-volume calibration;
- residual interpretation;
- action calibration;
- chart transition;
- evaluator-induced update.

3.2 Boundary face

The boundary face answers:

what distinction separates success, failure, inside, outside, admissible, or limiting?

Examples:

- λ in path-polarity;
- Λ in bounded-action dynamics;
- ε_V in count-volume calibration;
- null/boundary class in order-cone structure;
- no-go threshold for bridge adequacy.

3.3 Observer/readout face

The observer/readout face answers:

what makes the target distinction visible, comparable, or evaluable?

Examples:

- N_{pp} as interval-count readout;
- V_{pp} as scaled readout;
- $\mathcal{A}_{pp}$ as history evaluator;
- DynAdm as admissibility readout;
- chart covariance as atlas-level comparability.

Thus a bridge is never merely an arrow. It is a structured relation with boundary and readout.

4. Core definitions

Definition 4.1 — Target distinction family

A **target distinction family** is a declared set:

$$D'_Y \subseteq D_Y$$

of distinctions claimed to be recovered in the target context.

Examples:

$$D_{\text{order}}, \quad D_{\text{scale}}, \quad D_{\text{dyn}}, \quad D_{\text{phys}}.$$

A target claim is underdeclared until its target distinction family is named.

Definition 4.2 — Bridge candidate

A **bridge candidate** from source X to target Y is a tuple:

$$\mathfrak{B}_i = (R_i, B_i, O_i, P_i)$$

where:

1. R_i is the declared relation;
2. B_i is the boundary/admissibility condition;
3. O_i is the observer/readout/evaluator;
4. P_i is the preservation condition.

A bridge candidate is meaningful only relative to a target distinction family D'_Y .

Definition 4.3 — Bridge adequacy

A bridge candidate $\mathfrak{B}_i$ is **adequate for** D'_Y if:

$$D'_Y \subseteq \text{Rec}_{\mathfrak{B}_i}(D_X).$$

That is, the target distinctions are recoverable from the source distinctions under the declared bridge.

Definition 4.4 — No-go register

The **no-go register** is the set:

$$\mathcal{N}$$

of known programme obstructions.

Typical entries include:

- No Undeclared Relation;
- No-Free-Transfer;
- positive geometry is not Lorentzian signature;
- causal order is not scale;
- counting is not continuum volume;
- metric/scale is not dynamics;
- action-like evaluator is not physical action;
- admissible-history dynamics is not field equations;
- chart covariance is not physical covariance;
- formal residual is not physical residual;
- no total preservation under proper transfer.

The register may grow.

Definition 3.5 — Theorem register

The **theorem register** is the set:

$$\mathcal{T}$$

of positive bridge patterns already proved or conditionally established.

Typical entries include:

- path-polarity bridge recovers path-polarity;
- path-polarity plus composition closure yields preorder;
- antisymmetry yields partial order;
- local finiteness gives finite interval counting;
- scale unit gives scaled discrete readout;

- evaluator/admissibility gives admissible-history dynamics;
- chart covariance gives atlas-level comparability;
- persistence margin gives trace stability;
- bridge factorization gives component obligations.

The theorem register supplies constructive templates.

Definition 3.6 — Bridge trace / closure-bound record

The **bridge trace / closure-bound record** is the current record:

$$\mathcal{L} = (\mathcal{S}, \mathcal{F}, \mathcal{P}, \mathcal{O})$$

where:

- $\mathcal{S}$ records successful bridges;
- $\mathcal{F}$ records failed bridges;
- $\mathcal{P}$ records partial successes;
- $\mathcal{O}$ records open bridge obligations.

This trace record is the programme-scale analogue of a Recursive Chart Learning trace record.

Definition 3.7 — Candidate branch field

Given a source context, target family, theorem register, no-go register, and trace record, the **candidate branch field** is:

$$\mathcal{B}(T; \mathcal{T}, \mathcal{N}, \mathcal{L}) = \{\mathfrak{B}_1, \dots, \mathfrak{B}_n\}.$$

It is the set of bridge candidates available for forward calibration.

5. Recursive Bridge Calibration procedure

Procedure 4.1 — Recursive Bridge Calibration

Input:

1. a source context X ;
2. a target context Y ;
3. a target distinction family D'_Y ;
4. theorem register $\mathcal{T}$;
5. no-go register $\mathcal{N}$;
6. current bridge trace / closure-bound record $\mathcal{L}$.

Steps:

1. **Parse the claim**

$$X \Rightarrow Y \quad \rightsquigarrow \quad X - \mathfrak{B} - Y.$$

2. **Decompose the target**

$$D'_Y = D_1 \cup \dots \cup D_k.$$

3. **Generate candidate bridges**

$$\mathcal{B} = \{\mathfrak{B}_1, \dots, \mathfrak{B}_n\}.$$

4. **Audit each candidate** against the theorem and no-go registers.
 5. **Classify outcomes** as:

success, partial success, blocked, premature, wrong target, overclaim risk.
 6. **Compute blocking/unblocking dependencies** among candidates.
 7. **Select the next bridge target** using dependency and no-go information.
 8. **Attempt construction** of the selected bridge.
 9. **Update trace record** with success, partial success, failure, or new no-go.
 10. **Recurse** with the updated source and trace record.
-

6. Triadic closure-atlas refinement

This section is the **canonical procedural home** for closure-atlas navigation. The companion paper *Triadic Substitution, Coupling, and Closure Atlases* supplies the structural justification; this paper states the operational method.

Recursive Bridge Calibration can now be read as navigation through a triadic closure atlas.

A bridge failure is not only a missing arrow. It may be a missing or unstable role face:

$$Z, \quad R, \quad O.$$

It may also be a higher interface failure:

$$\text{substitution, coupling, residual, trace, recursion readout, face recovery, stranding, overclaim.}$$

6.1 Triadic RBC procedure

For each bridge target:

1. identify the active relation-triad locus;
2. identify the missing or unstable role subconfiguration or typed micro-triad;
3. classify whether the failure is singleton, dyadic, or coupling-interface failure;
4. identify which recursion face is active or missing:

Z-residual, R-trace, O-substitution/readout;
5. generate candidate role substitutes;
6. check each substitute for local triadic closure;
7. test coupling interfaces for landedness;
8. check whether a declared compatibility operator, face-recovery operation, or typed micro-triad admissibility condition is required;
9. evaluate residual, readout, and admissibility;
10. update the closure-bound record.

6.2 Triadic obstruction vector

The canonical triadic obstruction vector for Recursive Bridge Calibration is:

$$\mathbf{o}_T = (o_Z, o_R, o_O, o_{\text{sub}}, o_{\text{coup}}, o_{\text{res}}, o_{\text{trace}}, o_{\text{recurread}}, o_{\text{face}}, o_{\text{micro}}, o_{\text{strand}}, o_{\text{over}}).$$

Where:

- o_Z : boundary-face obstruction;
- o_R : mediation-face obstruction;
- o_O : observer/readout obstruction;
- o_{sub} : role-substitution obstruction;
- o_{coup} : coupling-interface obstruction;
- o_{res} : residual pressure not yet realized;
- o_{trace} : trace/update path missing or inadmissible;
- $o_{\text{recurread}}$: recursion readout/substitution missing;
- o_{face} : compatibility operator or face-recovery operation missing or invalid;
- o_{micro} : typed micro-triad compatibility missing or invalid;
- o_{strand} : stranded or dangling trace obstruction;
- o_{over} : overclaim / terminal-totalization risk.

6.3 Relation to the original procedure

This does not replace the original RBC procedure. It refines steps 4–9 of the procedure by making explicit which triadic face or interface is responsible for the obstruction.

The companion closure-atlas paper explains why these components are structurally forced. This paper uses them as the procedure.

A face-recovery failure is present when the bridge treats one triadic face as recoverable from the other two but does not declare the algebraic, order-theoretic, or categorical operation that makes the recovery valid.

A typed micro-triad failure is present when a bridge selects components from boundary, mediation, and readout faces but does not show that the boundary component bounds the mediation component or that the readout reads the mediated distinction.

7. Forward calibration rubric

For each bridge candidate, ask:

Criterion	Question
Source	What source distinctions are available?
Target	What target distinctions are claimed?
Relation	What relation is declared?
Boundary	What boundary/admissibility/tolerance is declared?
Observer/readout	What makes the target visible or comparable?
Recursion face	Is the active recursion residual-, trace-, or substitution-dominant?
Coupling interface	Does the bridge land in a closure-complete interface?
Compatibility / face recovery	Is a compatibility operator or residual/quotient operation needed and declared?
Typed micro-triad	If components are combined, do boundary, mediation, and readout type-check?
No-go repaired	Which obstruction does the bridge repair?
Remaining no-go	Which obstruction remains?
Composition	Does the bridge compose with previous bridges?
External template	Does a mature field contain an analogue?
Overclaim risk	Does the bridge claim too much?
Status	success / partial / blocked / premature / wrong target

The result is not a numerical score unless one is useful. The central output is a dependency map.

8. Blocking and unblocking

Definition 8.1 — Blocks

A candidate bridge $\mathfrak{B}_i$ is **blocked** by a no-go $N \in \mathcal{N}$ if:

$$D'_Y \not\subseteq \text{Rec}_{\mathfrak{B}_i}(D_X)$$

and N identifies the missing relation, boundary, or readout.

Definition 8.2 — Unblocks

A candidate bridge $\mathfrak{B}_i$ **unblocks** a later candidate $\mathfrak{B}_j$ if the target distinctions recovered by $\mathfrak{B}_i$ are required as source distinctions for $\mathfrak{B}_j$.

Symbolically:

$$\text{Rec}_{\mathfrak{B}_i}(D_X) \cap \text{Req}(\mathfrak{B}_j) \neq \emptyset.$$

Definition 8.3 — Premature bridge

A bridge $\mathfrak{B}_j$ is **premature** if it requires source distinctions not yet supplied by earlier bridges.

Example:

action-to-physical-action

is premature before:

continuum calibration

if the target physical variables and domains are not yet available.

9. Selection rule

Definition 9.1 — Next-bridge selection

Given candidate bridges $\mathcal{B}$, select a bridge $\mathfrak{B}_*$ satisfying:

1. it repairs a current high-priority no-go;
2. it is not premature;
3. it unlocks at least one downstream bridge;
4. it has controlled overclaim risk;
5. it has either a theorem-register template or a mature external analogue;
6. failure would still yield a useful diagnostic.

This is the programme's bridge-selection rule.

It is not optimization for convenience. It is no-go-guided learning.

10. Elementary-after-declaration mode

Many of the programme’s bridge-repair theorems have an intentionally elementary proof form.

A typical pattern is:

1. a compressed claim uses an undeclared relation;
2. Recursive Bridge Calibration identifies the missing relation, boundary, and readout;
3. the bridge is declared;
4. the target distinction follows directly from the declaration.

This can make the final proof look “trivial by definition.” In this programme, that is often the expected successful mode.

The point is not to hide difficult mathematics inside a proof. The point is to force the missing relation into the open so that the success or failure of the bridge becomes checkable.

the theorem becomes elementary because the missing relation has been supplied.

Definition 10.1 — Elementary-after-declaration theorem

A theorem is **elementary-after-declaration** when:

1. the original claim is underdeclared;
2. the calibration procedure identifies the missing bridge data;
3. once the bridge data are declared, the target distinction follows by definition, direct inclusion, or a short verification.

Examples include:

- path-polarity recovery after declaring $(\rightsquigarrow, \Omega, \lambda, \text{Adm})$;
 - interval counting after declaring local finiteness;
 - admissible-history dynamics after declaring a history field, evaluator, and admission rule;
 - contextual objecthood after declaring local sections and gluing compatibility.
-

10.2 Why this is not a weakness

The objection:

“the result is trivial because it follows from the definition”

misses the role of the method.

Before calibration, the relevant definition was missing. The compressed claim was doing hidden work. After calibration, the hidden relation has been declared, typed, bounded, and made evaluable.

Thus the elementary proof is evidence that the bridge has been successfully repaired.

The programme’s local standard is not:

make every proof technically difficult.

It is:

make every used relation explicit enough that the proof or failure becomes inspectable.

Theorem 10.3 — Bridge repair should simplify verification

If a bridge repair supplies all relation, boundary, and readout data required for a target distinction D'_Y , then verifying recovery of D'_Y should reduce to a direct check against the declared bridge.

Proof

Bridge adequacy is defined by:

$$D'_Y \subseteq \text{Rec}_{\mathfrak{B}}(D_X).$$

If the repair supplies the relation, boundary, readout, and preservation conditions that define $\text{Rec}_{\mathfrak{B}}(D_X)$, then checking adequacy is precisely checking the inclusion above. This is a direct verification relative to the declared bridge. $\square$

10.4 Not every theorem has this mode

This does not mean every result in the programme must be definitional.

Some results require external mathematics, computation, or empirical testing:

- causal reconstruction theorems;
- TDA stability comparisons;
- modular-cocycle calculations;
- count-volume calibration;
- galaxy morphology/environment tests;
- Standard Model representation constraints;
- physical action or continuum-limit bridges.

So the precise claim is:

elementary-after-declaration is the expected mode of bridge-repair verification, not the only mode of all programme mathematics.

This distinction matters. The programme uses elementary bridge-repair theorems to expose hidden relations, but it still needs nontrivial mathematics and empirical work where the target domain demands them.

11. Calibration progress functional

Recursive learning requires an evaluator. In this programme, the evaluator is not a generic loss function imposed from outside. It is built from the programme's own bridge obligations.

A bridge attempt improves the programme when it:

1. recovers a target distinction;
2. repairs a no-go;
3. reduces underdeclared relation;
4. preserves chart/readout visibility;
5. composes with existing successful bridges;
6. lowers overclaim risk;
7. produces a precise failure diagnosis if it fails.

This motivates a general **calibration progress functional**.

Definition 11.1 — Calibration state

A **calibration state** is a tuple:

$$\mathfrak{C}_t = (\mathcal{L}_t, D_t, \mathcal{O}_t, \mathcal{R}_t)$$

where:

- $\mathcal{L}_t$ is the bridge trace / closure-bound record at stage t ;
 - D_t is the current unresolved target distinction family;
 - $\mathcal{O}_t$ is the current set of open obligations;
 - $\mathcal{R}_t$ is the current overclaim-risk register.
-

Definition 11.2 — Obstruction vector

The **obstruction vector** of a calibration state is:

$$\mathbf{o}(\mathfrak{C}_t) = (u_t, b_t, c_t, r_t, q_t)$$

where:

1. u_t counts undeclared or underdeclared relations;
2. b_t counts unrepaired no-gos;
3. c_t counts bridge-composition failures;
4. r_t counts missing readout/chart-visibility conditions;
5. q_t counts overclaim risks.

The entries may be literal counts, weighted counts, or ordinal ranks. The only requirement is that they are declared.

Definition 9.3 — Calibration loss

A **calibration loss** is a map:

$$\mathcal{E}(\mathfrak{C}_t) = w_u u_t + w_b b_t + w_c c_t + w_r r_t + w_q q_t$$

with nonnegative declared weights:

$$w_u, w_b, w_c, w_r, w_q \geq 0.$$

This is the scalar version.

The lexicographic version is:

$$\mathbf{o}(\mathfrak{C}_t) \prec_{\text{lex}} \mathbf{o}(\mathfrak{C}_s).$$

The lexicographic version is often safer, because it prevents a bridge from reducing a minor count while increasing a major no-go.

Definition 11.4 — Admissible improvement step

A bridge attempt from $\mathfrak{C}_t$ to $\mathfrak{C}_{t+1}$ is an **admissible improvement step** if either:

$$\mathcal{E}(\mathfrak{C}_{t+1}) < \mathcal{E}(\mathfrak{C}_t),$$

or, in the lexicographic version:

$$\mathbf{o}(\mathfrak{C}_{t+1}) \prec_{\text{lex}} \mathbf{o}(\mathfrak{C}_t).$$

A partial success may be an improvement if it reduces some obstruction entries without increasing higher-priority entries.

A failed bridge may also be an improvement if it replaces an ambiguous obstruction with a precise open obligation. In that case the evaluator is not only “distance to success”; it is also “clarity of failure.”

Definition 9.5 — Branch-gradient direction

Given candidate bridges:

$$\mathcal{B}_t = \{\mathfrak{B}_1, \dots, \mathfrak{B}_n\},$$

a **branch-gradient direction** is a candidate $\mathfrak{B}_*$ whose expected calibration state gives maximal declared improvement:

$$\mathfrak{B}_* \in \arg \min_{\mathfrak{B}_i \in \mathcal{B}_t} \hat{\mathcal{E}}(\mathfrak{C}_{t+1}^{(i)}).$$

This is analogous to gradient descent only in role: it selects the next move by expected decrease in obstruction. It is not a differentiable gradient unless the bridge space is given differentiable structure.

Definition 9.6 — Diagnostic convergence

A sequence:

$$\mathfrak{C}_0, \mathfrak{C}_1, \dots$$

diagnostically converges if it reaches one of:

1. a successful bridge state, where the target distinctions are recovered;
2. a stable partial-success state, where recovered distinctions and remaining no-gos are fully classified;
3. a blocked state, where every available candidate is blocked, premature, or overclaiming and the open obligations are explicit.

This is weaker than truth-convergence. It is the right convergence concept for a foundational research programme.

12. Convergence theorems

Theorem 12.1 — Monotone calibration descent

If every bridge attempt is an admissible improvement step under $\mathcal{E}$, then the calibration loss is monotonically non-increasing, and strictly decreasing on successful improvement steps.

Proof

By Definition 8.4, an admissible improvement step satisfies:

$$\mathcal{E}(\mathfrak{C}_{t+1}) < \mathcal{E}(\mathfrak{C}_t)$$

or the corresponding lexicographic decrease. Therefore the sequence of losses decreases at each improvement step. If partial/failure clarification steps are allowed to keep the scalar loss constant while refining the trace record, then the scalar loss is non-increasing and the trace record information increases. $\square$

Theorem 12.2 — Finite local termination

Assume:

1. the candidate bridge field $\mathcal{B}_t$ is finite at each local stage;
2. the obstruction vector is valued in a well-founded ordered set;
3. every admitted bridge attempt strictly decreases the obstruction vector or terminates as blocked;
4. no candidate is repeated without new trace record information.

Then Recursive Bridge Calibration locally terminates in success, stable partial success, or explicit blockage.

Proof

A strictly decreasing sequence in a well-founded ordered set cannot continue indefinitely. Since the candidate field is finite and repeated candidates require new trace record information, the local run cannot cycle without progress. Therefore the run terminates in one of the declared terminal states: success, stable partial success, or explicit blockage. $\square$

Theorem 12.3 — No truth guarantee

Recursive Bridge Calibration does not guarantee that a selected bridge is physically true or empirically realized.

Proof

The method evaluates declared relations, recovered target distinctions, no-go repair, and bridge composition. Physical truth or empirical realization requires additional target-world correspondence, measurement, and validation. These are not guaranteed by the formal procedure. $\square$

13. General theorems**Theorem 13.1 — No arbitrary next bridge**

In a relation-first programme, the next bridge cannot be chosen arbitrarily if candidate bridges have dependency relations.

Proof

If a bridge $\mathfrak{B}_j$ requires source distinctions supplied only by $\mathfrak{B}_i$, then attempting $\mathfrak{B}_j$ before $\mathfrak{B}_i$ leaves its source underdeclared. By No-Undeclared-Relation, the inference is invalid. Therefore dependency relations constrain bridge order. $\square$

Theorem 13.2 — Failure is trace record information

If a candidate bridge fails because a no-go identifies a missing relation, boundary, or readout, then the failure updates the bridge trace / closure-bound record with a new open obligation.

Proof

A failed bridge identifies:

1. the attempted target distinction;
2. the missing bridge component;
3. the no-go responsible for the failure.

These are exactly the data required for $\mathcal{O}$, the open-obligation component of the trace record. Therefore failure is not empty; it updates the trace record. $\square$

Theorem 11.3 — Partial success composes only through recovered distinctions

A partial-success bridge can be used downstream only through the target distinctions it actually recovered.

Proof

Let $\mathfrak{B}_i$ recover $D'_i \subsetneq D_Y$. A downstream bridge $\mathfrak{B}_j$ can use only source distinctions available from $\text{Rec}_{\mathfrak{B}_i}(D_X)$. Distinctions not in D'_i were not recovered. Using them would violate No-Free-Transfer. $\square$

Theorem 11.4 — Recursive Bridge Calibration terminates locally when no admissible bridge is available

For a fixed finite candidate set $\mathcal{B}$, if every candidate is blocked, premature, or overclaiming, then the local calibration run terminates with an open obligation rather than a construction target.

Proof

The selection rule requires an admissible candidate satisfying the criteria in Definition 7.1. If none exists, no bridge is selected. The failed candidates and their blockers are recorded in the trace record / closure bound as open obligations. $\square$

14. Worked example: Lorentzian bridge chain

The Lorentzian chain is the first full worked example of Recursive Bridge Calibration.

14.1 Initial target

The initial compressed claim was:

positive / information / relation-first structure $\Rightarrow$ Lorentzian spacetime.

Target distinctions included:

1. signature;
2. causal order;
3. scale / volume;
4. dynamics;
5. physical interpretation.

14.2 First audit

The no-go register blocked the direct inference:

positive geometry is not Lorentzian signature.

recoverability is not causality.

causal order is not scale.

metric / scale is not dynamics.

The forward calibration selected:

path-polarity bridge

as the first target.

14.3 Construction steps

The chain then proceeded:

oriented residual relation $\rightarrow$ path-polarity,

path-polarity $\rightarrow$ preorder / partial order / order-cone candidate,

locally finite order $\rightarrow$ interval counting / scale readout,

scale readout + histories $\rightarrow$ admissible-history dynamics.

Each step was a partial success.

12.4 Chain output

The output was:

$$\mathcal{S}_{\text{formal}} = (X, \preceq_{\text{pp}}, \Omega, \lambda, N_{\text{pp}}, V_{\text{pp}}, \text{Hist}_{\text{pp}}^{\text{dyn}}, \mathcal{A}_{\text{pp}}).$$

This recovers:

formal order + discrete scale readout + admissible-history dynamics.

It does not recover:

physical Lorentzian spacetime or GR.

12.5 Second audit

With the formal skeleton complete, the next audit treats:

$$\mathcal{S}_{\text{formal}}$$

as source and asks for:

$$G_{\text{phys/L}}$$

as target.

The candidate bridges were:

1. order embedding;
2. interval-region calibration;
3. count-volume calibration;
4. residual interpretation;
5. action interpretation;
6. dynamics interpretation;
7. physical covariance;
8. probabilistic / quantum branch weighting.

12.6 Dependency result

The forward run produced:

order embedding → interval-region calibration → count-volume calibration → residual interpretation → action interpretation →
--

Physical covariance is cross-cutting.

Probabilistic / quantum weighting is a later optional branch.

12.7 Selected next target

The selected next construction target was:

count-volume / continuum calibration.

Reason:

1. it repairs the immediate no-go:
counting is not continuum volume;
2. it composes directly with order embedding and interval-region calibration;
3. it has a mature external analogue in causal-set methodology;
4. it unlocks action and dynamics interpretation later.

This is exactly Recursive Bridge Calibration in action.

15. Worked results brief

This section records three programme results as examples of Recursive Bridge Calibration at work. These are not re-proved here; the point is to show how the method operates formally across different domains.

15.1 Lorentzian Bridge result

Initial compressed claim

positive information geometry $\Rightarrow$ Lorentzian structure.

No-go detected

positive geometry is not Lorentzian signature.

Calibration move

Decompose Lorentzian structure into target distinction families:

signature/order, scale/volume, dynamics/update.

Result

The Lorentzian Bridge paper produced the factorization requirement:

full Lorentzian recovery requires sign/order, scale, and dynamics bridge factors.

Methodological status

This is Recursive Bridge Calibration at the factorization stage: the no-go does not end the programme; it decomposes the target into bridge obligations.

13.2 Lorentzian construction chain result

Initial target

Build the factorized bridge at the formal level.

Calibration path

path-polarity $\rightarrow$ causal/order-cone candidate $\rightarrow$ scale readout $\rightarrow$ admissible-history dynamics.

Result

The chain recovered:

charted locally finite path-polarity order + scaled discrete readout + admissible-history dynamics.

Remaining no-go

formal skeleton is not physical Lorentzian spacetime.

Methodological status

This is Recursive Bridge Calibration at the construction-chain stage: each bridge repairs one no-go and passes a precise remaining blocker to the next step.

13.3 Sheaf/contextuality contribution

Initial compressed claim

local chart compatibility $\Rightarrow$ global objecthood.

No-go detected

local compatibility is not global objecthood without gluing.

Calibration move

Read objecthood as a charted global-section problem:

local sections – gluing / transition compatibility – charted object.

Result

The contextual-objecthood work showed that standard deterministic/strong sheaf contextuality is recoverable as a special case of charted objecthood obstruction under a declared measurement-context bridge. It also identified non-posetal / non-invertible chart-transition obstructions as programme-native generalizations.

Methodological status

This is Recursive Bridge Calibration at the cross-disciplinary transfer stage: a known external obstruction is recovered under a declared bridge, while the programme's broader chart machinery identifies adjacent structures not naturally expressed by the narrower bridge.

13.4 What the three results show

Together these examples show three modes of the method:

Mode	Example	Output
factorization	Lorentzian Bridge	target decomposed into bridge obligations
construction chain	Lorentzian sequence	formal skeleton built
cross-disciplinary transfer	sheaf/contextuality	bridge-by-bridge external result recovered and generalized under declared bridge

This is why Recursive Bridge Calibration is not merely a planning heuristic. It has already produced factorization results, construction chains, and cross-disciplinary bridge results.

16. Approximation as the admissible middle

Recursive Bridge Calibration treats approximation not as a defect but as the normal admissible state of a relation-first programme.

A compressed claim at the initial boundary is underdeclared:

$$X \Rightarrow Y.$$

A completed total identity at the terminal boundary would overclaim:

$$X = Y$$

or:

$$\text{Rec}_{\mathfrak{B}}(D_X) = D_Y$$

without remainder.

The programme's natural working region is between these two boundaries:

$$\boxed{X - \mathfrak{B} - Y' \subseteq Y.}$$

Here, Y' is the recovered target distinction family, while:

$$Y \setminus Y'$$

records the remaining open obligations.

Thus a successful bridge is usually not total identification. It is a calibrated recovery of declared target distinctions under declared tolerances, with unrecovered distinctions explicitly preserved in the trace record.

16.1 Initial and terminal failure modes

Recursive Bridge Calibration recognizes two opposite failure modes.

Initial-boundary failure

The bridge is too undeclared:

$$X \Rightarrow Y.$$

No relation, boundary, readout, or preservation condition is specified.

Failure mode:

$$\boxed{\text{underdeclaration.}}$$

Terminal-boundary failure

The bridge is too totalizing:

$$X = Y$$

or:

the source is treated as if it recovers every target distinction.

Failure mode:

overclaim / total preservation fantasy.

The admissible state is neither.

14.2 Approximate bridge adequacy

A bridge may be adequate up to tolerance.

Let D'_Y be a target distinction family and let ε be a declared tolerance or admissibility boundary.

A bridge $\mathfrak{B}$ is **approximately adequate** for D'_Y if:

$$D'_Y \subseteq_{\varepsilon} \text{Rec}_{\mathfrak{B}}(D_X),$$

meaning every target distinction in D'_Y is recovered within the declared tolerance, comparison class, or admissibility boundary.

This is not weaker than exact adequacy in an informal sense. It is a different declared target:

recover within ε

rather than:

recover exactly.

14.3 Calibration principle

The calibration principle is:

A bridge is successful when it recovers the declared target distinctions to the declared tolerance and leaves the remainder expl

This is why partial success is a real result. It lives in the admissible middle between:

no bridge

and:

total identity.

The programme should therefore prefer:

calibrated partial recovery

over both undeclared transfer and premature unification.

14.4 Consequence for convergence

Diagnostic convergence does not require:

$$\mathcal{E}(\mathfrak{C}_t) \rightarrow 0$$

for every possible target.

It requires convergence relative to a declared target family and tolerance:

$$\mathcal{E}_{D'_Y, \varepsilon}(\mathfrak{C}_t) \rightarrow 0,$$

or termination in a stable partial-success state where the remaining obstruction is explicit.

This is exactly what happened in the Lorentzian chain. The formal bridge-factor target reached zero obstruction relative to:

order + discrete scale readout + admissible-history dynamics.

But when the target changed to physical Lorentzian spacetime, a new obstruction vector opened.

That is not regression. It is target refinement.

17. The calibrator role

The previous section says that approximation is admissible when the target, tolerance, and readout are declared. This section makes the missing role explicit:

the calibrator is the observer/readout role for approximation.

A bridge may recover a target distinction only approximately. That approximation is not meaningful until something declares:

1. what is being compared;
2. what tolerance is allowed;
3. which distinctions count as preserved;
4. which failures count as informative;
5. when the bridge is admitted, rejected, or recalibrated.

That role is the **calibrator**.

15.1 Definition — Calibrator

A **calibrator** for a bridge attempt is a tuple:

$$\mathfrak{K} = (D'_Y, \varepsilon, \mathcal{E}, \text{Adm}, \text{Update})$$

where:

1. D'_Y is the declared target distinction family;
2. ε is the declared tolerance or admissibility boundary;
3. $\mathcal{E}$ is the calibration progress functional;
4. Adm is the admission rule for success / partial success / failure;
5. Update is the trace-update rule after evaluation.

Thus the calibrator is not merely a score. It is the role that turns approximation into an admissible bridge result.

15.2 Calibrator as boundary–relation–observer structure

The calibrator itself has the programme’s triadic form.

Calibrator component	Programme role
target distinction family D'_Y	relation target
tolerance ε	boundary
progress functional $\mathcal{E}$	evaluator/readout
admission rule Adm	observer decision
trace update Update	recursive trace continuation

So the calibrator is not external bookkeeping. It is the programme’s observer/evaluator structure applied to bridge construction.

15.3 Calibration functional as evaluator

The calibration functional:

$$\mathcal{E}(\mathfrak{C}_t) = w_u u_t + w_b b_t + w_c c_t + w_r r_t + w_q q_t$$

or its lexicographic version, is the evaluator face of the calibrator.

It measures obstruction relative to the declared target:

$$(D'_Y, \varepsilon).$$

This matters because the same bridge can be a success relative to one target and a failure relative to another.

Example:

admissible-history dynamics

is a success relative to:

$$D'_Y = \text{formal dynamics-as-selection,}$$

but a failure relative to:

$$D'_Y = \text{Einstein field equations.}$$

The calibrator prevents these from being confused.

15.4 Admission rule

A bridge attempt is admitted as:

Success

if:

$$\mathcal{E}_{D'_Y, \varepsilon}(\mathfrak{C}_{t+1}) = 0$$

or all declared target distinctions are recovered to tolerance.

Partial success

if:

$$\mathcal{E}_{D'_Y, \varepsilon}(\mathfrak{C}_{t+1}) < \mathcal{E}_{D'_Y, \varepsilon}(\mathfrak{C}_t)$$

and the remaining obstruction is explicit.

Failure

if the bridge does not recover the declared target and does not reduce obstruction.

Diagnostic failure

if the bridge does not recover the target but identifies a new precise missing bridge component.

Diagnostic failure updates the trace record even though it is not a success.

15.5 Approximation requires a calibrator

Approximation without a calibrator is vague.

Approximation with a calibrator is a declared bridge relation:

$$\boxed{X - (\mathfrak{B}, \mathfrak{K}) - Y'_\varepsilon.}$$

Here:

$$Y'_\varepsilon$$

means:

target distinction family Y' recovered to tolerance ε .

Thus the full approximate bridge form is not:

$$X \approx Y.$$

It is:

$$X - \mathfrak{B} - Y' \quad \text{as evaluated by} \quad \mathfrak{K}.$$

15.6 Convergence is calibrator-relative

The convergence statement:

$$\mathcal{E}(\mathfrak{C}_t) \rightarrow 0$$

is incomplete unless the calibrator is declared.

The correct form is:

$$\mathcal{E}_{\mathfrak{K}}(\mathfrak{C}_t) \rightarrow 0.$$

Meaning:

obstruction goes to zero relative to the target, tolerance, and admission rule declared by $\mathfrak{K}$.

If the target changes, the calibrator changes, and a new obstruction vector may open.

This is why the Lorentzian chain can be complete relative to:

formal order + scale readout + admissible-history dynamics

but incomplete relative to:

physical Lorentzian spacetime.

That is not inconsistency. It is calibrator-relative convergence.

15.7 The calibrator theorem

Theorem 15.7 — Approximate success is admissible only relative to a calibrator

Let $\mathfrak{B}$ be a bridge from X to Y . Suppose $\mathfrak{B}$ approximately recovers a target distinction family D'_Y . Then the claim of approximate success is well-typed only if a calibrator:

$$\mathfrak{K} = (D'_Y, \varepsilon, \mathcal{E}, \text{Adm}, \text{Update})$$

is declared.

Proof

Approximate recovery requires specifying which target distinctions are being recovered, what tolerance counts as adequate, how the remaining obstruction is evaluated, and whether the result is admitted as success, partial success, or failure. These data are precisely the components of $\mathfrak{K}$. Without them, “approximately recovers” is underdeclared. Therefore approximate success is admissible only relative to a declared calibrator. $\square$

15.8 Calibrator boundedness

The calibrator is itself bounded.

Let:

$$z_-$$

denote the initial underdeclaration boundary: no declared relation, no target distinction family, no tolerance, no evaluator, no admission rule, no update rule.

Let:

$$z_+$$

denote the terminal totalization boundary: full identity, total preservation, no unrecovered remainder, and no need for calibration.

A valid calibrator lives strictly between these limits:

$$z_- < \mathfrak{K} < z_+.$$

This means that the calibrator is neither empty nor totalizing. It declares enough structure to evaluate a bridge, but not so much that bridge work collapses into total identity.

Theorem 15.9 — Calibrator Boundedness Theorem

A calibrator:

$$\mathfrak{K} = (D'_Y, \varepsilon, \mathcal{E}, \text{Adm}, \text{Update})$$

is admissible only if it lies strictly between the initial underdeclaration boundary z_- and the terminal totalization boundary z_+ .

Proof

If:

$$\mathfrak{K} = z_-,$$

then no target distinction family D'_Y , tolerance ε , evaluator $\mathcal{E}$, admission rule Adm , or update rule Update is declared. The bridge cannot be evaluated. This is underdeclaration.

If:

$$\mathfrak{K} = z_+,$$

then the calibrator demands total recovery:

$$\text{Rec}_{\mathfrak{B}}(D_X) = D_Y$$

with no unrecovered remainder. Calibration collapses into total identity. This violates the programme's no-totalization discipline and prevents partial recovery from being admitted as learning.

Therefore an admissible calibrator must satisfy:

$$z_- < \mathfrak{K} < z_+.$$

□

Corollary 15.10 — Calibrated Approximation Sufficiency

If a bridge $\mathfrak{B}$ recovers the declared target distinction family D'_Y within the declared tolerance ε , and the calibrator records unrecovered distinctions in the trace record, then the bridge is sufficient for that calibrated target.

Formally, if:

$$D'_Y \subseteq_\varepsilon \text{Rec}_{\mathfrak{B}}(D_X),$$

and:

$$D_Y \setminus D'_Y$$

is recorded in $\mathcal{L}$, then $\mathfrak{B}$ is admitted as a success or partial success relative to $\mathfrak{K}$.

Proof

The target of calibration is not all of D_Y . It is the declared target distinction family D'_Y under tolerance ε . If those distinctions are recovered to tolerance, the declared target has been met. Since unrecovered distinctions are preserved in the trace record, the bridge does not overclaim total recovery. Therefore it is sufficient relative to the calibrator. □

Corollary 15.11 — Exact Local Calibration as Local Boundary

If a bridge $\mathfrak{B}$ recovers the declared local target distinction family D'_Y with zero tolerance error under a declared calibrator $\mathfrak{K}$, then the result lies on the local calibration boundary for that target.

Formally, if:

$$D'_Y \subseteq_0 \text{Rec}_{\mathfrak{B}}(D_X),$$

then:

$$\mathcal{E}_{\mathfrak{K}}(\mathfrak{C}_{t+1}) = 0$$

relative to D'_Y . The bridge has reached the terminal point of that local calibrated task.

Proof

The calibrator defines the local target D'_Y , tolerance ε , evaluator $\mathcal{E}$, admission rule, and update rule. If $\varepsilon = 0$ and all distinctions in D'_Y are recovered, then no obstruction remains relative to that local calibrated target. Hence the calibration loss is zero for $\mathfrak{K}$, and the result lies at the local terminal boundary of that task. □

Important qualification

This does not imply:

$$\text{Rec}_{\mathfrak{B}}(D_X) = D_Y$$

for the full target D_Y .

It implies only:

$$\text{Rec}_{\mathfrak{B}}(D_X) \supseteq D'_Y$$

with zero tolerance error for the declared local target. The unrecovered remainder:

$$D_Y \setminus D'_Y$$

may still be open.

Thus exact local calibration is boundary contact **inside a declared subtask**, not global totalization.

Corollary 15.12 — General Exact Calibration Boundary

If a sequence of bridge attempts recovers every distinction in a declared target family D'_Y exactly under a calibrator $\mathfrak{K}$, then the sequence has reached the calibration boundary for that declared target.

Equivalently:

$$\mathcal{E}_{\mathfrak{K}}(\mathfrak{C}_t) = 0$$

means:

the declared calibration task is complete.

It does not mean:

all possible targets are complete.

Proof

The calibration functional is defined relative to $\mathfrak{K}$. Therefore zero obstruction means zero obstruction relative to the target, tolerance, evaluator, admission rule, and trace-update rule declared by $\mathfrak{K}$. If the target is later enlarged, a new calibrator and a new obstruction vector may open. $\square$

15.13 Consequence — Exactness is local unless the target is total

Exactness is always indexed to a calibrator.

So the correct form is:

exact for $(D'_Y, \mathfrak{K})$

not simply:

exact absolutely.

A bridge can be exact for path-polarity and still fail for causal order. It can be exact for formal admissible-history dynamics and still fail for physical field equations. It can be exact for deterministic sheaf-global-section obstruction and still fail to capture probabilistic contextuality.

This is why the programme treats exact local success and partial global success as compatible.

15.14 Consequence — Approximation is not a fallback

The programme should not treat approximation as a weakened substitute for exact identity.

The native bridge form is:

$$X - (\mathfrak{B}, \mathfrak{K}) - Y'_\epsilon \subseteq Y.$$

That is, the bridge recovers a declared target family to declared tolerance, while the unrecovered remainder remains visible.

So the precise principle is:

calibrated approximation is sufficient for a declared target under a declared calibrator.

This is stronger and safer than saying:

approximation is enough.

Approximation is enough only when the calibrator makes clear:

1. enough for what target;
 2. under what tolerance;
 3. by what evaluator;
 4. with what admission rule;
 5. with what remaining obligations recorded.
-

18. End-to-end status without completion

The branching atlas should be read as **end-to-end** but not **complete**.

It is end-to-end because the programme now has a method that reaches across:

foundational primitives → no-go discipline → bridge construction → external-domain calibration → empirical or mathematical

It is not complete because many branches remain open, conditional, or only partially calibrated.

This distinction matters.

A completed theory would claim:

all target structures are derived.

This paper claims something different:

the programme has a disciplined recursive method for deciding what bridge comes next, why it comes next, and what remains

That is the sense in which Recursive Bridge Calibration is the programme's current end-to-end analytical method.

19. Branching atlas of programme results

Recursive Bridge Calibration is not only a local method. It produces a **branching atlas** of the programme.

A branching atlas records:

1. the source result already available;
2. the external or internal target domain;
3. the no-go or obstruction that blocks free transfer;
4. the first bridge that would repair the obstruction;
5. the downstream bridge sequence;
6. the status of the branch.

This is the method's programme-level expression. It shows how unification appears here: not as a single totalizing identity, but as a network of declared bridges among relation, boundary, and observer/readout structures.

18.0 Branch maturity key

The branches below are not at the same maturity level.

Status class	Meaning
Completed formal chain	a multi-step bridge sequence has been constructed internally
External result recovered	a known external result is recovered under a declared bridge
External theorem candidate	a theorem has been produced and is ready for domain-facing review
Mathematical home identified	the likely formal category is identified, but theorem work remains
Empirical branch open	data target and obstruction are identified, but empirical model remains to be built
Open high-value branch	target is important but only the first bridge is identified
Method branch formalized	the branch is the method itself

This key is necessary because the atlas is not a claim that all branches are equally developed.

18.1 Branch atlas table

Branch	Source result	Target domain	First blocker	First repair bridge	Status
Lorentzian formal skeleton	path-polarity/order/scale/dynamics/chain	emergent spacetime/causal-set-adjacent structure	positive/information structure is not Lorentzian spacetime	path-polarity then order/scale/dynamics factors	formal chain completed
Continuum calibration	$\mathcal{S}_{\text{formal}}$	physical/continuum Lorentzian target	formal skeleton is not physical spacetime	order embedding + interval-region + count-volume calibration	next target selected
Sheaf/contextuality	charted object-hood/gluing	deterministic/strong contextual	local compatibility is not global objecthood	measurement-context bridge / global-section reading	external result recovered
TDA stability	persistence support + trace	applied topology / dynamic persistence	local support is not stable trace	margin / moving-support bridge	theorem candidate completed
Modular cocycle structure	accessibility/compression matrix $\mathbb{M}$	essential theory / AQFT / cocycle geometry	state picture underclassifies transition structure	Connes-cocycle / groupoid-compression bridge	mathematical home identified
Galaxy calibration	RAR/lensing closure	empirical dark-sector phenomenology	RAR closure has no new content without morphol-ogy/environment term	morphology/environment boundary term	empirical branch open
Standard Model partition	latent partitions λ	gauge/Higgs/Yukawa structure	partition count is not physical gauge theory	partition-to-representation bridge	open high-value branch
Probability / branch weighting	branch field + evaluator	probability / quantum measure	branch weights are not probability/amplitude	normalization/event algebra/update bridge	open method branch
Methodology itself	no-go/theorem register + trace record	programme-level learning	no bridge-selection rule	Recursive Bridge Calibration	current paper

20. Light calibration audits for major branches

This section gives light audits for the branching atlas. Each audit is intentionally brief. It does not solve the branch; it identifies the first bridge and the proposed stepwise path.

19.1 Lorentzian formal skeleton branch

Source

relation-first / information / boundary structure.

Target

Lorentzian bridge factors.

No-go

positive information geometry is not Lorentzian spacetime.

Calibration result

The target decomposes into:

sign/order $\rightarrow$ scale $\rightarrow$ dynamics.

Stepwise bridge path

path-polarity $\rightarrow$ causal/order-cone $\rightarrow$ locally finite order $\rightarrow$ scale readout $\rightarrow$ admissible-history dynamics.

Status

formal bridge skeleton completed.

Remaining blocker

formal skeleton is not physical Lorentzian spacetime.

19.2 Continuum calibration branch

Source

$$\mathcal{S}_{\text{formal}} = (X, \preceq_{\text{pp}}, \Omega, \lambda, N_{\text{pp}}, V_{\text{pp}}, \text{Hist}_{\text{pp}}^{\text{dyn}}, \mathcal{A}_{\text{pp}}).$$

Target

$$G_{\text{phys/L}}.$$

No-go

formal order/scale/dynamics are not continuum physical structure.

First bridge

$$\mathfrak{B}_{\text{calib}} = (\Phi, \mathcal{R}, \kappa, \mathcal{I}_{\Omega}, \mathcal{I}_A, \mathcal{C}).$$

Stepwise bridge path

order embedding $\rightarrow$ interval-region calibration $\rightarrow$ count-volume calibration $\rightarrow$ residual interpretation $\rightarrow$ action interpretation $\rightarrow$

Status

forward trace computed; first construction target is count-volume calibration.

19.3 Sheaf/contextuality branch

Source

charted objecthood as compatible family across charts.

Target

sheaf-theoretic contextuality.

No-go

local sections are not global objecthood without gluing.

First bridge

measurement-context bridge

mapping contexts, outcome assignments, restriction maps, and admissible local sections into charted objecthood data.

Stepwise bridge path

local chart sections $\rightarrow$ overlap compatibility $\rightarrow$ global section / objecthood $\rightarrow$ contextual obstruction if no section exists.

Result

Standard deterministic/strong sheaf contextuality is recovered as a special case of charted objecthood obstruction under the declared bridge.

Extension

Non-posetal or non-invertible chart transitions supply programme-native generalizations beyond the narrow restriction-only bridge.

Status

external result recovered and generalized.

19.4 TDA persistence / trace stability branch

Source

persistence support + threshold trace + charted path.

Target

dynamic trace stability.

No-go

local support membership is not whole-trace stability.

First bridge

persistence margin bridge

with margin:

$$m_i = \min(\theta_i - \ell_i, u_i - \theta_i).$$

Stepwise bridge path

fixed support margin $\rightarrow$ whole-trace margin $\rightarrow$ moving-support budget $\rightarrow$ failure localization.

Result

The theorem chain gives sufficient conditions for a transported organization trace to remain proper under threshold perturbation and support drift.

Status

external-facing quantitative theorem branch completed at first level.

Remaining bridge

application-level computation / probabilistic extension.

19.5 Modular cocycle / $\mathbb{M}$ branch**Source**

$\mathbb{M}_{AB}$ = accessibility amplitude between compressions.

Composition defect:

$$\Omega_{ABC} = \log \frac{\mathbb{M}_{AB}\mathbb{M}_{BC}}{\mathbb{M}_{AC}}.$$

Target

modular theory / groupoid cocycle / AQFT formal home.

No-go

state-on-algebra picture is too small for transition/accessibility structure.

First bridge

Connes-cocycle / groupoid-compression bridge.

Stepwise bridge path

compression amplitudes $\rightarrow$ cocycle condition $\rightarrow$ flat sector / compatible physics $\rightarrow$ curved sector / holonomy residual $\rightarrow$ scale-d

Result

The branch identifies a mathematical home for $\mathbb{M}$: modular cocycle / compression-groupoid structure.

Status

mathematical-home branch opened strongly; theorem work remains.

Next bridge

cocycle norm / holonomy to empirical scale leakage.

19.6 Galaxy morphology / empirical calibration branch**Source**

$$\Delta_C(R) = \ln \left(\frac{g_{\text{obs}}}{g_{\text{bar}}} \right).$$

Target

empirical dark-sector / lensing / morphology dependence.

No-go

RAR closure alone is not new predictive content.

The current closure reproduces the RAR/MOND-style relation unless additional morphology or environment terms are supplied.

First bridge

morphology/environment boundary term.

Candidate observable bridge data

Possible readouts include:

- fast/slow rotator class;
- λ_R ;
- ellipticity;
- anisotropy β_z ;
- velocity-moment scale;
- environment / isolation;
- stellar mass and surface-density class.

Stepwise bridge path

RAR baseline $\rightarrow$ morphology residual $\rightarrow$ boundary term B_{morph} $\rightarrow$ lensing/RAR residual prediction $\rightarrow$ empirical falsification.

Status

highest-value empirical calibration branch.

Next bridge

$$\Delta_C = \Delta_{\text{RAR}} + B_{\text{morph}}(\lambda_R, \epsilon, \beta_z, \dots).$$

19.7 Standard Model partition / Higgs branch

Source

Latent partition structure:

$$\lambda = (k_1, \dots, k_m),$$

degeneracy:

$$\Omega_\lambda = \frac{N!}{\prod_i k_i!}.$$

Target

gauge sectors / representations / Higgs anchoring.

No-go

partition counting is not physical gauge theory.

First bridge

partition-to-representation bridge.

Stepwise bridge path

partition $\rightarrow$ internal symmetry group $\rightarrow$ representation content $\rightarrow$ connection/gauge dynamics $\rightarrow$ Higgs anchoring $\rightarrow$ Yukawa/n

Status

open high-value structural branch.

First target

Do not attempt full Standard Model derivation first. Attempt:

$$\lambda \rightarrow G_\lambda = S \left(\prod_i U(k_i) \right)$$

as a controlled bridge, then audit what remains.

19.8 Probability / branch weighting branch**Source**

Branch field plus evaluator:

$$\mathcal{B}, \quad \mathcal{E}.$$

Target

probability / amplitude / quantum measure.

No-go

branch weights are not probability or amplitude without role data.

First bridge

task-role-evaluator probability bridge.

Required bridge data

- event algebra;
- normalization;
- measure or amplitude composition rule;
- update rule;
- interpretation of weights;
- empirical or task semantics.

Stepwise bridge path

branch field $\rightarrow$ weight/evaluator $\rightarrow$ normalization $\rightarrow$ event algebra $\rightarrow$ probability/amplitude $\rightarrow$ update/calibration.

Status

methodologically central, physically later.

19.9 Methodology branch**Source**

theorem register + no-go register + bridge trace / closure-bound record.

Target

programme-scale learning method.

No-go

the programme cannot choose bridges by intuition alone.

First bridge

Recursive Bridge Calibration.

Result

The current paper formalizes the method:

candidate bridge field $\rightarrow$ calibration functional $\rightarrow$ dependency roadmap $\rightarrow$ selected bridge $\rightarrow$ trace update.

Status

method branch formalized.

21. What the branching atlas shows

The branching atlas shows that the programme is not a linear derivation.

It is a structured relation network.

Each branch has the same form:

source result — declared bridge — target distinction.

The no-go register prevents premature transfer. The theorem register supplies constructive templates. The calibrator turns approximation into admissible partial recovery. The trace record preserves both success and failure.

This is what unification looks like in the Theory of Organization:

not one identity, but an atlas of calibrated relations.

That is why the method itself is a relation.

The phrase “Analytical Method of reality” should be read in this disciplined sense. It does not mean that this paper has completed reality. It means that the programme’s account of reality is analyzed through declared relations, bounded calibration, observer/readout roles, and recursive trace updates. The method is the programme’s way of making reality-claims inspectable.

22. Worked calibration traces

The worked results above show where Recursive Bridge Calibration has been used. This section shows the calibration functional operating step by step.

The scores below are not empirical measurements. They are a declared diagnostic scoring for exposition. Let the obstruction vector be:

$$\mathbf{o} = (u, b, c, r, q)$$

where:

- u = undeclared relation count;
- b = unrepaired no-go count;
- c = bridge-composition failure count;
- r = missing readout/chart-visibility count;
- q = overclaim-risk count.

Use the unit-weight scalar calibration loss:

$$\mathcal{E}(\mathfrak{C}) = u + b + c + r + q.$$

A real application may use different weights or lexicographic ordering. The point here is to show how the evaluator changes as bridges are declared.

20.1 Lorentzian Bridge factorization calibration

Initial compressed claim

positive information geometry $\Rightarrow$ Lorentzian spacetime.

Obstruction vector:

$$\mathbf{o}_0 = (1, 4, 1, 1, 1), \quad \mathcal{E}_0 = 8.$$

Interpretation:

- one undeclared bridge arrow;
- four major no-gos: positive-to-indefinite, recoverability-to-causality, order-is-not-scale, metric-is-not-dynamics;
- one composition failure because target factors are not separated;
- one readout failure because the target distinction family is not visible;
- one overclaim risk because “Lorentzian spacetime” is claimed wholesale.

Calibration step: target factorization

The target is decomposed:

$$D_L = D_{\text{sign/order}} \cup D_{\text{scale}} \cup D_{\text{dyn}}.$$

New obstruction vector:

$$\mathbf{o}_1 = (0, 3, 0, 1, 0), \quad \mathcal{E}_1 = 4.$$

Improvement:

$$\Delta\mathcal{E} = -4.$$

Interpretation:

The invisible arrow is repaired by declaring factor obligations. The overclaim risk drops because the paper no longer claims full Lorentzian recovery in one step. Three no-gos remain because the factors are not yet constructed.

20.2 Lorentzian construction chain calibration

The construction chain proceeds through four bridge attempts.

Step A — Path-polarity bridge

Bridge:

$$(\rightsquigarrow, \Omega, \lambda, \text{Adm}) \rightarrow D_{\text{pp}}.$$

Recovered:

future-like / boundary-like / exterior-like path distinctions.

Obstruction vector:

$$\mathbf{o}_A = (0, 3, 0, 0, 0), \quad \mathcal{E}_A = 3.$$

Improvement from factorized state:

$$\Delta\mathcal{E} = -1.$$

Remaining blockers:

order, scale, dynamics.

Step B — Order / cone candidate

Bridge:

$$D_{\text{pp}} \rightarrow (X, \preceq_{\text{pp}}, \Omega, \lambda).$$

Recovered:

- preorder / partial order under declared hypotheses;
- order-cone candidate;
- local finiteness when declared;
- chart compatibility when declared.

Obstruction vector:

$$\mathbf{o}_B = (0, 2, 0, 0, 0), \quad \mathcal{E}_B = 2.$$

Improvement:

$$\Delta\mathcal{E} = -1.$$

Remaining blockers:

scale, dynamics.

Step C — Scale readout

Bridge:

$$I_{\text{pp}}(x, y) \rightarrow N_{\text{pp}}(x, y) \rightarrow V_{\text{pp}}(x, y) = \nu N_{\text{pp}}(x, y).$$

Recovered:

scaled discrete interval-counting readout.

Obstruction vector:

$$\mathbf{o}_C = (0, 1, 0, 0, 0), \quad \mathcal{E}_C = 1.$$

Improvement:

$$\Delta\mathcal{E} = -1.$$

Remaining blocker:

dynamics.

Step D — Admissible-history dynamics

Bridge:

$$\text{Hist}_{\text{pp}} \rightarrow \mathcal{A}_{\text{pp}} \rightarrow \text{DynAdm} \rightarrow \text{Hist}_{\text{pp}}^{\text{dyn}}.$$

Recovered:

admissible-history dynamics.

Obstruction vector:

$$\mathbf{o}_D = (0, 0, 0, 0, 0), \quad \mathcal{E}_D = 0$$

relative to the **formal bridge-factor target**.

Improvement:

$$\Delta\mathcal{E} = -1.$$

Important qualifier:

$$\mathcal{E}_D = 0$$

only for the formal target:

order + discrete scale readout + admissible-history dynamics.

If the target is upgraded to physical Lorentzian spacetime or GR, a new obstruction vector must be opened.

20.3 Post-skeleton calibration trace

After formal completion, the source becomes:

$$\mathcal{S}_{\text{formal}}.$$

The new target is:

$$G_{\text{phys/L}}.$$

This opens a new calibration state.

Initial physical-target obstruction vector:

$$\mathbf{o}_{\text{phys},0} = (1, 6, 2, 3, 1), \quad \mathcal{E}_{\text{phys},0} = 13.$$

Interpretation:

- undeclared calibration bridge;
- six major physical/continuum no-gos:
 1. formal order is not continuum causal order;
 2. formal intervals are not continuum regions;
 3. counting is not continuum volume;
 4. formal residual is not physical residual;
 5. action-like evaluator is not physical action;
 6. admissible histories are not field equations;
- composition failures because physical dynamics is being requested before calibration;
- missing readout/covariance conditions;
- overclaim risk if the formal skeleton is treated as GR.

Forward calibration run

The candidate bridges are scored by expected obstruction reduction.

Candidate	Expected repaired obstruction	Expected remaining blocker	Status
order embedding	formal order not continuum causal order	interval/volume/action/dynamics	necessary but not sufficient
interval-region calibration	formal intervals not continuum regions	count-volume	prerequisite
count-volume calibration	counting not continuum volume	residual/action/dynamics interpretation	strongest next full target
residual interpretation	formal residual not physical residual	needs calibrated target domain	premature before region/volume
action calibration	action-like not physical action	needs physical variables/domain	premature before calibration
dynamics interpretation	admissible histories not field equations	needs action/covariance/coupling	downstream

Candidate	Expected repaired obstruction	Expected remaining blocker	Status
physical covariance	chart covariance not physical covariance	must accompany every bridge	cross-cutting
probability/quantum weighting	branch weights not probability/amplitude	needs event algebra/normalization	later optional branch

Selected bridge:

$$\boxed{\text{count-volume} / \text{continuum calibration}}$$

but with prerequisites:

$$\boxed{\text{order embedding} \rightarrow \text{interval-region calibration} \rightarrow \text{count-volume calibration.}}$$

After selecting the next bridge target, the calibration state becomes:

$$\mathbf{o}_{\text{phys},1} = (0, 5, 1, 2, 0), \quad \mathcal{E}_{\text{phys},1} = 8.$$

Improvement:

$$\Delta \mathcal{E} = -5.$$

Interpretation:

The broad physical overclaim has been decomposed into a concrete next bridge. The chain is still blocked, but the blocker is now localized.

20.4 Sheaf/contextuality calibration trace

Initial compressed claim

local compatibility $\Rightarrow$ global objecthood.

Initial obstruction vector:

$$\mathbf{o}_0 = (1, 2, 1, 1, 1), \quad \mathcal{E}_0 = 6.$$

Interpretation:

- undeclared gluing bridge;
- local-to-global no-go;
- possible contextuality obstruction;
- composition/gluing not checked;
- objecthood target not made chart-visible;
- overclaim risk if local sections are treated as objects.

Calibration step: charted objecthood as global section

Declare:

local sections – gluing / transition compatibility – charted object.

New obstruction vector:

$$\mathbf{o}_1 = (0, 1, 0, 0, 0), \quad \mathcal{E}_1 = 1.$$

Remaining blocker:

contextual obstruction / no global section.

Calibration result

The bridge recovers standard deterministic/strong sheaf contextuality as a special case under a measurement-context bridge. The remaining obstruction is not a defect; it is the result:

local sections may fail to glue globally.

Final obstruction vector relative to the declared target:

$$\mathbf{o}_2 = (0, 0, 0, 0, 0), \quad \mathcal{E}_2 = 0,$$

because the obstruction itself has been classified as the target phenomenon.

20.5 What the calibration traces show

Across the three worked examples, the calibrator does the same job:

Example	Initial failure	Calibration move	Result
Lorentzian Bridge	positive geometry falsely asked to recover all Lorentzian structure	factor target into sign/order, scale, dynamics	construction path opened
Lorentzian Chain	factor obligations unresolved	build bridge factors one by one	formal skeleton completed
Physical Calibration	formal skeleton overclaimed as physics	compute next bridge roadmap	count-volume target selected
Sheaf/contextuality	local compatibility overclaimed as global objecthood	declare gluing bridge	contextual obstruction classified

The calibration functional is therefore not decoration. It turns the programme's learning loop into an inspectable sequence of obstruction reductions, partial successes, and new target selections.

23. Relation to Recursive Chart Learning

Recursive Bridge Calibration is the programme-scale version of Recursive Chart Learning.

Recursive Chart Learning	Recursive Bridge Calibration
branch	bridge candidate
evaluator	bridge adequacy / no-go audit
trace record	theorem/no-go/bridge trace / closure-bound record
admitted branch	successful bridge
failed branch	no-go-diagnosed bridge
recalibration	updated target / next bridge selection
trace	bridge chain

The key shared principle is:

failure is not discarded; it updates the next branch field.

Thus the Lorentzian chain is not merely a series of papers. It is a learning trace.

24. Relation to No Undeclared Relation

No Undeclared Relation supplies the negative constraint:

no bridge may be used before it is declared.

Recursive Bridge Calibration supplies the constructive complement:

when many bridges are possible, select the next bridge by no-go-guided dependency analysis.

Together:

No Undeclared Relation forbids invisible arrows;

Recursive Bridge Calibration chooses the next visible arrow.

25. Relation to the programme guide

The programme guide helps external readers navigate the programme. Recursive Bridge Calibration helps the programme navigate itself.

The guide answers:

where should a reader enter?

Recursive Bridge Calibration answers:

where should the programme move next?

The two are complementary.

26. Claims and non-claims

26.1 Claims

This note claims:

1. Recursive Bridge Calibration is a programme-native method;
2. the method is generated by relation-first, no-go discipline, theorem-register construction, and recursive learning;
3. the method selects bridges by dependency and no-go repair rather than intuition;
4. the elementary-after-declaration proof mode is expected for bridge-repair verification;
5. success, partial success, and failure all update the bridge trace / closure-bound record;
6. the calibration progress functional supplies an evaluator for programme-scale recursive learning;
7. local convergence can be stated as monotone obstruction reduction or diagnostic termination;
8. approximation is an admissible middle state between undeclared transfer and total identity;
9. approximate adequacy is valid when target distinction, tolerance, and readout are declared;
10. the calibrator is the observer/readout role that makes approximate bridge success admissible;
11. the calibrator is bounded between initial underdeclaration z_- and terminal totalization z_+ ;
12. calibrated approximation is sufficient for a declared target under a declared calibrator;
13. exact calibration means boundary completion relative to the declared calibrator, not absolute completion of all possible targets;
14. convergence is calibrator-relative, not absolute across all possible targets;
15. Recursive Bridge Calibration is the programme's current analytic method for disciplined expansion;
16. the branching atlas compiles the programme's major outward bridge paths while distinguishing maturity levels;
17. the atlas shows unification as an organized network of calibrated relations rather than a single total identity;
18. the Lorentzian chain is a worked example of the method;
19. the sheaf/contextuality contribution is a cross-disciplinary worked result of the same method;
20. worked calibration traces show obstruction-vector reduction at each major step;
21. the numerical obstruction vectors in the worked traces are declared diagnostic scores, not empirical measurements;
22. this paper is the canonical procedural home for the triadic obstruction vector;
23. the triadic closure-atlas refinement identifies whether a bridge failure is boundary-, mediation-, readout-, substitution-, coupling-, residual-, trace-, recursion-readout-, face-recovery-, typed-micro-triad-, stranding-, or overclaim-based;
24. bridge selection can be read as repairing the first unstable role-interface whose repair unlocks downstream closure;
25. valued bridge candidates must declare any compatibility operator or face-recovery operation they use;
26. component-level bridge candidates must satisfy typed micro-triad admissibility rather than merely selecting one component from each face.

26.2 Non-claims

This note does not claim:

1. the method guarantees physical truth;
2. the method derives GR;
3. the method derives the Standard Model;
4. the method completes the Theory of Organization;
5. the method replaces domain expertise;
6. the method proves every selected bridge will succeed;
7. the method makes empirical testing unnecessary;
8. the branching atlas is complete;
9. the companion closure-atlas paper, rather than this methodology paper, is the place where all structural justification is proved.

27. Summary

Recursive Bridge Calibration formalizes what the programme has been doing in practice. It is the programme's current analytical method: the relation-first recursive loop by which proposed unifications are parsed, tested, repaired, admitted, or rejected.

Its characteristic proof mode is elementary-after-declaration: once the missing relation, boundary, and readout are supplied, verification should become direct. That is a strength, not a defect, for bridge-repair theorems.

It takes:

target $\rightarrow$ target distinction decomposition $\rightarrow$ theorem/no-go register $\rightarrow$ candidate bridge field $\rightarrow$ forward calibration $\rightarrow$ dependence

Its evaluator is the calibration progress functional:

$$\mathcal{E}(\mathfrak{C}_t) = w_u u_t + w_b b_t + w_c c_t + w_r r_t + w_q q_t.$$

It is relation-first because every candidate is a declared bridge.

It is recursive because every result updates the trace record and changes the next branch field.

It is constructive because it does not stop at no-go diagnosis.

It is cautious because every partial success is limited to the target distinctions actually recovered.

It is boundary-native because it treats calibrated approximation as the admissible middle between underdeclared transfer and premature total identity.

The calibrator is the role that makes this possible:

$$\mathfrak{K} = (D'_Y, \varepsilon, \mathcal{E}, \text{Adm}, \text{Update}).$$

So convergence is not absolute; it is convergence relative to a declared calibrator:

$$\mathcal{E}_{\mathfrak{K}}(\mathfrak{C}_t) \rightarrow 0.$$

The Lorentzian bridge chain is the first large worked example. The sheaf/contextuality result shows the same method operating in a different disciplinary setting. The branching atlas shows that the method now organizes the programme's major outward paths: Lorentzian emergence, continuum calibration, contextuality, TDA stability, modular cocycles, empirical galaxy calibration, Standard-Model partition questions, probability, and methodology itself.

The worked calibration traces show the evaluator explicitly:

$$\mathbf{o}(\mathfrak{C}_t) = (u_t, b_t, c_t, r_t, q_t), \quad \mathcal{E}(\mathfrak{C}_t) = u_t + b_t + c_t + r_t + q_t$$

in the unit-weight illustrative case.

The next application is:

count-volume / continuum calibration.

The calibrator is also bounded:

$$z_- < \mathfrak{K} < z_+.$$

It is not the initial absence of relation, and it is not terminal total identity. It is the admissible middle role that makes approximation meaningful.

So the precise approximation principle is:

$$D'_Y \subseteq_\varepsilon \text{Rec}_{\mathfrak{B}}(D_X) \quad \text{relative to } \mathfrak{K}.$$

That is: calibrated approximation is sufficient for a declared target under a declared calibrator.

Exact calibration has the same boundary logic. If:

$$\mathcal{E}_{\mathfrak{K}}(\mathfrak{C}_t) = 0,$$

then the declared calibration task has reached its local boundary. But this is always indexed to:

$$(D'_Y, \varepsilon, \mathfrak{K}).$$

It is exactness for the declared target, not automatic completion of every larger target.

References / Adjacent methodology

- Ladyman, J. and Ross, D. (2007). *Every Thing Must Go: Metaphysics Naturalized*. Oxford University Press.
- van Fraassen, B. C. (1980). *The Scientific Image*. Oxford University Press.
- Bartha, P. (2010). *By Parallel Reasoning: The Construction and Evaluation of Analogical Arguments*. Oxford University Press.
- Lakatos, I. (1978). *The Methodology of Scientific Research Programmes*. Cambridge University Press.
- Wimsatt, W. C. (2007). *Re-Engineering Philosophy for Limited Beings: Piecewise Approximations to Reality*. Harvard University Press.
- Hardy, L. (2001). *Quantum Theory From Five Reasonable Axioms*. arXiv:quant-ph/0101012.
- Chiribella, G., D'Ariano, G. M., and Perinotti, P. (2011). *Informational Derivation of Quantum Theory*. Physical Review A, 84, 012311.

References / Internal dependencies

- Relation-First as a Constraint on Foundational Inference.
- No Undeclared Relation and Bridge Completion.
- Recursive Chart Learning Theory.
- Cross-Closure Theorems.
- The Lorentzian Bridge.
- Lorentzian No-Go Repair Audit.
- From Path-Polarity to Causal Order and Cone Boundary.
- From Local Finiteness to Scale Readout.
- From Scale Readout to Dynamics Update.

•

The Lorentzian Bridge Chain.

AI-assistance disclosure

This manuscript was developed with AI-assisted drafting and review support. The author directed the research programme, selected and revised the mathematical and methodological content, and is responsible for all claims and errors.