

An Encoder-Decoder Deep Neural Network for Binary Segmentation of Seismic Facies


Gefersom Cardoso Lima, Gabriel de Oliveira Ramos, Sandro José Rigo, Felipe André Zeiser, Ariane Santos da Silveira
Vale do Rio dos Sinos University, São Leopoldo, Brazil

IN A NUTSHELL

- A deep neural network that outperforms state-of-the-art methods with fewer parameters
- A composite loss function that linearly combines cross-entropy and Jaccard loss
- Fast segmentation of an arbitrary number of seismic facies
- A seismic facies dataset for binary segmentation

SEISMIC FACIES GEOMETRY SEGMENTATION PROBLEM

- Manually identify seismic facies geometries is a time-consuming and arduous task to be performed
- There are GigaBytes of seismic data to be analyzed
- Seismic datasets are scarce and need a specialized professional for their creation
- How to segment an arbitrary number of seismic facies geometries using neural networks?



- Using only the cross-entropy loss function is not enough to obtain detailed segmentation of seismic facies geometries identify


PROPOSED METHOD

- Proposed an encoder-decoder **Deep neural network for facies segmentation** (DNFS) compared with StNet and U-Net variants to find a minimum neural network
- Creation of a binary dataset in which black lines represented the transition of seismic facies geometry
- **Composite loss function** by the linear combination of **cross-entropy** and **Jaccard loss**


$$Loss = (1 - \eta)CrossEntropy_l(A, B) + \eta JaccardLoss(A, B)$$

- Five experiments were performed to find the (η) composite loss function coefficient.
- Neural network total number of parameter variations by factors (Ω): 4, 8, 16, 32, 64, 128

SCHEME FOR VARIATION OF THE TOTAL NUMBER OF PARAMETERS




Deep neural network for facies segmentation (DNFS)




EXPERIMENTAL RESULTS

- Composite loss function coefficient (η) chosen value: 0.5



0.5 * CrossEntropy + 0.5 * JaccardLoss

- Examples of predictions with factors (Ω) 8 and 64



- DNFS has high accuracy than StNet and U-Net, and it was trained in about 15 minutes
- DNFS (with factor 8) has approximately 0.3 million parameters and occupies 3 megabytes on disk