

Московский Авиационный Институт  
(Национальный исследовательский Университет)

Факультет: «Информационные технологии и прикладная математика»  
Кафедра: 806 «Вычислительная математика и программирование»

**Лабораторная работа № 5**  
**по курсу «ООП»**

**Тема:**  
**Основы работы с коллекциями: итераторы.**

Студент:	Козлов А.Д.
Группа:	М80-206Б-18
Преподаватель:	Журавлев А.А.
Вариант:	7
Оценка:	
Дата:	

Москва  
2019

## 1. Код

### stack.hpp:

```
#ifndef CONT_STACK_HPP
#define CONT_STACK_HPP

#include <exception>
#include <memory>

namespace cont {
    template<class T>
    class stack {
    private:
        class stack_node;
        std::shared_ptr<stack_node> head;
        std::shared_ptr<stack_node> tail;
    public:
        class iterator;
        class const_iterator;
        stack();
        stack(const stack&) = delete;
        stack& operator =(const stack&) = delete;

        bool empty() const;
        void push(const T&);
        void pop();
        T& top();
        size_t size() const;

        iterator begin();
        iterator end();
        const_iterator begin() const;
        const_iterator end() const;

        void insert(iterator, const T&);
        void erase(iterator);
    };

    template<typename T>
    struct stack<T>::stack_node {
        stack_node() = default;
        stack_node(T new_value) : value(new_value) {}

        T value;
```

```

        std::shared_ptr<stack_node> next = nullptr;
        std::weak_ptr<stack_node> prev;
    };

    template<typename T>
    stack<T>::stack() {
        head = std::make_shared<stack_node>();
        tail = head;
    }

    template<typename T>
    bool stack<T>::empty() const {
        return head == tail;
    }

    template<typename T>
    void stack<T>::push(const T& value) {
        std::shared_ptr<stack_node> new_elem =
std::make_shared<stack_node>(value);
        if(empty()) {
            head = new_elem;
            head->next = tail;
            tail->prev = head;
        } else {
            new_elem->next = head;
            head->prev = new_elem;
            head = new_elem;
        }
    }

    template<typename T>
    void stack<T>::pop() {
        if(empty()) {
            throw std::out_of_range("Pop from empty stack");
        }
        head = head->next;
    }

    template<typename T>
    T& stack<T>::top() {
        return head->value;
    }

```

```

template<typename T>
size_t stack<T>::size() const {
    size_t size = 0;
    for(auto i : *this) {
        ++size;
    }
    return size;
}

```

```

template<typename T>
typename stack<T>::iterator stack<T>::begin() {
    return iterator(head, this);
}

```

```

template<typename T>
typename stack<T>::iterator stack<T>::end() {
    return iterator(tail, this);
}

```

```

template<typename T>
typename stack<T>::const_iterator stack<T>::begin() const {
    return const_iterator(head, this);
}

```

```

template<typename T>
typename stack<T>::const_iterator stack<T>::end() const {
    return const_iterator(tail, this);
}

```

```

template<typename T>
void stack<T>::insert(iterator it, const T& value) {
    if(it.collection != this) {
        throw std::runtime_error("Iterator does not belong to this collection");
    }
    std::shared_ptr<stack_node> it_ptr = it.node.lock();
    if(!it_ptr) {
        throw std::runtime_error("Iterator is corrupted");
    }
    if(it == begin()) {
        push(value);
        return;
    }
    std::shared_ptr<stack_node> new_elem =
std::make_shared<stack_node>(value);
    if(it == end()) {
        it_ptr->prev.lock()->next = new_elem;
    }
}

```

```

    new_elem->prev = it_ptr->prev;
    new_elem->next = it_ptr;
    it_ptr->prev = new_elem;
} else {
    std::shared_ptr<stack_node> next_ptr = it_ptr->next;
    std::weak_ptr<stack_node> prev_ptr = it_ptr;
    new_elem->next = next_ptr;
    next_ptr->prev = new_elem;
    new_elem->prev = prev_ptr;
    prev_ptr.lock()->next = new_elem;
}
}

template<typename T>
void stack<T>::erase(iterator it) {
    if(it.collection != this) {
        throw std::runtime_error("Iterator does not belong to this collection");
    }
    std::shared_ptr<stack_node> it_ptr = it.node.lock();
    if(!it_ptr) {
        throw std::runtime_error("Iterator is corrupted");
    }
    if(it == end()) {
        throw std::runtime_error("Erase of end iterator");
    }
    if(it == begin()) {
        pop();
    } else {
        std::shared_ptr<stack_node> next_ptr = it_ptr->next;
        std::weak_ptr<stack_node> prev_ptr = it_ptr->prev;
        next_ptr->prev = prev_ptr;
        prev_ptr.lock()->next = next_ptr;
    }
}

```

```

template<typename T>
class stack<T>::iterator {
    friend stack<T>;
public:
    using value_type = T;
    using reference = T&;
    using pointer = T*;
    using difference_type = ptrdiff_t;

```

```

using iterator_category = std::forward_iterator_tag;

iterator(std::shared_ptr<stack_node> init_ptr, const stack<T>* ptr) :
node(init_ptr), collection(ptr) {}
    iterator(const iterator& other) : node(other.node), collection(other.collection)
{}

    iterator& operator =(const iterator&);
    bool operator ==(const iterator&) const;
    bool operator !=(const iterator&) const;
    iterator& operator ++();
    iterator operator ++(int);
    T& operator *() const;
private:
    std::weak_ptr<stack_node> node;
    const stack<T>* collection;
};

template<typename T>
typename stack<T>::iterator& stack<T>::iterator::operator =(const iterator&
other) {
    node = other.node;
    return *this;
}
template<typename T>
bool stack<T>::iterator::operator ==(const iterator& other) const {
    auto lhs = node.lock();
    auto rhs = other.node.lock();
    if (lhs && rhs) {
        return lhs.get() == rhs.get();
    }
    return false;
}
template<typename T>
bool stack<T>::iterator::operator !=(const iterator& other) const {
    return !(*this == other);
}
template<typename T>
typename stack<T>::iterator& stack<T>::iterator::operator ++() {
    std::shared_ptr<stack_node> tmp = node.lock();
    if(tmp) {
        if(tmp->next == nullptr) {
            throw std::out_of_range("Going out of container boundaries");

```

```

        }
        tmp = tmp->next;
        node = tmp;
        return *this;
    } else {
        throw std::runtime_error("Element pointed by this iterator doesnt exist anymore");
    }
}

template<typename T>
typename stack<T>::iterator stack<T>::iterator::operator ++(int) {
    iterator result(*this);
    ++(*this);
    return result;
}

template<typename T>
T& stack<T>::iterator::operator *() const {
    std::shared_ptr<stack_node> tmp = node.lock();
    if(tmp) {
        if(tmp->next == nullptr) {
            throw std::runtime_error("Dereferencing of end iterator");
        }
        return tmp->value;
    } else {
        throw std::runtime_error("Element pointed by this iterator doesnt exist anymore");
    }
}

template<typename T>
class stack<T>::const_iterator {
private:
    std::weak_ptr<stack_node> node;
    const stack<T>* collection;
public:
    using value_type = T;
    using reference = T&;
    using pointer = T*;
    using difference_type = ptrdiff_t;
    using iterator_category = std::forward_iterator_tag;

```

```

    const_iterator(std::shared_ptr<stack_node> init_ptr, const stack<T>* ptr) :
node(init_ptr), collection(ptr) {}
    const_iterator(const const_iterator& other) : node(other.node),
collection(other.collection) {}

    const_iterator& operator =(const const_iterator&);
    bool operator ==(const const_iterator&) const;
    bool operator !=(const const_iterator&) const;
    const_iterator& operator ++();
    const_iterator operator ++(int);
    T& operator *() const;
};

template<typename T>
typename stack<T>::const_iterator& stack<T>::const_iterator::operator =(const
const_iterator& other) {
    node = other.node;
    return *this;
}
template<typename T>
bool stack<T>::const_iterator::operator ==(const const_iterator& other) const {
    auto lhs = node.lock();
    auto rhs = other.node.lock();
    if (lhs && rhs) {
        return lhs.get() == rhs.get();
    }
    return false;
}
template<typename T>
bool stack<T>::const_iterator::operator !=(const const_iterator& other) const {
    return !(*this == other);
}
template<typename T>
typename stack<T>::const_iterator& stack<T>::const_iterator::operator ++() {
    std::shared_ptr<stack_node> tmp = node.lock();
    if(tmp) {
        if(tmp->next == nullptr) {
            throw std::out_of_range("Going out of container boundaries");
        }
        tmp = tmp->next;
        node = tmp;
        return *this;
    } else {

```



```

        throw std::runtime_error("Element pointed by this iterator doesnt exist anymore");
    }
}
template<typename T>
typename stack<T>::const_iterator stack<T>::const_iterator::operator ++(int) {
    const_iterator result(*this);
    ++(*this);
    return result;
}

template<typename T>
T& stack<T>::const_iterator::operator *() const {
    std::shared_ptr<stack_node> tmp = node.lock();
    if(tmp) {
        if(tmp->next == nullptr) {
            throw std::runtime_error("Dereferencing of end iterator");
        }
        return tmp->value;
    } else {
        throw std::runtime_error("Element pointed by this iterator doesnt exist anymore");
    }
}
}

#endif

```

### **point.hpp:**

```

#ifndef T_POINT_HPP
#define T_POINT_HPP

#include <iostream>

template<typename T>
struct point {
    T x;
    T y;
    point<T> operator +(point<T>&);
    point<T> operator -(point<T>&);
};

template<typename T>

```

```

point<T> point<T>::operator +(point<T>& other) {
    return {x + other.x, y + other.y};
}

template<typename T>
point<T> point<T>::operator -(point<T>& other) {
    return {x - other.x, y - other.y};
}

template<typename T>
std::ostream& operator <<(std::ostream& os, const point<T>& p) {
    os << p.x << " " << p.y;
    return os;
}

template<typename T>
std::istream& operator >>(std::istream& is, point<T>& p) {
    is >> p.x >> p.y;
    return is;
}

#endif

```

### **hexagon.hpp:**

```

#ifndef T_HEXAGON_HPP
#define T_HEXAGON_HPP

#include <iostream>
#include <exception>

#include "point.hpp"

template<typename T>
class hexagon {
public:
    hexagon() = default;
    hexagon(point<T>&, point<T>&, point<T>&, point<T>&, point<T>&,
point<T>&);
    point<double> center() const;
    double area() const;
    void write(std::ostream&) const;
    void read(std::istream&);
private:

```

```
    point<T> p1, p2, p3, p4, p5, p6;
};
```

```
template<typename T>
hexagon<T>::hexagon(point<T>& p1_, point<T>& p2_, point<T>& p3_,
    point<T>& p4_, point<T>& p5_, point<T>& p6_)
    : p1(p1_), p2(p2_), p3(p3_), p4(p4_), p5(p5_), p6(p6_) {};
```

```
template<typename T>
point<double> hexagon<T>::center() const {
    point<double> res;
    res.x = double(p1.x + p2.x + p3.x + p4.x + p5.x + p6.x) / 6;
    res.y = double(p1.y + p2.y + p3.y + p4.y + p5.y + p6.y) / 6;
    return res;
}
```

```
template<typename T>
double hexagon<T>::area() const {
    double A = (p1.x * p2.y + p2.x * p3.y + p3.x * p4.y + p4.x * p5.y + p5.x * p6.y
        + p6.x * p1.y)
        - (p2.x * p1.y + p3.x * p2.y + p4.x * p3.y + p5.x * p4.y + p6.x * p5.y) - (p1.x
        * p6.y);
    return A >= 0 ? (A * 0.5) : (-A * 0.5);
}
```

```
template<typename T>
void hexagon<T>::write(std::ostream& os) const {
    os << "Hexagon p1: " << p1 << ", p2: " << p2 << ", p3: " << p3 << ", p4: " << p4
    << ", p5: " << p5 << ", p6: " << p6;
}
```

```
template<typename T>
void hexagon<T>::read(std::istream& is) {
    point<T> p1_, p2_, p3_, p4_, p5_, p6_;
    is >> p1_ >> p2_ >> p3_ >> p4_ >> p5_ >> p6_;
    *this = hexagon(p1_, p2_, p3_, p4_, p5_, p6_);
}
```

```
template<typename T>
std::ostream& operator <<(std::ostream& os, const hexagon<T>& hex) {
    hex.write(os);
    return os;
}
```

```

template<typename T>
std::istream& operator >>(std::istream& is, hexagon<T>& hex) {
    hex.read(is);
    return is;
}

```

```

#endif

```

### **main.cpp:**

```

#include <iostream>
#include <string>
#include <algorithm>

```

```

#include "../include/hexagon.hpp"
#include "../include/stack.hpp"

```

```

int main() {
    std::string command;
    cont::stack<hexagon<int>> figures;
    while(std::cin >> command) {
        if (command == "menu") {
            std::cout << "1) add\n";
            std::cout << "2) erase\n";
            std::cout << "3) size\n";
            std::cout << "4) print\n";
            std::cout << "5) count\n";
            std::cout << "6) exit\n";
        } else if (command == "help") {
            std::cout << "1) add - add a figure by index\n \t example: add 0 1 1 1 1 1 1
1 1 1 1 1 1\n It means: add hexagon {{1,1}, {1,1}, {1,1}, {1,1}, {1,1}, {1,1}} to
position 0\n";
            std::cout << "2) erase - erase a figure by index\n\n\t example: erase 0\n It
means: erase shape from position 0\n";
            std::cout << "3) size - print size of stack\n";
            std::cout << "4) print - print all shapes in a stack and their area\n";
            std::cout << "5) count - print the number of figures with a given area\n";
        } else if (command == "add") {
            size_t position;
            std::cin >> position;
            auto it = figures.begin();
            try {
                it = std::next(it, position);
            }
        }
    }
}

```

```

    } catch(std::exception& ex) {
        std::cout << "Position is too big\n";
        continue;
    }
    hexagon<int> new_figure;
    try {
        std::cin >> new_figure;
    } catch(std::exception& ex) {
        std::cout << ex.what() << "\n";
    }
    figures.insert(it, new_figure);
    std::cout << new_figure << "\n";
} else if (command == "erase") {
    size_t index;
    std::cin >> index;
    auto it = figures.begin();
    try {
        it = std::next(it, index);
        figures.erase(it);
    } catch(...) {
        std::cout << "Index is too big\n";
        continue;
    }
} else if (command == "size") {
    std::cout << figures.size() << "\n";
} else if (command == "print") {
    std::for_each(figures.begin(), figures.end(), [](const hexagon<int>& fig) {
        std::cout << fig << "\n";
        std::cout << "Center: " << fig.center() << "\n";
        std::cout << "Area: " << fig.area() << "\n";
    });
} else if (command == "count") {
    size_t required_area;
    std::cin >> required_area;
    std::cout << std::count_if(figures.begin(), figures.end(), [&required_area]
(const hexagon<int>& fig) {
        return fig.area() < required_area;
    });
    std::cout << "\n";
} else if (command == "exit") {
    break;
} else {
    std::cout << "Incorrect command\n";
}

```

```

        std::cin.ignore(32767, '\n');
    }
}
return 0;
}

```

### **CmakeLists.txt:**

```

cmake_minimum_required(VERSION 3.0)
project(oop_exercise_05)

```

```

set(CMAKE_CXX_STANDARD 17)

```

```

set(MAIN ./source/main.cpp)

```

```

add_executable(oop_exercise_05 ${MAIN})

```

## **2. Ссылка на репозиторий на GitHub.**

[https://github.com/ArtemKD/oop\\_exercise\\_05](https://github.com/ArtemKD/oop_exercise_05)

## **3. Набор testcases.**

### **test\_01.txt:**

```

add 0
0 0 0 0 0 0 0 0 0 0 0
add 1
1 1 1 1 1 1 1 1 1 1 1
add 0
2 2 2 2 2 2 2 2 2 2 2
print
size
erase
1
print

```

### **test\_02.txt:**

```

add 0
0 0 0 0 0 0 0 0 0 0 0
add 1
1 1 1 1 1 1 1 1 1 1 1
add 2
2 2 2 2 2 2 2 2 2 2 2
add 3
3 3 3 3 3 3 3 3 3 3 3
add 4

```

4 4 4 4 4 4 4 4 4 4 4 4  
add 2  
5 5 5 5 5 5 5 5 5 5 5 5  
print  
size  
erase 3  
print

#### **4. Результаты выполнения тестов.**

##### **test\_01.txt:**

Hexagon p1: 0 0, p2: 0 0, p3: 0 0, p4: 0 0, p5: 0 0, p6: 0 0  
Hexagon p1: 1 1, p2: 1 1, p3: 1 1, p4: 1 1, p5: 1 1, p6: 1 1  
Hexagon p1: 2 2, p2: 2 2, p3: 2 2, p4: 2 2, p5: 2 2, p6: 2 2  
Hexagon p1: 2 2, p2: 2 2, p3: 2 2, p4: 2 2, p5: 2 2, p6: 2 2  
Center: 2 2  
Area: 0  
Hexagon p1: 0 0, p2: 0 0, p3: 0 0, p4: 0 0, p5: 0 0, p6: 0 0  
Center: 0 0  
Area: 0  
Hexagon p1: 1 1, p2: 1 1, p3: 1 1, p4: 1 1, p5: 1 1, p6: 1 1  
Center: 1 1  
Area: 0  
3  
Hexagon p1: 2 2, p2: 2 2, p3: 2 2, p4: 2 2, p5: 2 2, p6: 2 2  
Center: 2 2  
Area: 0  
Hexagon p1: 1 1, p2: 1 1, p3: 1 1, p4: 1 1, p5: 1 1, p6: 1 1  
Center: 1 1  
Area: 0

##### **test\_02.txt:**

Hexagon p1: 0 0, p2: 0 0, p3: 0 0, p4: 0 0, p5: 0 0, p6: 0 0  
Hexagon p1: 1 1, p2: 1 1, p3: 1 1, p4: 1 1, p5: 1 1, p6: 1 1  
Hexagon p1: 2 2, p2: 2 2, p3: 2 2, p4: 2 2, p5: 2 2, p6: 2 2  
Hexagon p1: 3 3, p2: 3 3, p3: 3 3, p4: 3 3, p5: 3 3, p6: 3 3  
Hexagon p1: 4 4, p2: 4 4, p3: 4 4, p4: 4 4, p5: 4 4, p6: 4 4  
Hexagon p1: 5 5, p2: 5 5, p3: 5 5, p4: 5 5, p5: 5 5, p6: 5 5  
Hexagon p1: 0 0, p2: 0 0, p3: 0 0, p4: 0 0, p5: 0 0, p6: 0 0  
Center: 0 0  
Area: 0  
Hexagon p1: 1 1, p2: 1 1, p3: 1 1, p4: 1 1, p5: 1 1, p6: 1 1  
Center: 1 1  
Area: 0

Hexagon p1: 2 2, p2: 2 2, p3: 2 2, p4: 2 2, p5: 2 2, p6: 2 2

Center: 2 2

Area: 0

Hexagon p1: 5 5, p2: 5 5, p3: 5 5, p4: 5 5, p5: 5 5, p6: 5 5

Center: 5 5

Area: 0

Hexagon p1: 3 3, p2: 3 3, p3: 3 3, p4: 3 3, p5: 3 3, p6: 3 3

Center: 3 3

Area: 0

Hexagon p1: 4 4, p2: 4 4, p3: 4 4, p4: 4 4, p5: 4 4, p6: 4 4

Center: 4 4

Area: 0

6

Hexagon p1: 0 0, p2: 0 0, p3: 0 0, p4: 0 0, p5: 0 0, p6: 0 0

Center: 0 0

Area: 0

Hexagon p1: 1 1, p2: 1 1, p3: 1 1, p4: 1 1, p5: 1 1, p6: 1 1

Center: 1 1

Area: 0

Hexagon p1: 2 2, p2: 2 2, p3: 2 2, p4: 2 2, p5: 2 2, p6: 2 2

Center: 2 2

Area: 0

Hexagon p1: 3 3, p2: 3 3, p3: 3 3, p4: 3 3, p5: 3 3, p6: 3 3

Center: 3 3

Area: 0

Hexagon p1: 4 4, p2: 4 4, p3: 4 4, p4: 4 4, p5: 4 4, p6: 4 4

Center: 4 4

Area: 0

## **5. Объяснение результатов работы программы.**

В программе реализовано меню с пунктами:

- 1) add - добавление элемента в стек фигур по индексу
- 2) erase - удаление фигуры по идексу
- 3) size - размер стека
- 4) print - вывод всех фигур стека, середины и площади
- 5) count - вывод кол-ва фигур с заданной площадью, которые лежат в стеке

## **6. Вывод.**

Выполняя данную лабораторную я получил опыт работы коллекциями и итераторами. Создал шаблонный класс stack, hexagon, point.



Реализовал сохранение введенных фигур в стек по индексу, удаление по индексу вывод фигур и их площадей. Также реализовал подсчет кол-ва фигур с заданной площадью.