

Practical-10

AIM: Orchestration of ML project containers using Kubernetes

The objective of this lab is to introduce you to the fundamentals of orchestrating applications with Kubernetes. You will learn how to define, deploy, and manage containerized applications using Kubernetes manifests.

Lab Steps:

Step 1: Verify Kubernetes Cluster Ensure your Kubernetes cluster is up and running by checking the cluster nodes

```
PS D:\Desktop\stream> kubectl get nodes
```

NAME	STATUS	ROLES	AGE	VERSION
docker-desktop	Ready	control-plane	22m	v1.27.2

Step 2: Define a Deployment using YAML manifest and apply the deployment to your cluster

```
deployment.yml
1 # deployment.yaml
2 apiVersion: apps/v1
3 kind: Deployment
4 metadata:
5   name: ml-deployment
6 spec:
7   replicas: 3
8   selector:
9     matchLabels:
10      app: ml-app
11   template:
12     metadata:
13       labels:
14         app: ml-app
15     spec:
16       containers:
17       - name: ml-container
18         image: your-ml-image:tag
19         ports:
20         - containerPort: 8080
```

Apply the deployment :

```
PS D:\Desktop\stream> kubectl apply -f deployment.yaml
deployment.apps/ml-deployment created
```

Step 3: Describe Deployment

```

PS D:\Desktop\stream> kubectl describe deployment ml-deployment
Name:                ml-deployment
Namespace:            default
CreationTimestamp:    Thu, 23 Nov 2023 18:58:29 +0530
Labels:               <none>
Annotations:          deployment.kubernetes.io/revision: 1
Selector:             app=ml-app
Replicas:             3 desired | 3 updated | 3 total | 0 available | 3 unavailable
StrategyType:         RollingUpdate
MinReadySeconds:      0
RollingUpdateStrategy: 25% max unavailable, 25% max surge
Pod Template:
  Labels:  app=ml-app
  Containers:
    ml-container:
      Image:        your-ml-image:tag
      Port:         8080/TCP
      Host Port:    0/TCP
      Environment:  <none>
      Mounts:       <none>
      Volumes:      <none>
  Conditions:
    Type           Status  Reason
    ----           -
    Available       False   MinimumReplicasUnavailable
    Progressing     True    ReplicaSetUpdated
OldReplicaSets:    <none>
NewReplicaSet:     ml-deployment-5fcc5656fc (3/3 replicas created)
Events:
  Type     Reason          Age   From                  Message
  ----     -
  Normal   ScalingReplicaSet   24s   deployment-controller  Scaled up replica set ml-deployment-5fcc5656fc to 3

```

Step 4 : Expose Service

```

# service.yaml
1  # service.yaml
2  apiVersion: v1
3  kind: Service
4  metadata:
5  |   name: ml-service
6  spec:
7  |   selector:
8  |   |   app: ml-app
9  |   ports:
10 |   |   - protocol: TCP
11 |   |     port: 80
12 |   |     targetPort: 8080
13 |   type: LoadBalancer

```

Step 5: Access the Service

```

PS D:\Desktop\stream> kubectl apply -f service.yaml
service/ml-service created

```

Step 6: Scale Deployment

```
PS D:\Desktop\stream> kubectl scale deployment ml-deployment --replicas=5  
deployment.apps/ml-deployment scaled
```

Step 7: Update Deployment

```
deployment-updated.yaml  
1 # deployment-update.yaml  
2 apiVersion: apps/v1  
3 kind: Deployment  
4 metadata:  
5   name: ml-deployment  
6 spec:  
7   replicas: 3  
8   selector:  
9     matchLabels:  
10    app: ml-app  
11   template:  
12     metadata:  
13       labels:  
14         app: ml-app  
15     spec:  
16       containers:  
17       - name: ml-container  
18         image: your-updated-ml-image:tag  
19       ports:  
20       - containerPort: 8080  
21
```

Step 8: Rollout Status

```
PS D:\Desktop\stream> kubectl rollout status deployment ml-deployment  
Waiting for deployment "ml-deployment" rollout to finish: 1 out of 3 new replicas have been updated...
```

Step 9: Rollback Deployment

```
PS D:\Desktop\stream> kubectl rollout undo deployment ml-deployment  
deployment.apps/ml-deployment rolled back
```

Step 10: Delete Resources

```
PS D:\Desktop\stream> kubectl delete deployment ml-deployment  
deployment.apps "ml-deployment" deleted  
PS D:\Desktop\stream> kubectl delete service ml-service  
service "ml-service" deleted
```