PART REV. PART NEMA 4X ENCLOSURE PN-1323, PN-1323-C AND PN-1323-DG 11-17-08 DATE NAME No. INDUSTRY STANDARDS: POLYCARBONATE (LIGHT GRAY AND CLEAR) UL94-HB FLAMMABILITY RATING (UL FILE #E41613) UV STABILIZED **◄** 0.115 SERVICE TEMPERATURE RANGE: -40°C TD +120°C SILICONE GASKET (CLFAR) ABS (DARK GRAY) UL94-HB FLAMMABILITY RATING (UL FILE #E56070) SERVICE TEMPERATURE RANGE: -40°C TO +80°C 0.310 DIA. 0.080 -0.172 DIA. C'BORE 0.120 -DETAIL "C" 0.234 - 3.076 -0.434 --— 3<mark>.</mark>543 – – 2.676 *–*  $M4 \times 0.315 LG$ 1.640 **←** 2,165 **←** 0.588 ---2.367 **--**- 3.076 **-** 0.234 THREADED INSERT - 0.297 0.591 REF. -- 0.236 0.181 (4) PLACES 0.236 - 0.172 DIA. -- 0.591 1.150 0.090 -0.120 3,181 -0.181 -3.031 4.056 3.546 4.528 4.056 4.528 4.166 **→** 0.120 - 0.088 1.150 3.307 -0.118 TYP. — 2,264 - 0.313 DIA. 0.749 0.050 0.491 1.177 — SEE DETAIL "C" 0.178 TYP. -1.184 1.190 0.315 DIA. BOSS SECTION "B-B" SECTION "A-A" WITH M3  $\times$  0.188 LG. 0.844 --COVER THREADED INSERT 1.855 (4) PLACES 3,543 (SCREWS NOT SUPPLIED) NOTE: ALL DIMENSIONS HAVE ±0.015 TOLERANCE UNLESS OTHERWISE SPECIFIED.  $B\square DY$ MATERIAL FINISH PART NUMBER HARDWARE KIT COVER BODY COVER  $B\square DY$ POLYCARBONATE LIGHT GRAY PN-1323 KIT CONTAINS (4) PN-1323-C POLYCARBONATE LIGHT GRAY CLEAR  $M4 \times 20mm (0.787'') LG.$ 

PN-1323-DG

HIGH-IMPACT ABS

DARK GRAY

SCREWS FOR ASSEMBLY