


# Generative adversarial neural networks for state-of-the-art image reconstruction.

Arthur Conmy and Dr Subhadip Mukherjee. *The following face does not exist: it was generated as the 'average' face from a pre-trained GAN. You can view your own synthetic faces (that no one will have seen before) at [thispersondoesnotexist.com](http://thispersondoesnotexist.com), and reload the page to generate a different face.*



# Plan

## 1 Background context: machine learning for mathmos.

- Neural nets.
- Generative modelling.
- GANs.

## 2 Our work.

- Image reconstruction.
- Our contribution.

# Plan

## 1 Background context: machine learning for mathmos.

- Neural nets.
- Generative modelling.
- GANs.

## 2 Our work.

- Image reconstruction.
- Our contribution.

# Neural networks

For the purposes of this talk, it will be useful to think of neural networks as black-boxes that are very good at representing high-dimensional functions that lie in very large function classes.

- Dog / cat classifier:

$$f : [0, 1]^{H \times W \times C} \rightarrow \{\text{Dog, Cat}\} \quad (1)$$

# Neural networks

For the purposes of this talk, it will be useful to think of neural networks as black-boxes that are very good at representing high-dimensional functions that lie in very large function classes.

- Dog / cat classifier:

$$f : [0, 1]^{H \times W \times C} \rightarrow \{\text{Dog, Cat}\} \quad (1)$$

- More exciting example to come:

$$\mathcal{F} = \{f : f : [0, 1]^{H \times W \times C} \rightarrow \mathbb{R}, f \in \text{Lip}(1)\} \quad (2)$$

# Generative modelling.

- Consider a *fixed, but unknown* probability density function  $p_d : \mathbb{R}^n \rightarrow \mathbb{R}$ , of which we have access to a large number of i.i.d samples from:  $x_1, x_2, \dots, x_N \sim p_d$ .

# Generative modelling.

- Consider a *fixed, but unknown* probability density function  $p_d : \mathbb{R}^n \rightarrow \mathbb{R}$ , of which we have access to a large number of i.i.d samples from:  $x_1, x_2, \dots, x_N \sim p_d$ .
- Open-ended problem: how can we generate samples  $x'_1, x'_2, \dots$  that are similar to the samples  $x_1, x_2, \dots, x_N$ ?

# Generative modelling.

- Consider a *fixed, but unknown* probability density function  $p_d : \mathbb{R}^n \rightarrow \mathbb{R}$ , of which we have access to a large number of i.i.d samples from:  $x_1, x_2, \dots, x_N \sim p_d$ .
- Open-ended problem: how can we generate samples  $x'_1, x'_2, \dots$  that are similar to the samples  $x_1, x_2, \dots, x_N$ ?
  - We assume that we derive such samples from some generated distribution  $p_g$ , but we are only required to have samples from  $p_g$ .


# Generative modelling.

- Consider a *fixed, but unknown* probability density function  $p_d : \mathbb{R}^n \rightarrow \mathbb{R}$ , of which we have access to a large number of i.i.d samples from:  $x_1, x_2, \dots, x_N \sim p_d$ .
- Open-ended problem: how can we generate samples  $x'_1, x'_2, \dots$  that are similar to the samples  $x_1, x_2, \dots, x_N$ ?
  - We assume that we derive such samples from some generated distribution  $p_g$ , but we are only required to have samples from  $p_g$ .
- Big question: what does ‘similar’ mean?

# Taxonomy

From Goodfellow's 2016 NIPS GANs tutorial:

## Taxonomy of Generative Models



(Goodfellow 2016)

# GANs, part one.

**By analogy**

- The gang have a generator of fake money.

**By formalism**

# GANs, part one.

## By analogy

- The gang have a generator of fake money.

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$

# GANs, part one.

## By analogy

- The gang have a generator of fake money.
- The police have a discriminator that (imperfectly) distinguishes fake from real money.

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$

# GANs, part one.

## By analogy

- The gang have a generator of fake money.
- The police have a discriminator that (imperfectly) distinguishes fake from real money.

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$
- $D : \mathcal{X} \rightarrow (0, 1)$   
representing the probability an image is real.

# GANs, part one.

## By analogy

- The gang have a generator of fake money.
- The police have a discriminator that (imperfectly) distinguishes fake from real money.
- Have the gang try and outwit the police, while the police try and uncover the gang.

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$
- $D : \mathcal{X} \rightarrow (0, 1)$  representing the probability an image is real.

# GANs, part one.

## By analogy

- The gang have a generator of fake money.
- The police have a discriminator that (imperfectly) distinguishes fake from real money.
- Have the gang try and outwit the police, while the police try and uncover the gang.

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$
- $D : \mathcal{X} \rightarrow (0, 1)$  representing the probability an image is real.
- Jointly optimize  $G$  (to maximise the probability  $D$  misclassifies generated images), and  $D$  (to minimise the probability it misclassifies images).

## By analogy

- The gang have a generator of fake money.
- The police have a discriminator that (imperfectly) distinguishes fake from real money.
- Have the gang try and outwit the police, while the police try and uncover the gang.
- Given some loss function penalising  $G$  and  $D$ , we're already in the setting to apply back-prop, but sadly this is a FAR more delicate procedure than suggested.

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$
- $D : \mathcal{X} \rightarrow (0, 1)$  representing the probability an image is real.
- Jointly optimize  $G$  (to maximise the probability  $D$  misclassifies generated images), and  $D$  (to minimise the probability it misclassifies images).

## By analogy

- The gang have a generator of fake money.
- The police have a discriminator that (imperfectly) distinguishes fake from real money.
- Have the gang try and outwit the police, while the police try and uncover the gang.
- Given some loss function penalising  $G$  and  $D$ , we're already in the setting to apply back-prop, but sadly this is a FAR more delicate procedure than suggested.

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$
- $D : \mathcal{X} \rightarrow (0, 1)$  representing the probability an image is real.
- Jointly optimize  $G$  (to maximise the probability  $D$  misclassifies generated images), and  $D$  (to minimise the probability it misclassifies images).

## By analogy

- The gang have a generator of fake money.
- The police have a discriminator that (imperfectly) distinguishes fake from real money.
- Have the gang try and outwit the police, while the police try and uncover the gang.
- Given some loss function penalising  $G$  and  $D$ , we're already in the setting to apply back-prop, but sadly this is a FAR more delicate procedure than suggested.

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$
- $D : \mathcal{X} \rightarrow (0, 1)$  representing the probability an image is real.
- Jointly optimize  $G$  (to maximise the probability  $D$  misclassifies generated images), and  $D$  (to minimise the probability it misclassifies images).

## By analogy

- The gang have a generator of fake money.
- The police have a discriminator that (imperfectly) distinguishes fake from real money.
- Have the gang try and outwit the police, while the police try and uncover the gang.
- Given some loss function penalising  $G$  and  $D$ , we're already in the setting to apply back-prop, but sadly this is a FAR more delicate procedure than suggested.
- HOWEVER, significant advances have been made to GAN theory since this initial work, citing Cedric Villani's optimal transport theory to redesign the loss function between the distributions!

## By formalism

- $G : \mathbb{R}^m \rightarrow \mathcal{X}$
- $D : \mathcal{X} \rightarrow (0, 1)$  representing the probability an image is real.
- Jointly optimize  $G$  (to maximise the probability  $D$  misclassifies generated images), and  $D$  (to minimise the probability it misclassifies images).

## GANs, part two


The most natural way to choose a loss function is the analogue of cross entropy loss in this case:

$$V(D, G) = \mathbb{E}_{p_d}[\log D(x)] + \mathbb{E}_{z \sim \mathcal{N}}[\log(1 - D(G(z)))]$$


A much better choice of loss function between distributions is the Wasserstein distance:

$$\text{EMD}(p_d, p_g) = \sup_{\|f\|_{L \leq 1}} \mathbb{E}_{x \sim p_d} f(x) - \mathbb{E}_{x \sim p_g} f(x).$$

# GANs, part three.



(a) Traditional



(b) Style-based generator

# Plan

## 1 Background context: machine learning for mathmos.

- Neural nets.
- Generative modelling.
- GANs.

## 2 Our work.

- Image reconstruction.
- Our contribution.

# Inverse problems

- Inverse problems are ill-posed problems where  $y = A(x)$ , and we need reconstruct  $x$  given  $y$ .

# Inverse problems

- Inverse problems are ill-posed problems where  $y = A(x)$ , and we need reconstruct  $x$  given  $y$ .
- Non-uniqueness of solutions means that it turns out to be important to solve

$$\hat{x} \in \operatorname{argmin}_x L(y, A(x)) + \lambda \psi(x) \quad (3)$$

where  $L$  is the loss of the reconstruction, and  $\psi$  a *regularizer*.

# Inverse problems

- Inverse problems are ill-posed problems where  $y = A(x)$ , and we need reconstruct  $x$  given  $y$ .
- Non-uniqueness of solutions means that it turns out to be important to solve


$$\hat{x} \in \operatorname{argmin}_x L(y, A(x)) + \lambda \psi(x) \quad (3)$$

where  $L$  is the loss of the reconstruction, and  $\psi$  a *regularizer*.

Ground truth



Masked



No regularization



BRGM



L-BRGM



# Our contribution.

- The previous SOTA for image reconstruction (where reconstruction could mean from down-sampling to lower resolution, masking parts of the image, or blurring (the last not considered in our work)) was *BRGM*:

# Our contribution.

- The previous SOTA for image reconstruction (where reconstruction could mean from down-sampling to lower resolution, masking parts of the image, or blurring (the last not considered in our work)) was *BRGM*:

$$w^* = \arg \min_w \underbrace{\sum_i \left( \frac{w_i - \mu}{\sigma_i} \right)^2}_{\mathcal{L}_w} - 2\kappa \underbrace{\sum_{i,j} \frac{w_i w_j^T}{|w_i||w_j|}}_{\mathcal{L}_{colin}} + \sigma_{pixel}^{-2} \underbrace{\|I - f \circ G(w)\|_2^2}_{\mathcal{L}_{pixel}} + \sigma_{percept}^{-2} \underbrace{\|I - \phi \circ f \circ G(w)\|_2^2}_{\mathcal{L}_{percept}}$$

•

(6)

# Our contribution.

- The previous SOTA for image reconstruction (where reconstruction could mean from down-sampling to lower resolution, masking parts of the image, or blurring (the last not considered in our work)) was *BRGM*:

$$w^* = \arg \min_w \underbrace{\sum_i \left( \frac{w_i - \mu}{\sigma_i} \right)^2}_{\mathcal{L}_w} - 2\kappa \underbrace{\sum_{i,j} \frac{w_i w_j^T}{|w_i||w_j|}}_{\mathcal{L}_{colin}} + \sigma_{pixel}^{-2} \underbrace{\|I - f \circ G(w)\|_2^2}_{\mathcal{L}_{pixel}} + \sigma_{percept}^{-2} \underbrace{\|I - \phi \circ f \circ G(w)\|_2^2}_{\mathcal{L}_{percept}}$$

- We used a new ‘guided’ approach to the optimization over the two latent spaces.

# Our contribution.

- The previous SOTA for image reconstruction (where reconstruction could mean from down-sampling to lower resolution, masking parts of the image, or blurring (the last not considered in our work)) was *BRGM*:


$$w^* = \arg \min_w \underbrace{\sum_i \left( \frac{w_i - \mu}{\sigma_i} \right)^2}_{\mathcal{L}_w} - 2\kappa \underbrace{\sum_{i,j} \frac{w_i w_j^T}{|w_i||w_j|}}_{\mathcal{L}_{colin}} + \sigma_{pixel}^{-2} \underbrace{\|I - f \circ G(w)\|_2^2}_{\mathcal{L}_{pixel}} + \sigma_{percept}^{-2} \underbrace{\|I - \phi \circ f \circ G(w)\|_2^2}_{\mathcal{L}_{percept}}$$

- We used a new ‘guided’ approach to the optimization over the two latent spaces.

The resulting optimization reads  $\min_{(z, w^+)} J(w^+, z)$ , where

$$\begin{aligned} J(w^+, z) := & \lambda_{pix} \|y - A G(w^+)\|_2^2 + \lambda_{map} \sum_{i=1}^L \|w_i - M(z)\|_2^2 \\ & + \lambda_{vgg} \|\varphi(y) - \varphi(A G(w^+))\|_2^2 + \lambda_{lat} \|z\|_2^2. \end{aligned} \quad (5)$$

# Results



We changed the regularization term used to reconstruct images, and obtained strong results.

Inpainting <sup>20</sup>	Input	Mask	Model	LPIPS				SSIM		
				1	0.303	2	0.303	59	0.625	
256 <sup>2</sup>	Half		DeepGIN	1	0.303	2	0.303	59	0.625	
			BRGM	47	0.226	57	<b>0.231</b>	21	0.606	
			L-BRGM	<b>51</b>	<b>0.224</b>	40	0.240	19	0.594	
1024 <sup>2</sup>	Half		BRGM	17	0.495					
			L-BRGM	<b>82</b>	<b>0.460</b>					
		Eyepatch	BRGM	10	0.428					
			L-BRGM	<b>89</b>	<b>0.393</b>					
Super-resolution	Input	Output	Model	LPIPS				SSIM		
				GFPGAN	<b>72</b>	<b>0.231</b>	<b>77</b>	<b>0.231</b>	89	0.534
				BRGM	6	0.294	9	0.295	10	0.480
	64 <sup>2</sup>	256 <sup>2</sup>	BRGM	21	0.277	13	0.294	0	0.404	
			L-BRGM	<b>67</b>	<b>0.414</b>					
	32 <sup>2</sup>	1024 <sup>2</sup>	BRGM	32	0.426					
			L-BRGM	<b>66</b>	<b>0.445</b>					

**Table 1.** Quantitative evaluation of L-BRGM, BRGM, DeepGIN and GFPGAN. The two columns marked with an asterisk refer to minimal *final* values of those metrics, i.e on the 2000<sup>th</sup> optimization step for (L-)BRGM.