

Trees and Graphs Interview Questions

[Add Question \(/add\)](#)

CareerCup is the world's biggest and best source for software engineering interview preparation. See all our resources (</resources>).

Open Chat in New Window (<http://tlk.io/careercup>)

Page:

[1 2 \(https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=2\)](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=2)
[3](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=3)
[4](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=4)
[5](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=5)
[6](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=6)
[7](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=7)
[8](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=8)
[9](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=9)
[10](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=10)
[11](https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=11)

Filter: (None) (None) Trees and Graphs Go Clear

Sort By:

[Date | Number of Comments \(?pid=trees-and-graphs-interview-questions&sort=comments\)](#) |
 [Most Recent Comment \(?pid=trees-and-graphs-interview-questions&sort=recentcomments\)](#) |
 [Votes \(?pid=trees-and-graphs-interview-questions&sort=votes\)](#)



0 of 0 votes

Given a root to a binary tree, find the level of the tree with the minimum sum.

for example:

50
 /\n
 6 2
 /\n
 30 80 7

the answer is: level 2

[\(/question?id=5633825693499392\)](https://www.careercup.com/question?id=5633825693499392) - [Ladym \(/user?id=6204128637222912\)](https://www.careercup.com/user?id=6204128637222912) [October 10, 2017 \(2017-10-10T10:43:02.207200Z\)](#) in [Israel](#) | [Report Duplicate \(/reportduplicate?id=5633825693499392\)](#) | [Flag \(/flagquestion?id=5633825693499392\)](#)

3

Answers
 (/question?id=5633825693499392)



1 of 1 vote

A binary tree is started burning from a leaf node. What is the time(1ms to burn from node to node) it takes to entire tree get burned? The fire will spread to all the paths from a node.

[\(/question?id=5756760659853312\)](https://www.careercup.com/question?id=5756760659853312) - [SIVA R \(/user?id=5714514479677440\)](https://www.careercup.com/user?id=5714514479677440) [August 20, 2017 \(2017-08-20T07:47:40.849880Z\)](#) in [United States](#) | [Report Duplicate \(/reportduplicate?id=5756760659853312\)](#) | [Flag \(/flagquestion?id=5756760659853312\)](#)

4

Answers
 (/question?id=5756760659853312)



0 of 0 votes

Given a binary tree, write a recursive method boolean method(int x, int y) which will return true

1. if node y (meaning a node with a value of int y) is a node that is contained in one of the two possible subtrees of x,
 2. true if x==y, and a node with a value x==y exists, otherwise
 3. return false,
- basically whether x contains y? I had a question like this on my exam, I solved this problem using four arguments in my function. I wonder whether it is even possible to solve it with only 2 int arguments and recursively.

5

Answers
 (/question?id=568587304)

[How Can You Help CareerCup? \(/helpcareercup\)](#)

[Find Out When Gayle / CareerCup / Cracking the Coding Interview is in Your City \(https://careercup.wufoo.com/forms/cracking-the-interview-talk-notifier/\)](#)

Top Companies

[Amazon \(4480\) \(/page?pid=amazon-interview-questions\)](#)

[Microsoft \(2034\) \(/page?pid=microsoft-interview-questions\)](#)

[Google \(1369\) \(/page?pid=google-interview-questions\)](#)


[Bloomberg LP \(676\) \(/page?pid=bloomberg-lp-interview-questions\)](#)

(/question?id=5685873063493632) - bojanlozanovski77 (/user?id=5745852114010112) August 16, 2017 (2017-08-16T14:41:41.901590Z) in United States | Report Duplicate (/reportduplicate?id=5685873063493632) | Flag (/flagquestion?id=5685873063493632)



Given a list/array of "Assign" trees with integers, operators and variables, return the result of the requested "Result" tree expression.

Example:



(/question?id=5644714492559360) - thetinysheep (/user?id=4655025178542080) August 13, 2017 (2017-08-13T20:48:18.645240Z) in United States | Report Duplicate (/reportduplicate?id=5644714492559360) | Flag (/flagquestion?id=5644714492559360)



I've got these trees of integers; they're like regular trees, but they can share nodes.

I need to know if any branch of this tree sums to 100.

```
7
/\
8 6
/\ \
2 3 9
/\ \ \
5 4 1 100
```

Follow up question was how would you change the code to handle negative numbers.

(/question?id=5769269718548480) - NinjaCoder (/user?id=575567922772928) July 20, 2017 (2017-07-20T02:34:19.855590Z) in United States | Report Duplicate (/reportduplicate?id=5769269718548480) | Flag (/flagquestion?id=5769269718548480)



Find distance between any two nodes of binary tree and binary search tree.

(/question?id=5656126992416768) - Raje (/user?id=4810838773858304) July 19, 2017 (2017-07-19T18:40:12.989580Z) in India | Report Duplicate (/reportduplicate?id=5656126992416768) | Flag (/flagquestion?id=5656126992416768)



Given a binary tree of integers, write code to store the tree into a list of integers and recreate the original tree from a list of integers.

Here's what your method signatures should look like (in Java):

```
List<Integer> store(Node root)
Node restore(List<Integer> list)
```

Example Tree:

```
5
/\
3 2
/\ \
1 6 1
```

6

Answers
(/question?id=5644714492559360)

Facebook (563) (/page?pid=facebook-interview-questions)

Adobe (459) (/page?pid=adobe-interview-questions)

Yahoo (284) (/page?pid=yahoo-interview-questions)

Goldman Sachs (237) (/page?pid=goldman-sachs-interview-questions)

Epic Systems (217) (/page?pid=epic-systems-interview-questions)

NVIDIA (203) (/page?pid=nvidia-interview-questions)

More Companies »
(/categories)

Top Jobs

Software Engineer / Developer (7988) (/page?pid=software-engineer-developer-interview-questions)

Software Engineer in Test (818) (/page?pid=software-engineer-in-test-interview-questions)

SDE1 (683) (/page?pid=sde1-interview-questions)

SDE-2 (538) (/page?pid=sde-2-interview-questions)

Software Engineer (516) (/page?pid=software-engineer-interview-questions)

Developer Program Engineer (454) (/page?pid=developer-program-engineer-interview-questions)

Software Developer (336) (/page?pid=software-developer-interview-questions)

Financial Software Developer (292) (/page?pid=financial-software-developer-interview-questions)

Intern (257) (/page?pid=intern-interview-questions)

Java Developer (235) (/page?pid=java-developer-interview-questions)

More Jobs » (/categories)

Top Topics

(/question?id=563278333555072) - Null0 (/user?id=5764037536120832) May 13, 2017 (2017-05-13T20:14:02.172160Z) | Report Duplicate (/reportduplicate?id=563278333555072) | Flag (/flagquestion?id=563278333555072)



0
of 0 votes

You are given a NxN boolean matrix, where matrix(i,j) will be one if 'i' is a parent of 'j' in a tree, otherwise, it is zero. Construct this tree.

(/question?id=5181088604356608) - sonesh (/user?id=14962663) May 11, 2017 (2017-05-11T10:57:14.485590Z) in United States | Report Duplicate (/reportduplicate?id=5181088604356608) | Flag (/flagquestion?id=5181088604356608)



0
of 0 votes

You are given an array of nodes where each node consists of node name, isValid flag, and parent Node index. so, this array actually represents a tree(forest). where root node has -1 as its index for the parent node. rest all node have their parent's index value.


You will be given this array and an index. You have to cut down the subtree from the index. Cutting down a tree means, making all the nodes of that subtree false(Isvalid flag). He was expecting O(N) solution.

(/question?id=5931143976189952) - sonesh (/user?id=14962663) May 08, 2017 (2017-05-08T23:53:43.909540Z) in United States | Report Duplicate (/reportduplicate?id=5931143976189952) | Flag (/flagquestion?id=5931143976189952)



0
of 0 votes

Q 4. You are given a binary tree, and you have to return list of lists of node. where same level nodes should be in the same list, nodes are in oposite order in next list from the previous list
Ex:



Output would be
[[4], [5, 3], [1, 10, -4]]


Desigred Complexity : O(N) + O(N).

(/question?id=5732233789833216) - sonesh (/user?id=14962663) April 28, 2017 (2017-04-28T23:02:09.927880Z) in United States | Report Duplicate (/reportduplicate?id=5732233789833216) | Flag (/flagquestion?id=5732233789833216)



0
of 0 votes

You are given a BST of integers and an integer K. You have to find the smallest greater integer then K in the BST.
Ex



(/question?id=5168978356862976) - sonesh (/user?id=14962663) April 20, 2017 (2017-04-20T00:11:54.258390Z) in United States | Report Duplicate (/reportduplicate?id=5168978356862976) | Flag (/flagquestion?id=5168978356862976)



2
of 2 votes

Given the following set of strings, write a function that stores this information.

```
// /Electronics/Computers/Graphics Cards
// /Electronics/Computers/Graphics Cards
// /Electronics/Computers/SSDs
// /Electronics/Computers/Graphics Cards
// /Electronics/Computers/SSDs
// /Electronics/TVs
// /Electronics/Computers/Graphics Cards
// /Electronics/TVs
// /Electronics/TVs
// /Garden
```

Algorithm (5825) (/page?pid=algorithm-interview-questions)

google (1036) (/page?pid=google-interview-questions)

Coding (955) (/page?pid=coding-interview-questions)

Data Structures (828) (/page?pid=data-structures-interview-questions)

Java (750) (/page?pid=java-interview-questions)

C (572) (/page?pid=c-interview-questions)

C++ (546) (/page?pid=c-plus-plus-interview-questions)

Arrays (447) (/page?pid=arrays-interview-questions)

Object Oriented Design (354) (/page?pid=object-oriented-design-interview-questions)

Brain Teasers (329) (/page?pid=brain-teasers-interview-questions)

[More Topics » \(/categories\)](#)

What's Going On



ChrisK said I interprete the question as follows: - suppose number n is ...



Double_A said void main() { int i,j,k,n1,n2,c,x ...



manikadanmanio up-voted sudip.innovates's comment: O(n) approach ...



manikadanmanio up-voted sandak's comment: {{{ public class Solution { public ...



sandak said O(N^2) time, no additional space. less than O ...

Report a Bug or Issue
(<https://careercup.wufoo.com/bug-report/>)

6

Answers
(/question?id=5181088604356608)

3

Answers
(/question?id=5931143976189952)

9

Answers
(/question?id=5732233789833216)

4

Answers
(/question?id=5168978356862976)

3

Answers
(/question?id=56490043566608)

// /Automotive/Parts

Your datastructure should be able to provide information as such:

// = 11

// /Electronics = 9

// /Electronics/Computers = 6

// /Electronics/Computers/Graphics Cards = 4

// /Electronics/TVs = 3

// etc

// ["/Electronics/Computers/Graphics Cards", "/Garden"]

(/question?id=5649004302958592) - JSDUDE (/user?id=7532680) April 19, 2017
(2017-04-19T16:52:58.183950Z) in United States | Report Duplicate (/reportduplicate?id=5649004302958592) | Flag (/flagquestion?id=5649004302958592)



▲ 0 ▼
of 0 votes

Q1. You are given a binary search tree (with unique values) and two values. You need to find their lowest common ancestor. (Expected Complexity $O(\log(n)) + O(1)$)
Q2. Now let's assume the tree has duplicates, and when a duplicate number come, the insertion logic chooses left node. (Expected Complexity $O(\log(n)) + O(1)$)
Q3. Now let's assume the input tree is a binary tree instead of the binary search tree. (Expected Complexity $O(n) + O(1)$)

5

Answers
(/question?id=5198851397910528)

(/question?id=5198851397910528) - sonesh (/user?id=14962663) April 13, 2017
(2017-04-13T19:43:55.631030Z) in United States | Report Duplicate (/reportduplicate?id=5198851397910528) | Flag (/flagquestion?id=5198851397910528)



▲ 0 ▼
of 0 votes

/**
* A tournament tree is a binary tree
* where the parent is the minimum of the two children.
* Given a tournament tree find the second minimum value in the tree.
* A node in the tree will always have 2 or 0 children.
* Also all leaves will have distinct and unique values.
* 2
* /\n
* 2 3
* /\|\n
* 4 2 5 3
*
* In this given tree the answer is 3.
*/

18

Answers
(/question?id=5196022759292928)

```
class Node {
    Integer value;
    Node left, right;
    Node(Integer value, Node left, Node right) {
        this.value = value;
        this.left = left;
        this.right = right;
    }
}

class Solution {
    /**
     * This should return the second minimum
     * int value in the given tournament tree
     */
    public static Integer secondMin(Node root) {
    }
}
```

(/question?id=5196022759292928) - Ikpunisher (/user?id=5758152687484928) April 05, 2017 (2017-04-05T03:23:02.380870Z) in United States | Report Duplicate (/reportduplicate?id=5196022759292928) | Flag (/flagquestion?id=5196022759292928)



▲ 0 ▼
of 0 votes

find the given Binary tree is mirrored tree or not should be like

60
/\n
30 30
/\|\n
20 50 50 20

9

Answers
(/question?id=5169267562512384)

(/question?id=5169267562512384) - Jagadeesh (/user?id=5686138690863104) March 12, 2017 (2017-03-12T03:53:11.812390Z) in India for Kindle | Report Duplicate (/reportduplicate?id=5169267562512384) | Flag (/flagquestion?id=5169267562512384)



▲ 0 ▼
of 0 votes

Given a BST (Binary Search Tree) , Each node value should replace with sum of the node which are greater-than the given node.

conditions :

No Extra space / variable can use

Modify the existing tree in optimal way.

(/question?id=5758569019342848) - Jagadeesh (/user?id=5686138690863104) March 12, 2017 (2017-03-12T03:53:11.310950Z) in India for Kindle | Report Duplicate (/reportduplicate?id=5758569019342848) | Flag (/flagquestion?id=5758569019342848)

10

Answers
(/question?id=5758569019342848)



▲ 2 ▼
of 2 votes

Given a Binary tree and value X. Find X in the tree and return its parent

X:

10

4 3

5 7 9 8

If X = 7, return 4

(/question?id=5726490420314112) - neelabhsingh (/user?id=18613666) January 18, 2017 (2017-01-18T13:21:48.457480Z) in India for Hyderabad | Report Duplicate (/reportduplicate?id=5726490420314112) | Flag (/flagquestion?id=5726490420314112)

13

Answers
(/question?id=5726490420314112)



▲ -4 ▼
of 4 votes

na

(/question?id=5711314321145856) - Anonymous (/user?id=5734615156260864) January 10, 2017 (2017-01-10T13:00:43.544440Z) in United States | Report Duplicate (/reportduplicate?id=5711314321145856) | Flag (/flagquestion?id=5711314321145856)

0

Answers
(/question?id=5711314321145856)



▲ -3 ▼
of 3 votes

Convert an unordered tree to a binary tree

(/question?id=5699311095513088) - mh4wt@virginia.edu (/user?id=5767014007177216) December 18, 2016 (2016-12-18T06:11:02.157540Z) in United States | Report Duplicate (/reportduplicate?id=5699311095513088) | Flag (/flagquestion?id=5699311095513088)

0

Answers
(/question?id=5699311095513088)



▲ 1 ▼
of 1 vote

merge two binary search trees

(/question?id=5733590840115200) - mh4wt@virginia.edu (/user?id=5767014007177216) December 18, 2016 (2016-12-18T06:11:01.557390Z) in United States | Report Duplicate (/reportduplicate?id=5733590840115200) | Flag (/flagquestion?id=5733590840115200)

3

Answers
(/question?id=5733590840115200)



▲ 0 ▼
of 0 votes

You are given a binary tree. Each node in the tree is a house and the value of node is the cash present in the house. A thief can rob houses in alternate levels only. If thief decides to rob house at level 0 then he can rob houses in levels 2,4,6... or he can rob houses in levels 1,3,5,7...Find out the maximum possible amount thief can rob.

(/question?id=5701538572926976) - 256.cool (/user?id=570790742224384) December 14, 2016 (2016-12-14T06:43:53.287830Z) in United States | Report Duplicate (/reportduplicate?id=5701538572926976) | Flag (/flagquestion?id=5701538572926976)

2

Answers
(/question?id=5701538572926976)



▲ 1 ▼
of 3 votes

Create a function to calculate the height of an n-ary tree.

(/question?id=5762815223660544) - theNightsKing16 (/user?id=5664716224462848) November 03, 2016 (2016-11-03T02:42:20.189670Z) in United States | Report Duplicate (/reportduplicate?id=5762815223660544) | Flag (/flagquestion?id=5762815223660544)

14

Answers
(/question?id=5762815223660544)



▲ 0 ▼
of 0 votes

From here : question?id=5660692209205248

In-order traversal:

A->B->C->D->E->F->H->L->M->P->R->S->T

Write a function (pseudo-code is fine) that given a starting node, advances to the next in-order node in a binary tree.
Please also provide a data-structure definition of a node.

(/question?id=5734782106337280) - NoOne (/user?id=568789666275840) October 19, 2016 (2016-10-19T15:43:25.091100Z) in United States | Report Duplicate (/reportduplicate?id=5734782106337280) | Flag (/flagquestion?id=5734782106337280)

2

Answers
(/question?id=5734782106337280)



▲ 0 ▼
of 0 votes

Given an n-ary tree, find the longest sequence in it. The sequence doesn't end to start at the root. It can go from leaf to leaf.

10

Answers
(/question?id=514081051)

of 0 votes

(/question?id=5140810577215488) - ul (/user?id=5646877983768576) ~~October 16, 2016 (2016-10-16T18:07:39.179520Z)~~ in United States | Report Duplicate (/reportduplicate?id=5140810577215488) | Flag (/flagquestion?id=5140810577215488)



▲ 0 ▼
of 0 votes

Need to traverse below n-ary in postorder and throw error message if the node are cyclic

```
Node001
/|\
/|\
/|\
Node002 Node003 Node004
//|\
//|\
Node005 Node006 Node007 Node008
/
/
Node009
\
\
Node003
```

In above case it should through error because Node009 has child Node003 which is derived from it.

(/question?id=5706319660056576) - sunny346 (/user?id=5759656040333312) ~~October 13, 2016 (2016-10-13T05:33:30.176240Z)~~ in United States | Report Duplicate (/reportduplicate?id=5706319660056576) | Flag (/flagquestion?id=5706319660056576)



▲ 0 ▼
of 0 votes

Hi Implemented this sample code for N-ary postOrder Traversal.
Now i want to throw error statement id the parent node is dependent on child.

Can some one help

```
package dependencyAlgorithm;
import java.util.*;
```

```
public class Dependency
{
```

```
    class MainRule
    {
        String ruleName;
        ArrayList<MainRule> subrule;
        public MainRule(String name)
        {
            this.ruleName=name;
            subrule=new ArrayList<>();
        }
    }
```

```
    public static void postOrder(MainRule rootRule)
    {
```

```
        Stack<List<MainRule>> stack = new Stack<>();
        MainRule rule = rootRule;
        List<MainRule> list = null;
        while (true)
        {
            if(rule != null)
            {
                list = rule.subrule;
                for(int i=0;i<list.size();i++)
                {
                    if(rule.ruleName == list.get(i).ruleName)
                        break;
                }
                rule = null;
                if(list!=null && list.size()>0)
                {
                    //push the list in the stack (do not modify original tree structure).
                    stack.push(new ArrayList<>(list));
```

```
                //get first item from this list
                rule = stack.peek().get(0);
                System.out.print("\n1 ListSize: "+list.size());
            }
        }
        else if (!stack.isEmpty())
        {
            System.out.print("\n2 \n");
            list = stack.pop();
            System.out.print("\n2 ListSize: "+list.size());
            rule = list.remove(0); //shift left
            System.out.print("\n2.1 ListSize: "+list.size());
```

0

Answers
(/question?
id=5706319660056576)

1

Answer
(/question?
id=5660994660056576)

```

System.out.print("\n"+rule.ruleName+" ");
rule = null;
if(list.size()>0)
{
    System.out.print("\n3 ListSize "+list.size());
    stack.push(list); //push back remaining list into stack
    rule = stack.peek().get(0); //prepare for next iteration
}
}
else
break;
}

```

```

System.out.println(rootRule.ruleName);
}

```

```

/*
Fml001
/|\
/|\
/|\
Fml002 C001_Base Tot001
//|\
//|\
Fml003 Fml004 R001_Base R001_TxPat
/
/
Tot002
\
\
C001_TxPat
*/

```

```

public void createBinaryTree()
{
    MainRule rootRule;
    MainRule Fml001 =new MainRule("Fml001");
    MainRule Fml002=new MainRule("Fml002");
    MainRule Fml003=new MainRule("Fml003");
    MainRule Fml004=new MainRule("Fml004");
    MainRule C001_Base=new MainRule("C001_Base");
    MainRule R001_Base=new MainRule("R001_Base");
    MainRule Tot001=new MainRule("Tot001");
    MainRule Tot002 =new MainRule("Tot002");
    MainRule R001_TxPat =new MainRule("R001_TxPat");
    MainRule C001_TxPat =new MainRule("C001_TxPat");
    rootRule=Fml001;
    rootRule.subrule.add(Fml002);
    rootRule.subrule.add(C001_Base);
    rootRule.subrule.add(Tot001);
    Fml002.subrule.add(Fml003);
    C001_Base.subrule.add(Fml004);
    C001_Base.subrule.add(R001_Base);
    C001_Base.subrule.add(R001_TxPat);
    R001_Base.subrule.add(Tot002);
    Tot002.subrule.add(C001_TxPat);
    postOrder(rootRule);
}

```

```

public static void main(String[] args)
{
    Dependency dependency=new Dependency();
    // Creating a tree structure
    System.out.println("Path Traversed:");
    dependency.createBinaryTree();
}
}

```

(/question?id=5660984669634560) - sunny346 (/user?id=575965604033312)
 October 11, 2016 (2016-10-11T06:12:59.126630Z) in India | Report Duplicate (/reportduplicate?id=5660984669634560) | Flag (/flagquestion?id=5660984669634560)



▲ 1 ▼
of 1 vote

Given two (binary) trees, return the first pair of non-matching leaves

Tree 1: A, B, C, D, E, null, null
 Tree 2: A, D, B

Output: (E,B)

(/question?id=5673248478986240) - bobshanely (/user?id=5721520958603264)
 October 03, 2016 (2016-10-03T23:23:02.904600Z) in United States | Report Duplicate (/reportduplicate?id=5673248478986240) | Flag (/flagquestion?id=5673248478986240)



▲ 3 ▼
of 3 votes

Given an undirected graph with weights, return the sum of the weight of each path between two nodes (shortest path between two vertices). Assume there are no cycles.

15


Answers
(/question?id=567324847)

23

Answers
(/question?id=56798978)

Example:

Input:



Output:

18
since
A to B has weight 1
A to C has weight 3
A to D has weight 4
B to C has weight 2
B to D has weight 3
C to D has weight 5

Edit: Thanks, wangchenClark0512, forgot about C to D

Edit2: @Lukas, The question is just the sum of the shortest paths between two vertices. Also, all edges are positive.

Edit3: Assume the graph has no cycles, did not get to the follow-up, but follow-up probably is probably change your algorithm so that it works for cycles

(/question?id=5679897813975040) - djway (/user?id=5667077504368640) August 18, 2016 (2016-08-18T04:05:25.571630Z) in United States | Report Duplicate (/reportduplicate?id=5679897813975040) | Flag (/flagquestion?id=5679897813975040)



▲ 0 ▼
of 0 votes

Suggest a data structure and implement efficient phrase search along with word search in a huge chunk of text.

(/question?id=5084421972557824) - novicedhunnu (/user?id=5129565731028992) August 14, 2016 (2016-08-14T04:15:52.972620Z) in India for N/A | Report Duplicate (/reportduplicate?id=5084421972557824) | Flag (/flagquestion?id=5084421972557824)

3

Answers
(/question?id=5084421972557824)



▲ 6 ▼
of 6 votes

You are given a graph with no cycles, each node representing different cities and there are stadiums for baseball games in all cities.

Each node contains a value representing the population of the city, and a list of neighbors. (feel free to extend data structure)

Every time there is a baseball game at a city, everyone from all the different cities will go to the city with the baseball game.

Return the maximum traffic between a city and its neighbours when there is a game at that city, for all cities. (Does not have to be sorted)

The total run-time after returning everything should be $O(n)$.

Examples:

38

Answers
(/question?id=569504673)

Input:
1 2
 \
 /
 5
 /
 \
4 3
Output:
1 14
2 13
3 12
4 11
5 4

Input:
 38
 /
 8
 /
 7
 /
1 2
 \
 /
 5 15
 /
 \
4 3
Output:
1 82
2 53
3 80
4 79
5 70
7 46
15 68
8 38
38 45

(/question?id=5695046734053376) - djway (user?id=5667077504368640) August 10, 2016 (2016-08-10T05:47:06-0800Z) in United States | Report Duplicate (/reportduplicate?id=5695046734053376) | Flag (/flagquestion?id=5695046734053376)

Page:

1 2 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=2>) 3 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=3>) 4 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=4>) 5 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=5>) 6 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=6>) 7 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=7>) 8 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=8>) 9 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=9>) 10 (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=10>) » (<https://www.careercup.com/page?pid=trees-and-graphs-interview-questions&n=11>)

Filter: (None) (None) (None) Go Clear

Sort By:

Date | [Number of Comments \(?pid=trees-and-graphs-interview-questions&sort=comments\)](#) | [Most Recent Comment \(?pid=trees-and-graphs-interview-questions&sort=recentcomments\)](#) | [Votes \(?pid=trees-and-graphs-interview-questions&sort=votes\)](#)

Books

[Cracking the Tech Career](http://www.amazon/0984782850850t/111896:ie=UTF8&camp=15121&creative=390961&cr20) (<http://www.amazon/0984782850850t/111896:ie=UTF8&camp=15121&creative=390961&cr20>) is a comprehensive book on getting a job at a top tech company, while [Cracking the Coding Interview](http://www.amazon.ca/gp/product/09847828:ie=UTF8&camp=15121&creative=39098478220) (<http://www.amazon.ca/gp/product/09847828:ie=UTF8&camp=15121&creative=39098478220>) focuses on dev interviews and [Cracking the PM Interview](#)

Videos

CareerCup's interview videos give you a real-life look at technical interviews. In these unscripted videos, watch how other candidates handle tough questions and how the interviewer thinks about their performance.

[Learn More \(video\)](#)

Resume Review

Most engineers make critical mistakes on their resumes -- we can fix your resume with our custom resume review service.

Mock Interviews

Our Mock Interviews will be conducted "in character" just like a real interview, and can focus on whatever topics you want.

And, we use fellow engineers as our resume reviewers, so you can be sure that we "get" what you're saying.

All our interviewers have worked for Microsoft, Google or Amazon, you know you'll get a true-to-life experience.

[Learn More \(Interviewers\)](#)

[Learn More \(Interviewers\)](#)

Get the Interview Book that Amazon reviewers **love.**

Cracking the Coding Interview: 150
Programming Questions and Solutions
Gayle Laakmann McDowell
Founder / CEO of CareerCup.com

5 / 5 stars
after 160 reviews (and counting)

"loved it" "invaluable training"
"very comprehensive" "excellent"
"highly recommended"
"best resource for interview preparation"

<http://www.amazon.ca/gp/product/098478ie=UTF8&camp=15121&creative=390984720>

Information

Team, Contact & About (/about)
Salaries (/salary)
RSS
(<http://feeds.feedburner.com/Careercup>)
Additional Resources
(<http://www.crackingthecodinginterview.cc>)

Products

Cracking the Coding Interview
(<http://www.amazon.ca/gp/product/098478ie=UTF8&camp=15121&creative=39098420>)
Cracking the PM Interview
(<http://www.amazon.ca/gp/product/098478ie=UTF8&camp=15121&creative=39098420>)
Cracking the Tech Career
(<http://www.amazon0984782850850/111ie=UTF8&camp=15121&creative=39098420>)
Videos (/video)

Services

Mock Interviews (/interview)
Resume Review (/resumereview)
Acquisition Interview Consulting
(<http://www.gayle.com/consulting/>)

Social

CareerCup on Facebook
(<http://www.facebook.com/careercup>)
CTCI on Facebook
(<http://www.facebook.com/ctcibook>)
Gayle McDowell on Facebook
(<http://www.facebook.com/gayle>)
CareerCup on Twitter
(<http://www.twitter.com/careercup>)
Gayle on Twitter
(<http://www.twitter.com/gayle>)
CareerCup Blog
(<http://blog.careercup.com>)