

[Suggest a Topic](#)[Login](#)[Write an Article](#)

Bitmasking and Dynamic Programming | Set 1 (Count ways to assign unique cap to every person)

Consider the below problems statement.

There are 100 different types of caps each having a unique id from 1 to 100. Also, there are 'n' persons each having a collection of a variable number of caps. One day all of these persons decide to go in a party wearing a cap but to look unique they decided that none of them will wear the same type of cap. So, count the total number of arrangements or ways such that none of them is wearing the same type of cap.

Constraints: $1 \leq n \leq 10$ Example:

The first line contains the value of n, next n lines contain collections of all the n persons.

Input:

```
3
5 100 1    // Collection of the first person.
2          // Collection of the second person.
5 100      // Collection of the third person.
```

Output:

```
4
Explanation: All valid possible ways are (5, 2, 100), (100, 2, 5),
(1, 2, 5) and (1, 2, 100)
```

Since, number of ways could be large, so output modulo 1000000007

We strongly recommend you to minimize your browser and try this yourself first.

A **Simple Solution** is to try all possible combinations. Start by picking the first element from the first set, marking it as visited and recur for remaining sets. It is basically a Backtracking based solution.

A **better solution is to use Bitmasking and DP**. Let us first introduce Bitmasking.

What is Bitmasking?

Suppose we have a collection of elements which are numbered from 1 to N. If we want to represent a subset of

this set then it can be encoded by a sequence of N bits (we usually call this sequence a “mask”). In our chosen subset the i -th element belongs to it if and only if the i -th bit of the mask is set i.e., it equals to 1. For example, the mask 10000101 means that the subset of the set $[1... 8]$ consists of elements 1, 3 and 8. We know that for a set of N elements there are total 2^N subsets thus 2^N masks are possible, one representing each subset. Each mask is, in fact, an integer number written in binary notation.

Our main methodology is to assign a value to each mask (and, therefore, to each subset) and thus calculate the values for new masks using values of the already computed masks. Usually our main target is to calculate value/solution for the complete set i.e., for mask 11111111. Normally, to find the value for a subset X we remove an element in every possible way and use values for obtained subsets $X'_1, X'_2... ,X'_k$ to compute the value/solution for X . This means that the values for X'_i must have been computed already, so we need to establish an ordering in which masks will be considered. It's easy to see that the natural ordering will do: go over masks in increasing order of corresponding numbers. Also, We sometimes, start with the empty subset X and we add elements in every possible way and use the values of obtained subsets $X'_1, X'_2... ,X'_k$ to compute the value/solution for X .

We mostly use the following notations/operations on masks:

`bit(i, mask)` – the i -th bit of mask

`count(mask)` – the number of non-zero bits in the mask

`first(mask)` – the number of the lowest non-zero bit in the mask

`set(i, mask)` – set the i th bit in the mask

`check(i, mask)` – check the i th bit in the mask

How is this problem solved using Bitmasking + DP?

The idea is to use the fact that there are upto 10 persons. So we can use an integer variable as a bitmask to store which person is wearing a cap and which is not.

Let i be the current cap number (caps from 1 to $i-1$ are already processed). Let integer variable `mask` indicates that the persons wearing and not wearing caps. If i 'th bit is set in `mask`, then i 'th person is wearing a cap, else not.

```
// consider the case when ith cap is not included
// in the arrangement
countWays(mask, i) = countWays(mask, i+1) +

// when ith cap is included in the arrangement
// so, assign this cap to all possible persons
// one by one and recur for remaining persons.
Σ countWays(mask | (1 << j), i+1)
for every person j that can wear cap i
```

Note that the expression "`mask | (1 << j)`" sets j 'th bit in `mask`. And a person can wear cap i if it is there in the person's cap list provided as input.

If we draw the complete recursion tree, we can observe that many subproblems are solved again and again. So we use Dynamic Programming. A table `dp[i][j]` is used such that in every entry `dp[i][j]`, `i` is mask and `j` is cap number.

Since we want to access all persons that can wear a given cap, we use an array of vectors, `capList[101]`. A value `capList[i]` indicates the list of persons that can wear cap `i`.

Below is the implementation of above idea.

C/C++

```
// C++ program to find number of ways to wear hats
#include<bits/stdc++.h>
#define MOD 1000000007
using namespace std;

// capList[i]'th vector contains the list of persons having a cap with id i
// id is between 1 to 100 so we declared an array of 101 vectors as indexing
// starts from 0.
vector<int> capList[101];

// dp[2^10][101] .. in dp[i][j], i denotes the mask i.e., it tells that
// how many and which persons are wearing cap. j denotes the first j caps
// used. So, dp[i][j] tells the number ways we assign j caps to mask i
// such that none of them wears the same cap
int dp[1025][101];

// This is used for base case, it has all the N bits set
// so, it tells whether all N persons are wearing a cap.
int allmask;

// Mask is the set of persons, i is cap-id (OR the
// number of caps processed starting from first cap).
long long int countWaysUtil(int mask, int i)
{
    // If all persons are wearing a cap so we
    // are done and this is one way so return 1
    if (mask == allmask) return 1;

    // If not everyone is wearing a cap and also there are no more
    // caps left to process, so there is no way, thus return 0;
    if (i > 100) return 0;

    // If we already have solved this subproblem, return the answer.
    if (dp[mask][i] != -1) return dp[mask][i];

    // Ways, when we don't include this cap in our arrangement
    // or solution set.
    long long int ways = countWaysUtil(mask, i+1);

    // size is the total number of persons having cap with id i.
    int size = capList[i].size();

    // So, assign one by one ith cap to all the possible persons
    // and recur for remaining caps.
    for (int j = 0; j < size; j++)
    {
        // if person capList[i][j] is already wearing a cap so continue as
        // we cannot assign him this cap
        if (mask & (1 << capList[i][j])) continue;

        // Else assign him this cap and recur for remaining caps with
        // new updated mask vector
        else ways += countWaysUtil(mask | (1 << capList[i][j]), i+1);
        ways %= MOD;
    }
}
```

```

    // Save the result and return it.
    return dp[mask][i] = ways;
}

// Reads n lines from standard input for current test case
void countWays(int n)
{
    //----- READ INPUT -----
    string temp, str;
    int x;
    getline(cin, str); // to get rid of newline character
    for (int i=0; i<n; i++)
    {
        getline(cin, str);
        stringstream ss(str);

        // while there are words in the streamobject ss
        while (ss >> temp)
        {
            stringstream s;
            s << temp;
            s >> x;

            // add the ith person in the list of cap if with id x
            capList[x].push_back(i);
        }
    }
    //-----

    // All mask is used to check whether all persons
    // are included or not, set all n bits as 1
    allmask = (1 << n) - 1;

    // Initialize all entries in dp as -1
    memset(dp, -1, sizeof dp);

    // Call recursive function count ways
    cout << countWaysUtil(0, 1) << endl;
}

// Driver Program
int main()
{
    int n; // number of persons in every test case
    cin >> n;
    countWays(n);
    return 0;
}

```

[Run on IDE](#)

Java

```

// Java program to find number of ways to wear hats

import java.io.BufferedReader;
import java.io.InputStreamReader;
import java.util.Vector;

class Test
{
    static final int MOD = 1000000007;

    // for input
    static BufferedReader br = new BufferedReader(new InputStreamReader(System.in));

    // capList[i]'th vector contains the list of persons having a cap with id i
    // id is between 1 to 100 so we declared an array of 101 vectors as indexing
    // starts from 0.
    static Vector<Integer> capList[] = new Vector[101];
}

```

```

// dp[2^10][101] .. in dp[i][j], i denotes the mask i.e., it tells that
// how many and which persons are wearing cap. j denotes the first j caps
// used. So, dp[i][j] tells the number ways we assign j caps to mask i
// such that none of them wears the same cap
static int dp[][] = new int[1025][101];

// This is used for base case, it has all the N bits set
// so, it tells whether all N persons are wearing a cap.
static int allmask;

// Mask is the set of persons, i is cap-id (OR the
// number of caps processed starting from first cap).
static long countWaysUtil(int mask, int i)
{
    // If all persons are wearing a cap so we
    // are done and this is one way so return 1
    if (mask == allmask) return 1;

    // If not everyone is wearing a cap and also there are no more
    // caps left to process, so there is no way, thus return 0;
    if (i > 100) return 0;

    // If we already have solved this subproblem, return the answer.
    if (dp[mask][i] != -1) return dp[mask][i];

    // Ways, when we don't include this cap in our arrangement
    // or solution set.
    long ways = countWaysUtil(mask, i+1);

    // size is the total number of persons having cap with id i.
    int size = capList[i].size();

    // So, assign one by one ith cap to all the possible persons
    // and recur for remaining caps.
    for (int j = 0; j < size; j++)
    {
        // if person capList[i][j] is already wearing a cap so continue as
        // we cannot assign him this cap
        if ((mask & (1 << capList[i].get(j))) != 0) continue;

        // Else assign him this cap and recur for remaining caps with
        // new updated mask vector
        else ways += countWaysUtil(mask | (1 << capList[i].get(j)), i+1);
        ways %= MOD;
    }

    // Save the result and return it.
    return dp[mask][i] = (int) ways;
}

// Reads n lines from standard input for current test case
static void countWays(int n) throws Exception
{
    //----- READ INPUT -----
    String str;
    String split[];
    int x;

    for (int i=0; i<n; i++)
    {
        str = br.readLine();
        split = str.split(" ");

        // while there are words in the split[]
        for (int j = 0; j < split.length; j++) {
            // add the ith person in the list of cap if with id x
            x = Integer.parseInt(split[j]);
            capList[x].add(i);
        }
    }
    //-----

```

```

// All mask is used to check of all persons
// are included or not, set all n bits as 1
allmask = (1 << n) - 1;

// Initialize all entries in dp as -1
for (int[] is : dp) {
    for (int i = 0; i < is.length; i++) {
        is[i] = -1;
    }
}

// Call recursive function count ways
System.out.println(countWaysUtil(0, 1));
}

// Driver method
public static void main(String args[]) throws Exception
{
    int n;    // number of persons in every test case

    // initializing vector array
    for (int i = 0; i < capList.length; i++)
        capList[i] = new Vector<>();

    n = Integer.parseInt(br.readLine());
    countWays(n);
}
}
// This code is contributed by Gaurav Miglani

```

Run on IDE

Python

```

#Python program to find number of ways to wear hats
from collections import defaultdict

class AssignCap:

    # Initialize variables
    def __init__(self):

        self.allmask = 0

        self.total_caps = 100

        self.caps = defaultdict(list)

    # Mask is the set of persons, i is the current cap number.
    def countWaysUtil(self, dp, mask, cap_no):

        # If all persons are wearing a cap so we
        # are done and this is one way so return 1
        if mask == self.allmask:
            return 1

        # If not everyone is wearing a cap and also there are no more
        # caps left to process, so there is no way, thus return 0;
        if cap_no > self.total_caps:
            return 0

        # If we have already solved this subproblem, return the answer.
        if dp[mask][cap_no] != -1 :
            return dp[mask][cap_no]

        # Ways, when we don't include this cap in our arrangement
        # or solution set
        ways = self.countWaysUtil(dp, mask, cap_no + 1)

```

```

# assign ith cap one by one to all the possible persons
# and recur for remaining caps.
if cap_no in self.caps:

    for ppl in self.caps[cap_no]:

        # if person 'ppl' is already wearing a cap then continue
        if mask & (1 << ppl) : continue

        # Else assign him this cap and recur for remaining caps with
        # new updated mask vector
        ways += self.countWaysUtil(dp, mask | (1 << ppl), cap_no + 1)

        ways = ways % (10**9 + 7)

# Save the result and return it
dp[mask][cap_no] = ways

return dp[mask][cap_no]

```

```

def countWays(self,N):

    # Reads n lines from standard input for current test case
    # create dictionary for cap. cap[i] = list of person having
    # cap no i
    for ppl in range(N):

        cap_posessed_by_person = map(int, raw_input().strip().split())

        for i in cap_posessed_by_person:

            self.caps[i].append(ppl)

    # allmask is used to check if all persons
    # are included or not, set all n bits as 1
    self.allmask = (1 << N) -1

    # Initialize all entries in dp as -1
    dp = [[-1 for j in range(self.total_caps + 1)] for i in range(2 ** N)]

    # Call recursive function countWaysUtil
    # result will be in dp[0][1]
    print self.countWaysUtil(dp, 0, 1,)

```

#Driver Program

```

def main():
    No_of_people = input() # number of persons in every test case

    AssignCap().countWays(No_of_people)

```

```

if __name__ == '__main__':
    main()

```

This code is contributed by Neelam Yadav

Run on IDE

Input:

```

3
5 100 1
2
5 100

```


Output:

4

This article is contributed by Gaurav Ahirwar. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Practice Tags : Dynamic Programming

Article Tags : Dynamic Programming



Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

[Login to Improve this Article](#)

Recommended Posts:

[Digit DP | Introduction](#)

[Program for Fibonacci numbers](#)

[Longest Repeating Subsequence](#)

[Bitmasking and Dynamic Programming | Set-2 \(TSP\)](#)

[Bitmasking and Dynamic Programming | Set 1 \(Count ways to assign unique cap to every person\)](#)

[Weird Number](#)

[Semiperfect Number](#)

[Maximum sum in circular array such that no two elements are adjacent](#)

[Number of ways to reach Nth floor by taking at-most K leaps](#)

[Number of ways to represent a number as sum of k fibonacci numbers](#)

(Login to Rate)

4.4 Average Difficulty : **4.4/5.0**
Based on **117** vote(s)

Add to TODO List

Mark as DONE

Feedback

Add Notes

Improve Article

Basic

Easy

Medium

Hard

Expert

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

Share this post!

A computer science portal for geeks

710-B, Advant Navis Business Park,
Sector-142, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

About Us
Careers
Privacy Policy
Contact Us

PRACTICE

Company-wise
Topic-wise
Contests
Subjective Questions

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

CONTRIBUTE

Write an Article
Write Interview Experience
Internships
Videos

@geeksforgeeks, Some rights reserved

