

CIS 200 - Lab/Project

1. Problem Statement

Given a struct clientData, build a program that can fill a file with instances of this data and read it back.

2. Requirements

2.1 Assumptions

- Some of the code is provided on the “instruction” sheet.
- Command Line Input Only
- User will only enter integers where applicable
- User will only enter doubles where applicable

2.2 Specifications

- Struct clientData will be used
- File will be accessed randomly
- File will accommodate 100 user inputs
- User can request specific accounts
- Program will print out all used accounts in order

3. Decomposition Diagram

- Program
 - Input
 - Integer Account Number
 - Character Array First Name
 - Character Array Last Name
 - Double Account Balance
 - Process
 - Create Default File
 - Push Respective Data to Output Stream
 - Output
 - Output Default File
 - Push Output Stream to File
 - Print Data to Console

4. Test Strategy

- Valid Data

- Invalid Data

5. Test Plan Version 1

Test Strategy	#	Description	Input	Expected Output	Actual Output	Pass/Fail
Valid Data	1	File Exists				
Valid Data	2	Set Account #				
Valid Data	3	Set Account #				
Valid Data	4	Set Account First Name				
Valid Data	5	Set Account Last Name				
Valid Data	6	Set Balance				
Valid Data	7	Set Balance				
Invalid Data	1	Set Account #				
Invalid Data	2	Set Account #				
Invalid Data	3	Set First Name Too Large				
Invalid Data	4	Set Last Name Too Large				
Invalid Data	5	Set Balance Negative				
Invalid Data	6	Asking for unused account				

6. Initial Algorithm

1. Create Struct clientData
 - a. Integer accountNumber
 - b. Character Array lastName[15]
 - c. Character Array firstName[10]
 - d. Float balance

2. Create Function createBlankFile
 - a. Parameters: clientData blankClient
 - b. Return: Void
 - c. Method:
 - i. Open Output Stream
 - ii. Name File "client.dat"
 - iii. Iterate 100 Times
 1. Fill with blankClient
 - iv. Close Output Stream
3. Create Function writeToFile
 - a. Parameters: clientData client
 - b. Return: Void
 - c. Method:
 - i. Open Output Stream
 - ii. Do While Account Number is not 0
 1. Prompt for initial Account Number
 2. IF 0
 - a. Exit Function
 3. Else IF 1 >= Account Number >= 100
 - a. Fill First Name
 - b. Fill Last Name
 - c. Fill Balance
 - d. Seek Position of Account Number in file
 - e. Write client data to file
 4. Else
 - a. Alert Invalid Account Number
4. Create Function userRead
 - a. Parameters: clientData client
 - b. Return: Void
 - c. Method:
 - i. Create Input Stream
 - ii. Do While
 1. Prompt for Account Number
 2. IF input = 0
 - a. Return/Exit
 3. Else IF 1 <= input <= 100
 - a. Seek Input
 - b. Read Input
 - c. IF Input != 0
 - i. Output Data
 - d. Else
 - i. Alert Invalid Account Number
5. Create Function printAllRecords

- a. Parameters: clientData client
 - b. Return: Void
 - c. Method:
 - i. Create Input Stream
 - ii. Read Initial Data
 - iii. While inCredit && !inCredit @ End Of File
 1. IF client.accountNumber != 0
 - a. Output Data
 2. Read Next Data
6. Create MAIN
- a. Create and Initialize client and blankClient as {0, "", "", 0.0}
 - b. Perform createBlankFile(blankClient)
 - c. Perform writeToFile(client)
 - d. Perform userRead(client)
 - e. Perform printAllRecords(client)
 - f. Return 0;

7. Test Plan Version 2

Test Strategy	#	Description	Input	Expected Output	Actual Output	Pass/Fail
Valid Data	1	File Exists	createBlankFile	File Output Correct		
Valid Data	2	Set Account #	1	Account #1		
Valid Data	3	Set Account #	100	Account #100		
Valid Data	4	Set Account First Name	Bill	First Name: Bill		
Valid Data	5	Set Account Last Name	Gates	Last Name: Bill		
Valid Data	6	Set Balance	1234.56	Balance: 1234.56		
Valid Data	7	Set Balance	1	Balance: 1		
Invalid Data	1	Set Account #	-1	Out of Range		
Invalid Data	2	Set Account #	101	Out of Range		
Invalid Data	3	Set First Name Too Large	abcdefghijkl	First Name Corrupted		

Invalid Data	4	Set Last Name Too Large	abcdefghijklmno p	Last Name Corrupted		
Invalid Data	5	Set Balance Negative	-100	Try Again		
Invalid Data	6	Asking for unused account	1 when unused	Account Not In Use		

8. Code

[source.cpp]

```
//Program Name: Client Data - RANDOM ACCESS
//Programmer Name: Arthur Aigeltinger IV
//Description: A toe dipped in the water of random file access that is still a little
over my head but I'm glad I made it this far. Thanks for coming to my TedTalk...
//Date Created: 10/29/18

#include <fstream>
#include <iostream>
#include <ostream>

//Define Struct
struct clientData
{
    int accountNumber;
    char lastName[15];
    char firstName[10];
    float balance;
};

//Function Prototypes
void createBlankFile(clientData);
void writeToFile(clientData);
void userRead(clientData);
void printAllRecords(clientData);

int main()
{
    //Initialize Blank and Holder Client
    clientData blankClient = { 0,"","",0.0 };
    clientData client = { 0,"","",0.0 };

    createBlankFile(blankClient);
```

```

        writeToFile(client);
        userRead(client);
        printAllRecords(client);

        system("pause");
        return 0;
}

//Description: Creates and Initialized a "blank" file with the size and space to fit
100 instances of struct [clientData]
//Pre-Condition: We need a file
//Post-Condition: WE'VE GOT A FILE
void createBlankFile(clientData blankClient)
{
    //Create and Open Output Stream
    std::ofstream outCredit("credit.dat", std::ios::out);

    //Fill File with blankClient
    for (int i = 0; i < 100; i++)
    {
        outCredit.write(reinterpret_cast<const char *>(&blankClient),
sizeof(clientData));
    }

    //Close File Stream
    outCredit.close();
}

//Description: Enters loop to ask user for client data to be pushed to the
pre-generated file
//Pre-Condition: File is at its default, empty state
//Post-Condition: File is filled with individual user accounts as determined bu the
user
void writeToFile(clientData client)
{
    //Open Client Output Stream
    std::ofstream outCredit1("credit.dat", std::ios::ate);

    //Announce Function to User
    std::cout << std::endl;
    std::cout << "Inputting Specific User Data" << std::endl;
    std::cout << std::endl;

    do //Filling Client Data until accountNumber = 0
    {
        //Initial Prompt
        std::cout << std::endl;
        std::cout << "Please Enter an Account Number (1-100)" << std::endl;
    }

```

```

std::cout << "Entering 0 Will Exit User Input" << std::endl;
std::cout << "Account Number: ";
std::cin >> client.accountNumber;

if (client.accountNumber == 0)
{
    outCredit1.close(); //Close Output Stream
    return; //Exit Function
}
else if (client.accountNumber >= 1 && client.accountNumber <= 100)
{
    //Fill In Order
    std::cout << "First Name: ";
    std::cin >> client.firstName;
    std::cout << "Last Name: ";
    std::cin >> client.lastName;
    do
    {
        std::cout << "Balance: ";
        std::cin >> client.balance;
    } while (client.balance < 0);

    outCredit1.seekp((client.accountNumber - 1) *
sizeof(clientData));
    outCredit1.write(reinterpret_cast<const char*>(&client),
sizeof(clientData));
    }
    else
    {
        std::cout << "Invalid Account Number" << std::endl;
    }
    } while (client.accountNumber != 0); //Checking to repeat even though case [0]
is handled with initial "if"
}

//Description: Allows user to request specific client accounts and have them printed
to the screen
//Pre-Condition: Filled client data file via writeToFile()
//Post-Condition: Client account(s) requested are printed to console
void userRead(clientData client)
{
    //Holder Variable
    int userIn = 0;

    //Open Input Stream
    std::ifstream inCredit("credit.dat", std::ios::in);

    //Announce Function to User

```

```

std::cout << std::endl;
std::cout << "Request Specific User Data" << std::endl;
//std::cout << std::endl;

do
{
    std::cout << std::endl;
    std::cout << "Enter 0 To Exit" << std::endl;
    std::cout << "Enter Account Number: ";
    std::cin >> userIn;

    if (userIn == 0)
    {
        std::cout << "Exiting" << std::endl;
        inCredit.close(); //Close Input Stream
        return; //Exit Function
    }
    else if (userIn >= 1 && userIn <= 100)
    {
        inCredit.seekg((userIn - 1) * sizeof(clientData));
        inCredit.read(reinterpret_cast<char *>(&client),
sizeof(clientData));

        if (client.accountNumber == userIn)
        {
            //Output In Order
            std::cout << "Account Number: ";
            std::cout << client.accountNumber << std::endl;
            std::cout << "First Name: ";
            std::cout << client.firstName << std::endl;
            std::cout << "Last Name: ";
            std::cout << client.lastName << std::endl;
            std::cout << "Balance: ";
            std::cout << client.balance << std::endl;
        }
        else //Checking for Invalid Within Range
        {
            std::cout << "ACCOUNT NUMBER NOT IN USE" <<
std::endl;

            client.accountNumber = -1;
        }
    }
    else //Checking for Invalid Outside Range
    {
        std::cout << "ACCOUNT NUMBER OUT OF RANGE" << std::endl;
        client.accountNumber = -1;
    }
}

```



```

        } while (client.accountNumber != 0); //Checking to repeat even though case
[0] is handled with initial "if"
    }

//Description: Prints all of the filled records within "credit.dat"
//Pre-Condition: A valid, filled "credit.dat" file
//Post-Condition: All filled client data is printed on the console
void printAllRecords(clientData client)
{
    //Open Input Stream
    std::ifstream inCredit("credit.dat", std::ios::in);

    //Announce Function to User
    std::cout << std::endl;
    std::cout << "Printing ALL RECORDS" << std::endl;
    std::cout << std::endl;

    inCredit.read(reinterpret_cast<char *>(&client), sizeof(clientData));

    while (inCredit && !inCredit.eof())
    {
        if (client.accountNumber != 0) //MAY CAUSE INFINITE LOOP (TRY 100?)
        {
            //Output In Order
            std::cout << "Account Number: ";
            std::cout << client.accountNumber << std::endl;
            std::cout << "First Name: ";
            std::cout << client.firstName << std::endl;
            std::cout << "Last Name: ";
            std::cout << client.lastName << std::endl;
            std::cout << "Balance: ";
            std::cout << client.balance << std::endl << std::endl;
        }

        inCredit.read(reinterpret_cast<char *>(&client), sizeof(clientData));
    }
}

```

9. Updated Algorithm

1. Create Struct clientData
 - a. Integer accountNumber
 - b. Character Array lastName[15]
 - c. Character Array firstName[10]
 - d. Float balance

2. Create Function createBlankFile
 - a. Parameters: clientData blankClient
 - b. Return: Void
 - c. Method:
 - i. Open Output Stream
 - ii. Name File "client.dat"
 - iii. Iterate 100 Times
 1. Fill with blankClient
 - iv. Close Output Stream
3. Create Function writeToFile
 - a. Parameters: clientData client
 - b. Return: Void
 - c. Method:
 - i. Open Output Stream
 - ii. Do While Account Number is not 0
 1. Prompt for initial Account Number
 2. IF 0
 - a. Exit Function
 3. Else IF 1 >= Account Number >= 100
 - a. Fill First Name
 - b. Fill Last Name
 - c. Fill Balance
 - d. Seek Position of Account Number in file
 - e. Write client data to file
 4. Else
 - a. Alert Invalid Account Number
4. Create Function userRead
 - a. Parameters: clientData client
 - b. Return: Void
 - c. Method:
 - i. Create Input Stream
 - ii. Do While
 1. Prompt for Account Number
 2. IF input = 0
 - a. Return/Exit
 3. Else IF 1 <= input <= 100
 - a. Seek Input
 - b. Read Input
 - c. IF Input != 0
 - i. Output Data
 - d. Else
 - i. Alert Invalid Account Number
 - ii. accountNumber = -1

4. Else
 5. Alert Account Number Out Of Range
 6. accountNumber = -1
5. Create Function printAllRecords
 - a. Parameters: clientData client
 - b. Return: Void
 - c. Method:
 - i. Create Input Stream
 - ii. Read Initial Data
 - iii. While inCredit && !inCredit @ End Of File
 1. IF client.accountNumber != 0
 - a. ~~Output Data~~
 - b. Output Account Number
 - c. Output First Name
 - d. Output Last Name
 - e. Output Balance
 2. Read Next Data
6. Create MAIN
 - a. Create and Initialize client and blankClient as {0, "", "", 0.0}
 - b. Perform createBlankFile(blankClient)
 - c. Perform writeToFile(client)
 - d. Perform userRead(client)
 - e. Perform printAllRecords(client)
 - f. Return 0;

10. Test Plan Version 3

Test Strategy	#	Description	Input	Expected Output	Actual Output	Pass/ Fail
Valid Data	1	File Exists	createBlankFile	File Output Correct	File Output Correct	Pass
Valid Data	2	Set Account #	1	Account #1	Account #1	Pass
Valid Data	3	Set Account #	100	Account #100	Account #100	Pass
Valid Data	4	Set Account First Name	Bill	First Name: Bill	First Name: Bill	Pass
Valid Data	5	Set Account Last Name	Gates	Last Name: Bill	Last Name: Bill	Pass

Valid Data	6	Set Balance	1234.56	Balance: 1234.56	Balance: 1234.56	Pass
Valid Data	7	Set Balance	1	Balance: 1	Balance: 1	Pass
Invalid Data	1	Set Account #	-1	Out of Range	Out of Range	Pass
Invalid Data	2	Set Account #	101	Out of Range	Out of Range	Pass
Invalid Data	3	Set First Name Too Large	abcdefghijkl	First Name Corrupted	First Name Corrupted	Pass
Invalid Data	4	Set Last Name Too Large	abcdefghijklmno	Last Name Corrupted	Last Name Corrupted	Pass
Invalid Data	5	Set Balance Negative	-100	Try Again	Try Again	Pass
Invalid Data	6	Asking for unused account	1 when unused	Account Not In Use	Account Not In Use	Pass

11. Screenshots

Valid 1, 2, 4, 5, 6.

```

C:\Users\ArthuriVA\source\repos\CIS200_LABS\lab07\lab0701\Debug\lab0701.exe

Inputting Specific User Data

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number: 1
First Name: Bill
Last Name: Gates
Balance: 1234.56

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number: 0

Request Specific User Data

Enter 0 To Exit
Enter Account Number: 1
Account Number: 1
First Name: Bill
Last Name: Gates
Balance: $1234.56

Enter 0 To Exit
Enter Account Number:

```

Valid 3, 4, 5, 7.

```
C:\Users\ArthuriVA\source\repos\CIS200_LABS\lab07\lab0701\Debug\lab0701.exe

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number: 100
First Name: Bill
Last Name: Gates
Balance: 1

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number: 0

Request Specific User Data

Enter 0 To Exit
Enter Account Number: 100
Account Number: 100
First Name:    Bill
Last Name:    Gates
Balance:      $1

Enter 0 To Exit
Enter Account Number:
```

Invalid 1, 2.

```
C:\Users\ArthuriVA\source\repos\CIS200_LABS\lab07\lab0701\Debug\lab0701.exe

Inputting Specific User Data

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number: -1
Invalid Account Number

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number: 101
Invalid Account Number

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number:
```

Invalid 3, 4, 5, 6.

```
C:\Users\ArthurIVA\source\repos\CIS200_LABS\lab07\lab0701\Debug\lab0701.exe
Inputting Specific User Data

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number: 2
First Name: abcdefghijk
Last Name: abcdefghijklmnop
Balance: -100
Balance: 1234.56

Please Enter an Account Number (1-100)
Entering 0 Will Exit User Input
Account Number: 0

Request Specific User Data

Enter 0 To Exit
Enter Account Number: 2
Account Number: 2
First Name: p
Last Name: abcdefghijklmnop
Balance: $1234.56

Enter 0 To Exit
Enter Account Number: 1
ACCOUNT NUMBER NOT IN USE

Enter 0 To Exit
Enter Account Number:
```

12. Error Log

Error Type (Logic/Runtime)	Cause of Error	Solution to Error
Logic	Not Resetting accountNumber while checking for valid input.	Include resetting to -1 so that userIn can be compared correctly.

13. Status

Program is working. Just don't stress it out too much, it has anxiety.