

Study Case. Switching and routing




Figure #1. Scenario Topology

Scenario

It is a small to mid-size company with corporate offices and a branch. This company contracted a company to help in the management activities remotely in such a way that they have to make the necessary configurations to allow the company to access the company's servers.

The architecture of the LAN has a hierarchical design (Access, Distribution, Core), which meets the design requirements of a fault tolerant network, scalability, QoS, and security.

Will practice and be evaluated in the following skills:

- A. Configuration of initial device settings
- B. Interface addressing
- C. Configuration of **VLANs** and **trunking**
- D. Routing between **VLANs**
- E. Dynamic routing with **OSPF multiarea**
- F. Configuration of standard, extended **ACLs**
- G. **Switch port security** configuration
- H. Remote switch management configuration
- I. **Syslog** and **NTP** configuration
- J. Interface activation and addressing in IPv4
- K. Static and default routing in IPv4
- L. **Static** and dynamic **NAT** configuration
- M. **DHCP** server configuration
- N. Configure PPP encapsulation and CHAP authentication for serial links.
- O. Configure a GRE tunnel.
- P. Configure dynamic routing OSPF, EIGRP
- Q. Configure BGP.
- R. Configure **standard** and **extended** IPv4 ACLs.
- S. STP
- T. EtherChannel & HSRP

Tasks to do

1. Create the topology in Packet Tracer multiuser mode according to the diagram
2. Design a **VLSM** addressing scheme that meets the needs of the company.
 - a. Three zones
 - b. VLANs
 - c. Segmentos requeridos
 - d. Tablas de distribución de segmentos de redes
 - e. Direcciones IP estáticas para servidores y dispositivos intermedios
 - f. IP dinámicas para dispositivos finales
3. Initial configuration of device values
4. Configure the addressing of the interfaces
5. Configure VLANs and Trunking
6. Configure inter-VLAN required
7. Dynamic routing
 - a. OSPF multiarea en las tres áreas
8. Configuration of standard, extended ACLs
 - a. According to the requirements of the company, create the necessary ACLs::
The company that was hired to assist in the administration remotely can:
 1. Access the HQ servers
 2. El acceso remoto debe ser a través de una conexión segura SSH.
9. **Servers:**
They must have static IP addresses according to the assigned segment. They must also be configured with **static NAT** so that they can be accessed from anywhere in the network.
 - a. WEB
 - b. FTP
 - c. Email
 - d. DHCP
10. **Security**
 - a. Firewall (ACLs)
 - b. Point-to-Point GRE VPN Tunnel between route rA2, rC1
 - c.
11. **Management**
 - a. Configurar los siguientes servicios
 - i. DNS
 - ii. NAT
 - iii. Syslog
 - iv. NTP
12. **LAN**
 - a. Switch port security configuration
 - b. Remote switch management configuration
 - c. VLANs

- i. VLANs (Sales, Accounting, HR, , Production, Management, Native)
 - ii. VTP
 - iii. Inter-VLAN routing
- d. DTP
- e. STP (version)
- f. **Redundancy**
 - i. Configure Etherchannel where necessary, making use of:
 - 1. LACP
 - 2. PAgP
 - ii. HSRP
 - 1. Configure in Router B2, B3

13. NAT

- The servers in the DMZ zone must be configured to have a **static NAT** in such a way that they can be accessed from any part of the internetwork
- **Dynamic NAT** for others situations

14. DHCP

- Configure a DHCP server
- The routers (rB1, rB2, rB3) must be configured as DHCP relay agents

15. DELIVERABLES

Evidences for:

1. VLSM Scheme addressing (addressing tables)
2. Output (screen capture) of evidence of commands where the verification of its operation is shown

NOTE:

Any modification that is required to make over the original topology must be justified to the instructor and reported before performing.

	Direccionamiento	
#	Privado	Público
1	10.0.0.0/8	200.10.0.0/16
2	11.0.0.0/8	200.11.0.0/16
3	12.0.0.0/8	200.12.0.0/16
4	13.0.0.0/8	200.13.0.0/16
5	14.0.0.0/8	200.14.0.0/16
6	15.0.0.0/8	200.15.0.0/16
7	16.0.0.0/8	200.16.0.0/16
8	17.0.0.0/8	200.17.0.0/16
9	18.0.0.0/8	200.18.0.0/16
10	19.0.0.0/8	200.19.0.0/16
11	20.0.0.0/8	200.20.0.0/16
12	21.0.0.0/8	200.21.0.0/16