

ENGINEERING — Road Repair Technical Report

1. System Overview

The Stealth UCAV (GJ-11) is a critical asset in engineering operations. This document covers road repair analysis for the Stealth UCAV platform.

2. Technical Parameters

- IF Bandwidth: 20 MHz
- Peak Power: 45 kW
- Availability: 99.5 %
- EMC Level: GJB 151B
- Effective Range: 150 km

3. Operational Procedures

3.1 Pre-Operation Checks

1. Verify power supply voltage is within specified range
2. Run Built-In Test (BIT) and confirm all PASS
3. Establish communication link with command post
4. Confirm GPS lock with CEP < 10m
5. Log start-up time and initial parameters

3.2 Mission Execution

Monitor system performance indicators continuously. Report any anomaly exceeding threshold within 5 minutes. Maintain log entries at minimum 15-minute intervals

.

4. Fault Diagnosis

- ERR-008: Nav accuracy degraded -> Check subsystem logs and replace module
- ERR-009: FCS computation error -> Check subsystem logs and replace module
- ERR-001: Transmitter power low -> Check subsystem logs and replace module

5. Maintenance Schedule

- Daily Maintenance: Perform ■■
- Annual Maintenance: Perform ■■
- Quarterly Maintenance: Perform ■■■

6. Safety Precautions

- Ensure all personnel maintain safe distance during high-power transmission
- Follow lock-out/tag-out procedures before maintenance
- Report all near-miss incidents within 24 hours
- Maintain radiation exposure records for all personnel

Document ID: ENGINEER-RoadRepair-027

Classification: UNCLASSIFIED // FOR OFFICIAL USE ONLY