

MISSILES — Ballistic Computation Technical Report

1. System Overview

The IRBM (DF-26) is a critical asset in missiles operations. This document covers ballistic computation analysis for the IRBM platform.

2. Technical Parameters

- TX Power: 20 W
- Vibration Grade: MIL-STD-810G
- MTBF: 500 h
- Hop Rate: 500 hop/s
- Detection Range: 60 km

3. Operational Procedures

3.1 Pre-Operation Checks

1. Verify power supply voltage is within specified range
2. Run Built-In Test (BIT) and confirm all PASS
3. Establish communication link with command post
4. Confirm GPS lock with CEP < 10m
5. Log start-up time and initial parameters

3.2 Mission Execution

Monitor system performance indicators continuously. Report any anomaly exceeding threshold within 5 minutes. Maintain log entries at minimum 15-minute intervals

.

4. Fault Diagnosis

- ERR-008: Nav accuracy degraded -> Check subsystem logs and replace module
- ERR-010: Data bus error -> Check subsystem logs and replace module
- ERR-006: Temperature alarm -> Check subsystem logs and replace module

5. Maintenance Schedule

- Weekly Maintenance: Perform ■■
- Annual Maintenance: Perform ■■
- Monthly Maintenance: Perform ■■

6. Safety Precautions

- Ensure all personnel maintain safe distance during high-power transmission
- Follow lock-out/tag-out procedures before maintenance
- Report all near-miss incidents within 24 hours
- Maintain radiation exposure records for all personnel

Document ID: MISSILE-BallisticComputation-003

Classification: UNCLASSIFIED // FOR OFFICIAL USE ONLY