





[illegible]

- ██████████
- ████████████±57 Hz
- ████████████████████80%
- ████████████████
- ██████████████████

Figure 1: Schematic representation of the data structure. The figure shows a grid of data points for eight error types (ERR-001 to ERR-008). Each error type has two columns of data points, each represented by a 4x4 grid of black squares. The columns are separated by a vertical line. The rows are labeled with error types on the left. The columns are labeled with 'ERR-001' and 'ERR-002' at the top, and 'ERR-003' and 'ERR-004' at the bottom. The columns are also labeled with 'ERR-005' and 'ERR-006' at the bottom. The columns are also labeled with 'ERR-007' and 'ERR-008' at the bottom. The columns are also labeled with 'ERR-009' and 'ERR-010' at the bottom.

- GJB 9001C-2017 ■■■■■■■■■■

- GJB 150A-2009 ■■■■■■■■■■■■■■■■■■

- GJB 899A-2009 ■■■■■■■■■■■■

- GJB 450B-2008 ■■■■■■■■■■■■

- GJB 451A-2005 ■■■■■■■■■■■■

- GJB 7869-2012 ■■■■■■■■■■

- GJB 2924-1997 ■■■■■■■■■■■■■■■■■■

- GJB 5309-2004 ■■■■■■■■■■■■

- GJB 792-1990 ■■■■■■■■■■

