

■■■■.■■■■ ■■■■

****■■■■■** GJB-E5AF-005-2024**

****■■■■■** ■■■■ / Missile Weapons**

** [REDACTED] ** [REDACTED]

** [REDACTED] ** [REDACTED]

■■■■■ 2024■■06■■06■

■ ■ ■ ■ ■

1.1 ■■■■■

-2017

1.2 ■■■■

- [REDACTED]

- [REDACTED]

—

- [] [] [] [] [] [] [] [] [] [] []

###

2.1 ■■■■■■

- ■■■HQ-9B■■■200 km■■■GJB 5309-2004

- ■■■HQ-9B■■■0.5-30 km■■■GJB 5309-2004

- ■■■■■■HQ-9B■■■4.2 Ma■■■■■■■■■■

- ■■■■■HQ-9B■■■■■+■■+■■■ ■■■■GJB 5309-2004

- ■■■■HQ-9B■■■180 kg■■■■■■■■■

[REDACTED]

3.1 ■■■■■■■■■■

CEP

CEP

[illegible]

- ██████████
- ████████████ ±55 Hz
- ████████████████████ 80%
- ████████████
- ████████████

Figure 1: Schematic representation of the data structure. The figure shows a grid of data points for eight error types (ERR-001 to ERR-008). Each error type has two columns of data points, each represented by a 4x4 grid of black squares. The columns are separated by a vertical line. The rows are labeled with error codes on the left. The columns are labeled with 'ERR-001' and 'ERR-008' at the top. The grid is divided into two main sections by a vertical line. The left section contains the error codes and the right section contains the data points.

- ■■■■■■■■■■■■■■■■■■■■10■■
- ■■■■■■■■■■■■■■■■■■■■15■■
- ■■■■■■■■■■■■■■■■■■■■5■■
- ■■■■■■■■■■■■■■■■■■■■10■■

6.2

- 80
- 30
-

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#5

GJB 908A-2012
100% AQL 3%

5/
35%

10

65%

25%

+50°C 13 5%
4 3

' '

