

230kN HTPB

132J

3.2

- -40°C +55°C GJB 150A-2009
- 5-500 Hz 0.04 g²/Hz GJB 150.16
- 30g 11ms GJB 150.18
- 95% RH +35°C GJB 150.9
- 5% NaCl 48h GJB 150.11
- EMC GJB 151B-2013 CE102 RE102
- MTBF 400 GJB 899A-2009
- MTTR 3

3.3

-
- BIT 21
-
-
-
-
-

4.1

-
- DC 24V ± 10%
- BIT
- 14°C 76°C
-

4.2

- ██

- ██

- ██ ±2%

- ██

- ██

[illegible]

Figure 1: Schematic representation of the data structure. The figure shows a grid of data points for eight error types (ERR-001 to ERR-008). Each error type has two columns of data points, each represented by a 5x5 grid of black squares. The columns are separated by a vertical line. The rows are labeled with error types on the left. The top row is labeled with 'ERR-001' to 'ERR-008' on the left and 'ERR-001' to 'ERR-008' on the right. The bottom row is labeled with 'ERR-001' to 'ERR-008' on the left and 'ERR-001' to 'ERR-008' on the right. The grid is divided into four quadrants by a vertical line and a horizontal line. The top-left quadrant contains the error types, the top-right quadrant contains the error types, the bottom-left quadrant contains the error types, and the bottom-right quadrant contains the error types.

- ██████████ 52

- ██████████ 78

- ██████████ 26

- ██████████ 52

6.2

- 80
- 30
-

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#26

71%

46%

+50°C 10 5% 4 4

26

16 19

7%

5 3 8

50

(LCC)

26:29