

[REDACTED] . [REDACTED] [REDACTED] [REDACTED]

****■■■■■** GJB-E8A3-007-2024**

****■■■■■** ■■■■ / Armor Vehicles**

** [REDACTED] ** [REDACTED]

[REDACTED] [REDACTED]

****■■■■■** 2024■■08■■08■**

■■■ ■■

1.1 ■■■■■

-2017

1.2 ■■■■

- [REDACTED]

[illegible]

■■■■■■■■

2.1 ■■■■■■

- ■■■■■ ZTZ-99A ■■ 55 t ■■■ GJB 792-1990

- ■■■■■■ZTZ-99A■■■1500 hp■■■GJB 792-1990

- ■■■■■■ZTZ-99A■■■70 km/h■■■■■■■■■■

- ■■■■ZTZ-99A■■■125 mm■■■GJB 792-1990

- ■■■■■ ZTZ-99A ■■41 ■■■■■

■■■■■■■■■■

3.1 ■■■■■■

12345678910111213141516171819202122232425262728293031323334353637383940414243444546474849505152535455565758596061626364656667686970717273747576777879808182838485868788899091929394959697989910010110210310410510610710810911011111211311411511611711811912012112212312412512612712812913013113213313413513613713813914014114214314414514614714814915015115215315415515615715815916016116216316416516616716816917017117217317417517617717817918018118218318418518618718818919019119219319419519619719819920020120220320420520620720820921021121221321421521621721821922022122222322422522622722822923023123223323423523623723823924024124224324424524624724824925025125225325425525625725825926026126226326426526626726826927027127227327427527627727827928028128228328428528628728828929029129229329429529629729829930030130230330430530630730830931031131231331431531631731831932032132232332432532632732832933033133233333433533633733833934034134234334434534634734834935035135235335435535635735835936036136236336436536636736836937037137237337437537637737837938038138238338438538638738838939039139239339439539639739839940040140240340440540640740840941041141241341441541641741841942042142242342442542642742842943043143243343443543643743843944044144244344444544644744844945045145245345445545645745845946046146246346446546646746846947047147247347447547647747847948048148248348448548648748848949049149249349449549649749849950050150250350450550650750850951051151251351451551651751851952052152

150027kW/t

670mm

3.2

- -40°C+55°CGJB 150A-2009
- 5-500 Hz0.04 g²/HzGJB 150.16
- 30g11msGJB 150.18
- 95% RH+35°CGJB 150.9
- 5% NaCl48hGJB 150.11
- EMCGJB 151B-2013CE102RE102
- MTBF500GJB 899A-2009
- MTTR2

3.3

-
- BIT22
-
-
-
-
-

##

4.1

-
- DC 24V ± 10%
- BIT
- 33°C57°C
-

4.2

- ██
- ██
- ██ ±3%
- ██
- ██

[illegible]

Figure 1: Schematic representation of the data structure. The figure shows a grid of data points for eight error types (ERR-001 to ERR-008). Each error type has two columns of data points, each represented by a 4x4 grid of black squares. The columns are separated by a vertical line. The rows are labeled with error types on the left. The columns are labeled with 'ERR-001' to 'ERR-008' at the top. The grid is divided into two main sections by a horizontal line. The top section contains the error types and the bottom section contains the data points.

- GJB 9001C-2017 ■■■■■■■■■■
- GJB 150A-2009 ■■■■■■■■■■■■■■■■■■■■
- GJB 899A-2009 ■■■■■■■■■■■■■■
- GJB 450B-2008 ■■■■■■■■■■■■■■■■
- GJB 451A-2005 ■■■■■■■■■■■■■■■■
- GJB 7869-2012 ■■■■■■■■■■
- GJB 2924-1997 ■■■■■■■■■■■■■■■■■■■
- GJB 5309-2004 ■■■■■■■■■■■■■■
- GJB 792-1990 ■■■■■■■■■■

