



410/

3.2

- ■■■■■■■■■■-40°C■+55°C■■■GJB 150A-2009■■■■■■■■■
- ■■■■5-500 Hz■■■■■■■■■0.04 g²/Hz■■■GJB 150.16■■■■
- ■■■■■■■■■■30g■11ms■■■GJB 150.18■■■■
- ■■■■95% RH■+35°C■■■GJB 150.9■■■■
- ■■■■5% NaCl■■■■■■■■■48h■■■GJB 150.11■■■■
- EMC■■■■GJB 151B-2013■■■■CE102■RE102■■■■
- MTBF■■■■400■■■■■GJB 899A-2009■■■■
- MTTR■■■■■3■■■

1. 
2. 
3. 
4. 
5. 
6. 
7. 

4.1 ■■■■

1. 
2.  DC 24V $\pm$ 10% 
3.  BIT 
4.  -29°C  61°C 
5. 

4.2 ■■■

6.2

- 80
- 30
-

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#11

9

GJB 908A-2012 100% AQL 3%

11 41%

11

71%

31%

+50°C 11 5%

44

'

11