

[illegible]

3.2

- ■■■■■■■■-40°C■+55°C■■■GJB 150A-2009■■■■■■■■■
- ■■■■5-500 Hz■■■■■■■■■0.04 g²/Hz■■■GJB 150.16■■■■
- ■■■■■■■■■■30g■11ms■■■GJB 150.18■■■■
- ■■■■95% RH■+35°C■■■GJB 150.9■■■■
- ■■■■5% NaCl■■■■■■■■■48h■■■GJB 150.11■■■■
- EMC■■■■GJB 151B-2013■■■■CE102■RE102■■■■
- MTBF■■■■600■■■■■GJB 899A-2009■■■■
- MTTR■■■■■1■■■

[illegible]

4.1 ■■■■

1. 
2.  DC 24V $\pm$ 10% 
3.  BIT 
4.  -37°C  53°C 
5. 

4.2 ■■■

- ██

- ██

- ██ ±4%

- ██

- ██

[illegible]

Figure 1: Schematic representation of the data structure. The figure shows a grid of data points for eight error types (ERR-001 to ERR-008). Each error type has two columns of data points, each represented by a 4x4 grid of black squares. The columns are separated by a vertical dashed line. The rows are labeled with error codes on the left.

- ██████████6███
- ██████████9███
- ██████████3███
- ██████████6███

6.2

- 80
- 30
-

##

7.1

-
- 1.
 - 2.
 - 3.
 - 4.
 - 5.

7.2

-
- -30°C +50°C
- 80%
-
-

7.3

-
-
-
- GJB 5313-2004

7.4

-
- CO
 -
 -
 -

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#3

61927

(LCC)3:6

43%

11

GJB 908A-2012100%AQL1%

333%

13

63%

23%

#####+50°C#####11#####5%
#####2#####6#####

#####'#####'
#####3#####

#####13#####
#####10#####

#13

#####73%#####

#####33%#####
#####

#####+50°C#####13#####5%
#####3#####6#####

#####'#####'
#####13#####

#####13#####
#####20#####

#####10%
#####

#####4#####2#####7%
#####37#####

#####(LCC)#####
#####13:16#####

#####53%#

#####11#####
#####

