

[REDACTED] . [REDACTED] [REDACTED] [REDACTED]

****■■■■■** GJB-E980-026-2024**

■■■■■ ■■■■ / Communications Equipment

** [REDACTED] ** [REDACTED]

■■■■ 2024■■03■■27■

###

1.1 ■■■■■

-2017

1.2 ■■■■

- [REDACTED]

1	2	3	4	5	6	7	8	9	10	11	12
---	---	---	---	---	---	---	---	---	----	----	----

—

[] [] [] [] [] [] [] []

2.1 ■■■■■■

- ■■■■■ ZBD-2000 ■■ 30-512 MHz ■■■ GJB 2924-1997

- ■■■■■ ZBD-2000 ■■■ 5/20/50 W■■■■ GJB 2924-1997

- ■■■■■■ZBD-2000■■■-40~+55 °C■■■■GJB 150A-2009

- ■■■■■ ZBD-2000 ■■■ IP67 ■■■ GJB 4206-2000

- ■■■■ZBD-2000■■■3.5 kg■■■■■

              

3.1 ■■■■■■■■■■

Downloaded from <http://ajph.org/> on November 10, 2014

(SDF)

- ██
- ██
- ██ ±2%
- ██
- ██

[illegible]

Figure 1: Schematic representation of the data structure. The figure shows a grid of data points for eight error types (ERR-001 to ERR-008). Each error type has two columns of data points, each represented by a 5x5 grid of black squares. The columns are separated by a vertical line. The rows are labeled with error types on the left. The top row is labeled with 'ERR-001' to 'ERR-008' on the left and 'ERR-001' to 'ERR-008' on the right. The top row of data points is labeled with 'ERR-001' to 'ERR-008' on the left and 'ERR-001' to 'ERR-008' on the right. The top row of data points is labeled with 'ERR-001' to 'ERR-008' on the left and 'ERR-001' to 'ERR-008' on the right.

- ██████████ 52

- ██████████ 78

- ██████████ 26

- ██████████ 52

6.2

- 80
- 30
-

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#26

71%

46%

+50°C 10 5% 4 4

26

16 19

7%

5 3 8

50

(LCC)

26:29