



450/

3.2

- -40°C+55°C GJB 150A-2009
- 5-500 Hz 0.04 g²/Hz GJB 150.16
- 30g 11ms GJB 150.18
- 95% RH +35°C GJB 150.9
- 5% NaCl 48h GJB 150.11
- EMC GJB 151B-2013 CE102 RE102
- MTBF 300 GJB 899A-2009
- MTTR 1

1. 
2. 
3. 
4. 
5. 
6. 
7. 

4.1 ■■■■

1. 
2.  DC 24V $\pm$ 10% 
3.  BIT 
4.  -25°C  65°C 
5. 

4.2 ■■■

6.2

- 80
- 30
-

##

7.1

-
- 1.
 - 2.
 - 3.
 - 4.
 - 5.

7.2

-
- -30°C +50°C
- 80%
-
-

7.3

-
-
-
- GJB 5313-2004

7.4

-
- CO
 -
 -
 -

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#15

158

12%

61939

(LCC)15:18

55%

8

GJB 908A-2012100%AQL1%

15%/45%

10

