




510/

3.2

- ■■■■■■■■■■-40°C■+55°C■■■GJB 150A-2009■■■■■■■■■
- ■■■■5-500 Hz■■■■■■■■■0.04 g²/Hz■■■GJB 150.16■■■■
- ■■■■■■■■■■30g■11ms■■■GJB 150.18■■■■
- ■■■■95% RH■+35°C■■■GJB 150.9■■■■
- ■■■■5% NaCl■■■■■■■■■48h■■■GJB 150.11■■■■
- EMC■■■GJB 151B-2013■■■CE102■RE102■■■■
- MTBF■■■■400■■■■■GJB 899A-2009■■■■
- MTTR■■■■1■■■

1. 
2. BIT16
3. 
4. 
5. 
6. 
7. 

4.1 ■■■■

1. 
2.  DC 24V $\pm$ 10% 
3.  BIT 
4.  -19°C  71°C 
5. 

4.2 ■■■

Page 10 of 10

- [illegible]

4.3 ■■■■

Page 10 of 10

- [illegible]

■■■ ■■■■■■■■

5.1 ■■■■■■

☐ ☐ ☐ ☐ | ☐ ☐ ☐ ☐ | ☐ ☐ ☐ ☐ |

A horizontal number line with four vertical tick marks, creating three equal segments. Each segment contains a dashed line for a missing number.

| ERR-001 | ■■■■ | ■■■■■■■■■■ |

| ERR-002 | ■■■■ | ■■■■■■■■■■ |

| ERR-003 | ■■■■ | ■■■■■■■■■■ |

| ERR-004 | ■■■■ | ■■■■■■■■■■ |

| ERR-005 | ■■■■ | ■■■■■■■■■■ |

| ERR-006 | ■■■■ | ■■■■■■■■■■ |

| ERR-007 | ■■■■ | ■■■■■■■■ |

| ERR-008 | ■■■■ | ■■■■■■■■■■ |

■■■ ■■■■■

6.1 ■■■■

■■■■■24■■■

XXXXXXXXXXXXXXXXXXXXXXXXXXXX

5/5/2014

- ██████████ 42
- ██████████ 63
- ██████████ 21
- ██████████ 42

6.2

- 80
- 30
-

##

7.1

-
- 1.
 - 2.
 - 3.
 - 4.
 - 5.

7.2

-
- -30°C +50°C
- 80%
-
-

7.3

-
-
-
- GJB 5313-2004

7.4

-
- CO
 -
 -
 -

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#21

' ' 21

11 14

10%

6 1 15 45

(LCC) 21:24

61%

9

GJB 908A-2012 100% AQL 1%

21 51%

