

■■■■.■■■■ ■■■■

****■■■■■** GJB-E980-020-2024**

****■■■■■** ■■■■ / Communications Equipment**

** ☐ ☐ ☐ ☐ ** ☐ ☐ ☐ ☐

** [REDACTED] ** [REDACTED]

********* 20240921

■■■ ■■

1.1 ■■■■■

[illegible]

1.2 ■■■■

- 
- 
- 
- 

■■■ ■■■■■■■■

2.1 ■■■■■■

- ■■■■■ZBD-2000■■■30-512 MHz■■■GJB 2924-1997
- ■■■■■ZBD-2000■■■5/20/50 W■■■GJB 2924-1997
- ■■■■■ZBD-2000■■■-40~+55 °C■■■GJB 150A-2009
- ■■■■■ZBD-2000■■■IP67 ■■■GJB 4206-2000
- ■■■■ZBD-2000■■■3.5 kg■■■■■

■■■ ■■■■■■■■

3.1 ■■■■■■■■■■

(SDF)


500

3.2

- ■■■■■■■■■■-40°C■+55°C■■■GJB 150A-2009■■■■■■■■■
- ■■■■5-500 Hz■■■■■■■■■0.04 g²/Hz■■■GJB 150.16■■■■
- ■■■■■■■■■■30g■11ms■■■GJB 150.18■■■■
- ■■■■95% RH■+35°C■■■GJB 150.9■■■■
- ■■■■5% NaCl■■■■■■■■■48h■■■GJB 150.11■■■■
- EMC■■■GJB 151B-2013■■■■CE102■RE102■■■■
- MTBF■■■■300■■■■■GJB 899A-2009■■■■
- MTTR■■■■3■■■

1. 
2.  BIT  15 
3. 
4. 
5. 
6. 
7. 

4.1 ■■■■

1. 
2.  DC 24V $\pm$ 10% 
3.  BIT 
4.  -20°C  70°C 
5. 

4.2 ■■■

6.2

- 80
- 30
-

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#20

40%

+50°C 12 5% 4 3

20

10 13

9%

5 3 14 44

(LCC)

