


440

3.2

- ■■■■■■■■■■-40°C■+55°C■■■GJB 150A-2009■■■■■■■■■
- ■■■■5-500 Hz■■■■■■■■■0.04 g²/Hz■■■GJB 150.16■■■■
- ■■■■■■■■■■30g■11ms■■■GJB 150.18■■■■
- ■■■■95% RH■+35°C■■■GJB 150.9■■■■
- ■■■■5% NaCl■■■■■■■■■48h■■■GJB 150.11■■■■
- EMC■■■GJB 151B-2013■■■CE102■RE102■■■■
- MTBF■■■■700■■■■■GJB 899A-2009■■■■
- MTTR■■■■■3■■■

[illegible]

4.1 ■■■■

1. 
2.  DC 24V $\pm$ 10% 
3.  BIT 
4.  -26°C  64°C 
5. 

4.2 ■■■

6.2

- 80
- 30
-

A

- GJB 9001C-2017
- GJB 150A-2009
- GJB 899A-2009
- GJB 450B-2008
- GJB 451A-2005
- GJB 7869-2012
- GJB 2924-1997
- GJB 5309-2004
- GJB 792-1990
- GJB 7866-2012

#14

+50°C 14 5% 4 7

' ' 14

14 7

11%

5 3 8 38

(LCC) 14:17

