# **Booleans**

https://csci-1301.github.io/about#authors

June 12, 2021 (11:21:53 AM)

### **Contents**

1	Truth Tables	J
2	Precedence and Order of Evaluation	2
	2.1 Reading and Understanding	2
	2.2 Computing Simple Boolean Expressions	4
	2.3 Computing Expressions Involving Booleans and Numerical Values	5

This lab serves four core goals: - To help you manipulate boolean values, - To practice boolean operators, - To understand the concept of *precedence*, - To practice simple mental calculations.

## 1 Truth Tables

1. Copy-and-paste the following code into the Main method of a new project:

```
Console.WriteLine("Conjunction (and, &&) truth table:"
+ "\n\n && ||\t" + true+ "\t| " + false
+ "\n-----|------"
+ "\n" + true + " ||\t" + (true && true)+ "\t| " + (true && false)
+ "\n" + false+ " ||\t" + (false && true)+ "\t| " + (false && false)
+ "\n\n*-*-*-*-*-*-*-*-*-*-*-*-*\n");

Console.WriteLine("Negation (not, !) truth table:"
+ "\n\n value ||\t ! \t "
+ "\n-----"
+ "\n" + true+ "\t ||\t" + false
+ "\n" + (!true)+ "\t ||\t" + (!false)
+ "\n\n*-*-*-*-*-*-*-*-*-*-*-");
```

- 1. Compile and execute it. This should display to the screen truth tables for conjunction (and, &&) and negation (not, !).
- 2. Make sure you understand both the code and its output.
- 3. Add after the truth table for the negation, write code to display truth tables for
  - a) the binary operators disjunction (or, ||),
  - b) identity (equality, ==) and
  - c) difference (inequality, !=). Normally, using the find-and-replace feature of your IDE should make this a quick and easy task.

4. You can make sure you completed this exercise correctly by checking that your output match the truth tables on wikipedia for disjunction<sup>1</sup> and equality<sup>2</sup>. For inequality, in this case check against the table for exclusive disjunction<sup>3</sup>. Exclusive disjunction (XOR) is conceptually different than inequality, but has the same truth table.

# 2 Precedence and Order of Evaluation

## 2.1 Reading and Understanding

If you read the documentation on operator precedence<sup>4</sup>, you will see that operators are evaluated in a particular order. From higher precedence (that is, evaluated first) to lower precedence (that is, evaluated last), this order is: | (\* / %) (+ -) (< > <= >=) (== !=) && | |. Inside each group in parenthesis, operations are evaluated from left to right.

So that, for instance, ! true | | false && 3 \* 2 == 6 will be evaluated as

Note that an expression like !3 > 2 doesn't make any sense: C# would try to take the negation of 3, but you can't negate the truth value of an integer! Along the same lines, an expression like false \* true doesn't make any sense: you can not multiply booleans (what would be "true times false"?)! Similarly, 3 % false will cause an error: can you see why? These are all examples of "illegal" expressions.

#### 2.2 Computing Simple Boolean Expressions

Evaluate the following expressions. Try to do this "by hand," and write your answers down on paper.

```
true && false || true
!true && false
false || true && !false
false == !true || false
!(true || false || true && true)
!(true || false) && (true && !false)
!true || false && (true && !false)
true != !(false || true)
```

#### 2.3 Computing Expressions Involving Booleans and Numerical Values

For each of the following expressions, decide if it is "legal" or not. If it is, give the result of its evaluation.

• 3 > 2

 $<sup>^{-1}</sup> https://en.wikipedia.org/wiki/Truth\_table\#Logical\_disjunction\_(OR)$ 

<sup>&</sup>lt;sup>2</sup>https://en.wikipedia.org/wiki/Truth\_table#Logical\_equality

<sup>&</sup>lt;sup>3</sup>https://en.wikipedia.org/wiki/Truth\_table#Exclusive\_disjunction

<sup>&</sup>lt;sup>4</sup>https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/operators/#operator-precedence

- 2 == 4
- 3 >= 2 != false
- 3 > false
- true && 3 + 5 \* 8 == 43
- 3 + true != false