

Constructors and ToString Methods

Principles of Computer Programming I
Spring/Fall 20XX



AUGUSTA
UNIVERSITY


Outline

- Instance variables and default values
- Constructors
 - Definition and usage
 - Multiple constructors
- ToString Methods

Remember This Lab Activity?

```
class Program
{
    static void Main(string[] args)
    {
        Rectangle myRect = new Rectangle();
        Console.WriteLine($"Length is {myRect.GetLength()}");
        Console.WriteLine($"Width is {myRect.GetWidth()}");
    }
}
```

No SetLength or SetWidth




Output:

```
Length is 0
Width is 0
```

Variables and Default Values

- **Local** variables have **no** default value: you must assign them a value before using them

```
int myVar1;  
int myVar2 = myVar1 + 5;
```




Error! Can't use unassigned variable myVar1

- **Instance** variables (in an object) have default values:

Type	Default Value
Numeric types	0
string	null
bool	false
char	'\0'

Example Class: Classroom

- UML diagram for the class:



ClassRoom Implementation

```
class Classroom
{
    private string building;
    private int number;

    public void SetBuilding(string buildingParam) ← Set accessor for building
    {
        building = buildingParam;
    }
    public string GetBuilding() ← Get accessor for building
    {
        return building;
    }
}
```

ClassRoom Implementation

```
public void SetNumber(int numberParam) ← Set accessor for number
{
    number = numberParam;
}
public int GetNumber() ← Get accessor for number
{
    return number;
}
}
```

Default Values for Classroom

```
static void Main(string[] args)
{
    Classroom english = new Classroom();
    Console.WriteLine($"Building is {english.GetBuilding()}");
    Console.WriteLine($"Room number is {english.GetNumber()}");
}
```

What will this print?

Output:

```
Building is 
Room number is 0
```

A null string prints nothing


Outline

- Instance variables and default values
- **Constructors**
 - Definition and usage
 - Multiple constructors
- ToString Methods

Object Instantiation

- Look carefully at instantiation syntax:

```
ClassRoom english = new ClassRoom();
```



Parentheses, just like a method call
e.g. GetBuilding()

- Instantiation does call a method: the **constructor**
- Constructor: A method that creates an instance of an object
- If you don't write one, C# generates a “default” constructor

Constructor Syntax

- Method name must equal class name
- No return type, not even void
 - Output of method is always an instance of the class

```
class Classroom
{
    public Classroom(string buildingParam, int numberParam)
    {
        //body of constructor goes here...
    }
}
```

Diagram illustrating the syntax of a constructor for the `ClassRoom` class:

- `public`: Access modifier
- `ClassRoom`: Parameter type (must match the class name)
- `buildingParam`: Parameter name
- `,`: comma
- `int`: Parameter type
- `numberParam`: second parameter
- `//body of constructor goes here...`: Body of the constructor

Constructor Implementation

- Constructor “sets up” object
- Body of constructor: assign values to all instance variables

```
class Classroom
{
    public Classroom(string buildingParam, int numberParam)
    {
        building = buildingParam;
        number = numberParam;
    }
```

Instance variables hidden to save space

no return statement – return value is “this object”

Constructor Usage


- Instantiation calls a constructor
- Just like other method calls, arguments go in parentheses

Instantiation with new

First argument:

Second argument:

```
static void Main(string[] args)
{
    Classroom csci = new Classroom("Allgood East", 356);
    Console.WriteLine($"Building is {csci.GetBuilding()}");
    Console.WriteLine($"Room number is {csci.GetNumber()}");
}
```



Output:

```
Building is Allgood East
Room number is 356
```

Multi-Parameter Methods

- Can use same syntax for ordinary methods, e.g. in Rectangle:

```
public void MultiplyBoth(int lengthFactor, int widthFactor)
{
    length *= lengthFactor;
    width *= widthFactor;
}
```

- Use it like this:

```
myRect.SetLength(5);
myRect.SetWidth(10);
myRect.MultiplyBoth(3, 5);
```

Now myRect has
length 15 and width 50

Multi-Parameter Methods

- Order of arguments matters

```
myRect.MultiplyBoth(3, 5);
```

lengthFactor widthFactor

```
myRect.MultiplyBoth(5, 3);
```

lengthFactor widthFactor

- Types must match

```
ClassRoom csci = new ClassRoom(356, "Allgood East");
```

buildingParam, must
be a string

numberParam, must
be an int



Error!

Outline

- Instance variables and default values
- Constructors
 - Definition and usage
 - **Multiple constructors**
- ToString Methods

C# Constructor Rules

- If you don't write a constructor, C# generates a “default” one
 - Sets instance variables to their default values
- If you do write a constructor, no “default” constructor is generated
 - Now that we've written a Classroom constructor, this doesn't work:

```
ClassRoom csci = new ClassRoom();
```



Error! Constructor requires 2 arguments

- What if we still want the no-argument constructor?

Multiple Constructors

```
class Classroom
{
    public Classroom(string buildingParam, int numberParam)
    {
        building = buildingParam;
        number = numberParam;
    }
    public Classroom()
    {
        building = null;
        number = 0;
    }
}
```

Instance variables hidden to save space

Constructor with no parameters

Same as C#'s default constructor

Which Constructor is Called?

- Instantiation calls the constructor that matches the arguments

```
static void Main(string[] args)
```

```
{
```

```
    Classroom csci = new Classroom("Allgood East", 356);
```

```
    //csci has building = "Allgood East" and number = 356
```

```
    Classroom english = new Classroom();
```

```
    //english has building = null and number = 0;
```

```
}
```

string, int:
Matches first
constructor

No arguments: matches
second constructor

Outline

- Instance variables and default values
- Constructors
 - Definition and usage
 - Multiple constructors
- **ToString Methods**

Converting Numbers to Strings

- Recall: String interpolation uses ToString “behind the scenes”
- ToString() method returns the object converted to a string

Result: “42”

```
int num = 42;  
string intText = num.ToString();  
Console.WriteLine($"num is {num}");  
Console.WriteLine($"num is {num.ToString()}");
```

This is the same as this

- C# datatypes already have ToString() defined, but your classes need their own ToString()

Writing ToString

- Header of a ToString method is always the same

Keyword override: ToString is defined in parent class object

```
class Classroom
{
    public override string ToString()
    {
        return building + " " + number;
    }
}
```

Access must be public

Return type

No parameters

String concatenation

Automatically calls number.ToString()

- Body of ToString: return a string representation of the object

Using ToString

- ToString() will be called automatically when your object needs to be converted to a string
- Can also call it “explicitly” like any other method

```
static void Main(string[] args)
{
    Classroom csci = new Classroom("Allgood East", 356);
    Console.WriteLine(csci);
    Console.WriteLine($"The classroom is {csci}");
    Console.WriteLine("The classroom is " + csci.ToString());
}
```

Summary

- Instance variables and default values
- Constructors
 - Definition and usage
 - Multiple constructors
- ToString Methods