

# Booleans

<https://csci-1301.github.io/about#authors>

June 7, 2021 (10:03:16 PM)

## Contents

<b>1 Truth Tables</b>	<b>1</b>
<b>2 Precedence and Order of Evaluation</b>	<b>2</b>
2.1 Reading and Understanding . . . . .	2
2.2 Computing Simple Boolean Expressions . . . . .	2
2.3 Computing Expressions Involving Booleans and Numerical Values . . . . .	2

This lab serves four core goals: - To help you manipulate boolean values, - To practice boolean operators, - To understand the concept of *precedence*, - To practice simple mental calculations.

## 1 Truth Tables

1. Copy-and-paste the following code into the `Main` method of a new project:

```
Console.WriteLine("Conjunction (and, &&) truth table:")
+ "\n\n &&    ||\t" + true + "\t| " + false
+ "\n-----|-----|-----"
+ "\n" + true + "    ||\t" + (true && true) + "\t| " + (true && false)
+ "\n" + false + "    ||\t" + (false && true) + "\t| " + (false && false)
+ "\n\n*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-\n");
```

```
Console.WriteLine("Negation (not, !) truth table:")
+ "\n\n value    ||\t ! \t "
+ "\n-----|-----"
+ "\n" + true + "\t ||\t" + false
+ "\n" + (!true) + "\t ||\t" + (!false)
+ "\n\n*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-\n");
```

1. Compile and execute it. This should display to the screen truth tables for conjunction (and, `&&`) and negation (not, `!`).
2. Make sure you understand both the code and its output.
3. Add after the truth table for the negation, write code to display truth tables for
  - a) the binary operators disjunction (or, `||`),
  - b) identity (equality, `==`) and
  - c) difference (inequality, `!=`). Normally, using the find-and-replace feature of your IDE should make this a quick and easy task.

4. You can make sure you completed this exercise correctly by checking that your output match the truth tables on wikipedia for disjunction<sup>1</sup> and equality<sup>2</sup>. For inequality, in this case check against the table for exclusive disjunction<sup>3</sup>. Exclusive disjunction (XOR) is conceptually different than inequality, but has the same truth table.

## 2 Precedence and Order of Evaluation

### 2.1 Reading and Understanding

If you read the documentation on operator precedence<sup>4</sup>, you will see that operators are evaluated in a particular order. From higher precedence (that is, evaluated first) to lower precedence (that is, evaluated last), this order is: `! (* / %) (+ -) (< > <= >=) (== !=) && ||`. Inside each group in parenthesis, operations are evaluated from left to right.

So that, for instance, `! true || false && 3 * 2 == 6` will be evaluated as

<code>! true    false &amp;&amp; 3 * 2 == 6</code>	$\Rightarrow$	<code>false    false &amp;&amp; 3 * 2 == 6</code>
<code>false    false &amp;&amp; 3 * 2 == 6</code>	$\Rightarrow$	<code>false    false &amp;&amp; 6 == 6</code>
<code>false    false &amp;&amp; 6 == 6</code>	$\Rightarrow$	<code>false    false &amp;&amp; true</code>
<code>false    false &amp;&amp; true</code>	$\Rightarrow$	<code>false    false</code>
<code>false    false</code>	$\Rightarrow$	<code>false</code>

Note that an expression like `!3 > 2` doesn't make any sense: C# would try to take the negation of `3`, but you can't negate the truth value of an integer! Along the same lines, an expression like `false * true` doesn't make any sense: you can not multiply booleans (what would be "true times false"?). Similarly, `3 % false` will cause an error: can you see why? These are all examples of "illegal" expressions.

### 2.2 Computing Simple Boolean Expressions

Evaluate the following expressions. Try to do this "by hand," and write your answers down on paper.

- `true && false || true`
- `!true && false`
- `false || true && !false`
- `false == !true || false`
- `!(true || false || true && true)`
- `!(true || false) && (true && !false)`
- `!true || false && (true && !false)`
- `true != !(false || true)`

### 2.3 Computing Expressions Involving Booleans and Numerical Values

For each of the following expressions, decide if it is "legal" or not. If it is, give the result of its evaluation.

- `3 > 2`

<sup>1</sup>[https://en.wikipedia.org/wiki/Truth\\_table#Logical\\_disjunction\\_\(OR\)](https://en.wikipedia.org/wiki/Truth_table#Logical_disjunction_(OR))

<sup>2</sup>[https://en.wikipedia.org/wiki/Truth\\_table#Logical\\_equality](https://en.wikipedia.org/wiki/Truth_table#Logical_equality)

<sup>3</sup>[https://en.wikipedia.org/wiki/Truth\\_table#Exclusive\\_disjunction](https://en.wikipedia.org/wiki/Truth_table#Exclusive_disjunction)

<sup>4</sup><https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/operators/#operator-precedence>

- `2 == 4`
- `3 >= 2 != false`
- `3 > false`
- `true && 3 + 5 * 8 == 43`
- `3 + true != false`