

Using static keyword

<https://csci-1301.github.io/about#authors>

July 5, 2021 (02:35:08 PM)

Contents

1	Static classes	1
1.1	static Calculator	2
2	Static members in non-static class	2

1 Static classes

One use case for static classes is creating utility classes (or “helper class”) that contain related and frequently-used methods; making those methods easily callable anywhere in the program. Some examples of static classes in C# are `Math` and `Console` class.

Pay attention to how these classes are used:

- `Console` object is never instantiated before use
- `WriteLine` method is called referring to the *name of the class* (not some object)

```
using System;

class Program {
    static void Main() {
        Console.WriteLine("calling a static method");
    }
}
```

Using your IDE, see what happens if you do the following:

```
using System;

class Program {
    static void Main() {
        Console test = new Console();
    }
}
```

Indeed, it is *not possible* to instantiate an object when a class is declared `static`. Further, in a static class, all class members (attributes, methods, constructors, etc.) must also be declared `static`.

1.1 static Calculator

In your IDE create a new project. Then add a new class file called `Calculator.cs`

In `Calculator.cs`:

1. Declare a **static** class and name it `Calculator`.
2. Next add 5 **public** methods to `Calculator` class. Each method takes 2 arguments, `x` and `y`, of type **double**:
 - a) `Add` method that returns result of `x + y`.
 - b) `Subtract` method that returns result of `x - y`.
 - c) `Multiply` method that returns result of `x * y`.
 - d) `Divide` method that returns result of `x / y`.
 - e) `Modulo` method that returns result of `x % y`.

After implementing `Calculator`,

1. Open the file that contains program's `Main` method
2. Paste the following code inside `Main` method:

```
double x = 10d, y = 2d;

Console.WriteLine($"{x} + {y} = {Calculator.Add(x, y)}");
Console.WriteLine($"{x} - {y} = {Calculator.Subtract(x, y)}");
Console.WriteLine($"{x} * {y} = {Calculator.Multiply(x, y)}");
Console.WriteLine($"{x} / {y} = {Calculator.Divide(x, y)}");
Console.WriteLine($"{x} % {y} = {Calculator.Modulo(x, y)}");
```

Again, notice how

- no instance of `Calculator` is created before use, and
 - each `Calculator` method is called referring to the *name of the class*.
3. Execute the program
 - If your implementation of `Calculator` class matches the instructions, you will see meaningful output after executing the program.
 - Otherwise review the instructions again and retrace your implementation steps to resolve any issues.

Review `Calculator`¹ for a sample solution.

2 Static members in non-static class

A non-static class can contain both static or non-static class members.

Study the following program implementation, but do not execute it. After reading through the implementation, answer the follow-up questions below.

“`Student.cs`”

¹`Calculator.zip`

```

using System;

class Student{

    private int id;
    private string name;
    private static string universityName = "Augusta University";
    private static int studentCount = 0;

    public Student(int id, string name){
        this.id = id;
        this.name = name;
        studentCount++;
    }

    public static void DisplayStudentCount(){
        Console.WriteLine($"Number of students: {studentCount}");
    }

    public override string ToString(){
        return $"id: {id}\n"+
            $"name: {name}\n"+
            $"university: {universityName}";
    }
}

```

“Program.cs”

```

using System;

class Program {
    static void Main() {

        Student alice = new Student(1111, "Alice");
        Console.WriteLine(alice);

        Student.DisplayStudentCount(); // first time

        Student bob = new Student(1112, "Bob");
        Console.WriteLine(bob);

        Student.DisplayStudentCount(); // second time
    }
}

```

1. How many static attributes does **Student** class have?
2. What is the output of each of the following lines in “Program.cs”
 - a) `Console.WriteLine(alice);`
 - b) `Student.DisplayStudentCount();` *// first time*
 - c) `Console.WriteLine(bob);`
 - d) `Student.DisplayStudentCount();` *// second time*
3. if the `studentCount` attribute was *not* **static**, what would be the output of:
 - a) `Student.DisplayStudentCount();` *// first time*
 - b) `Student.DisplayStudentCount();` *// second time*

4. When a class contains both static and non-static members, is it possible to refer to non-static members inside a static method? For example, if we try to refer to `name` attribute inside `DisplayStudentCount`, will it work? Why or why not?

Check your answers by downloading and extracting Student² and executing it. To check the last question, uncomment line 16 in downloaded version of “Student.cs”.

²Student.zip