

OPERATORS

| Arithmetic | Comparison | Logical |
|---|---|---|
| <div><div><div><div><div>{v} + {v}</div><div>{v} - {v}</div><div>{v} * {v}</div><div>{v} / {v}</div><div>{v} % {v}</div></div></div></div></div> | <div><div><div><div><div>{v} < {v}</div><div>{v} <= {v}</div><div>{v} = {v}</div><div>{v} >= {v}</div><div>{v} > {v}</div><div>{v} <> {v}</div></div></div></div></div> | <div><div><div>NOT {cd}</div><div>Displays a record if the condition(s) is NOT TRUE</div></div><div><div>EXISTS({s})</div><div>TRUE if the subquery returns one or more records</div></div><div><div>{cd} AND {cd} {cd} & {cd}</div><div>TRUE if all the conditions separated by AND is TRUE</div></div><div><div>{cd} OR {cd} {cd} {cd}</div><div>TRUE if any of the conditions separated by OR is TRUE</div></div><div><div>{v} {cp} ALL({s})</div><div>TRUE if all of the subquery values meet the condition</div></div><div><div>{v} {cp} ANY({s} {v} {cp} SOME({s})</div><div>TRUE if any of the subquery values meet the condition</div></div><div><div>{v} IN({s})</div><div>TRUE if the operand is equal to one of a list of expressions</div></div><div><div>{v} BETWEEN {v} AND {v}</div><div>TRUE if the operand is within the range of comparisons</div></div><div><div>{v} LIKE '%_'</div><div>TRUE if the operand matches a pattern</div></div></div> |
| Bitwise | | |
| <div><div><div><div><div>{v} & {v}</div><div>{v} {v}</div><div>{v} ^ {v}</div></div></div></div></div> | | |
| Compound | | |
| <div><div><div><div><div>{v} += {v}</div><div>{v} -= {v}</div><div>{v} *= {v}</div><div>{v} /= {v}</div><div>{v} %= {v}</div></div><div><div>{v} &= {v}</div><div>{v} = {v}</div><div>{v} ^= {v}</div></div></div></div></div> | | |

DATATYPE

| String | Numeric | | Date & Time |
|--|--|--|---|
| BINARY(size) parameter size : [1-255] default = 1 VARBINARY(size) parameter size : [1;65 535] | BIT(size) parameter size : [1,64] default = 1 BOOL BOOLEAN values : [0;1] | | DATE format : YYYY-MM-DD values : [1000-01-01; 9999-12-31] DATETIME(fsp) format : YYYY-MM-DD hh:mm:ss values : [1000-01-01 00:00:00; 9999-12-31 23:59:59] TIMESTAMP(fsp) format : YYYY-MM-DD hh:mm:ss values : [1970-01-01 00:00:01; 2038-01-09 03:14:07] TIME(fsp) format : hh:mm:ss values : [-838:59:59; 838:59:59] YEAR format : YYYY values : [0000] & [1901;2155] |
| CHAR(size) parameter size : [1;255] default = 1 VARCHAR(size) parameter size : [1;65 535] TINYTEXT values : [0;255] TEXT(size) parameter size : [1;65 535] MEDIUMTEXT values : [0;16 777 215] LONGTEXT values : [0;4 294 967 295] | TINYINT(size) parameter size : [1,255] values : [-128;127] SMALLINT(size) parameter size : [1,255] values : [-32 768;32 767] MEDIUMINT(size) parameter size : [1,255] values : [-8 388 608;8 388 607] INT(size) INTEGER(size) parameter size : [1,255] values : [-2 147 483 648; 2 147 483 647] BIGINT(size) parameter size : [1,255] values : [-9 223 372 036 854 775 808; 9 223 372 036 854 775 807] | UNSIGNED TINYINT(size) values : [0;255] UNSIGNED SMALLINT(size) values : [0;65 535] UNSIGNED MEDIUMINT(size) values : [0;16 777 215] UNSIGNED INT(size) UNSIGNED INTEGER(size) values : [0;4 294 967 295] UNSIGNED BIGINT(size) values : [0;18 446 744 073 709 551 615] | |
| ENUM('val1', '...', 'val65535') SET('val1', '...', 'val64') | | | |
| TINYBLOB values : [0;255] BLOB(size) parameter size : [0;65 535] values : [0;65 535] MEDIUMBLOB values : [0;16 777 215] LOBLOB values : [0;4 294 967 295] | FLOAT(size, d) parameter size : [1;65] default 10, parameter d : [0,30] default 0 FLOAT(p) parameter p : [0;53] DEC(size, d) DECIMAL(size, d) parameter size : [1;65] default 10 parameter d : [0,30] default 0 | DOUBLE(size, d) parameter size : [1;65] default 10 parameter d : [0,30] default 0 DOUBLE PRECISION(size, d) parameter size : [1;65] default 10 parameter d : [0,30] default 0 | |

{?} : doit être remplacé:
cd : condition

cp : op. de comparaison

dt : datatype

f : formats

s : requête select

u : units

v : valeur

FUNCTIONS

| String | Numeric |
|---|---|
| <p>SPACE(number) Returns a string of the specified number of space characters</p> <p>FORMAT(number, decimal_place) Formats a number to a format like "#,###,###.##", rounded to a specified number of decimal places</p> <p>LOWER(string) LCASE(string) Converts a string to lower-case</p> <p>UCASE(string) UPPER(string) Converts a string to upper-case</p> <p>LTRIM(string) Removes leading spaces from a string</p> <p>RTRIM(string) Removes trailing spaces from a string</p> <p>TRIM(string) Removes leading and trailing spaces from a string</p> <p>LPAD(str, length, lpad_str) Left-pads a string with another string, to a certain length</p> <p>RPAD(string, length, rpad_string) Right-pads a string with another string, to a certain length</p> <p>REPEAT(string, number) Repeats a string as many times as specified</p> <p>LEFT(string, number_of_chars) Extracts a number of characters from a string (starting from left)</p> <p>MID(string, start, length) SUBSTR(string, start, length) SUBSTRING(string, start, length) Extracts a substring from a string (starting at any position)</p> <p>RIGHT(string, number_of_chars) Extracts a number of characters from a string (starting from right)</p> <p>SUBSTRING_INDEX(string, delimiter, number) Returns a substring of a string before a specified number of delimiter occurs</p> <p>CONCAT(str1, ..., strX) Adds two or more expressions together</p> | <p>PI() Returns the value of PI</p> <p>RAND(seed) Returns a random number</p> <p>ABS(number) Returns the absolute value of a number</p> <p>SIGN(number) Returns the sign of a number</p> <p>{v} DIV {v} Used for integer division</p> <p>EXP(number) Returns e raised to the power of a specified number</p> <p>SQRT(number) Returns the square root of a number</p> <p>POW({v},{v}) POWER({v},{v}) Returns the value of a number raised to the power of another number</p> <p>AVG(col1) Returns the average value of an expression</p> <p>COUNT(col1) Returns the number of records returned by a select query</p> <p>MAX({s}) Returns the maximum value in a set of values</p> <p>MIN({s}) Returns the minimum value in a set of values</p> <p>SUM({s}) Calculates the sum of a set of values</p> <p>CEIL(number) CEILING Returns the smallest integer value that is >= to a number</p> <p>GREATEST({s}) Returns the greatest value of the list of arguments</p> <p>LEAST({s}) Returns the smallest value of the list of arguments</p> |

{?} : doit être remplacé:

cd : condition cp : op. de comparaison dt : datatype f : formats s : requête select u : units v : valeur

| | | |
|---|---|------|
| Database : MySQL | Jessica Dupont | 2024 |
| <p>CONCAT_WS(separator, str1, ... strX) Adds two or more expressions together with a separator</p> <p>INSERT(string, position, number, str_insert) Inserts a string within a string at the specified position and for a certain number of characters</p> <p>REPLACE(string, substring, new_string) Replaces all occurrences of a substring within a string, with a new substring</p> <p>REVERSE(string) Reverses a string and returns the result = palindrome</p> <p>ASCII(character) Returns the ASCII value for the specific character</p> <p>CHAR_LENGTH(string) CHARACTER_LENGTH(string) Returns the length of a string (in characters)</p> <p>LENGTH(string) Returns the length of a string (in bytes)</p> <p>STRCMP(str1, str2) Compares two strings</p> <p>FIELD(search, val1, ..., valX) Returns the index position of a value in a list of values</p> <p>FIND_IN_SET(string, "str1, ..., strX") Returns the position of a string within a list of strings</p> <p>POSITION(substr IN string) LOCATE(substr, str, start) Returns the position of the first occurrence of a substring in a string</p> | <p>FLOOR(number) Returns the largest integer value that is <= to a number</p> <p>ROUND(number, decimals) Rounds a number to a specified number of decimal places</p> <p>TRUNCATE(number, decimals) Truncates a number to the specified number of decimal places</p> <p>DEGREES(number) Converts a value in radians to degrees</p> <p>RADIANS(number) Converts a degree value into radians</p> <p>LN(number) Returns the natural logarithm of a number</p> <p>LOG(number) Returns the natural logarithm of a number, or the logarithm of a number to a specified base</p> <p>LOG10(number) Returns the natural logarithm of a number to base 10</p> <p>LOG2(number) Returns the natural logarithm of a number to base 2</p> <p>ACOS(number) Returns the arc cosine of a number</p> <p>ASIN(number) Returns the arc sine of a number</p> <p>ATAN(number) Returns the arc tangent of one or two numbers</p> <p>ATAN2(a, b) Returns the arc tangent of two numbers</p> <p>COS(number) Returns the cosine of a number</p> <p>COT(number) Returns the cotangent of a number</p> <p>SIN(number) Returns the sine of a number</p> <p>TAN(number) Returns the tangent of a number</p> | |

| Date & Time | | Advanced | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|----------|---------------------------------------|----|-------------------------------------|----|------------------------------|----|--|----|--|----|---|----|---------------------------------|----|-----------------|----|-----------------|----|-----------------|----|--------------------|----|------------------------------|---|---|---|
| <div>UNITS</div> <div><div><div>MICROSECOND</div><div>SECOND</div><div>MINUTE</div><div>HOURL</div><div>DAY</div><div>MONTH</div><div>YEAR</div><div>WEEK</div><div>QUARTER</div><div>SECOND_MICROSECOND</div><div>MINUTE_MICROSECOND</div><div>HOURL_MICROSECOND</div><div>DAY_MICROSECOND,</div><div>MINUTE_SECOND</div><div>HOURL_SECOND</div><div>DAY_SECOND,</div><div>HOURL_MINUTE</div><div>DAY_MINUTE</div><div>DAY_HOURL</div><div>YEAR_MONTH</div></div></div> <div>FORMATS</div> <table><tr><td>%a</td><td>Abbreviated weekday name (Sun to Sat)</td></tr><tr><td>%b</td><td>Abbreviated month name (Jan to Dec)</td></tr><tr><td>%c</td><td>Numeric month name (0 to 12)</td></tr><tr><td>%D</td><td>Day of the month as a numeric value, followed by suffix (1st, 2nd, 3rd, ...)</td></tr><tr><td>%d</td><td>Day of the month as a numeric value (01 to 31)</td></tr><tr><td>%e</td><td>Day of the month as a numeric value (0 to 31)</td></tr><tr><td>%f</td><td>Microseconds (000000 to 999999)</td></tr><tr><td>%H</td><td>Hour (00 to 23)</td></tr><tr><td>%h</td><td>Hour (00 to 12)</td></tr><tr><td>%l</td><td>Hour (00 to 12)</td></tr><tr><td>%i</td><td>Minutes (00 to 59)</td></tr><tr><td>%j</td><td>Day of the year (001 to 366)</td></tr></table> | | %a | Abbreviated weekday name (Sun to Sat) | %b | Abbreviated month name (Jan to Dec) | %c | Numeric month name (0 to 12) | %D | Day of the month as a numeric value, followed by suffix (1st, 2nd, 3rd, ...) | %d | Day of the month as a numeric value (01 to 31) | %e | Day of the month as a numeric value (0 to 31) | %f | Microseconds (000000 to 999999) | %H | Hour (00 to 23) | %h | Hour (00 to 12) | %l | Hour (00 to 12) | %i | Minutes (00 to 59) | %j | Day of the year (001 to 366) | <div>DAY(date) DAYOFMONTH(date)</div> <div>Returns the day of the month for a given date</div> <div>DAYNAME(date)</div> <div>Returns the weekday name for a given date</div> <div>DAYOFWEEK(date)</div> <div>Returns the weekday index for a given date</div> <div>DAYOFYEAR(date)</div> <div>Returns the day of the year for a given date</div> <div>EXTRACT({u} FROM date)</div> <div>Extracts a part from a given date</div> <div>HOURL(datetime)</div> <div>Returns the hour part for a given date</div> <div>MICROSECOND(datetime)</div> <div>Returns the microsecond part of a time/datetime</div> <div>MINUTE(datetime)</div> <div>Returns the minute part of a time/datetime</div> <div>MONTH(date)</div> <div>Returns the month part for a given date</div> <div>MONTHNAME(date)</div> <div>Returns the name of the month for a given date</div> <div>QUARTER(date)</div> <div>Returns the quarter of the year for a given date value</div> <div>SECOND(datetime)</div> <div>Returns the seconds part of a time/datetime</div> <div>WEEK(date, firstdayofweek) WEEKOFYEAR(date) YEARWEEK(date, firstdayofweek)</div> <div>Returns the week number for a given date</div> <div>WEEKDAY(date)</div> <div>Returns the weekday number for a given date</div> <div>YEAR(date)</div> <div>Returns the year part for a given date</div> | <div>CURDATE() CURRENT_DATE()</div> <div>Returns the current date</div> <div>CURTIME() CURRENT_TIME()</div> <div>Returns the current time</div> <div>CURRENT_TIMESTAMP() LOCALTIMESTAMP()</div> <div>Returns the current date and time</div> <div>LOCALTIME() NOW() SYSDATE()</div> <div>Returns the current date and time</div> <div>DATE("YYYY-MM-DD hh:mm:ss")</div> <div>Extracts the date part from a datetime expression</div> <div>MAKEDATE(year, day)</div> <div>Creates and returns a date based on a year and a number of days value</div> <div>MAKETIME(hour, minute, second)</div> <div>Creates and returns a time based on an hour, minute, and second value</div> <div>SEC_TO_TIME(seconds)</div> <div>Returns a time value based on the specified seconds</div> <div>STR_TO_DATE(string, "{f}")</div> <div>Returns a date based on a string and a format</div> <div>TIME(string)</div> <div>Extracts the time part from a given time/datetime</div> <div>TIME_FORMAT(string, "{f}")</div> <div>Formats a time by a specified format</div> <div>TO_DAYS(date)</div> <div>Returns the number of days between a date and date "0000-00-00"</div> <div>LAST_DAY(date)</div> <div>Extracts the last day of the month for a given date</div> | <div>LAST_INSERT_ID()</div> <div>Returns the AUTO_INCREMENT id of the last row that has been inserted or updated in a table</div> <div>BIN(number)</div> <div>Returns a binary representation of a number</div> <div>BINARY {v}</div> <div>Converts a value to a binary string</div> <div>CONV(number, from_base, to_base)</div> <div>Converts a number from one numeric base system to another</div> <div>CONVERT({v}, {dt})</div> <div>Converts a value into the specified datatype or character set</div> <div>CAST({v} AS {dt})</div> <div>Converts a value (of any type) into a specified datatype</div> <div>COALESCE({s})</div> <div>Returns the first non-null value in a list</div> <div>ISNULL(expression)</div> <div>Returns 1 or 0 depending on whether an expression is NULL</div> <div>NULLIF(expr1, expr2)</div> <div>Compares two expressions and returns NULL if they are equal. Otherwise, the first expression is returned</div> <div>IFNULL(expression, {v})</div> <div>Return a specified value if the expression is NULL, otherwise return the expression</div> <div>IF(condition, {vTrue}, {vFalse})</div> <div>Returns a value if a condition is TRUE, or another value if a condition is FALSE</div> <div>CASE</div> <div>Goes through conditions and return a value when the first condition is met</div> |
| %a | Abbreviated weekday name (Sun to Sat) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %b | Abbreviated month name (Jan to Dec) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %c | Numeric month name (0 to 12) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %D | Day of the month as a numeric value, followed by suffix (1st, 2nd, 3rd, ...) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %d | Day of the month as a numeric value (01 to 31) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %e | Day of the month as a numeric value (0 to 31) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %f | Microseconds (000000 to 999999) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %H | Hour (00 to 23) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %h | Hour (00 to 12) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %l | Hour (00 to 12) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %i | Minutes (00 to 59) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| %j | Day of the year (001 to 366) | | | | | | | | | | | | | | | | | | | | | | | | | | | |

{?} : doit être remplacé:

cd : condition

cp : op. de comparaison

dt : datatype

f : formats

s : requête select

u : units

v : valeur

| | |
|----|---|
| %k | Hour (0 to 23) |
| %l | Hour (1 to 12) |
| %M | Month name in full (January to December) |
| %m | Month name as a numeric value (00 to 12) |
| %p | AM or PM |
| %r | Time in 12 hour AM or PM format (hh:mm:ss AM/PM) |
| %S | Seconds (00 to 59) |
| %s | Seconds (00 to 59) |
| %T | Time in 24 hour format (hh:mm:ss) |
| %U | Week where Sunday is the first day of the week (00 to 53) |
| %u | Week where Monday is the first day of the week (00 to 53) |
| %V | Week where Sunday is the first day of the week (01 to 53). Used with %X |
| %v | Week where Monday is the first day of the week (01 to 53). Used with %x |
| %W | Weekday name in full (Sunday to Saturday) |
| %w | Day of the week where Sunday=0 and Saturday=6 |
| %X | Year for the week where Sunday is the first day of the week. Used with %V |
| %x | Year for the week where Monday is the first day of the week. Used with %v |
| %Y | Year as a numeric, 4-digit value |
| %y | Year as a numeric, 2-digit value |

ADDDATE(date, INTERVAL {v} {u}) | DATE_ADD(date, INTERVAL {v} {u})

Adds a time/date interval to a date and then returns the date

ADDTIME(datetime, addtime)

Adds a time interval to a time/datetime and then returns the time/datetime

DATEDIFF(date1, date2)

Returns the number of days between two date values

DATE_SUB(date, INTERVAL {v} {u}) | SUBDATE(date, INTERVAL {v} {u})

Subtracts a time/date interval from a date and then returns the date

FROM_DAYS(number)

Returns a date from a numeric datevalue

PERIOD_ADD(period, number)

Adds a specified number of months to a period

PERIOD_DIFF(period1, period2)

Returns the difference between two periods

SUBTIME(datetime, time_interval)

Subtracts a time interval from a datetime and then returns the time/datetime

TIME_TO_SEC(time)

Converts a time value into seconds

TIMEDIFF(time1, time2)

Returns the difference between two time/datetime expressions

CASE

WHEN condition1 THEN

result1

WHEN condition2 THEN

result2

WHEN conditionN THEN

resultN

ELSE result

END;

VERSION()

Returns the current version of the MySQL database

DATABASE()

Returns the name of the current database

CURRENT_USER()

Returns the user name and host name for the MySQL account that the server used to authenticate the current client

SESSION_USER() | SYSTEM_USER() | USER()

Returns the current MySQL user name and host name

CONNECTION_ID()

Returns the unique connection ID for the current connection

{?} : doit être remplacé:

cd : condition cp : op. de comparaison dt : datatype f : formats s : requête select u : units v : valeur

REQUESTS DDL

Data Definition Language (DDL) refers to the CREATE, ALTER and DROP statements.
DDL or Data Definition Language actually consists of the SQL commands that can be used to define the database schema. DDL allows to add / modify / delete the logical structures which contain the data or which allow users to access / maintain the data (databases, tables, keys, views...). DDL is about "metadata".

| | | |
|--|--|---|
| <pre>CREATE DATABASE databasename; USE databasename;</pre> | <pre>SHOW databases;</pre> | <pre>DROP databasename;</pre> |
| <pre>CREATE TABLE table_name(column_name DATATYPE, ...);</pre> | <pre>ALTER TABLE table_name ADD columnX_name {dt}; ALTER TABLE table_name MODIFY COLUMN columnX_name {dt};</pre> | <pre>DROP TABLE table_name; ALTER TABLE table_name DROP COLUMN columnX_name;</pre> |
| <pre>SHOW tables;</pre> | <pre>ALTER TABLE table_name MODIFY COLUMN column_name {dt} AUTO_INCREMENT; ALTER TABLE table_name AUTO_INCREMENT={v};</pre> | |
| | <pre>ALTER TABLE table_name MODIFY COLUMN column_string_name DEFAULT '{v}'; ALTER TABLE table_name MODIFY COLUMN column_bool_name DEFAULT {v}; ALTER TABLE table_name MODIFY COLUMN column_numeric_name DEFAULT {v}; ALTER TABLE table_name MODIFY COLUMN column_date_name DEFAULT CURRENT_DATE();</pre> | |

| | | |
|---|--|--|
| | <pre>ALTER TABLE table_name ADD CONSTRAINT NN_column_name NOT NULL(column_name); ALTER TABLE table_name ADD CONSTRAINT U_column_name UNIQUE(column_name); ALTER TABLE table_name ADD CONSTRAINT PK_column1_name_column2_name PRIMARY KEY (column1_name, column2_name); ALTER TABLE table_name ADD CONSTRAINT FK_column_name FOREIGN KEY (column_name) REFERENCES table2_name(column_name); ALTER TABLE table_name ADD CONSTRAINT CHK_column_name_min CHECK (column_name {cp} {v});</pre> | <pre>ALTER TABLE table_name DROP INDEX U_column_name; ALTER TABLE table_name DROP PRIMARY KEY; ALTER TABLE table_name DROP FOREIGN KEY FK_column_name; ALTER TABLE table_name DROP CHECK CHK_column_name_min;</pre> |
| <pre>CREATE [UNIQUE] INDEX index_name ON table_name (column1_name, column2_name);</pre> | <pre>SHOW index FROM table_name; ALTER TABLE table_name;</pre> | <pre>DROP INDEX index_name;</pre> |
| <pre>CREATE VIEW view_name AS {s};</pre> | <pre>CREATE OR REPLACE VIEW view_name AS {s};</pre> | <pre>DROP VIEW view_name;</pre> |

REQUESTS DML

Data Manipulation Language (DML) refers to the INSERT, UPDATE and DELETE statements
DML allows to add / modify / delete data itself.

| | | |
|---|---|--|
| <pre>INSERT INTO table_name [(col1, ..., colX)] VALUES (val1, ..., valX);</pre> | <pre>UPDATE table_name SET col1 = val1, ..., colX = valX [WHERE condition];</pre> | <pre>DELETE FROM table_name [WHERE condition];</pre> |
|---|---|--|

REQUESTS DQL

Data Query Language (DQL) refers to the SELECT, SHOW and HELP statements (queries)
SELECT is the main DQL instruction. It retrieves data you need. SHOW retrieves infos about the metadata. HELP... is for people who need help.

| | | |
|---|--|--|
| <pre>SELECT coll [AS alias], ..., colX [AS alias] * fct() [AS alias] FROM table_name view_name [AS alias] [[LEFT INNER RIGHT CROSS] JOIN table_name view_name] [WHERE condition] [GROUP BY coll, ..., colX HAVING condition]] [ORDER BY coll, ..., colX [ASC DESC]] [LIMIT number [OFFSET number]] [UNION {sWithSameNameColumn}];</pre> | <pre>SHOW BINARY LOG STATUS SHOW BINARY LOGS SHOW BINLOG EVENTS [IN 'log_name'] [FROM pos] [LIMIT [offset,] row_count] SHOW {CHARACTER SET CHARSET} [like_or_where] SHOW COLLATION [like_or_where] SHOW [FULL] COLUMNS FROM tbl_name [FROM db_name] [like_or_where] SHOW CREATE DATABASE db_name SHOW CREATE EVENT event_name SHOW CREATE FUNCTION func_name SHOW CREATE PROCEDURE proc_name SHOW CREATE TABLE tbl_name SHOW CREATE TRIGGER trigger_name SHOW CREATE VIEW view_name SHOW DATABASES [like_or_where] SHOW ENGINE engine_name {STATUS MUTEX} SHOW [STORAGE] ENGINES SHOW ERRORS [LIMIT [offset,] row_count] SHOW EVENTS SHOW FUNCTION CODE func_name SHOW FUNCTION STATUS [like_or_where] SHOW GRANTS FOR user SHOW INDEX FROM tbl_name [FROM db_name] SHOW OPEN TABLES [FROM db_name] [like_or_where] SHOW PLUGINS SHOW PROCEDURE CODE proc_name SHOW PROCEDURE STATUS [like_or_where]</pre> | <pre>HELP 'search_string' HELP 'contents' HELP 'data types' HELP 'ascii' HELP 'create table' ...</pre> |
|---|--|--|

| | | |
|--|---|--|
| | <pre>SHOW PRIVILEGES SHOW [FULL] PROCESSLIST SHOW PROFILE [types] [FOR QUERY n] [OFFSET n] [LIMIT n] SHOW PROFILES SHOW RELAYLOG EVENTS [IN 'log_name'] [FROM pos] [LIMIT [offset,] row_count] SHOW REPLICATION STATUS [FOR CHANNEL channel] SHOW REPLICAS SHOW [GLOBAL SESSION] STATUS [like_or_where] SHOW TABLE STATUS [FROM db_name] [like_or_where] SHOW [FULL] TABLES [FROM db_name] [like_or_where] SHOW TRIGGERS [FROM db_name] [like_or_where] SHOW [GLOBAL SESSION] VARIABLES [like_or_where] SHOW WARNINGS [LIMIT [offset,] row_count] like_or_where: { LIKE 'pattern' WHERE expr }</pre> | |
|--|---|--|

REQUEST DCL

Data Control Language (DCL) refers to the GRANT and REVOKE statements
DCL is used to grant / revoke permissions on databases and their contents. DCL is simple, but MySQL's permissions are rather complex. DCL is about security.

| | | |
|---|---|--|
| <pre>CREATE USER 'nom_login'[@'adresse_client'] [IDENTIFIED BY [PASSWORD] 'mot_de_passe'];</pre> | <pre>RENAME USER 'ancien_login'@'ancienne_adresse_client' TO 'nouveau_login'@'nouvelle_adresse_client' ; SET PASSWORD FOR 'nom_login'@'adresse_client' = PASSWORD('nouveau_mot_de_passe');</pre> | <pre>DROP USER 'nom_login'@'adresse_client';</pre> |
| <pre>CREATE ROLE [IF NOT EXISTS] role1 [, role2];</pre> | | <pre>DROP ROLE [IF EXISTS] role1 [, role2];</pre> |
| <pre>CREATE USER [IF NOT EXISTS] nom_login DEFAULT ROLE role1 [, role1] ...</pre> | <pre>ALTER USER [IF EXISTS] nom_login DEFAULT ROLE {NONE ALL role1 [, role2] ...};</pre> | |
| <pre>GRANT privilège [(coll1, col2,...)] ON [type_élément] type_domaine TO nom_login [IDENTIFIED BY mot_de_passe]; GRANT ALL [PRIVILEGES] ON [type_élément] type_domaine TO nom_login [IDENTIFIED BY mot_de_passe]; GRANT USAGE ON *.* -- toujours sur tous les éléments TO nom_login IDENTIFIED BY mot_de_passe;</pre> | <pre>SHOW GRANTS [FOR nom_login_ou_role]; SELECT * FROM information_schema.column_privileges;</pre> | <pre>REVOKE privilège ON [type_élément] type_domaine FROM nom_login;</pre> |

| | | |
|--|--|--|
| <pre>GRANT GRANT OPTION ON [type_élément] type_domaine TO nom_login [IDENTIFIED BY mot_de_passe]; GRANT ... ON [type_élément] type_domaine TO nom_login [IDENTIFIED BY mot_de_passe] WITH GRANT OPTION;</pre> | | |
|--|--|--|

REQUEST DTL

Data Transaction Language (DTL) refers to the START TRANSACTION, SAVEPOINT, COMMIT and ROLLBACK [TO SAVEPOINT] statements
DTL is used to manage transactions (operations which include more instructions none of which can be executed if one of them fails).

- -- Déclaration des variables locales
- -- Déclaration des conditions
- -- Déclaration des curseurs
- -- Déclaration des gestionnaires d'erreur
- -- Début du traitement

| | | |
|---|---|--|
| <pre>SHOW variables WHERE variable_name LIKE '%autocommit%'; -- ou SELECT @@autocommit;</pre> | <pre>SET autocommit=OFF;</pre> | |
| <pre>START TRANSACTION; [request] COMMIT;</pre> | | |
| <pre>SAVEPOINT jalon_name;</pre> | <pre>ROLLBACK TO jalon_name;</pre> | <pre>RELEASE SAVEPOINT jalon_name;</pre> |
| <pre>LOCK TABLES table1[, table2] {READ WRITE}; {s} LOCK IN SHARE MODE; {s} FOR UPDATE;</pre> | <pre>SHOW OPEN TABLES FROM nom_db;</pre> | <pre>UNLOCK TABLES;</pre> |
| | <pre>SET [GLOBAL SESSION] TRANSACTION</pre> | |

| | | |
|--|---|---|
| | ISOLATION LEVEL {READ UNCOMMITTED READ COMMITTED REPEATABLE READ SERIALIZABLE}; | |
| SET @nom_variable = valeur; -- ou SET @nom_variable := valeur; -- à utiliser dans les requêtes SELECT coll, col2 INTO @coll, @col2 FROM table WHERE condition=1; | SELECT @nom_variable; | |
| PREPARE nom_requete_preparee FROM 'requête SQL' WHERE col=?; | EXECUTE nom_requete_preparee USING param; | DEALLOCATE PREPARE nom_requete_preparee; |
| DELIMITER \$\$ CREATE PROCEDURE nom_procedure([[IN OUT] [pi po pio]_name {dt}]) BEGIN {s} END \$\$ DELIMITER ; | CALL procedure_name([param]); SHOW CREATE PROCEDURE nom_procedure \G; SHOW PROCEDURE STATUS; -- ou SHOW PROCEDURE STATUS WHERE db='nom_db'; | DROP PROCEDURE [IF EXISTS] nom_procedure; |
| CREATE FUNCTION nom_fonction() RETURNS type_donnée_retour DETERMINISTIC BEGIN RETURN; END; | SELECT nom_fonction(); SHOW CREATE FUNCTION nom_fonction \G; SHOW FUNCTION STATUS; -- ou SHOW FUNCTION STATUS WHERE db='nom_db'; -- ou SELECT name, db, type FROM mysql.proc; | DROP FUNCTION [IF EXISTS] nom_fonction; |
| DECLARE nom_variable type_variable [DEFAULT val_default]; | SET nom_variable := valeur; | |
| IF condition(s) THEN Bloc d'instruction(s) END IF; | IF condition(s) 1 THEN Bloc d'instruction(s) 1 ELSEIF condition(s) 2 THEN | CASE variable WHEN valeur 1 THEN instruction(s) 1 |

{?} : doit être remplacé:

cd : condition

cp : op. de comparaison

dt : datatype

f : formats

s : requête select

u : units

v : valeur

| | | |
|---|---|--|
| | Bloc d'instruction(s) 2 ELSE Bloc d'instruction(s) 3 END IF; | WHEN valeur 2 THEN instruction(s) 2 ... ELSE -- équivalent du default en C instruction(s) n END CASE; |
| [label_de_boucle:]WHILE condition(s) DO instruction(s) END WHILE [label_de_boucle]; | [label_de_boucle:]REPEAT instruction(s) UNTIL condition(s) END REPEAT [label_de_boucle]; | [label_de_boucle:]LOOP instruction(s) IF l_compteur>l_max THEN LEAVE label_de_boucle; END IF; END LOOP [label_de_boucle]; |
| DECLARE condition_test CONDITION FOR SQLSTATE '99999'; SIGNAL {SQLSTATE valeur_état condition condition_test} [SET {MESSAGE_TEXT MYSQL_ERRNO SCHEMA_NAME TAB LE_NAME ...}[, ...]]; | DECLARE {CONTINUE EXIT UNDO} HANDLER FOR {code_erreur SQLSTATE [VALUE] etat_sql nom_condition SQLWARNING NOT FOUND SQLEXCEPTION}[,...] instruction(s); | |
| <ul style="list-style-type: none">• RETURNED_SQLSTATE• MESSAGE_TEXT• MYSQL_ERRNO• CONSTRAINT_NAME• SCHEMA_NAME• TABLE_NAME• COLUMN_NAME• CURSOR_NAME | GET [CURRENT STACKED] DIAGNOSTICS CONDITION numero_de_la_condition... | |
| DECLARE nom_du_curseur CURSOR FOR requête_sql; OPEN nom_du_curseur; | FETCH nom_du_curseur INTO var1[,var2,var3,...]; - ERROR 1329 (02000): No data - zero rows fetched, selected, or processed | CLOSE nom_du_curseur; |
| CREATE TRIGGER nom_trigger moment_trigger action_trigger | SHOW TRIGGERS; | DROP TRIGGER nom_trigger; |

{?} : doit être remplacé:

cd : condition

cp : op. de comparaison

dt : datatype

f : formats

s : requête select

u : units

v : valeur

| | | |
|--|---|--|
| <pre>ON nom_table FOR EACH ROW BEGIN instruction(s) END;</pre> | <pre>SHOW CREATE TRIGGER nom_trigger;</pre> | |
| <pre>SHOW VARIABLES LIKE 'event_scheduler'; -- généralement 'off' par défaut SET GLOBAL event_scheduler:=ON; CREATE EVENT [IF NOT EXISTS] nom_event ON SCHEDULE [AI INTERVAL {v} {u} EVERY {v} {u}] DO {s};</pre> | <pre>SHOW EVENTS; SHOW CREATE EVENT nom_event; SHOW PROCESSLIST; ALTER EVENT nom_event [ON SCHEDULE moment_planification] [RENAME TO nouveau_nom_event] [ENABLE DISABLE] [DO requête_sql];</pre> | <pre>DROP EVENT [IF EXISTS] nom_event;</pre> |

16/16