# AKADEMIA GÓRNICZO-HUTNICZA

# GŁĘBOKIE UCZENIE I INTELIGENCJA OBLICZENIOWA ${\rm Automatyka~i~Robotyka~II~Stopie\acute{n}}$ 2019/2020

# Optymalizacja fabryki z wykorzystaniem algorytmu immunologicznego (selekcji klonalnej)

# Skład zespołu:

Artur Bauer Kamil Szostek Sławomir Goździewski Wiktor Filipiak

# Opiekun:

dr hab. inż. Joanna Kwiecień


Złożono: 27 marca 2020

# Spis treści

L	Wst	ep .
	1.1	Factory model
		1.1.1 Factory main goal function:
		1.1.2 Punish
		1.1.3 Number of types
		1.1.4 Max number of items
		1.1.5 Real working time of the i-type machine/employee for one product
	1.2	Model assumption
	Bad	ny problem
	2.1	Przeglad literatury

### 1 Wstęp

#### 1.1 Factory model



Rysunek 1: Factory scheme

#### 1.1.1 Factory main goal function:

$$Income = \sum_{i=1}^{n_p} (p_i * (v_i - m_i * m_p)) - (1 + b_i) * \sum_{i=1}^{n_w} (w_i * s_i * t_{wi}) - m_r * m_p - punish$$

Where:

- $n_p$  number of item types ( param )
- $p_i(n_m)$  number of manufactured i-type items
- $v_i(v_{bi}, t_{wi}, t_{bi}, w_q)$  value of the i-type items
- $m_i$  number of material needed to manufacture the i-type item ( param )
- $m_p$  material price ( param )
- $n_w$  number of types of employees ( param )
- $w_i$  number of i-type employees (param)
- $s_i$  the salary of i-type employees
- $\bullet$  b the bonus for employees (param)
- $\bullet$   $t_{wi}$  real working time of the i-type machine/employee for one product
- $m_r(p_i, n_m)$  material remains, unused material
- $p_{i_{min}}$  minimum number of i-type items that must be manufactured to avoid punishment (param)
- $p_{i_{max}}$  maximum number of items that can be manufactured
- $n_m$  number of materials in the warehouse at the beginning of the day (param)
- $punish(p_{un}, p_{num_i}, v_i)$  punishment for not produced required item number

#### 1.1.2 Punish

$$punish = p_{un} * \sum_{i=1}^{n_p} (p_{num_i}) * v_i$$

$$p_{num_i} = \begin{cases} 0 & \text{if } p_{i_{min}} - p_i \leq 0 \\ p_{i_{min}} - p_i & \text{if } p_{i_{min}} - p_i > 0 \end{cases}$$
Where:

- $p_{un}$  punishment rate
- $p_{num_i}(p_{i_{min}}, p_i)$  number of i-type items for which a punishment will be charged

#### 1.1.3 Number of types

Number of types of employees and machines should be the same:  $n_p = n_w$ 

#### 1.1.4 Max number of items

Numbers of i-type items must meet:  $\sum_{i=1}^{n_p} p_{i_{max}} * m_i < n_m$ 

#### 1.1.5 Real working time of the i-type machine/employee for one product

$$t_{wi} = t_{pi} + p_i * t_{bi}$$

#### 1.2 Model assumption

Parameter	$_{\mathrm{mark}}$	value
Material number	$n_m$	[x - 100]
Material cost	$m_p$	15
Working time	?	[1 - 16]
Minimal number of big parts	$p_{0_{min}}$	[0 - 10]
Minimal number of small parts	$p_{1_{min}}$	[0 - 10]
Big machine worker salary	$s_0$	70
Big machine material requirements	$m_0$	4
Big machine preparation time	$t_{p0}$	$30 \min$
Base big machine item value	$v_{b0}$	50
Base big machine working time per item	$t_{b0}$	1h
Number of big machines	?	[0 - 10]
Small machine worker salary	$s_1$	60
Small machine material requirements	$m_1$	3
Small machine preparation time	$t_{p1}$	$45  \min$
Base small machine item value	$v_{b1}$	35
Base small machine working time per item	$t_{b1}$	$45  \min$
Number of small machines	?	[0 - 10]
Max working time per worker	?	8h
Worker bonus	b	[0.0 - 0.2]
Punishment rate	$p_{un}$	1.5

#### Where:

- $\bullet$  x number of required parts \* cost of part
- Input parameters are given in square brackets
- Worker is hired on full time. Must work 8h
- First and second shift are equal in machine and worker count and type
- We reserve materials for a require items
- Any item manufactured over require number is a profit

## 2 Badany problem

#### 2.1 Przegląd literatury

This article is about the Clonal Selection Algorithm used for Optimalization in Electromagnetics. The authors present their own concept of real-coded clonal selection algorithm that can be used in electromagnetic design optimization. The article describes in detail all the algorithm parameters as well as the operation of the algorithm for "The TEAM Workshop problem 22"[1].

This article is about the artificial immune system in industrial application. Basing on cutting parameters (force, vibrations, torque etc.) they try to detect tool brake using a negative-selection algorithm [2].

This article is about the artificial immune system in industrial application. Authors compare AIS with Social Learning Mechanisms to few others AIS which use cloning alghoritm. Basing on proportional—/integral—/derivative-time they try to tune a PID [6].

This article is about the Clonal Selection Based Memetic Algorithm for Job Shop Scheduling Problems. The authors' goal was to improve exploration and exploitation using a clonal selection algorithm. The article presents the use of clonal selection to construct an evolutionary search mechanism that is used for exploration[8].

This article is about Clonal Selection Algorithm in engineering applications. It describes theoretical functioning of the algorithm and illustrates the workings of implemented algorithm on three different problems: a binary character recognition, multi-modal optimization of function –  $f(x,y) = x \cdot \sin(4\pi x) - y \cdot \sin(4\pi y + \pi) + 1$  and Traveling Salesman Problem for 30 cities [3].

This article is about using Clonal Selection Algorithm to optimize the layout of a construction site. Presented algorithm is used to minimize production costs and traveling distance between n facilities which are represented in n x n permutation matrix [7].

This article is about the Artificial Immune System for solving the Capacitated Vehicle Routing Problem. The objective of the article was to investigate the suitable setting of clonal selection AIS parameters for solving the CVRP through the statistical design of experiment. The article also shows the performance of AIS and other methods for benchmarking twenty CVRP instances in terms of the quality of solutions and the computational time used [5].

This article is about using Clonal Selection Algorithm in determining optimal operation points in hybrid AC/DC low voltage microgrid. The objective was to minimize active power losses, operation costs and optimize nodal voltage level [4].

## Bibliografia

- [1] F. Campelo i in. "A clonal selection algorithm for optimization in electromagnetics". W: *IEEE Transactions on Magnetics* 41.5 (2005), s. 1736–1739.
- [2] Dipankar Dasgupta i Stephanie Forrest. "Artificial immune systems in industrial applications". W: Proceedings of the Second International Conference on Intelligent Processing and Manufacturing of Materials. IPMM'99 (Cat. No. 99EX296). T. 1. IEEE. 1999, s. 257–267.
- [3] Leandro De Castro i Fernando Von Zuben. "The Clonal Selection Algorithm with Engineering Applications 1". W: (sty. 2000).
- [4] Łukasz Rokicki. "The application of the CLONALG algorithm in the process of optimal operation control of hybrid AC/DC low voltage microgrid". W: *E3S Web of Conferences* 84 (sty. 2019), s. 02011. DOI: 10.1051/e3sconf/20198402011.
- [5] Warattapop Thapatsuwan, Pupong Pongcharoen i Peeraya Thapatsuwan. "Clonal Selection of Artificial Immune System for Solving the Capacitated Vehicle Routing Problem". W: Journal of Next Generation Information Technology 4 (maj 2013), s. 167–179. DOI: 10.4156/jnit.vol4.issue3.20.
- [6] Mingan Wang i in. "An Artificial Immune System Algorithm with Social Learning and Its Application in Industrial PID Controller Design". en. W: Mathematical Problems in Engineering 2017 (2017), s. 1–13. ISSN: 1024-123X, 1563-5147. DOI: 10.1155/2017/3959474. URL: https://www.hindawi.com/journals/mpe/2017/3959474/ (term. wiz. 25.03.2020).
- [7] Xi Wang i in. "Application of Clonal Selection Algorithm in Construction Site Utilization Planning Optimization". W: Procedia Engineering 145 (2016). ICSDEC 2016 Integrating Data Science, Construction and Sustainability, s. 267—273. ISSN: 1877-7058. DOI: https://doi.org/10.1016/j.proeng.2016.04.073. URL: http://www.sciencedirect.com/science/article/pii/S1877705816300789.
- [8] Jin-hui Yang i in. "Clonal selection based memetic algorithm for job shop scheduling problems". W: Journal of Bionic Engineering 5.2 (2008), s. 111–119.